




3M™ Multi-Channel I/O Twin Axial Cable Assembly



Scope

This document summarizes test methods, test conditions, and product performance requirements for 3M™ Multi-Channel I/O Twin Axial Cable Assembly.

Reference Documents

Note: Unless otherwise specified, latest edition of the reference documents applies. In the event of conflict between requirements of the references and 3M specification, 3M specification shall take precedence.

Reference Commercial standards, specifications and report

EIA-364

SFF-TA-1016

PCIe Gen 5.0

3M™ Multi-Channel I/O Twin Axial Cable Assembly	
Literature Code	Document Title
78-5100-2722-6	TS-2722/Customer Drawing, 85ohm, 31AWG, 8X, 8MS8 Series

Performance Testing

Unless otherwise specified, all tests shall be performed on some kind of sockets mated to some kind of headers using some cable at conditions per EIA-364. Unless otherwise specified, all values and limits are typical of those obtained by qualification testing of the subject product. All specifications are subject to revision and change without notice from 3M.

3M™ Multi-Channel I/O Twin Axial Cable Assembly

Ratings

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

3M™ Multi-Channel I/O Twin Axial Cable Assembly	
Feature	Value
Current rating	0.5A per contact
Voltage rating	30 V AC per contact
Operating temperature	0°C to +70°C
Non-operating Temperature	-20°C to +85°C
Humidity	80% RH Maximum

Materials

3M™ Multi-Channel I/O Twin Axial Cable Assembly	
Halogen content	See applicable assembly drawing
Metal Latch	Stainless Steel
Housing	
Material:	Glass filled thermoplastic
Paddle Card	
Material:	FR4 (Hal Free)
Mating pad under plate:	1.27 µm (50 µinch) Ni MIN
Mating pad finish:	0.76 µm (30 µinch) Au MIN
High speed ribbon twin axial cable:	See applicable 3M™ Twin Axial Ribbon Cable drawing for cable specification.

Regulatory Compliance

For regulatory information about this product, visit 3M.com/regs or contact your 3M representative.

Electrical

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

3M™ Multi-Channel I/O Twin Axial Cable Assembly				
Description or Parameter	Units	Values / Limits	Requirement or Conditions	Test Standard or Method
Dielectric Withstanding Voltage	V DC	300	EIA-364-20, Method B Subject a voltage of 300 VDC for 1 minute at sea level between adjacent contacts of mated and unmated connector assemblies.	EIA-364-20
Low level contact resistance (LLCR)	Milliohms	$\Delta R \leq 20$	Subject a voltage of 20 mV max open circuit at a current not exceeding of 100 mA max on mated connector assemblies.	EIA-364-23
Insulation Resistance	Mega ohms	>1000	Measured between adjacent and opposing contacts with 100 VDC applied for 1 minute.	EIA-364-21

3M™ Multi-Channel I/O Twin Axial Cable Assembly

Mechanical

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

3M™ Multi-Channel I/O Twin Axial Cable Assembly				
Description or Parameter	Units	Values / Limits	Requirement or Conditions	Test Standard or Method
Mating force (without latch)	Newtons	1.1N/pin +10N Max.	Mating speed 25+/-3mm/min	EIA-364-13
Unmating force (without latch)	Newtons	0.1N/pin Min.	Mating speed 25+/-3mm/min	EIA-364-13
Latched plug retention force	Newtons	50N Min	For both version of latch (below 74P and above 74P)	EIA-364-98
Mechanical shock	Milliohms	$\Delta R \leq 20$	Mated connectors shall exhibit no damage. 20 milliohm maximum ΔR contact resistance per mated interface throughout testing.	EIA-364-27
Vibration	Milliohms	$\Delta R \leq 20$	3.10G RMS between 20 and 500 Hz at 15 minutes in each of 3 mutually perpendicular directions. No damage. No discontinuity longer than 1 μ sec allowed.	EIA-364-28 Condition VII D
Durability (preconditioning)	No evidence of physical damage.	Nil	Perform 50 unplug/plug cycles.	EIA-364-09
Durability	No evidence of physical damage.	Nil	Perform 250 unplug/plug cycles.	EIA-364-09
Reseating	Milliohms	$\Delta R \leq 20$	Perform 3 unplug/plug cycles.	EIA-364-09

Environmental

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

3M™ Multi-Channel I/O Twin Axial Cable Assembly				
Description or Parameter	Units	Values/ Limits	Requirement or Conditions	Test Standard or Method
Temperature Life (Thermal Aging)	Degrees C Hours	85 500	No physical abnormalities. 20 milliohm maximum ΔR contact resistance initial testing. No physical damage.	EIA-364-17 Method A
Temperature Life (preconditioning)	Degrees C Hours	90 240	As Above	EIA-364-1000
Thermal Shock	Degrees Cycles	-55/25 & 85/25 10	No physical abnormalities. 20 milliohm maximum ΔR contact resistance throughout testing. 30mins each at extreme temp.	EIA-364-32 Condition 1
Humidity-Temperature Cycling	Degrees C % RH Cycles	25 at 80% & 65 at 50% 24	25°C, 80%RH to 65°C, 50%RH to 25°C 80%. Ramp time – 0.5 hour Dwell time – 1.0 hour. (65°C) 24Cycles – 24Hrs	EIA-364-1000 & 31 Method III (without condition)

3M™ Multi-Channel I/O Twin Axial Cable Assembly

Qualification Test Groups and Sequenced Tests

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

3M™ Multi-Channel I/O Twin Axial Cable Assembly					
Test Description	Test Group				
	1	2	3	4	5
	Test Sequence				
Visual Inspection	1,7	1,11	1,7	1,15	1
Mating Force	2	2		5	
Low Level Contact Resistance	3,5	3,6,9	2,4,6	2,7,12	
Durability (Preconditioning)		4			
Durability	4				
Unmating Force	6	10		8	
Temperature Life (Preconditioning)		5			
Temperature Life			3		
Reseating			5		
Vibration Shock		7			
Mechanical Shock		8			
Insulation Resistance				3,9,13	
Dielectric Withstanding Voltage				4,10,14	
Thermal Shock				6	
Cyclic Temperature and Humidity				11	
Latch Plug Retention Force					2

Regulatory: For regulatory information about this product, visit [3M.com/regs](https://www.3m.com/regs) or contact your 3M representative.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. **3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** If the 3M Product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



3M Company
Electronics Materials Solutions Division
13011 McCallen Pass, Bldg. C
Austin, TX 78753-5380
1-800-225-5373
www.3m.com/interconnect

3M is a trademark of 3M Company.
Please recycle.
©3M 2021. All rights reserved.
78-5102-0346-2, Rev A