

Turn-KeyConnectivity

Speed of 'Plug & Play' UL/cUL Industrial Cable Assembly Solutions Meet Data Center Demands

As one of the largest providers of distributed power & control interconnect systems in the World, we offer numerous plug & play, scalable solutions for your next high power installation. If one of our standard products doesn't fit your specific needs, our Engineers will work with you to custom design a solution specific to your application. We are your one source for proven, reliable and innovative results in today's ever changing and demanding interconnect markets.

- UL /cUL Quickly Achieve Standard Compliance
- Easy 'Plug & Play' Installation
- Tamperproof, Over-Molded Cord Sets
- TC-ER Cable Jacket Reduces Raceways & Conduit
- Industrial Grade Insulation Equals Higher Reliability
- IP67/IP68 rated (see individual datasheets)



**2237
2238**



RoHS



PB POWERBOSS™ M40



- 32A Power/5A Signal Max; 600V**
- Available in 6 Position (4 + 2), 40mm Size
 - 8-10AWG Max Wire Range
 - Standard or Quick Coupling System

PB POWERBOSSlite™ M35



- 32A Max; 10AWG Wire**
- Available in 3 or 4 Position, 35mm Size (1-3/8")
 - TC-ER or TC-ER / STOOV Rated Cable
 - Straight or 90 Degree Cable Exit
 - Standard Threading Coupling System

VB VersaBOSS™ Powerflex



- 20A Power/5A Signal Max; 600V Power/30V Signal**
- Available in 9 Pos w/ Multiple 4 Power/5 Signal Cable Config.
 - 12-18AWG Wire Range
 - VFD Rated Static or High-Flex Cable Options
 - Quick Locking Bayonet Coupling System, 32.9mm Size

PB POWERBOSS™ M29



- 25A Max UL/cUL 2237/ 29A Max UL/cUL 2238**
- Available in 4 Position for 3 Phase Control Power
 - 600V; 12AWG Wire, Shielded, TC-ER Per UL1277
 - Standard Threading, 29mm Standard Size

PB POWERBOSSlite™ M22



- 24A Max; 600V; 14AWG Wire**
- Available in 3 or 4 Position
 - TC-ER or TC-ER / STOOV Rated
 - Straight or 90 Degree Cable Exit
 - Standard Threading, 22mm (7/8") Size

mB miniBOSS™ M22



- 13A Max; 600V; 16AWG Wire**
- Available in 2 thru 6 Position
 - Utilizes UL STOOV/CSA Type ST Cable
 - High Flex TPE jacketed UL Listed TC-ER Cable Option
 - Straight or 90 Degree Cable Exit
 - Standard Threading, 22mm (7/8") Size

mB microBOSS™ M12



- 4A Max; 300V; 22AWG Wire**
- Available in 3, 4 and 5 position
 - Straight or 90 Degree Cable Exit
 - Standard Threading Coupling System



**Distributed Power & Control
Factory Automation**

Let's Move Forward**Together!**