



C091 signal|mate® C091 Family



Available in 2 thru 8, 12, 14 and 19 Position (Depending on Series)

Amphenol's **signal|mate® C091 (M16 Size) Family** of circular DIN connectors and cable assemblies are available in 5 options **M16 A, M16 B, M16 D, M16 D+ and M16 Q (Quicklock)** with either a threaded, bayonet or quicklock option offering environmental protection up to IP69K when mated. The compact design provides excellent EMI shielding capability ensuring the highest integrity for power and signal connections. The modular structure of the series enables a broad field of applications in diverse temperature ranges and many types for 4G/5G mobile radio networks, establishing the **signal|mate® C091 (M16) Family** as the recognized industry standard.

C091 M16 A **C091 M16 B** **C091 M16 D** **C091 M16 D+** **C091 M16 Q**

Potential Applications

Measuring Instruments and Equipment, Factory Automation, Drive Systems and Components, Lighting, Entertainment, CCTV/Security Cameras, Low Power/Signal Transmission, High Resolution Inspection Equipment, Heavy Equipment, Agriculture, Construction, Transportation, Off-Road Recreation, Industrial, Conveyors, Packaging Machinery, Motion Control, Servo Motors and Wireless Infrastructure

C091 C091 AISG/RET



Available in 4, 5 and 6 Position

Amphenol's **signal|mate® C091 (M16 Size) AISG/RET Cable Assemblies** for outdoor use meet all the requirements for extreme outdoor use. System coupling integrity, temperature, salt mist, and UV resistance are a few of the important criteria a connector must meet. Our AISG connectors are manufactured according to the AISG Standard (AISG C 485). Amphenol has set the standards with our C091 circular connector series. Compatible with industry cables from Andrew, Kathrein, Scala, Ericsson, Alcatel Lucent (ALU), Huawei, Kaelus, RFS, KMW, and many others.

First in the market as original innovators of AISG connector systems, we manufacture durable cable assemblies for antennas that are in service for several years in some of the harshest environments on the planet.

Potential Applications

Wireless Infrastructure, Harsh Environment



Standard products. Custom solutions
Customer Service +1 800 394 7732

signalmate® C091 Family Overview

Series	C091 M16 A	C091 M16 B	C091 M16 D	C091 M16 D+	C091 M16 Q
Image					
Positions	2, 3, 4, 5a, 5b, 6, 7a, 7b, 8, 12, 14a, and 14b	3, 4, 5a, 5b, 6, 7a, 7b, 8, 12, 14a, and 14b			3, 4, 5a, 5b, 6, 7a, 7b, 8, 12, 14a, 14b, and 19
Current Rating (+40°C)	2-3 pos: 10A 5-8 pos: 7A 12-14 pos: 3A	3-4 pos: 10A 5-8 pos: 7A 12-14 pos: 3A			3-4 pos: 10A 5-8 pos: 7A 12-19 pos: 3A
Operating Voltage	Up to 300V per IEC 60664-1 Standard				3-4 pos: 150V 5a pos: 100V 5b pos: 32V 6-7a pos: 100V 7b-19 pos: 32V
Temperature Range	-40°C to +100°C				
Coupling System	Metal Screw	Plastic Bayonet	Metal Screw		Quicklock
IP Rating (mated)	IP40		IP65/67/69K	IP68/69K	IP68
Dielectric Material	Thermoplastic				
Housing Material	Brass or Zinc Die-Cast, Nickel Plated, or Thermoplastic				Thermoplastic
Contact Plating	Silver/Gold				
Shieldable	Yes	No	Yes	Yes (360° Shielding)	No
Contact Termination	Solder, Crimp				
Contact Types	Machined; Stamped & Formed; Solder and PC Tail				
AWG Range	18 thru 28AWG				
Insulation Resistance	> 10 ¹⁰ Ω				
Contact Resistance	< 5mΩ				
Mating Cycles	Silver ≥ 500; Gold ≥1000				
Flammability	UL 94 V0				
Corrosion Resistance	N/A	N/A	720h (Salt Spray)		N/A

For more information, contact: Customer Service, +1 800 394 7732, csr@amphenol-sine.com

© 2019 Amphenol Sine Systems Corporation, 44274 Morley Drive, Clinton Township MI 48036 USA. www.amphenol-sine.com. Customer Service +1 800 394 7732
 Every effort has been made to ensure that the information contained in this document is accurate at the time of publication. Specifications or information stated in this document are subject to change without notice.