


# OCS 0.64 SERIES



OCS 0.64 Series  
Male & Female Terminals

## OCS FAMILY BENEFITS

- Cavity compatible with industry standards and/or major OEM cavity preferences
- Up to 40% less material than the competition
- Wide range of crimp sizes

## 0.64 SERIES FEATURES

- Multiple index features available
  - IUR (Index Up Rear) unsealed applications
  - ISM (Index Side Middle) sealed and unsealed applications
  - IDR (Index Down Rear) sealed and unsealed applications
- Contact tongue overstress and nose protection
- High performance Copper Alloy
- One-piece terminal construction




## AVAILABLE CONFIGURATIONS

Terminal Type	Box & blade
Locking Mechanism	Tangless
Crimp Validated to	USCAR-21
Blade Size (mm)	0.64
Wire Gage Range (AWG)	25 - 18
Wire Gage Range (mm <sup>2</sup> )	0.13 - 0.80
Genders	Female & male
Sealing Options	Unsealed, matte/block sealed
Plating Options	Sn, Ag

See back page for representative part numbers and packaging dimensions.



## TEMPERATURE



## VIBRATION




## MAX CURRENT



with 0.80 mm<sup>2</sup>



## CONTACT MATING FORCE



## About Aptiv

Aptiv is a global technology company that develops safer, greener and more connected solutions enabling the future of mobility. Headquartered in Dublin, Aptiv has approximately 150,000 employees and operates 14 technical centers, as well as manufacturing sites and customer support centers in 45 countries.

Visit [aptiv.com](http://aptiv.com)




Index	Sealing	Gender	Plating	Wire size range (AWG)	Wire size range (mm <sup>2</sup> )	Part number	Other available platings
ISM	Unsealed/Matte Sealed	F	Sn	18	0.75 - 0.80	13726148	N/A
ISM	Unsealed/Matte Sealed	F	Sn	21	0.35 - 0.50	13726147	N/A
ISM	Unsealed/Matte Sealed	F	Sn	25	0.13 - 0.22	13726146	N/A
IDR	Unsealed/Matte Sealed	F	Sn	18	0.75 - 0.80	35088738	Ag
IDR	Unsealed/Matte Sealed	F	Sn	21	0.35 - 0.50	35088739	Ag
IDR	Unsealed/Matte Sealed	F	Sn	25	0.13 - 0.22	35088740	Ag
IUR	Unsealed	F	Sn	18	0.75 - 0.80	35088745	Ag
IUR	Unsealed	F	Sn	21	0.35 - 0.50	35088746	Ag
IUR	Unsealed	F	Sn	25	0.13 - 0.22	35088747	Ag
	Unsealed/Matte Sealed	M	Sn	18	0.75 - 0.8	15504520	Ag
	Unsealed/Matte Sealed	M	Sn	21	0.35 - 0.50	15504521	Ag
	Unsealed/Matte Sealed	M	Sn	25	0.13 - 0.22	15504522	Ag

Please, refer to the OCS catalogue for the full part number list.

## TEMP RISE CURVE


### OCS 0.64 Series ISM Female Terminal



Aptiv taxi: ISM: 13756466  
 IDR: Sn - 13887649, Ag - 13919105  
 IUR: Sn, Ag - 13767042  
 Cable range: 0.13 - 0.80 mm<sup>2</sup>

\* For reference only

### OCS 0.64 Series IDR IUR Female Terminal



Crimp method: Standard  
 Contact plating: Sn  
 Test method: Single circuit in free air\*  
 Mated to: Compliant header

The test data was collected from single circuits in a draft free enclosure. This model does not account for all of the variables that would be present in an actual application.

For additional detailed product performance, visit our website at [aptiv.com](http://aptiv.com)

## COMPATIBLE WITH



Part numbers, specifications, dimensions and performance data in this document are for general references only and are subject to change without notice. To verify product information, please contact an Aptiv representative.

CS-SP82-OCS-En0119

• **APTIV** •

[aptiv.com](http://aptiv.com) | © 2019 Aptiv. All rights reserved