


# MIL PRF 32535 BME X7R MLCC

Defense Logistics Agency Approved



KYOCERA AVX has been approved by the Defense Logistics Agency (DLA) for its qualification of its Mil Prf 32535 BME X7R MLCC technology. Using its leading edge technology KYOCERA AVX can now offer Mil Prf 32535 approved capacitors from 0402 to 2220 case sizes. With capacitance & voltage ranges ranging from 2.2nF to 22μF, 16–100 volts, currently. KYOCERA AVXs Mil Prf 32535 meets the designer needs by boosting the CV range compared to the standard surface mount Mil Ranges and reduces the gap between commercial and Mil Spec product ranges while meeting the Mil reliability levels. The results of this technology has several key benefits for the Mil design engineer resulting in , ability to downsize case sizes, reducing PCB weight and allowing more efficient use of the PCB area available with the higher CV MLCCs. These surface mount components also incorporate Flexitem® , which greatly enhances resistance to any of the thermo-mechanical stress experienced by MLCCs during PCB assembly and during its life time.

## FEATURES

- “M” and “T” reliability levels available.
- Higher CV capability than standard Mil based capacitors resulting in reduced size/weight of components and saving in PCB space required.
- Flexitem® technology used as standard in range for enhanced thermo-mechanical stress resistance.
- Case sizes 0402-2220, cap values 2.2nF–22.0μF available.
- Voltages 16-100 Volts

## HOW TO ORDER


<b>M32535</b>	<b>08</b>	<b>E2</b>	<b>Z</b>	<b>226</b>	<b>K</b>	<b>R</b>	<b>M</b>	<b>B</b>
<b>Mil Spec</b> M32535	<b>Slash Sheet Number</b> 02 = 0402 03 = 0603 04 = 0805 05 = 1206 06 = 1210 07 = 1812 08 - 2220	<b>Characteristic</b> E2 (X7R ± 15%)	<b>Voltage</b> Y = 16V Z = 25V A = 50V B = 100V	<b>Capacitance</b> 682 = 6.8nF 103 = 10nF 474 = 470nF 475 = 4.7μF 226 = 22μF	<b>Tolerance</b> J = ±5% K = ±10% M = ±20%	<b>Termination</b> R = Epoxy Ni Sn/Pb	<b>Product Level</b> M = Standard T = Space Level	<b>Electrode</b> B = BME

Please note all parts are terminated with a minimum 10% Pb plating.

## DIMENSIONS

mm (inches)

Size	M3253502		M3253503		M3253504		M3253505		M3253506		M3253507		M3253508	
	0402		0603		0805		1206		1210		1812		2220	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
(L) Length	0.92 (0.036)	1.12 (0.044)	1.45 (0.057)	1.75 (0.069)	1.79 (0.069)	2.26 (0.089)	3.00 (0.118)	3.45 (0.136)	2.94 (0.116)	3.45 (0.136)	4.19 (0.165)	4.80 (0.190)	5.2 (0.208)	6.1 (0.24)
(W) Width	0.41 (0.016)	0.61 (0.024)	0.66 (0.026)	0.97 (0.038)	1.01 (0.040)	1.52 (0.060)	1.35 (0.053)	1.85 (0.073)	2.25 (0.088)	2.74 (0.108)	2.89 (0.114)	3.50 (0.138)	4.59 (0.181)	5.41 (0.213)
(T) Thickness	0.61 (0.24) Max.		0.99 (0.039) Max.		1.52 (0.060)		1.78 (0.070) Max.		2.80 (0.110) Max.		2.80 (0.110) Max.		2.80 (0.110) Max.	
(t) terminal	0.1 (0.004)	0.30 (0.012)	0.20 (0.008)	0.61 (0.024)	0.25 (0.010)	0.75 (0.030)	0.15 (0.006)	0.86 (0.034)	0.15 (0.006)	0.86 (0.034)	0.15 (0.006)	1.1 (0.042)	0.17 (0.007)	1.09 (0.043)



# MIL PRF 32535 BME X7R MLCC

Defense Logistics Agency Approved



## MIL PRF 32535 X7R APPROVED RANGE

Mil		M3253502			M3253503			M3253504			M3253505			M3253506			M3253507			M3253508			
Case Sizes		0402			0603			0805			1206			1210			1812			2220			
Code	Value	16/25V	50V	100V	16/25V	50V	100V	16/25V	50V	100V	16/25V	50V	100V	16/25V	50V	100V	16/25V	50V	100V	16/25V	50V	100V	
222	2.2 (nF)																						
272	2.7																						
332	3.3																						
392	3.9																						
472	4.7																						
562	5.6																						
682	6.8																						
822	8.2																						
103	10																						
123	12																						
153	15																						
183	18																						
223	22																						
273	27																						
333	33																						
393	39																						
473	47																						
563	56																						
683	68																						
823	82																						
104	100																						
124	120																						
154	150																						
184	180																						
224	220																						
274	270																						
334	330																						
394	390																						
474	470																						
564	560																						
684	680																						
824	820																						
105	1 (µF)																						
125	1.2																						
155	1.5																						
185	1.8																						
225	2.2																						
275	2.7																						
335	3.3																						
395	3.9																						
475	4.7																						
565	5.6																						
685	6.8																						
825	8.2																						
106	10																						
126	12																						
156	15																						
186	18																						
226	22																						