

D-Sub PushPull 9-pol M/F Cable Assemblies



Description	Links to Other Materials
-------------	--------------------------

The HARTING portfolio has been expanded to include D-Sub PushPull 9-Pin cable assemblies. HARTING's first series D-sub PushPull cable assemblies include the most common variants for a wide range of applications. This launch further strengthens our position as the innovation leader for D-Sub connectors and cable assemblies!

- [D-Sub Pushpull Cable Assemblies – B2B Shop](#)

Specs			
-------	--	--	--

- | | | | |
|--------------------------------|--------------|-----------------------|----------|
| ■ Protection rating: | IP30 | ■ Cable jacket color: | Grey |
| ■ Operating temperature range: | -40C to +80C | ■ Core Structure: | AWG 26/7 |
| ■ Shielding: | Shielded | ■ Voltage rating: | 300V |
| ■ Cable jacket material: | PVC/PUR | ■ Current Rating: | 6.5A |

Markets	
---------	--

- | | |
|----------------------|------------------------|
| ■ Transportation | ■ Robotics |
| ■ Machinery | ■ Smart Infrastructure |
| ■ Control Technology | ■ Automation |

Applications

- | |
|------------------------------|
| ■ Railway and Transportation |
| ■ Semiconductor Tools |
| ■ Signal and Data |

Feature	Advantage	Benefit
---------	-----------	---------

- | | | |
|--------------------------------------------------------------------|------------------------------------------------------------------|----------------------------------------------------------------------------------|
| ■ True PushPull locking functionality | ■ Removes manually screw lock, enabling quick, secure connection | ■ Reduces installation and maintenance time by up to 50%, no extra tooling costs |
| ■ Shock and vibration proof as per IEC 61373 – Category 1, Class B | ■ Ideal for use in demanding industrial environments | ■ Versatility across wide range of applications |
| ■ Backwards compatible locking pins | ■ Existing D-sub mating can be easily upgraded (retrofit) | ■ Additional flexibility |