

SPE Switch IP67 Ha-VIS eCon 4017GBT MXT-SPE



Description

We are pleased to announce to you the product launch of the new SPE Switches to support in migrating to the future technology of Single Pair Ethernet.

Up to 7 SPE End-devices can be connected, and the customer can integrate Sub-networks with SPE Devices in their application.

Links to Other Materials

- [20776170000](#)
- [20776350000](#)
- [T1 Industrial](#)
- [SPE Overview](#)

Specs

- | | | |
|--|---|---|
| <ul style="list-style-type: none"> ■ IP65/67 ■ SPE Integrated ■ 100Base-T1 ■ Gigabit options | <ul style="list-style-type: none"> ■ Robust Metal Housing ■ Standardized PushPull locking ■ Flat and compact design ■ acc. to IEC 63171-6 | <ul style="list-style-type: none"> ■ -40...+70C ■ Frame Size – 10.24 kB ■ Surge protection ■ MTBF = ~680k h |
|--|---|---|

Markets

- | | |
|--|--|
| <ul style="list-style-type: none"> ■ Machinery ■ Railway | <ul style="list-style-type: none"> ■ Robotics ■ Automation |
|--|--|

Applications

- | | |
|---|--|
| <ul style="list-style-type: none"> ■ Rolling stock ■ Bus ■ Driver information system | <ul style="list-style-type: none"> ■ Gigabit backbone ■ Agriculture machinery ■ Camera systems ■ Material handling |
|---|--|

Feature

Advantage

Benefit

- | | | |
|--|---|--|
| <ul style="list-style-type: none"> ■ M12 interface | <ul style="list-style-type: none"> ■ IP65/67 sealing | <ul style="list-style-type: none"> ■ Possibilities to use outside of cabinets – at edge level |
| <ul style="list-style-type: none"> ■ PushPull Locking | <ul style="list-style-type: none"> ■ Tools less and tactile installation | <ul style="list-style-type: none"> ■ Reduces errors and downtime |