

MIXED SIGNAL/POWER
CONTACT SIZE

MULTI-CON-X[®]



Switchcraft[®]
CONXALL[®]

HARSH ENVIRONMENT CONNECTIVITY SOLUTIONS



NEW
7 POS VERSION!

The Multi-Con-X® from Conxall® set the standard for harsh environment connectors, and this new configuration adds incredible flexibility. Two or three #12 contacts provide up to 23A of power, while #26 contacts provide the flexibility needed for signal, all within a single, compact connector. Custom, factory overmolded cable assemblies are also available from Conxall.

IP68
WATERPROOF
SEALED

The Multi-Con-X® Insta-Click® series is sealed to IP68 when mated (Bayonet version is sealed to IP67)


UL F1 RATED
UV RESISTANCE

High quality PBT Thermoplastic is intended to withstand outdoor environments and UV lighting.


CONXALL
QUALITY

Made in USA to the high standards that have made Conxall the leading name in harsh environment connectors.

SPECIFICATIONS

Lifecycles: 300 cycles min.
Operating Temp: -40°C to 85°C
Flame Rating: UL94HB
Shell (Insulator): Thermoplastic (PBT)
Grommet/ Strain Relief: Elastomer
Contacts: Gold plated copper alloy
Voltage Rating: 300V RMS

Ordering Code

