

WE-Series - Sensor Element with Wire Extensions

Temperature range -70 °C to +500 °C

Performance Characteristics

- Fast response time
- Excellent long-term stability
- High accuracy and interchangeability
- Reliable laser weld connection
- According to DIN EN 60751

Application Examples

- HVAC
- Chromatographs
- Process industry
- Various use as pre-finished sensor




Image for illustration purposes only

Dimensions and Materials

No.	Product Type	Element Nominal Resistance R_0 [Ω]	Dimensions and Tolerances (mm)					Conductor		Order Number
			L	W	H	WL	LØ	Material	Diameter	
1	M222-WE-200	Pt100 / F 0.3	2.3 +0.2 -0.1	2.1 ±0.2	0.9 +0.3 -0.2	200 ±2	0.2 ±0.02	Ni (99.6 %)	AWG32	5157675
2	M222-WE-200	Pt1000 / F 0.3	2.3 +0.2 -0.1	2.1 ±0.2	0.9 +0.3 -0.2	200 ±2	0.2 ±0.02	Ni (99.6 %)	AWG32	30200145
3	M310-WE-60	Pt1000 / F 0.3	3.0 ±0.15	1.0 ±0.15	0.8 +0.3 -0.2	60 ±2	0.15 ±0.02	Ni (99.6 %)	AWG32	5157677
4	M310-WE-200	Pt1000 / F 0.3	3.0 ±0.15	1.0 ±0.15	0.8 +0.3 -0.2	200 ±2	0.15 ±0.02	Ni (99.6 %)	AWG32	5157676

WE-Series - Sensor Element with Wire Extensions

Temperature range -70 °C to +500 °C

Performance Data

No.	Temperature Range	Response Time Water (v = 0.4 m/s)		Response Time Air (v = 2.0 m/s)		Pull Force [N]	Conductor Resistance [Ω/m]	Application
		T0.5 [s]	T0.9 [s]	T0.5 [s]	T0.9 [s]			
1	-70 °C to +500 °C	0.05	0.15	3	10	9	2.546	Multi-Purpose
2	-70 °C to +500 °C	0.05	0.15	3	10	9	2.546	Multi-Purpose
3	-70 °C to +500 °C	0.04	0.12	2.5	8	7	2.546	Multi-Purpose
4	-70 °C to +500 °C	0.04	0.12	2.5	8	7	2.546	Multi-Purpose

Temperature Coefficient

TCR = 3850 ppm/K

Measuring Current

Pt100 Ω: 0.3 to 1.0 mA
Pt1000 Ω: 0.1 to 0.3 mA
(self-heating has to be considered)

Self-Heating (Sensor Element)

0.4 K/mW at 0 °C

Storage Life

Min. 12 months (in original packaging)

Customization Options

- Sensor element (type and resistance)
- Wire extension length
- Wire material
- Certifications (e.g. IMDS, PPAP, IP rating)

Need more information?
Check out our
Sensor Academy!



The information provided in this data sheet describes certain technical characteristics of the product, but shall not be qualified or construed as quality guarantee (Beschaffenheitsgarantie) in the meaning of sections 443 and 444 German Civil Code. The information provided in this data sheet regarding measurement values (including, but not limited to, response time, long-term stability, vibration and shock resistance, insulation resistance and self-heating) are average values that have been obtained under laboratory conditions in tests of large numbers of the product. Product results or measurements achieved by customer or any other person in any production, test, or other environment may vary depending on the specific conditions of use. YAGEO Nexensos does not recommend the use of standard catalogue products or automotive grades for aerospace applications or manned space flight. The customer is solely responsible to determine whether the product is suited for the customer's intended use; in this respect YAGEO Nexensos cannot assume any liability. The sale of any products by YAGEO Nexensos is exclusively subject to the General Terms of Sale and Delivery of YAGEO Nexensos in their current version at the time of purchase, which is available under www.yageo-nexensos.com/tc or may be furnished upon request. This data sheet is subject to changes without prior notice.