

THE NEW VALUE FRONTIER



***Crystal Devices***  
***2018***



**KYOCERA Corporation**

Products		Dimensions (mm)			Applications					Frequency Range (MHz)				Conditions of Use				RoHS* Compliant		
Product Type	Part Number	L	W	T (max.)	Digital Electronics OA, PC Peripherals Amusement	Car Electronics ITS Car Audio Car Navigation	Car Electronics (ECU, Air Bag, ABS, TPMS etc.)	Mobile Comm. Wireless LAN Dedicated Short Range Comm. (DSRC)	Industrial Use (Broadcast, Medical, Base Station etc.)	1	10	50	100	300 to 900	Solder				Washable	
										Manual	Reflow	Flow	Manual	Reflow	Flow	Washable				
kHz Range Crystal Devices	ST2012SB (Tuning Fork Units)	2.0	1.2	0.6	○	○	○	○	○	○	○	○	○	○	Yes	Yes	No	TBA	Yes	
	ST3215SB (Tuning Fork Units)	3.2	1.5	0.9	○	○	○	○	○	○	○	○	○	○	Yes	Yes	No	TBA	Yes	
	KC2520B (Divided Down AT Cut Crystal Oscillators)	2.5	2.0	0.7	○	○	○	○	○	○	○	○	○	○	Yes	Yes	No	Yes	Yes	
	KC2520M (Divided Down AT Cut Crystal Oscillators)	2.5	2.0	0.7	○	○	○	○	○	○	○	○	○	○	Yes	Yes	No	Yes	Yes	
	KC3215A (Clock Oscillator)	3.2	1.5	1.0	○	○	○	○	○	○	○	○	○	○	TBA	Yes	No	No	Yes	
	KT3225T (DTCXO)	3.2	2.5	1.0	○	○	○	○	○	○	○	○	○	○	TBA	Yes	No	No	Yes	
	KR3225Y (Real Time Clock Module)	3.2	2.5	1.0	○	○	○	○	○	○	○	○	○	○	TBA	Yes	No	No	Yes	
Crystal Units	CT1612DB	1.6	1.2	0.65	○	○	○	○	○	○	○	○	○	38.4-----76.8	Yes	Yes	No	Yes	Yes	
	CT2016DB (Low Profile)	2.0	1.6	0.65	○	○	○	○	○	○	○	○	○	19.2-----60	Yes	Yes	No	Yes	Yes	
	CT2016DB	2.0	1.6	1.0	○	○	○	○	○	○	○	○	○	19.2-----60	Yes	Yes	No	Yes	Yes	
	CT2520DB	2.5	2.0	1.0	○	○	○	○	○	○	○	○	○	16-----60	Yes	Yes	No	Yes	Yes	
	CX1008SB	1.0	0.8	0.30	○	○	○	○	○	○	○	○	○	37.4-----80	Yes	Yes	No	Yes	Yes	
	CX1210DB	1.2	1.0	0.30	○	○	○	○	○	○	○	○	○	37.4-----80	Yes	Yes	No	Yes	Yes	
	CX1210SB	1.2	1.0	0.35	○	○	○	○	○	○	○	○	○	27.12 32	Yes	Yes	No	Yes	Yes	
	CX1612DB (for Consumer Products)	1.6	1.2	0.40	○	○	○	○	○	○	○	○	○	26-----60	Yes	Yes	No	Yes	Yes	
	CX1612DB (Mobile Communication)	1.6	1.2	0.33	○	○	○	○	○	○	○	○	○	37.4-----60	Yes	Yes	No	Yes	Yes	
	CX2016DB	2.0	1.6	0.45	○	○	○	○	○	○	○	○	○	16-----60	Yes	Yes	No	Yes	Yes	
	CX2016GR (for Automotive)	2.0	1.6	0.8	○	○	○	○	○	○	○	○	○	16-----60	Yes	Yes	No	Yes	Yes	
	CX2016SA (for Automotive)	2.0	1.6	0.5	○	○	○	○	○	○	○	○	○	16-----60	Yes	Yes	No	Yes	Yes	
	CX2520DB	2.5	2.0	0.55	○	○	○	○	○	○	○	○	○	12-----54	Yes	Yes	No	Yes	Yes	
	CX3225GA	3.2	2.5	0.95	○	○	○	○	○	○	○	○	○	8-----54	Yes	Yes	No	Yes	Yes	
	CX3225CA	3.2	2.5	0.9	○	○	○	○	○	○	○	○	○	12-----54	Yes	Yes	No	Yes	Yes	
	CX3225GB	3.2	2.5	0.9	○	○	○	○	○	○	○	○	○	12-----54	Yes	Yes	No	Yes	Yes	
	CX3225SA	3.2	2.5	0.8	○	○	○	○	○	○	○	○	○	8-----54	Yes	Yes	No	Yes	Yes	
	CX3225SB (for GPS)	3.2	2.5	0.6	○	○	○	○	○	○	○	○	○	19.2 26	Yes	Yes	No	Yes	Yes	
	CX3225SB (for Consumer Products, Mobile Communication)	3.2	2.5	0.6	○	○	○	○	○	○	○	○	○	12-----54	Yes	Yes	No	Yes	Yes	
	CX3225SB (for Automotive)	3.2	2.5	0.6	○	○	○	○	○	○	○	○	○	12-----54	Yes	Yes	No	Yes	Yes	
	CX5032SA	4.9	3.1	1.0	○	○	○	○	○	○	○	○	○	8-----40	Yes	Yes	No	Yes	Yes	
	CX5032SB	4.9	3.1	0.8	○	○	○	○	○	○	○	○	○	9.8-----80	Yes	Yes	No	Yes	Yes	
	CX5032GA (for Consumer Products)	5.0	3.2	1.5	○	○	○	○	○	○	○	○	○	8-----40	Yes	Yes	No	Yes	Yes	
	CX5032GA (for Automotive)	5.0	3.2	1.5	○	○	○	○	○	○	○	○	○	8-----40	Yes	Yes	No	Yes	Yes	
	CX8045GA (for Consumer Products)	8.0	4.5	2.0	○	○	○	○	○	○	○	○	○	4-----8	Yes	Yes	No	Yes	Yes	
	CX8045GA (for Automotive)	8.0	4.5	2.0	○	○	○	○	○	○	○	○	○	4-----8	Yes	Yes	No	Yes	Yes	
	Oscillators	KC2016K	2.0	1.6	0.8	○	○	○	○	○	○	○	○	○	1.5-----160	No	Yes	No	Yes	Yes
KC2520K		2.5	2.0	0.8	○	○	○	○	○	○	○	○	○	1.5-----160	No	Yes	No	Yes	Yes	
KC3225K		3.2	2.5	0.8	○	○	○	○	○	○	○	○	○	1.5-----160	No	Yes	No	Yes	Yes	
KC5032K		5.0	3.2	1.3	○	○	○	○	○	○	○	○	○	1.5-----160	No	Yes	No	Yes	Yes	
KC7050K		7.0	5.0	1.3	○	○	○	○	○	○	○	○	○	1.5-----160	No	Yes	No	Yes	Yes	
MC2016K		2.0	1.6	0.8	○	○	○	○	○	○	○	○	○	1.5-----160	No	Yes	No	Yes	Yes	
MC2520K		2.5	2.0	0.8	○	○	○	○	○	○	○	○	○	1.5-----160	No	Yes	No	Yes	Yes	
MC3225K		3.2	2.5	0.8	○	○	○	○	○	○	○	○	○	1.5-----160	No	Yes	No	Yes	Yes	
MC5032K		5.0	3.2	1.3	○	○	○	○	○	○	○	○	○	1.5-----160	No	Yes	No	Yes	Yes	
MC7050K		7.0	5.0	1.3	○	○	○	○	○	○	○	○	○	1.5-----160	No	Yes	No	Yes	Yes	
KC2016B-C1		2.0	1.6	0.65	○	○	○	○	○	○	○	○	○	○	1.5-----50	Yes	Yes	No	Yes	Yes
KC2520B-C1		2.5	2.0	0.8	○	○	○	○	○	○	○	○	○	○	1.5-----125	Yes	Yes	No	Yes	Yes
KC2520B-C2		2.5	2.0	0.8	○	○	○	○	○	○	○	○	○	○	1.5-----125-160	Yes	Yes	No	Yes	Yes
KC2520C-C1/ C2		2.5	2.0	0.8	○	○	○	○	○	○	○	○	○	○	1.5-----54	Yes	Yes	No	Yes	Yes
KC2520M		2.5	2.0	0.8	○	○	○	○	○	○	○	○	○	○	1.5-----60	Yes	Yes	No	Yes	Yes
KC3225A-C2/ C3		3.2	2.5	1.0	○	○	○	○	○	○	○	○	○	○	1.5-----125	Yes	Yes	No	Yes	Yes
KC5032A-CM		5.0	3.2	1.2	○	○	○	○	○	○	○	○	○	○	1.8-----50	Yes	Yes	No	Yes	Yes
KC5032A-C1		5.0	3.2	1.2	○	○	○	○	○	○	○	○	○	○	1.8-----50	Yes	Yes	No	Yes	Yes
KC5032A-C2		5.0	3.2	1.2	○	○	○	○	○	○	○	○	○	○	1.8-----135	Yes	Yes	No	Yes	Yes
KC5032A-C5		5.0	3.2	1.2	○	○	○	○	○	○	○	○	○	○	1.8-----135-170	Yes	Yes	No	Yes	Yes
KC5032E-C3		5.0	3.2	1.3	○	○	○	○	○	○	○	○	○	○	1.8-----50	Yes	Yes	No	Yes	Yes
KC7050A-C1		7.0	5.0	1.8	○	○	○	○	○	○	○	○	○	○	1.8-----14	Yes	Yes	No	Yes	Yes
KC7050A-C2		7.0	5.0	1.8	○	○	○	○	○	○	○	○	○	○	1.8-----39.99	Yes	Yes	No	Yes	Yes
KC7050A-C3		7.0	5.0	1.8	○	○	○	○	○	○	○	○	○	○	1.8-----125	Yes	Yes	No	Yes	Yes
KC7050A-C5		7.0	5.0	1.8	○	○	○	○	○	○	○	○	○	○	1.8-----170	Yes	Yes	No	Yes	Yes
KC7050A-C5		7.0	5.0	1.8	○	○	○	○	○	○	○	○	○	○	1.8-----50	Yes	Yes	No	Yes	Yes
KC7050B (FXO-37FNB)		7.0	5.0	2.0	○	○	○	○	○	○	○	○	○	○	1.8-----80	Yes	Yes	No	No	Yes
KC3225L-P2/ P3		3.2	2.5	1.1	○	○	○	○	○	○	○	○	○	○	25-----170	Yes	Yes	No	Yes	Yes
KC5032L-P2/ P3		5.0	3.2	1.65	○	○	○	○	○	○	○	○	○	○	25-----170	Yes	Yes	No	Yes	Yes
KC5032P-P2/ P3		5.0	3.2	1.3	○	○	○	○	○	○	○	○	○	○	25-----175	Yes	Yes	No	Yes	Yes
KC7050P-P2/ P3		7.0	5.0	1.8	○	○	○	○	○	○	○	○	○	○	25-----175	Yes	Yes	No	Yes	Yes
KC5032R		5.0	3.2	1.2	○	○	○	○	○	○	○	○	○	○	10-----900	Yes	Yes	No	Yes	Yes
KC5032G		5.0	3.2	1.2	○	○	○	○	○	○	○	○	○	○	10-----900	Yes	Yes	No	Yes	Yes
KC7050L-P2/ P3		7.0	5.0	1.8	○	○	○	○	○	○	○	○	○	○	25-----170	Yes	Yes	No	Yes	Yes
KC7050R-P3		7.0	5.0	1.8	○	○	○	○	○	○	○	○	○	○	10-----900	Yes	Yes	No	Yes	Yes
KC7050G-P3		7.0	5.0	1.8	○	○	○	○	○	○	○	○	○	○	10-----900	Yes	Yes	No	Yes	Yes
KC3225L-L2/ L3		3.2	2.5	1.15	○	○	○	○	○	○	○	○	○	○	25-----170	Yes	Yes	No	Yes	Yes
KC5032L-L2/ L3		5.0	3.2	1.65	○	○	○	○	○	○	○	○	○	○	25-----170	Yes	Yes	No	Yes	Yes
KC5032P-L2/ L3		5.0	3.2	1.3	○	○	○	○	○	○	○	○	○	○	25-----175	Yes	Yes	No	Yes	Yes
KC7050L-L2/ L3		7.0	5.0	1.8	○	○	○	○	○	○	○	○	○	○	25-----170	Yes	Yes	No	Yes	Yes
KC7050P-L2/ L3		7.0	5.0	1.8	○	○	○	○	○	○	○	○	○	○	25-----175	Yes	Yes	No	Yes	Yes



2.0x1.2mm for Consumer/ Mobile Equipment



RoHS Compliant

**Features**

- Ultra Small, Low Profile
- Ceramic Package
- Reflow Compatible

**Applications**

- Consumer/ Mobile Equipment

**How to Order**

ST2012SB 32768 □□ H P W □□  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency 32.768kHz
- ③ Load Capacitance
- ④ Frequency Tolerance

<b>H5</b>	12.5 pF	Std.
<b>E0</b>	9.0 pF	
<b>C0</b>	7.0 pF	
<b>B0</b>	6.0 pF	
<b>A0</b>	5.0 pF	
<b>Z0</b>	4.0 pF	

<b>H</b>	$\pm 20 \times 10^{-6}$
----------	-------------------------

- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability

<b>P</b>	-40 to +85°C
----------	--------------

<b>W</b>	$\pm 200 \times 10^{-6}$
----------	--------------------------

- ⑦ Individual Specification


Packaging (Tape & Reel 3000/ 12000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Nominal Frequency	f <sub>nom</sub>	32.768	kHz	
Frequency Tolerance	f <sub>tol</sub>	±20	×10 <sup>-6</sup>	25°C±3°C
Turnover Temperature	T <sub>i</sub>	+25±5	°C	
Parabolic Coefficient	B	-0.04 max.	×10 <sup>-6</sup> / °C <sup>2</sup>	
Motional Resistance	R <sub>1</sub>	80 max.	k-ohm	
Motional Capacitance	C <sub>1</sub>	5.8 typ.	fF	
Shunt Capacitance	C <sub>0</sub>	1.3 typ.	pF	
Load Capacitance	CL	4.0/ 5.0/ 6.0/ 7.0/ 9.0/ 12.5	pF	Please contact us for other Load Capacitance.
Drive Level	DL	0.1	μW	0.5 max.
Operating Temp. Range	T <sub>use</sub>	-40 to +85	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +85	°C	
Frequency Aging	f <sub>age</sub>	±3	×10 <sup>-6</sup>	


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)





3.2×1.5mm for Consumer/ Mobile Equipment/ Automotive



RoHS Compliant

**Features**

- Small, Low Profile
- Ceramic Package
- Reflow Compatible
- AEC-Q200 qualified

**Applications**

- Consumer/ Mobile Equipment
- Car navigation system
- Car audio system

**How to Order**

ST3215SB 32768 □□ □ P W □□  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency 32.768kHz
- ③ Load Capacitance
- ④ Frequency Tolerance

<b>H5</b>	12.5 pF	Std.
<b>E0</b>	9.0 pF	
<b>C0</b>	7.0 pF	
<b>B0</b>	6.0 pF	
<b>A0</b>	5.0 pF	
<b>Z0</b>	4.0 pF	

<b>F</b>	±10×10 <sup>-6</sup>
<b>H</b>	±20×10 <sup>-6</sup>

- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability

<b>P</b>	-40 to +85°C
----------	--------------

<b>W</b>	±200×10 <sup>-6</sup>
----------	-----------------------

- ⑦ Individual Specification


Packaging (Tape & Reel 3000/ 10000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Nominal Frequency	f <sub>nom</sub>	32.768	kHz	
Frequency Tolerance	f <sub>tol</sub>	±10, ±20	×10 <sup>-6</sup>	25°C±3°C
Turnover Temperature	T <sub>i</sub>	+25±5	°C	
Parabolic Coefficient	B	-0.04 max.	×10 <sup>-6</sup> / °C <sup>2</sup>	
Motional Resistance	R <sub>1</sub>	70 max.	k-ohm	
Motional Capacitance	C <sub>1</sub>	3.7 typ.	fF	
Shunt Capacitance	C <sub>0</sub>	0.9 typ.	pF	
Load Capacitance	CL	4.0/ 5.0/ 6.0/ 7.0/ 9.0/ 12.5	pF	Please contact us for other Load Capacitance.
Drive Level	DL	0.1	μW	0.5 max.
Operating Temp. Range	T <sub>use</sub>	-40 to +85	°C	
Storage Temp. Range	T <sub>stg</sub>	-55 to +85	°C	
Frequency Aging	f <sub>age</sub>	±3	×10 <sup>-6</sup>	


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



CMOS/ 1.8V ~ 5.0V/ 2.5×2.0mm



RoHS Compliant

**Features**

- Miniature ceramic package  
2.5 (L) × 2.0 (W) × 0.7 (H) mm (Typ.)
- Highly reliable with seam welding
- CMOS output
- Supply voltage 1.8/ 2.5/ 3.3/ 5.0V  
Wide operating voltage range 1.6 to 5.5V
- Low current consumption

**Applications**

- Consumer/ Mobile Equipment

**How to Order**

**KC2520B 32K7680 C M 2 E 00**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency (32.768kHz)
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V, 2.5V, 3.3V, 5.0V Compatible)
- ⑤ Frequency Tolerance (See Specifications)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Specifications		Units
			Min.	Max.	
Output Frequency Range	fo		32.768		kHz
Frequency Tolerance	f <sub>tol</sub>	Initial (25°C), Stability (-40 to 85°C), Voltage change	-25	+25	×10 <sup>-6</sup>
		Aging (@1year)	-3	+3	
		Other (load change, shock and vibration)	-4	+4	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C
Operating Temperature Range	T <sub>use</sub>		-40	+85	°C
Max. Supply Voltage	—		-0.3	+7.0	V
Supply Voltage	V <sub>CC</sub>		+1.6	+5.5	V
Current Consumption (Maximum Loaded/ 1.6≤V <sub>CC</sub> ≤2.0V)	I <sub>CC</sub>		—	120	μA
Current Consumption (Maximum Loaded/ 2.0<V <sub>CC</sub> ≤2.8V)			—	126	
Current Consumption (Maximum Loaded/ 2.8≤V <sub>CC</sub> ≤3.63V)			—	130	
Current Consumption (Maximum Loaded/ 3.63≤V <sub>CC</sub> ≤5.5V)			—	140	
Stand-by Current	I <sub>std</sub>		—	10	μA
Symmetry	SYM	@50% V <sub>CC</sub>	45	55	%
Rise/ Fall Time (10% V <sub>CC</sub> to 90% V <sub>CC</sub> Maximum Loaded)	tr/ tf		—	50	ns
Low Level Output Voltage	V <sub>OL</sub>	I <sub>OL</sub> = 1mA	—	10% V <sub>CC</sub>	V
High Level Output Voltage	V <sub>OH</sub>	I <sub>OH</sub> = -1mA	90% V <sub>CC</sub>	—	
Output Load	L <sub>CMOS</sub>	CMOS Output	—	15	pF
Low Level Input Voltage	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>CC</sub>	—	
Disable Time	t <sub>dis</sub>		—	100	ns
Enable Time	t <sub>ena</sub>		—	2	ms
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	5	ms

Note: All electrical characteristics are defined at the maximum load and operating temperature range.


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



CMOS/ 1.8V ~ 5.0V/ 2.5×2.0mm for Automotive



RoHS Compliant

**Features**

- Miniature ceramic package  
2.5 (L) × 2.0 (W) × 0.7 (H) mm (Typ.)
- Highly reliable with seam welding
- CMOS output
- Supply voltage 1.8/ 2.5/ 3.3/ 5.0V  
Wide operating voltage range 1.6 to 5.5V
- Low current consumption
- AEC-Q100/ 200 qualified

**Applications**

- Car accessory

**How to Order**

**KC2520M 32K7680 C M 3 E 00**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency (32.768kHz)
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V, 2.5V, 3.3V, 5.0V Compatible)
- ⑤ Frequency Tolerance (See Specifications)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Specifications		Units
			Min.	Max.	
Output Frequency Range	fo		32.768		kHz
Frequency Tolerance	f <sub>tol</sub>	Initial (25°C), Stability (-40 to 125°C), Voltage change	-90	+90	×10 <sup>-6</sup>
		Aging (@1year)	-3	+3	
		Other (load change, shock and vibration)	-4	+4	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C
Operating Temperature Range	T <sub>use</sub>		-40	+125	°C
Max. Supply Voltage	—		-0.3	+7.0	V
Supply Voltage	V <sub>CC</sub>		+1.6	+5.5	V
Current Consumption (Maximum Loaded/ 1.6≤V <sub>CC</sub> ≤2.0V)	I <sub>CC</sub>		—	150	μA
Current Consumption (Maximum Loaded/ 2.0<V <sub>CC</sub> ≤2.8V)			—	158	
Current Consumption (Maximum Loaded/ 2.8≤V <sub>CC</sub> ≤3.63V)			—	163	
Current Consumption (Maximum Loaded/ 3.63≤V <sub>CC</sub> ≤5.5V)			—	175	
Stand-by Current	I <sub>std</sub>		—	10	μA
Symmetry	SYM	@50% V <sub>CC</sub>	45	55	%
Rise/ Fall Time (10% V <sub>CC</sub> to 90% V <sub>CC</sub> Maximum Loaded)	tr/ tf		—	50	ns
Low Level Output Voltage	V <sub>OL</sub>	I <sub>OL</sub> = 0.8mA	—	10% V <sub>CC</sub>	V
High Level Output Voltage	V <sub>OH</sub>	I <sub>OH</sub> = -0.8mA	90% V <sub>CC</sub>	—	V
Output Load	L <sub>CMOS</sub>	CMOS Output	—	15	pF
Low Level Input Voltage	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>CC</sub>	—	V
Disable Time	t <sub>dis</sub>		—	100	ns
Enable Time	t <sub>ena</sub>		—	2	ms
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	5	ms

Note: All electrical characteristics are defined at the maximum load and operating temperature range.


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



CMOS/ 3.3V Typ./ 3.2×1.5mm



RoHS Compliant

**Features**

- Output frequency: 32.768kHz
- Miniature and Low profile ceramic package
- Wide operating voltage range 1.5V to 3.6V
- CMOS output
- Operating Temp. -40 to +105°C (option)
- AEC-Q200 qualified
- V<sub>IO</sub> controls amplitude.

**Applications**

- W-LAN etc.

**How to Order**

**KC3215A 32768 C 33 A A E 00**  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series
  - ② Output Frequency
  - ③ Output type
  - ④ Supply Voltage
  - ⑤ Frequency Tolerance
  - ⑥ Freq. Temp. Chrst.
  - ⑦ Output Waveform Symmetric
  - ⑧ Individual Specification
- 33** 3.3V  
**A** +10/-120×10<sup>-6</sup>  
**E** 45 to 55%  
**A** 5±23×10<sup>-6</sup> **00** STD Specification

Packaging (Tape & Reel 3000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Specifications			Units
			Min.	Typ.	Max.	
Output Frequency Range	f <sub>o</sub>	Standard Frequency	—	32.768	—	kHz
Frequency Tolerance	f <sub>tol</sub>	after 2times Reflow, V <sub>CC</sub> = 3.3V, T <sub>a</sub> = 25±2°C	-18	+5	+28	×10 <sup>-6</sup>
Frequency Temperature Characteristics	f <sub>o</sub> -T <sub>c</sub>	T <sub>a</sub> = -20 to +70°C (+25°C is reference)	-120	—	+10	×10 <sup>-6</sup>
Frequency Voltage Coefficient	f <sub>o</sub> -V	T <sub>a</sub> = +25±2°C	-2.0	—	2.0	×10 <sup>-6</sup> /V
Frequency Aging	F <sub>age</sub>	Per Year	-3.0	—	3.0	×10 <sup>-6</sup>
Storage Temperature	T <sub>stg</sub>		-55	—	+125	°C
Operating Temperature	T <sub>use</sub>		-40	—	+85	°C
Supply Voltage	V <sub>DD</sub>		1.5	—	3.6	V
Interface Power Supply Voltage	V <sub>IO</sub>		1.5	—	3.6	V
Current Consumption	I <sub>CC</sub>	No load, V <sub>DD</sub> = 3.3V, V <sub>IO</sub> = 3.3V	—	0.9	1.5	μA
		load: 15pF, V <sub>DD</sub> = 3.3V, V <sub>IO</sub> = 3.3V	—	2.2	4.2	μA
Symmetry	SYM	@50% V <sub>IO</sub>	45	—	55	%
Rise/ Fall Time	tr/ tf	load: 15pF, 20%V <sub>IO</sub> to 80%V <sub>IO</sub>	—	—	50	ns
Low Output Voltage	V <sub>OL</sub>	I <sub>OL</sub> = +0.4mA	—	—	0.4	V
High Output Voltage	V <sub>OH</sub>	I <sub>OH</sub> = -0.4mA	V <sub>IO</sub> -0.4	—	—	V
CMOS Load	L <sub>CMOS</sub>	CMOS Output	—	—	15	pF
Disable Delay Time	t <sub>dis</sub>		—	—	1.0	μs
Start-up Time	t <sub>str</sub>	Time at minimum Supply voltage to be 0 s	—	—	0.6	sec

\* Unless otherwise stated, characteristics(specifications) shown in the above table are based on the rated operating temperature and voltage condition.  
 \* Please contact us for other specifications.


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)





CMOS/ 3.0V Typ./ 3.2×2.5mm



RoHS Compliant

**Features**

- Miniature SMD type (3.2×2.5×1.0mm)
- 32.768kHz D-TCXO
- High frequency stability : ±5.0×10<sup>-6</sup>/ -40 to +85°C
- Low supply current : 1.5µA typ (V<sub>DD</sub> = 3.0V, Output at no load)
- Temperature compensated voltage Range : 2.0V to 5.5V
- Operating Temp. -40 to +105°C (option)
- AEC-Q200 qualified

**Applications**

- High accuracy time references
- Microcontroller with built in RTC

**How to Order**

Frequency Tolerance (vs Temp.) : ±3.8×10<sup>-6</sup>/ -10°C to 60°C

KT3225T 32768 D G R □ □ T xx  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

Frequency Tolerance (vs Temp.) : ±5.0×10<sup>-6</sup>/ -40°C to 85°C

KT3225T 32768 E A W □ □ T xx  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series
- ② Output Frequency
- ③ Frequency Stability
- ④ Lower Temperature
- ⑤ Upper Temperature

	③	④	⑤
DGR	±3.8×10 <sup>-6</sup>	-10°C	+60°C
EAW	±5.0×10 <sup>-6</sup>	-40°C	+85°C

- ⑥ Supply Voltage
- ⑦ Initial Frequency Tolerance

30	3.0V	T	±3.0×10 <sup>-6</sup>
33	3.3V		
50	5.0V		

- ⑧ Individual Specification

Packaging (Tape & Reel 3000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Specifications			Units
			Min.	Typ.	Max.	
Nominal Frequency	f <sub>nom</sub>		—	32.768	—	kHz
Oscillation Output Voltage	V <sub>DD</sub>		1.3	3.0	5.5	V
Temperature Compensated Voltage	V <sub>TEM</sub>		2.0	3.0	5.5	V
Storage Temperature	T <sub>stg</sub>		-40	+25	+85	°C
Operating Temperature	T <sub>use</sub>		-40	+25	+85	°C
Initial Frequency Tolerance	—	Ta = 25±2°C	-3.0	—	+3.0	×10 <sup>-6</sup>
Frequency Stability vs Temp.	fo-Tc	E : Ta = -40 to +85°C	-5.0	—	+5.0	×10 <sup>-6</sup>
Frequency Stability vs Supply Voltage	df/ fo	V <sub>DD</sub> = 2.0 to 5.5V, Ta = 25±2°C	-1.0	—	+1.0	×10 <sup>-6</sup> / V
Frequency Aging	f <sub>age</sub>		-3.0	—	+3.0	×10 <sup>-6</sup>
Low Level Output Voltage	V <sub>OL</sub>	I <sub>OL</sub> = +1.0mA, V <sub>DD</sub> = 3V	0.0	—	0.8	V
High Level Output Voltage	V <sub>OH</sub>	I <sub>OH</sub> = -1.0mA, V <sub>DD</sub> = 3V	2.2	—	3.0	V
Low Level Input Voltage	V <sub>IL</sub>	CLKOE pin	0.0	—	0.2×V <sub>DD</sub>	V
High Level Input Voltage	V <sub>IH</sub>	CLKOE pin	0.8×V <sub>DD</sub>	—	5.5	V
DUTY Ratio	Duty	CL = 15pF	40	—	60	%
Rise Time	tr	20%V <sub>DD</sub> →80%V <sub>DD</sub> , CL = 15pF, V <sub>DD</sub> = 3V	—	—	100	ns
Fall Time	tf	80%V <sub>DD</sub> →20%V <sub>DD</sub> , CL = 15pF, V <sub>DD</sub> = 3V	—	—	100	ns
Start-up Time	t <sub>str</sub>	Ta = 25°C	—	—	1.0	sec
		Ta = -40 to 85°C	—	—	3.0	sec
Power Supply Current1	I <sub>cc1</sub>	CLKOE = V <sub>SS</sub> , V <sub>DD</sub> = 3V	—	0.6	2.0	µA
Power Supply Current2	I <sub>cc2</sub>	CLKOE = V <sub>DD</sub> , V <sub>DD</sub> = 3V, Output at no load	—	1.5	4.0	µA
		CLKOE = V <sub>DD</sub> , V <sub>DD</sub> = 3V, CL = 15pF	—	2.7	5.5	µA
Output Load Condition	L <sub>CMOS</sub>	CMOS Output	—	—	15.0	pF

\* Please contact us for other specifications.


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)







Tape & Reel Specifications


■ kHz Range Crystal Units

■ kHz Range Crystal Oscillators


■ Real Time Clock Modules

	ST2012SB		ST3215SB		KC2520B KC2520M	KC3215A	KT3225T	KR3225Y	
T A P E	A	2.0±0.05		2.0±0.1		2.0±0.05	2.0±0.05	2.0±0.05	2.0±0.05
	B	4.0±0.1		4.0±0.1		4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1
	C	φ1.5+0.1/-0		φ1.5+0.1/-0		φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0
	D	4.0±0.1		4.0±0.1		4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1
	E	3.5±0.05		5.5±0.1		3.5±0.05	3.5±0.05	3.5±0.05	3.5±0.05
	F	1.75±0.1		1.75±0.1		1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1
	G	8.0±0.2		12.0±0.3		8.0±0.2	8.0±0.3	8.0±0.3	8.0±0.3
	H	φ1.0+0.2/-0		φ1.0+0.1/-0		φ1.1±0.1	φ1.0+0.2/-0	φ1.5+0.1/-0	φ1.5+0.1/-0
	J	2.25±0.1		3.6±0.1		2.7±0.1	3.5±0.05	3.5±0.1	3.5±0.1
	L	1.45±0.1		1.8±0.1		2.2±0.1	1.9±0.05	2.8±0.1	2.8±0.1
	N	0.75±0.1		1.0±0.1		1.0±0.1	1.1±0.05	1.1±0.1	1.1±0.1
	O	0.25±0.05		0.3±0.05		0.2±0.05	0.25±0.05	0.25±0.05	0.25±0.05
	R E E L	P	φ180+0/-1.5	φ330±2	φ180+0/-1.5	φ330±2	φ180+0/-3	φ180+0/-1.5	φ180+0/-1.5
Q		φ60+1.0/-0	φ100±1.0	φ60+1.0/-0	φ100±1.0	φ60+1/-0	φ60+1.0/-0	φ60+1.0/-0	φ60+1.0/-0
R		φ13±0.2		φ13±0.2		φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2
S		φ21±0.8		φ21±0.8		φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8
U		2.0±0.5		2.0±0.5		2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5
W		9.0+1.0/-0	9.4±1.0	13.0+1.0/-0	13.4±1.0	9.0+0.3/-0	9.0+1.0/-0	9.0+1.0/-0	9.0+1.0/-0
Qty.	3000		12000		3000	10000	2000	3000	3000

(Unit: mm)



1.6×1.2mm for Mobile Communications



RoHS対応品

**Features**

- Crystal Unit with Thermistor
- Reference frequency for telecommunication systems
- Reflow compatible
- Using ceramic package resulting in high reliability

**Applications**

- Mobile Communications, GPS

**How to Order**

CT1612DB 38400 □□ □□ □□ □□  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
  - ② Frequency
  - ③ Load Capacitance
  - ④ Frequency Tolerance
  - ⑤ Operating Temp. Range
  - ⑥ Frequency Temp. Stability
  - ⑦ Individual Specification
- |           |      |      |          |                      |      |
|-----------|------|------|----------|----------------------|------|
| <b>B0</b> | 6 pF | —    | <b>F</b> | ±10×10 <sup>-6</sup> | Std. |
| <b>C0</b> | 7 pF | —    | <b>G</b> | ±15×10 <sup>-6</sup> | —    |
| <b>D0</b> | 8 pF | Std. |          |                      |      |
- |           |               |  |
|-----------|---------------|--|
| <b>LH</b> | -30 to +105°C | ±12×10 <sup>-6</sup> (at -30 to +85°C) |
|-----------|---------------|--|

Packaging (Tape & Reel 12000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	38400 to 76800	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±10	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	10	μW	100μW max.
Operating Temp. Range	T <sub>use</sub>	-30 to +85	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +105	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±12	×10 <sup>-6</sup>	
Thermistor Resistance	—	Table 2	ohm	25°C±3°C
Thermistor B-Constant	—	Table 3	K	25°C to 50°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**

Frequency Range	Motional Series Resistance
38400 to 76800kHz	80Ω max.

**Table2 Thermistor Resistance**


Resistance	Specification
22kΩ	±1%
100kΩ	±1%

**Table3 Thermistor B-Constant**

B-Constant	Specification
3380K	±1%
4250K	±1%


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



2.0×1.6mm for Mobile Communications



RoHS Compliant

**Features**

- Crystal Unit with Thermistor
- Height 0.65 (max.) mm is also available
- Reference frequency for telecommunication systems
- Reflow compatible
- Using ceramic package resulting in high reliability

**Applications**

- Mobile Communications, GPS

**How to Order**

CT2016DB 19200 □ □ □ □ □ □ □  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
  - ② Frequency
  - ③ Load Capacitance
  - ④ Frequency Tolerance
  - ⑤ Operating Temp. Range
  - ⑥ Frequency Temp. Stability
  - ⑦ Individual Specification
- |           |      |      |          |                         |      |
|-----------|------|------|----------|-------------------------|------|
| <b>B0</b> | 6 pF | —    | <b>F</b> | $\pm 10 \times 10^{-6}$ | Std. |
| <b>C0</b> | 7 pF | Std. | <b>G</b> | $\pm 15 \times 10^{-6}$ | —    |
- |           |               |   |
|-----------|---------------|---|
| <b>PF</b> | -40 to +85°C  | $\pm 10 \times 10^{-6}$ (at -25 to +85°C) |
| <b>RH</b> | -40 to +105°C | $\pm 12 \times 10^{-6}$ (at -30 to +85°C) |

Packaging (Tape & Reel 12000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	19200 to 60000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	7	pF	
Frequency Tolerance	f <sub>tol</sub>	±10	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	10	μW	100μW max.
Operating Temp. Range	T <sub>use</sub>	-30 to +85	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +105	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±12	×10 <sup>-6</sup>	Freq. deviation from the value at 32°C
Thermistor Resistance	—	Table 2	ohm	25°C
Thermistor B-Constant	—	Table 3	K	25°C to 50°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**

Frequency Range	Motional Series Resistance
19200 to 25999kHz	80Ω max.
26000 to 29999kHz	60Ω max.
30000 to 60000kHz	50Ω max.

**Table2 Thermistor Resistance**


Resistance	Specification
100kΩ	±1%

**Table3 Thermistor B-Constant**

B-Constant	Specification
4250K	±1%


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



2.5×2.0mm for Mobile Communications/ Automotive



RoHS Compliant

**Features**

- Reference frequency for telecommunication systems
- Reflow compatible
- Using ceramic package resulting in high reliability
- AEC-Q200 qualified

**Applications**

- Mobile Communications, Bluetooth®, Wireless LAN, GPS
- Car navigation system
- Car audio system

\* Bluetooth® Trademarks are owned by Bluetooth SIG Inc.

**How to Order**

CT2520DB 19200 □□ □□ □□ □□  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance

<b>B0</b>	6 pF	—	<b>F</b>	±10×10 <sup>-6</sup>	Std.
<b>C0</b>	7 pF	Std.	<b>G</b>	±15×10 <sup>-6</sup>	—

- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability

<b>FF</b>	-20 to +70°C	±10×10 <sup>-6</sup>
<b>LH</b>	-30 to +85°C	±12×10 <sup>-6</sup>
<b>LJ</b>	-30 to +85°C	±15×10 <sup>-6</sup>

- ⑦ Individual Specification

Packaging (Tape & Reel 12000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	16000 to 60000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	7	pF	
Frequency Tolerance	f <sub>tol</sub>	±10	×10 <sup>-6</sup>	30°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	10	μW	100μW max.
Operating Temp. Range	T <sub>use</sub>	-30 to +85	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +105	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±12	×10 <sup>-6</sup>	Freq. deviation from the value at 30°C
Thermistor Resistance	—	Table 2	ohm	25°C
Thermistor B-Constant	—	Table 3	K	25°C to 50°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**

Frequency Range	Motional Series Resistance
16000 to 19199kHz	100Ω max.
19200 to 25999kHz	80Ω max.
26000 to 29999kHz	60Ω max.
30000 to 60000kHz	50Ω max.

**Table2 Thermistor Resistance**


Resistance	Specification
100kΩ	±1%

**Table3 Thermistor B-Constant**

B-Constant	Specification
4250K	±1%


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



1.0×0.8mm for Mobile Communications



RoHS Compliant

**Features**

- Ultra-miniature and low profile (1.0×0.8×0.3mm max.)
- Crystal unit for mobile communication Systems.
- Reflow compatible
- Using ceramic package resulting in high reliability

**Applications**

- Mobile Communications

**How to Order**

**CX1008SB 37400** □ □ □ □ □ □ □  
 ① ② ③ ④ ⑤ ⑥ ⑦

① Series	② Frequency
③ Load Capacitance	④ Frequency Tolerance
<b>B0</b> 6 pF —	<b>F</b> ±10×10 <sup>-6</sup> Std.
<b>C0</b> 7 pF Std.	<b>G</b> ±15×10 <sup>-6</sup> —
⑤ Operating Temp. Range	⑥ Frequency Temp. Stability
<b>LF</b> -30 to +85°C	±10×10 <sup>-6</sup>
⑦ Individual Specification	

Packaging (Tape & Reel 12000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	37400/ 80000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	7	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±10	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-30 to +85	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +105	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±10	×10 <sup>-6</sup>	

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
f <sub>nom</sub> =37400/ 80000kHz	60Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
f <sub>nom</sub> =37400/ 80000kHz	10μW (100μW max.)


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)





1.2×1.0mm for Mobile Communications



RoHS Compliant

**Features**

- Ultra-miniature and low profile (1.2×1.0×0.35mm max.)
- Crystal unit for mobile communication Systems.
- Reflow compatible
- Using ceramic package resulting in high reliability

**Applications**

- Mobile Communications, Bluetooth®, Wireless LAN

\* Bluetooth® Trademarks are owned by Bluetooth SIG Inc.

**How to Order**

CX1210SB 27120 □□ □□ □□ CC  
① ② ③ ④ ⑤ ⑥ ⑦

① Series	② Frequency
③ Load Capacitance	④ Frequency Stability
<b>B0</b> 6 pF	<b>F</b> ±10×10 <sup>-6</sup>
<b>D0</b> 8 pF	<b>G</b> ±15×10 <sup>-6</sup>
⑤ Operating Temp. Range	⑥ Frequency Temp. Stability
<b>FF</b> -20 to +70°C	±10×10 <sup>-6</sup>
<b>LJ</b> -30 to +85°C	±15×10 <sup>-6</sup>

⑦ Individual Specification (STD Specification is "CC")

Packaging (Tape & Reel 1000/ 3000/ 12000/ 21000pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	27120/ 32000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	
Frequency Tolerance	f <sub>tol</sub>	±10	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-30 to +85	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +105	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±10	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
f <sub>nom</sub> =27120kHz	100Ω max.
f <sub>nom</sub> =32000kHz	60Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
f <sub>nom</sub> =27120/ 32000kHz	10μW (100μW max.)


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



1.6×1.2mm for Consumer Products



RoHS Compliant

**Features**

- Crystal unit for Consumer Products
- Ultra-miniature and low profile
- Ceramic package
- Reflow compatible

**Applications**

- Digital Electronics
- Consumer Products
- 1seg. tuner

**How to Order**

CX1612DB 36000 □□ G E J CC  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD specification is "CC")

<b>B0</b>	6 pF	<b>G</b>	±15×10 <sup>-6</sup>
<b>D0</b>	8 pF		
<b>EJ</b>	-10 to +70°C		±15×10 <sup>-6</sup>

Packaging (Tape & Reel 3000/ 20000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	26000 to 60000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	
Frequency Tolerance	f <sub>tol</sub>	±15	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-10 to +70	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +85	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±15	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
26000 ≤ f <sub>nom</sub> < 37400 kHz	150Ω max.
37400 ≤ f <sub>nom</sub> < 50000 kHz	80Ω max.
50000 ≤ f <sub>nom</sub> ≤ 60000 kHz	50Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
26000 ≤ f <sub>nom</sub> ≤ 60000 kHz	10μW (100μW max.)


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)





2.0×1.6mm for Consumer Products/ Mobile Communications



RoHS Compliant

**Features**

- Crystal unit for Consumer Products
- Ultra-miniature and low profile (2.0×1.6×0.40mm)
- Ceramic package
- Reflow compatible

**Applications**

- Digital Electronics
- Consumer Products
- Mobile Communications, Bluetooth®, Wireless LAN

\* Bluetooth® Trademarks are owned by Bluetooth SIG Inc.

**How to Order**

**CX2016DB 27000 D0 G J CC**  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance ④ Frequency Tolerance
- ⑤ Operating Temp. Range ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Specification is "CC")

<b>D0</b>	8 pF	<b>G</b>	±15×10 <sup>-6</sup>
<b>EJ</b>	-10 to +70°C		±15×10 <sup>-6</sup>
<b>LJ</b>	-30 to +85°C		±15×10 <sup>-6</sup>

Packaging (Tape & Reel 1000/ 3000/ 15000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	16000 to 60000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±15	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-10 to +70	°C	-30 to +85
Storage Temp. Range	T <sub>stg</sub>	-40 to +85	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±15	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
16000≤f <sub>nom</sub> <18000kHz	200Ω max.
18000≤f <sub>nom</sub> <26000kHz	150Ω max.
26000≤f <sub>nom</sub> <40000kHz	60Ω max.
40000≤f <sub>nom</sub> ≤60000kHz	50Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
16000≤f <sub>nom</sub> ≤60000kHz	10μW (100μW max.)


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



2.5×2.0mm for Consumer Products/ Mobile Communications



RoHS Compliant

**Features**

- Crystal unit for Consumer Products
- Ceramic package
- Reflow compatible

**Applications**

- Digital Electronics
- Consumer Products
- Mobile Communications, Bluetooth®, Wireless LAN

\* Bluetooth® Trademarks are owned by Bluetooth SIG Inc.

**How to Order**

**CX2520DB 27000 D0 G J CC**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance    ④ Frequency Tolerance
- ⑤ Operating Temp. Range    ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Specification is "CC")

<b>D0</b>	8 pF	<b>G</b>	±15×10 <sup>-6</sup>
<b>EJ</b>	-10 to +70°C		±15×10 <sup>-6</sup>
<b>LJ</b>	-30 to +85°C		±15×10 <sup>-6</sup>

Packaging (Tape & Reel 1000/ 3000/ 12000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	12000 to 54000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±15	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-10 to +70	-30 to +85	°C
Storage Temp. Range	T <sub>stg</sub>	-40 to +85		°C
Frequency Temp. Characteristics	f <sub>tem</sub>	±15	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
12000 ≤ f <sub>nom</sub> < 16000kHz	150Ω max.
16000 ≤ f <sub>nom</sub> < 26000kHz	80Ω max.
26000 ≤ f <sub>nom</sub> < 30000kHz	60Ω max.
30000 ≤ f <sub>nom</sub> ≤ 54000kHz	50Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
12000 ≤ f <sub>nom</sub> ≤ 54000kHz	10μW (100μW max.)


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



3.2×2.5mm for Consumer Products



RoHS Compliant

**Features**

- Crystal unit for Consumer Products
- Small and low profile 0.9mm max. (3.2×2.5×0.8mm)
- Ceramic package
- Reflow compatible

**Applications**

- Digital Electronics
- Consumer Products

**How to Order**

**CX3225GB 27000 D0 H E Q CC**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Specification is "CC")

**D0** 8 pF **H** ±20×10<sup>-6</sup>

**EQ** -10 to +70°C ±30×10<sup>-6</sup>

Packaging (Tape & Reel 3000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	12000 to 54000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±20	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-10 to +70	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +85	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±30	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
12000 ≤ f <sub>nom</sub> < 13000kHz	150Ω max.
13000 ≤ f <sub>nom</sub> < 14000kHz	100Ω max.
14000 ≤ f <sub>nom</sub> < 20000kHz	80Ω max.
20000 ≤ f <sub>nom</sub> < 27000kHz	60Ω max.
27000 ≤ f <sub>nom</sub> ≤ 54000kHz	50Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
12000 ≤ f <sub>nom</sub> ≤ 54000kHz	10μW (100μW max.)


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



3.2×2.5mm for GPS



RoHS Compliant

**Features**

- Crystal unit for GPS Products
- Miniature and low profile (3.2×2.5×0.55mm)
- Ceramic package
- Reflow compatible

**Applications**

- GPS

**How to Order**

**CX3225SB 19200 DO G L J CC**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Specification is "CC")

<b>DO</b>	8 pF	<b>G</b>	±10×10 <sup>-6</sup>
<b>LJ</b>	-30 to +85°C		±15×10 <sup>-6</sup>

Packaging (Tape & Reel 1000/ 3000 pcs./ reel)


**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	19200      26000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±10	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	80      50	ohm	
Drive Level	DL	10	μW	
Operating Temp. Range	T <sub>use</sub>	-30 to +85	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +85	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±15	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



3.2×2.5mm for Consumer Products/ Mobile Communications



RoHS Compliant

**Features**

- Crystal unit for Consumer Products
- Miniature and low profile (3.2×2.5×0.55mm)
- Ceramic package
- Reflow compatible

**Applications**

- Digital Electronics
- Consumer Products
- Mobile Communications, Bluetooth®, Wireless LAN

\* Bluetooth® Trademarks are owned by Bluetooth SIG Inc.

**How to Order**

**CX3225SB 12000 DO G □ J CC**  
 ① ② ③ ④ ⑤ ⑥ ⑦

① Series	② Frequency
③ Load Capacitance	④ Frequency Tolerance
<b>DO</b> 8 pF	<b>G</b> ±15×10 <sup>-6</sup>
⑤ Operating Temp. Range	⑥ Frequency Temp. Stability

<b>EJ</b> -10 to +70°C	±15×10 <sup>-6</sup>
<b>LJ</b> -30 to +85°C	±15×10 <sup>-6</sup>

⑦ Individual Specification (STD Specification is "CC")

Packaging (Tape & Reel 3000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	12000 to 54000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±15	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-10 to +70	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +85		
Frequency Temp. Characteristics	f <sub>tem</sub>	±15	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
12000 ≤ f <sub>nom</sub> < 13000kHz	150Ω max.
13000 ≤ f <sub>nom</sub> < 20000kHz	80Ω max.
20000 ≤ f <sub>nom</sub> ≤ 54000kHz	50Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
12000 ≤ f <sub>nom</sub> ≤ 54000kHz	10μW (100μW max.)


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



5.0×3.2mm for Mobile Communications



RoHS Compliant

**Features**

- Reference frequency for telecommunication systems
- Ceramic package
- Reflow compatible

**Applications**

- Mobile Communications, Bluetooth®, Wireless LAN

\* Bluetooth® Trademarks are owned by Bluetooth SIG Inc.

**How to Order**

**CX5032SB 26000 HO F L J Z1**  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Specification is "Z1")

<b>HO</b>	12 pF	<b>F</b>	±10×10 <sup>-6</sup>
<b>LJ</b>	-30 to +85°C		±15×10 <sup>-6</sup>

Packaging (Tape & Reel 1000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	9800 to 50000	50 to 80 (MHz)	kHz
Overtone Order	OT	Fundamental	3rd. Overtone	—
Load Capacitance	CL	12	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±10	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-30 to +85	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +85	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±15	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**

Frequency Range	Motional Series Resistance
9800 ≤ f <sub>nom</sub> < 10000 kHz	150Ω max.
10000 ≤ f <sub>nom</sub> < 12000 kHz	80Ω max.
12000 ≤ f <sub>nom</sub> < 26000 kHz	50Ω max.
26000 ≤ f <sub>nom</sub> ≤ 50000 kHz	40Ω max.
* 50 ≤ f <sub>nom</sub> ≤ 80 (MHz)	80Ω max.


\* 3rd Overtone

**Table2 Level of Drive**

Frequency Range	Level of Drive
9800 ≤ f <sub>nom</sub> ≤ 50000 kHz	10μW (100μW max.)
50 ≤ f <sub>nom</sub> ≤ 80 (MHz)	


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



5.0×3.2mm for Consumer Products



RoHS Compliant

**Features**

- Crystal unit for Consumer Products
- Small and low profile (5.0×3.2×1.3mm)
- Ceramic package
- Reflow compatible

**Applications**

- Digital Electronics
- Consumer Products

**How to Order**

**CX5032GA 08000 H0 H E Q Z1**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Standard is "Z1")

<b>H0</b>	12 pF	<b>Q</b>	±20×10 <sup>-6</sup>
<b>EQ</b>	-10 to +70°C		±30×10 <sup>-6</sup>

Packaging (Tape & Reel 1000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	8000 to 40000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	12	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±20	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-10 to +70	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +85	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±30	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
8000 ≤ f <sub>nom</sub> < 9500kHz	300Ω max.
9500 ≤ f <sub>nom</sub> < 10000kHz	200Ω max.
10000 ≤ f <sub>nom</sub> < 14000kHz	150Ω max.
14000 ≤ f <sub>nom</sub> < 20000kHz	100Ω max.
20000 ≤ f <sub>nom</sub> < 30000kHz	70Ω max.
30000 ≤ f <sub>nom</sub> ≤ 40000kHz	50Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
8000 ≤ f <sub>nom</sub> < 16000kHz	10μW (500μW max.)
16000 ≤ f <sub>nom</sub> < 25000kHz	10μW (300μW max.)
25000 ≤ f <sub>nom</sub> ≤ 40000kHz	10μW (100μW max.)


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



8.0×4.5mm for Consumer Products



RoHS Compliant

**Features**

- Crystal unit for Consumer Products
- Small and low profile (8.0×4.5×1.8mm)
- Ceramic package
- Reflow compatible

**Applications**

- Digital Electronics
- Consumer Products

**How to Order**

**CX8045GA 08000 HO P E Q Z1**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Specification is "Z1")

<b>HO</b>	12 pF	<b>Q</b>	±50×10 <sup>-6</sup>
<b>EQ</b>	-10 to +70°C		±50×10 <sup>-6</sup>

Packaging (Tape & Reel 1000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	4000 to 8000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	12	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±100	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-10 to +70	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +85	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±50	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
4000 ≤ f <sub>nom</sub> < 8000kHz	300Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
4000 ≤ f <sub>nom</sub> < 8000kHz	10μW (500μW max.)


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



2.0×1.6mm for Automotive



RoHS Compliant

**Features**

- Crystal unit for automotive electronics
- Ultra-miniature and low profile (2.0×1.6×0.8mm)
- Ceramic package
- Reflow compatible
- AEC-Q200 qualified

**Applications**

- ECU
- Automotive Camera
- Radar

**How to Order**

**CX2016GR 27000 D0 G T V** □ □  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification

**D0** 8 pF **G** ±15×10<sup>-6</sup>

**TV** -40 to +150°C ±150×10<sup>-6</sup>

Packaging (Tape & Reel 3000/ 15000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	16000 to 60000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±15	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-40 to +150	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +150	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±150	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
16000 ≤ f <sub>nom</sub> < 18000kHz	300Ω max.
18000 ≤ f <sub>nom</sub> < 20000kHz	200Ω max.
20000 ≤ f <sub>nom</sub> < 40000kHz	100Ω max.
40000 ≤ f <sub>nom</sub> ≤ 64000kHz	50Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
16000 ≤ f <sub>nom</sub> < 64000kHz	10μW (200μW max.)


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



2.0×1.6mm for Automotive



RoHS Compliant

**Features**

- Crystal unit for automotive electronics
- Ultra-miniature and low profile (2.05×1.65×0.45mm)
- Ceramic package
- Reflow compatible
- AEC-Q200 qualified

**Applications**

- ECU
- Automotive Camera
- Radar

**How to Order**

**CX2016SA 20000 DO G S S** □ □  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification

<b>DO</b>	8 pF	<b>G</b>	±15×10 <sup>-6</sup>
<b>SS</b>	-40 to +125°C		±50×10 <sup>-6</sup>

Package (Tape & Reel 3000/ 15000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	16000 to 60000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±15	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-40 to +125    -40 to +150	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +150	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±50    ±150	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
16000 ≤ f <sub>nom</sub> < 18000kHz	200Ω max.
18000 ≤ f <sub>nom</sub> < 26000kHz	150Ω max.
26000 ≤ f <sub>nom</sub> < 40000kHz	60Ω max.
40000 ≤ f <sub>nom</sub> ≤ 60000kHz	50Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
16000 ≤ f <sub>nom</sub> < 60000kHz	10μW (200μW max.)


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



3.2×2.5mm for Automotive



RoHS Compliant

**Features**

- Crystal unit for automotive electronics
- Improved solderability
- Small and low profile (3.2×2.5×0.85mm)
- Ceramic package
- Reflow compatible
- Acceptable heat cycle solder junction for 3000 cycle (-40 to +125°C)
- AEC-Q200 qualified

**Applications**

- ECU
- TPMS
- High-Speed Automotive Network

**How to Order**

**CX3225GA 16000 DO P T V CC**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Specification is "CC")

<b>DO</b>	8 pF	<b>P</b>	±50×10 <sup>-6</sup>
<b>TV</b>	-40 to +150°C		±150×10 <sup>-6</sup>

Packaging (Tape & Reel 3000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	8000 to 54000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±50	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-40 to +150	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +150	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±150	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
8000 ≤ f <sub>nom</sub> < 9800kHz	500Ω max.
9800 ≤ f <sub>nom</sub> < 13560kHz	200Ω max.
13560 ≤ f <sub>nom</sub> < 16000kHz	120Ω max.
16000 ≤ f <sub>nom</sub> ≤ 54000kHz	100Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
8000 ≤ f <sub>nom</sub> ≤ 54000kHz	10μW (200μW max.)


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



3.2×2.5mm for Automotive



RoHS Compliant

**Features**

- Crystal unit for automotive electronics
- Small and low profile (3.2×2.5×0.80mm)
- Ceramic package
- Reflow compatible
- AEC-Q200 qualified

**Applications**

- ECU
- High-Speed Automotive Network

**How to Order**

**CX3225CA 16000 D0 P S V CC**  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Standard is "CC")

<b>D0</b>	8 pF	<b>P</b>	±50×10 <sup>-6</sup>
<b>SV</b>	-40 to +125°C		±150×10 <sup>-6</sup>

Packaging (Tape & Reel 3000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	12000 to 54000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±50	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-40 to +125	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +150	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±150	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
12000 ≤ f <sub>nom</sub> < 13560 kHz	200Ω max.
13560 ≤ f <sub>nom</sub> < 16000 kHz	120Ω max.
16000 ≤ f <sub>nom</sub> ≤ 54000 kHz	100Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
12000 ≤ f <sub>nom</sub> ≤ 54000 kHz	10μW (200μW max.)


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



3.2×2.5mm for Automotive



RoHS Compliant

**Features**

- Crystal unit for automotive electronics
- Improved solderability
- Improved mounting stability with 4 terminals
- Improved anti-noise performance with GND terminal
- Ceramic package
- Small and low profile
- Improved rust prevention performance
- Reflow compatible
- Highly reliable solder junction (3000 heat cycles -40 to +125°C)
- AEC-Q200 qualified

**Applications**

- ECU
- TPMS
- High-Speed Automotive Network

**How to Order**

**CX3225SA 12000 DO P T V CC**  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Standard is "CC")

<b>DO</b>	8 pF	<b>P</b>	±50×10 <sup>-6</sup>
<b>TV</b>	-40 to +150°C		±150×10 <sup>-6</sup>

Packaging (Tape & Reel 3000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	8000 to 54000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±15	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-40 to +150	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +150	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±150	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
8000 ≤ f <sub>nom</sub> < 9800kHz	500Ω max.
9800 ≤ f <sub>nom</sub> < 13560kHz	200Ω max.
13560 ≤ f <sub>nom</sub> < 16000kHz	100Ω max.
16000 ≤ f <sub>nom</sub> < 20000kHz	60Ω max.
20000 ≤ f <sub>nom</sub> ≤ 54000kHz	50Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
8000 ≤ f <sub>nom</sub> ≤ 54000kHz	10μW (200μW max.)


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



3.2×2.5mm for Automotive



RoHS Compliant

**Features**

- Crystal unit for automotive electronics
- Miniature and low profile (3.2×2.5×0.55mm)
- Ceramic package
- Reflow compatible
- AEC-Q200 qualified

**Applications**

- Car Electronics
- High Speed Network
- Automotive Camera

**How to Order**

**CX3225SB 12000 D0 G S S CC**  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Specification is "CC")

**D0** 8 pF **G** ±15×10<sup>-6</sup>

**SS** -40 to +125°C ±50×10<sup>-6</sup>

Packaging (Tape & Reel 3000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	12000 to 54000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±15	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-40 to +125	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +125	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±50	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
12000 ≤ f <sub>nom</sub> < 13000kHz	150Ω max.
13000 ≤ f <sub>nom</sub> < 20000kHz	80Ω max.
20000 ≤ f <sub>nom</sub> ≤ 54000kHz	50Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
12000 ≤ f <sub>nom</sub> ≤ 54000kHz	10μW (100μW max.)


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



5.0×3.2mm for Automotive



RoHS Compliant

**Features**

- Crystal unit for automotive electronics
- Improved solderability
- Ceramic package
- Small and low profile
- Improved rust prevention performance
- Reflow compatible
- AEC-Q200 qualified

**Applications**

- ECU
- TPMS
- High-Speed Automotive Network

**How to Order**

**CX5032SA 08000 HO P T V Z1**  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Specification is "Z1")

**HO** 12 pF **P** ±50×10<sup>-6</sup>

**TV** -40 to +150°C ±150×10<sup>-6</sup>

Packaging (Tape & Reel 1000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	8000 to 40000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	12	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±15	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-40 to +150	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +150	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±150	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
8000 ≤ f <sub>nom</sub> < 9000kHz	200Ω max.
9000 ≤ f <sub>nom</sub> < 12000kHz	150Ω max.
12000 ≤ f <sub>nom</sub> < 20000kHz	100Ω max.
20000 ≤ f <sub>nom</sub> ≤ 40000kHz	50Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
8000 ≤ f <sub>nom</sub> ≤ 40000kHz	10μW (100μW max.)


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



5.0×3.2mm for Automotive



RoHS Compliant

**Features**

- Crystal unit for automotive electronics
- Small and low profile (5.0×3.2×1.3mm)
- Ceramic package
- Reflow compatible
- AEC-Q200 qualified

**Applications**

- ECU

**How to Order**

**CX5032GA 08000 HO Q T V Z1**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Specification is "Z1")

<b>HO</b>	12 pF	<b>Q</b>	±100×10 <sup>-6</sup>
<b>TV</b>	-40 to +150°C		±150×10 <sup>-6</sup>

Packaging (Tape & Reel 1000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	8000 to 40000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	12	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±50	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-40 to +150	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +150	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±150	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
8000 ≤ f <sub>nom</sub> < 9500kHz	300Ω max.
9500 ≤ f <sub>nom</sub> < 10000kHz	200Ω max.
10000 ≤ f <sub>nom</sub> < 14000kHz	150Ω max.
14000 ≤ f <sub>nom</sub> < 20000kHz	100Ω max.
20000 ≤ f <sub>nom</sub> < 30000kHz	70Ω max.
30000 ≤ f <sub>nom</sub> ≤ 40000kHz	50Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
8000 ≤ f <sub>nom</sub> < 16000kHz	10μW (500μW max.)
16000 ≤ f <sub>nom</sub> < 25000kHz	10μW (300μW max.)
25000 ≤ f <sub>nom</sub> ≤ 40000kHz	10μW (100μW max.)


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



8.0×4.5mm for Automotive



RoHS Compliant

**Features**

- Crystal unit for automotive electronics
- Small and low profile (8.0×4.5×1.8mm)
- Ceramic package
- Reflow compatible
- AEC-Q200 qualified

**Applications**

- ECU

**How to Order**

**CX8045GA 08000 HO Q T V Z1**  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Tolerance
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification (STD Specification is "Z1")

<b>HO</b>	12 pF	<b>Q</b>	±100×10 <sup>-6</sup>
<b>TV</b>	-40 to +150°C		±150×10 <sup>-6</sup>

Packaging (Tape & Reel 1000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Units	Remarks
Frequency Range	f <sub>nom</sub>	4000 to 8000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	12	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f <sub>tol</sub>	±50	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-40 to +150	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +150	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±150	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

**Table1 Motional Series Resistance**


Frequency Range	Motional Series Resistance
4000 ≤ f <sub>nom</sub> < 8000kHz	300Ω max.

**Table2 Level of Drive**

Frequency Range	Level of Drive
4000 ≤ f <sub>nom</sub> < 8000kHz	10μW (500μW max.)


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)





## 1. Shock & Drop • Vibration

Do not inflict excessive shock and mechanical vibration that exceeds the norm, such as hitting or mistakenly dropping, when transporting and mounting on a board. There are cases when pieces of crystal break, and pieces that are used become damaged, and become inoperable. When a shock or vibration that exceeds the norm has been inflicted, make sure to check the characteristics.

## 2. Cleaning

Since a crystal piece can be broken by resonance when a crystal device is cleaned by ultrasonic cleaning, be careful when carrying out ultrasonic cleaning.


## 3. Soldering conditions

To maintain the product reliability, please follow recommended conditions.

### Standard soldering iron conditions

	Crystal Units
Soldering iron	280°C to 340°C
Time	3+1/ -0 sec. max.

### Reflow conditions (Example)



Recommended reflow Conditions vary depending upon products. Please check with the respective specification for details.

## 4. Mounting Precautions

The lead of the device and the pattern of the board is soldered on the surface. Since extreme deformation of the board tears off the pattern, tears off the lead metal, cracks the solder and damages the sealed part of the device and there are cases in which performance deteriorates and operation fails, use it within the stipulated bending conditions. Due to the small cracks in the board resulting from mounting, please pay sufficient attention when attaching a device at the position where the warping of the board is great.

When using an automatic loading machine, as far as possible, select a type that has a small impact and use it while confirming that there is no damage.

Surface mount devices are NOT flow soldering compatible.

## 5. Storage Condition

Since the long hour high temperature and low temperature storage, as well as the storage at high humidity are causes of deterioration in frequency accuracy and solderability.

Parts should be stored in temperature range of -5 to +40°C, humidity 40 to 60% RH, and avoid direct sunlight. Then use within 6 months.




## Tape & Reel Specifications

### Crystal Units

(Unit: mm)


	CT1612DB	CT2016DB	CT2520DB	CX1008SB	CX1210DB CX1210SB	CX1612DB		CX2016DB CX2016SA CX2016GR	CX2520DB		
T A P E	A	2.0±0.05	2.0±0.05	2.0±0.05	2.0±0.05	2.0±0.05	2.0±0.05	2.0±0.05	2.0±0.05	2.0±0.05	
	B	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	
	C	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0	
	D	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	
	E	3.5±0.05	3.5±0.05	3.5±0.05	3.5±0.05	3.5±0.05	3.5±0.05	3.5±0.05	3.5±0.05	3.5±0.05	
	F	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	
	G	8.0±0.2	8.0±0.2	8.0±0.2	8.0±0.2	8.0±0.2	8.0±0.2	8.0±0.2	8.0±0.2	8.0±0.2	
	H	φ0.5+0.05	φ1.0+0.1/-0	φ1.0+0.1/-0	φ0.5±0.1	φ0.5+0.05	φ0.5±0.05	φ1.05±0.05	φ1.05±0.05	φ1.05±0.05	
	J	1.90±0.1	2.3±0.05/ 2.2±0.05	2.9±0.05	1.20±0.05	1.55±0.05	1.80±0.1	2.30±0.1	2.7±0.1		
	L	1.50±0.1	1.9±0.05	2.4±0.05	1.00±0.05	1.35±0.05	1.40±0.1	1.90±0.1	2.2±0.1		
N	0.75±0.05	1.1±0.05/ 0.75±0.05	1.1±0.05	0.45±0.05	0.45±0.05	0.5±0.1	0.7±0.05	0.6±0.1			
O	0.2±0.05	0.25±0.05	0.25±0.05	0.2±0.05	0.25±0.05	0.2±0.05	0.2±0.05	0.2±0.05			
R E E L	P	φ330±2	φ330±0.2	φ330±2	φ330±2	φ180+0/-3	φ330±2	φ180+0/-3	φ330±2	φ180+0/-3	φ330±2
	Q	φ100±1.0	φ100±1.0	φ100±1.0	φ100±1.0	φ100±1.0	φ60+1/-0	φ100±1.0	φ60+1/-0	φ100±1.0	φ100±1.0
	R	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2
	S	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8
	U	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5
	W	9.4±1.0	9.4±1.0	9.4±1.0	9.4±1.0	9.4±1.0	9.0±1.0	9.4±1.0	9.0±1.0	9.4±1.0	9.4±1.0
	Qty.	15000	12000	12000	21000	12000/21000	3000	20000	3000	15000	3000

	CX3225SA CX3225SB CX3225GA CX3225CA CX3225GB	CX5032SA CX5032SB	CX5032GA	CX8045GA	
T A P E	A	2.0±0.05	2.0±0.1	2.0±0.1	
	B	4.0±0.1	4.0±0.1	4.0±0.1	
	C	φ1.55±0.05	φ1.5±0.1	φ1.55±0.05	φ1.5+0.1/-0
	D	4.0±0.05	8.0±0.1	8.0±0.1	8.0±0.1
	E	3.5±0.05	5.5±0.1	5.5±0.1	7.5±0.1
	F	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1
	G	8.0±0.2	12.0±0.3	12.0±0.3	16.0±0.3
	H	φ1.05±0.1	φ1.5±0.1	φ1.55±0.05	φ1.55±0.05
	J	3.5±0.1	5.5±0.1	5.4±0.1	8.3±0.1
	L	2.8±0.1	3.7±0.1	3.6±0.1	4.8±0.1
N	1.0±0.1	1.4±0.1	1.7±0.1	2.1±0.1	
O	0.25±0.05	0.3±0.05	0.3±0.05	0.3±0.05	
R E E L	P	φ180+0/-3	φ180+0/-3	φ180+0/-3	φ254±2
	Q	φ60+1/-0	φ80±1.0	φ60+1/-0	φ100+2/-0
	R	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2
	S	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8
	U	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5
	W	9.0±1.0	12.8±1.0	13.0±1.0	22.4±1.0
	Qty.	3000	1000	1000	1000





CMOS/ 1.8V, 2.5V, 3.3V, 5.0V / 2.0×1.6, 2.5×2.0, 3.2×2.5, 5.0×3.2, 7.0×5.0mm



RoHS Compliant

### Features

- Frequency Range 1.5 to 160MHz
- CMOS output
- Wide Supply Voltage
  - 1.6 to 3.63V (Ver.E)
  - 2.5,3.3,5.0V(Ver.N)
- Low current consumption
- Option: Low Phase Noise Version

### Applications

- Consumer/ Networking/ Industrial/ Audio Codec/ Amuse

### How to Order

**KC2520K 25.0000 C**    **00**  
 ①                      ②                      ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency (25.0000: 25MHz)
- ③ Output Type (C: CMOS)
- ④ Supply Voltage
  - Standard : Version E
  - 1 : 1.8V/ 2.5V/ 3.3V compatible
  - 2 : 2.5V/ 3.3V compatible
  - Low Phase Noise : Version N
  - 2 : 2.5V
  - 3 : 3.3V
  - 5 : 5.0V

⑤ Frequency Tolerance (See Table 1)

⑥ Symmetry/ INH Function  
 E : 45/ 55%, Stand-by  
 N : 45/ 55%, Stand-by

⑦ Individual Specification  
 (STD Specification is "00")


Packaging Tape & Reel  
 KC7050K/ KC5032K  
 : 1000 pcs/ reel  
 KC3225K/ KC2520K/ KC2016K  
 : 2000 pcs/ reel

Table 1

Freq. Tol. Code	Tol. × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25	-40 to +85	With only certain frequencies
G	± 50		
6	± 50		


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)





CMOS/ 1.8V, 2.5V, 3.3V, 5.0V / 2.0×1.6, 2.5×2.0, 3.2×2.5, 5.0×3.2, 7.0×5.0mm

**Specifications**

Item	Symbol	Conditions		Version E (Standard)		Version N (Low Phase Noise)		Units			
				Min.	Max.	Min.(codeU)	Max.(codeU)				
Output Frequency Range <sup>Note1</sup>	fo			1.5	160	1.5	80	MHz			
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -10 to +70°C / -40 to +85°C / -40 to +105°C	-50	+50	-50	+50	× 10 <sup>-6</sup>			
			Op. Temp.: -10 to +70°C	-30	+30	-30	+30				
			Op. Temp.: -10 to +70°C	-25	+25	-25	+25				
Frequency Aging	f <sub>age</sub>	@25°C First year		-3	+3	-3	+3	×10 <sup>-6</sup> /y			
Storage Temperature Range	T <sub>stg</sub>			-55	+125	-55	+125	°C			
Operating Temperature Range	T <sub>use</sub>			-10	+70	-10	+70	°C			
				-40	+85	-40	+85				
				-40	+105	-40	+105				
Max. Supply Voltage	—			-0.3	+4.0	-0.3	+7.0	V			
Supply Voltage	V <sub>cc</sub>	Code ④ : 1/ E : 1.5≤F0≤125MHz		+1.60	+3.63	—	—	V			
		Code ④ : 2/ E : 125<F0≤160MHz		+2.25	+3.63	—	—				
		Code ④ : 2/ N : 1.5≤F0≤80MHz		—	—	+2.25(+2.38)	+2.75(+2.62)				
		Code ④ : 3/ N : 1.5≤F0≤80MHz		—	—	+2.97(+3.14)	+3.63(+3.46)				
		Code ④ : 5/ N : 1.5≤F0≤80MHz		—	—	+4.5(+4.75)	+5.5(+5.25)				
Current Consumption (Maximum Loaded)	I <sub>cc</sub>	1.5≤F0<24MHz	E : 1.6≤V <sub>cc</sub> ≤2.25V	—	2.5	—	—	mA			
			E : 2.25<V <sub>cc</sub> ≤2.8V / N : 2.25≤V <sub>cc</sub> ≤2.75V	—	3.0	—	4				
			E : 2.8<V <sub>cc</sub> ≤3.63V / N : 2.97≤V <sub>cc</sub> ≤3.63V	—	3.5	—	6				
			N : 4.50≤V <sub>cc</sub> ≤5.50V	—	—	—	24				
		24≤F0≤40MHz	E : 1.6≤V <sub>cc</sub> ≤2.25V	—	3.5	—	—				
			E : 2.25<V <sub>cc</sub> ≤2.8V / N : 2.25≤V <sub>cc</sub> ≤2.75V	—	4.5	—	5				
			E : 2.8<V <sub>cc</sub> ≤3.63V / N : 2.97≤V <sub>cc</sub> ≤3.63V	—	5.0	—	7				
			N : 4.50≤V <sub>cc</sub> ≤5.50V	—	—	—	24				
		40<F0≤62.5MHz	E : 1.6≤V <sub>cc</sub> ≤2.25V	—	5.0	—	—				
			E : 2.25<V <sub>cc</sub> ≤2.8V / N : 2.25≤V <sub>cc</sub> ≤2.75V	—	5.5	—	8				
			E : 2.8<V <sub>cc</sub> ≤3.63V / N : 2.97≤V <sub>cc</sub> ≤3.63V	—	6.0	—	11				
			N : 4.50≤V <sub>cc</sub> ≤5.50V	—	—	—	24				
		62.5<F0≤80MHz	E : 1.6≤V <sub>cc</sub> ≤2.25V	—	6.0	—	—				
			E : 2.25<V <sub>cc</sub> ≤2.8V / N : 2.25≤V <sub>cc</sub> ≤2.75V	—	6.5	—	14				
			E : 2.8<V <sub>cc</sub> ≤3.63V / N : 2.97≤V <sub>cc</sub> ≤3.63V	—	8.0	—	18				
			N : 4.50≤V <sub>cc</sub> ≤5.50V	—	—	—	40				
		80<F0≤125MHz	E : 1.6≤V <sub>cc</sub> ≤2.25V	—	11.0	—	—				
			E : 2.25<V <sub>cc</sub> ≤2.8V	—	14.0	—	—				
			E : 2.8<V <sub>cc</sub> ≤3.63V	—	17.0	—	—				
		125<F0≤160MHz	E : 2.25<V <sub>cc</sub> ≤2.8V	—	25.0	—	—				
			E : 2.8<V <sub>cc</sub> ≤3.63V	—	27.0	—	—				
		Stand-by Current	I <sub>std</sub>	1.5≤F0≤80MHz		—	5.0		—	10.0	μA
				80≤F0≤125MHz		—	5.0		—	—	
				125≤F0≤160MHz		—	10.0		—	—	
Symmetry	SYM	@50% V <sub>cc</sub>		45	55	45	55	%			
Rise/ Fall Time (10% to 90% Output Level)	tr/ tf	1.5≤F0≤80MHz	E : 1.6≤V <sub>cc</sub> ≤2.25V	—	6.0	—	—	ns			
			E : 2.25<V <sub>cc</sub> ≤2.8V / N : 2.25≤V <sub>cc</sub> ≤2.75V	—	5.0	—	6.0				
			E : 2.8<V <sub>cc</sub> ≤3.63V / N : 2.97≤V <sub>cc</sub> ≤3.63V	—	4.5	—	5.0				
			N : 4.50≤V <sub>cc</sub> ≤5.50V	—	—	—	8.0				
		80<F0≤125MHz	E : 1.6<V <sub>cc</sub> ≤3.63V	—	4.0	—	—				
125<F0≤160MHz	E : 2.25<V <sub>cc</sub> ≤3.63V	—	2.5	—	—						
Low Level Output Voltage	V <sub>OL</sub>	E : I <sub>OL</sub> = 4mA		—	10% V <sub>cc</sub>	—	10% V <sub>cc</sub>	V			
		N (1.5≤F0≤62.5MHz) : I <sub>OL</sub> = 4mA									
		N (62.5<F0≤80MHz) : I <sub>OL</sub> = 8mA									
High Level Output Voltage	V <sub>OH</sub>	E : I <sub>OH</sub> = -4mA		90% V <sub>cc</sub>	—	90% V <sub>cc</sub>	—	V			
		N (1.5≤F0≤62.5MHz) : I <sub>OH</sub> = -4mA									
		N (62.5 < F0≤80MHz) : I <sub>OH</sub> = -8mA									
Output Load	L <sub>CMOS</sub>			15		30		pF			
Low Level Input Voltage	V <sub>IL</sub>			—	30% V <sub>cc</sub>	—	30% V <sub>cc</sub>	V			
High Level Input Voltage	V <sub>IH</sub>			70% V <sub>cc</sub>	—	70% V <sub>cc</sub>	—	V			



CMOS/ 1.8V, 2.5V, 3.3V, 5.0V / 2.0×1.6, 2.5×2.0, 3.2×2.5, 5.0×3.2, 7.0×5.0mm

Item	Symbol	Conditions		Version E (Standard)		Version N (Low Phase Noise)		Units
				Min.	Max.	Min.(codeU)	Max.(codeU)	
<b>Disable Time</b>	t <sub>dis</sub>	1.5≤F0≤80MHz		—	200	—	150	ns
		80<F0≤125MHz		—	200	—	—	
		125<F0≤160MHz		—	100	—	—	
<b>Enable Time</b>	t <sub>ena</sub>			—	5	—	5	ms
<b>Start-up Time</b>	t <sub>str</sub>	1.5≤F0≤80MHz	@Minimum operating voltage to be 0 sec.	—	5	—	5	ms
		80<F0≤125MHz		—	10	—	—	
		125<F0≤160MHz		—	—	—	—	
<b>1Sigma Jitter</b>	J <sub>Sigma</sub>	1.5≤F0≤80MHz	Measured with Wavecrest SIA-3000	—	5	—	4	ps
		80<F0≤125MHz		—	5	—	—	
		125<F0≤160MHz		—	3	—	—	
<b>Peak to Peak Jitter</b>	J <sub>PK-PK</sub>	1.5≤F0≤80MHz		—	50	—	40	ps
		80<F0≤125MHz		—	50	—	—	
		125<F0≤160MHz		—	25	—	—	
<b>Phase Jitter</b>	J <sub>Phase</sub>	@25MHz	BW : 12kHz to 20MHz	—	1.0	—	0.5	ps
<b>Phase Noise</b>	—	@25MHz	@10Hz offset	Typ. -89		Typ. -92		dBc/ Hz
			@100Hz offset	Typ. -119		Typ. -126		
			@1kHz offset	Typ. -143		Typ. -151		
			@10kHz offset	Typ. -157		Typ. -160		
			@100kHz offset	Typ. -160		Typ. -167		
			@1MHz offset	Typ. -162		Typ. -170		
			@10MHz offset	Typ. -162		Typ. -170		

Note: All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Pad Connections	
#1	Enable/ Disable
#2	Case GND
#3	Output
#4	Vcc

INH Function	
<b>Pad1</b>	Pad3 (Output)
<b>Open</b>	Active
<b>"H" Level</b>	Active
<b>"L" Level</b>	High Z (No-Oscillation)




# Clock Oscillators Surface Mount Type

## Clock MC-K Series



CMOS/ 1.8V, 2.5V, 3.3V, 5.0V / 2.0×1.6, 2.5×2.0, 3.2×2.5, 5.0×3.2, 7.0×5.0mm for Automotive



RoHS Compliant

### Features

- Frequency Range 1.5 to 80MHz
- CMOS output
- Wide Supply Voltage
  - 1.6 to 3.63V (Ver.E)
  - 2.5,3.3,5.0V(Ver.N)
- Low current consumption
- Option: Low Phase Noise Version
- AEC-Q100/ 200 qualified

### Applications

- Automotive Radar/ Camera Navigation/ Sensor Mirror/ Head light

### Table 1

Freq. Tol. Code	$\times 10^{-6}$	Operating Temperature Range (°C)	Note
G	$\pm 50$	-40 to +85	Standard specifications
6	$\pm 50$	-40 to +105	
X	$\pm 100$	-40 to +125	

### How to Order


MC2520K 25.0000 C    00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency (25.0000: 25MHz)
- ③ Output Type (C: CMOS)
- ④ Supply Voltage  
 Standard : Version E  
 1 : 1.8V/ 2.5V/ 3.3V compatible  
 2 : 2.5V/ 3.3V compatible  
 Low Phase Noise : Version N  
 2 : 2.5V  
 3 : 3.3V  
 5 : 5.0V
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function  
 E : 45/ 55%, Stand-by  
 N : 45/ 55%, Stand-by, Low Phase Noise
- ⑦ Individual Specification (STD Specification is "00")

Packaging Tape & Reel  
 MC7050K/ MC5032K  
 : 1000 pcs/ reel  
 MC3225K/ MC2520K/ MC2016K  
 : 2000 pcs/ reel


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)





CMOS/ 1.8V, 2.5V, 3.3V, 5.0V / 2.0×1.6, 2.5×2.0, 3.2×2.5, 5.0×3.2, 7.0×5.0mm for Automotive

**Specifications**

Item	Symbol	Conditions		Version E (Standard)		Version N (Low Phase Noise)		Units			
				Min.	Max.	Min.(codeU)	Max.(codeU)				
Output Frequency Range <sup>Note1</sup>	fo			1.5	160	1.5	80	MHz			
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C/ -40 to +105°C	-50	+50	-50	+50	×10 <sup>-6</sup>			
			Op. Temp.: -40 to +125°C	-100	+100	-100	+100				
Frequency Aging	f <sub>age</sub>	@25°C First year		-3	+3	-3	+3	×10 <sup>-6</sup> /y			
Storage Temperature Range	T <sub>stg</sub>			-55	+125	-55	+125	°C			
Operating Temperature Range	T <sub>use</sub>			-40	+85	-40	+85	°C			
				-40	+105	-40	+105				
Max. Supply Voltage	—			-0.3	+4.0	-0.3	+7.0	V			
Supply Voltage	V <sub>cc</sub>	Code ④ : 1/ E : 1.5≤F0≤125MHz		+1.60	+3.63	—	—	V			
		Code ④ : 2/ E : 125<F0≤160MHz		+2.25	+3.63	—	—				
		Code ④ : 2/ N : 1.5≤F0≤80MHz		—	—	+2.25(+2.38)	+2.75(+2.62)				
		Code ④ : 3/ N : 1.5≤F0≤80MHz		—	—	+2.97(+3.14)	+3.63(+3.46)				
		Code ④ : 5/ N : 1.5≤F0≤80MHz		—	—	+4.5(+4.75)	+5.5(+5.25)				
Current Consumption (Maximum Loaded)	I <sub>cc</sub>	1.5≤F0<24MHz	E : 1.6≤V <sub>cc</sub> ≤2.25V	—	2.5	—	—	mA			
			E : 2.25<V <sub>cc</sub> ≤2.8V/ N : 2.25≤V <sub>cc</sub> ≤2.75V	—	3.0	—	4				
			E : 2.8<V <sub>cc</sub> ≤3.63V/ N : 2.97≤V <sub>cc</sub> ≤3.63V	—	3.5	—	6				
			N : 4.50≤V <sub>cc</sub> ≤5.50V	—	—	—	24				
		24≤F0≤40MHz	E : 1.6≤V <sub>cc</sub> ≤2.25V	—	3.5	—	—				
			E : 2.25<V <sub>cc</sub> ≤2.8V/ N : 2.25≤V <sub>cc</sub> ≤2.75V	—	4.5	—	5				
			E : 2.8<V <sub>cc</sub> ≤3.63V/ N : 2.97≤V <sub>cc</sub> ≤3.63V	—	5.0	—	7				
			N : 4.50≤V <sub>cc</sub> ≤5.50V	—	—	—	24				
		40<F0≤62.5MHz	E : 1.6≤V <sub>cc</sub> ≤2.25V	—	5.0	—	—				
			E : 2.25<V <sub>cc</sub> ≤2.8V/ N : 2.25≤V <sub>cc</sub> ≤2.75V	—	5.5	—	8				
			E : 2.8<V <sub>cc</sub> ≤3.63V/ N : 2.97≤V <sub>cc</sub> ≤3.63V	—	6.0	—	11				
			N : 4.50≤V <sub>cc</sub> ≤5.50V	—	—	—	24				
		62.5<F0≤80MHz	E : 1.6≤V <sub>cc</sub> ≤2.25V	—	6.0	—	—				
			E : 2.25<V <sub>cc</sub> ≤2.8V/ N : 2.25≤V <sub>cc</sub> ≤2.75V	—	6.5	—	14				
			E : 2.8<V <sub>cc</sub> ≤3.63V/ N : 2.97≤V <sub>cc</sub> ≤3.63V	—	8.0	—	18				
			N : 4.50≤V <sub>cc</sub> ≤5.50V	—	—	—	40				
		80<F0≤125MHz	E : 1.6≤V <sub>cc</sub> ≤2.25V	—	11.0	—	—				
			E : 2.25<V <sub>cc</sub> ≤2.8V	—	14.0	—	—				
			E : 2.8<V <sub>cc</sub> ≤3.63V	—	17.0	—	—				
			E : 2.25<V <sub>cc</sub> ≤2.8V	—	25.0	—	—				
		125<F0≤160MHz	E : 2.8<V <sub>cc</sub> ≤3.63V	—	27.0	—	—				
		Stand-by Current	I <sub>std</sub>	1.5≤F0≤80MHz		—	5.0		—	10.0	μA
				80≤F0≤125MHz		—	5.0		—	—	
125≤F0≤160MHz				—	10.0	—	—				
Symmetry	SYM	@50% V <sub>cc</sub>		45	55	45	55	%			
Rise/ Fall Time (10% to 90% Output Level)	tr/ tf	1.5≤F0≤80MHz	E : 1.6≤V <sub>cc</sub> ≤2.25V	—	6.0	—	—	ns			
			E : 2.25<V <sub>cc</sub> ≤2.8V/ N : 2.25≤V <sub>cc</sub> ≤2.75V	—	5.0	—	6.0				
			E : 2.8<V <sub>cc</sub> ≤3.63V/ N : 2.97≤V <sub>cc</sub> ≤3.63V	—	4.5	—	5.0				
			N : 4.50≤V <sub>cc</sub> ≤5.50V	—	—	—	8.0				
80<F0≤125MHz	E : 1.6<V <sub>cc</sub> ≤3.63V	—	4.0	—	—						
125<F0≤160MHz	E : 2.25<V <sub>cc</sub> ≤3.63V	—	2.5	—	—						
Low Level Output Voltage	V <sub>oL</sub>	E : I <sub>oL</sub> = 4mA		—	10% V <sub>cc</sub>	—	10% V <sub>cc</sub>	V			
		N (1.5≤F0≤62.5MHz) : I <sub>oL</sub> = 4mA									
		N (62.5<F0≤80MHz) : I <sub>oL</sub> = 8mA									
High Level Output Voltage	V <sub>oH</sub>	E : I <sub>oH</sub> = -4mA		90% V <sub>cc</sub>	—	90% V <sub>cc</sub>	—	V			
		N (1.5≤F0≤62.5MHz) : I <sub>oH</sub> = -4mA									
		N (62.5 < F0≤80MHz) : I <sub>oH</sub> = -8mA									
Output Load	L <sub>CMOS</sub>			15		30		pF			
Low Level Input Voltage	V <sub>IL</sub>			—	30% V <sub>cc</sub>	—	30% V <sub>cc</sub>	V			
High Level Input Voltage	V <sub>IH</sub>			70% V <sub>cc</sub>	—	70% V <sub>cc</sub>	—	V			



CMOS/ 1.8V, 2.5V, 3.3V, 5.0V / 2.0×1.6, 2.5×2.0, 3.2×2.5, 5.0×3.2, 7.0×5.0mm for Automotive

Item	Symbol	Conditions		Version E (Standard)		Version N (Low Phase Noise)		Units
				Min.	Max.	Min.(codeU)	Max.(codeU)	
Disable Time	t <sub>dis</sub>	1.5≤F0≤80MHz		—	200	—	150	ns
		80<F0≤125MHz		—	200	—	—	
		125<F0≤160MHz		—	100	—	—	
Enable Time	t <sub>ena</sub>			—	5	—	5	ms
Start-up Time	t <sub>str</sub>	1.5≤F0≤80MHz	@Minimum operating voltage to be 0 sec.	—	5	—	5	ms
		80<F0≤125MHz		—	10	—	—	
		125<F0≤160MHz		—	—	—	—	
1Sigma Jitter	J <sub>Sigma</sub>	1.5≤F0≤80MHz	Measured with Wavecrest SIA-3000	—	5	—	4	ps
		80<F0≤125MHz		—	5	—	—	
		125<F0≤160MHz		—	3	—	—	
Peak to Peak Jitter	J <sub>PK-PK</sub>	1.5≤F0≤80MHz	Measured with Wavecrest SIA-3000	—	50	—	40	ps
		80<F0≤125MHz		—	50	—	—	
		125<F0≤160MHz		—	25	—	—	
Phase Jitter	J <sub>Phase</sub>	@25MHz	BW : 12kHz to 20MHz	—	1.0	—	0.5	ps
Phase Noise	—	@25MHz	@10Hz offset	Typ. -89		Typ. -92		dBc/ Hz
			@100Hz offset	Typ. -119		Typ. -126		
			@1kHz offset	Typ. -143		Typ. -151		
			@10kHz offset	Typ. -157		Typ. -160		
			@100kHz offset	Typ. -160		Typ. -167		
			@1MHz offset	Typ. -162		Typ. -170		
@10MHz offset	Typ. -162		Typ. -170					


Note: All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Pad Connections	
#1	Enable/ Disable
#2	Case GND
#3	Output
#4	Vcc

INH Function	
Pad1	Pad3 (Output)
Open	Active
"H" Level	Active
"L" Level	High Z (No-Oscillation)

CMOS/ 1.8V to 3.3V/ 2.0×1.6mm



RoHS Compliant

### Features

- Ultra Miniature ceramic package  
2.0 (L) × 1.6 (W) × 0.55 (H) mm (Typ.)
- Highly reliable with seam welding
- CMOS output
- Supply voltage  $V_{CC} = 1.8V/ 2.5V/ 3.3V$   
Wide operating voltage range 1.6 to 3.63V
- Low current consumption

Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	-10 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$	-40 to +85	Please contact us for available frequencies.
F	$\pm 100$		
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC2016B 40.0000 C 1 □ E 00  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V, 2.5V, 3.3V Compatible)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)


### Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	$f_o$		1.5	50	MHz	
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	$\times 10^{-6}$
			Op. Temp.: -10 to +70°C/ -40 to +85°C/-40 to +105°C	-50	+50	
			Op. Temp.: -10 to +70°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
Storage Temperature Range	$T_{stg}$		-55	+125	°C	
Operating Temperature Range	$T_{use}$	Standard Specifications	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-0.6	+6.0	V	
Supply Voltage	$V_{CC}$		+1.6	+3.63	V	
Current Consumption (Maximum Loaded/ 1.6< $V_{CC}$ <2.0V)	$I_{CC}$	1.5< $f_o$ <24MHz	—	2.5	mA	
		24< $f_o$ <40MHz	—	3.5		
		40< $f_o$ <50MHz	—	4.5		
Current Consumption (Maximum Loaded/ 2.0< $V_{CC}$ <2.8V)	1.5< $f_o$ <24MHz	—	3.0			
	24< $f_o$ <40MHz	—	4.5			
	40< $f_o$ <50MHz	—	5.0			
Current Consumption (Maximum Loaded/ 2.8< $V_{CC}$ <3.63V)	1.5< $f_o$ <24MHz	—	3.5			
	24< $f_o$ <40MHz	—	5.0			
	40< $f_o$ <50MHz	—	6.0			
Stand-by Current	$I_{std}$		—	10	$\mu A$	
Symmetry	SYM	@50% $V_{CC}$	45	55	%	
Rise/ Fall Time (10% $V_{CC}$ to 90% $V_{CC}$ Maximum Loaded)	$t_r/ t_f$	1.6< $V_{CC}$ <2.0V	—	6.5	ns	
		2.0< $V_{CC}$ <2.8V	—	5.0		
		2.8< $V_{CC}$ <3.63V	—	4.5		
Low Level Output Voltage	$V_{OL}$	$I_{OL} = 4mA$	—	10% $V_{CC}$	V	
High Level Output Voltage	$V_{OH}$	$I_{OH} = -4mA$	90% $V_{CC}$	—	V	
CMOS Load	$L_{CMOS}$	CMOS Output	—	15	pF	
Input Voltage Range	$V_{IN}$		0	$V_{CC}$	V	
Low Level Input Voltage	$V_{IL}$		—	30% $V_{CC}$	V	
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$	—	V	
Disable Time	$t_{dis}$		—	100	ns	
Enable Time	$t_{ena}$		—	5	ms	
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	$J_{Sigma}$	Measured with Wavecrest SIA-3000	—	8	ps	
Peak to Peak Jitter	$J_{PK-PK}$		—	80	ps	

Note: All electrical characteristics are defined at the maximum load and operating temperature range.  
Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)



CMOS/ 1.8V to 3.3V/ 2.5×2.0mm



RoHS Compliant

**Features**

- Miniature ceramic package  
2.5 (L) × 2.0 (W) × 0.7 (H) mm (Typ.)
- Highly reliable with seam welding
- CMOS output
- Supply voltage 1.8/ 2.5/ 3.3V  
Wide operating voltage range 1.6 to 3.63V
- Low current consumption
- High output frequency 125MHz

**Table 1**

Freq. Tol. Code	Tol. × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25	-40 to +85	Please contact us for available frequencies.
F	± 100		
G	± 50		
6	± 50		

**How to Order**

KC2520B 25.0000 C 1 □ E 00  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V, 2.5V, 3.3V Compatible)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Specifications		Units	
			Min.	Max.		
Output Frequency Range	f <sub>o</sub>		1.5	125	MHz	
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Aging (1 year @25°C), Shock and vibration	Op.Temp.: -40 to +85°C	-100	+100	×10 <sup>-6</sup>
			Op. Temp.: -10 to +70°C/ -40 to +85°C/ -40 to +105°C	-50	+50	
			Op.Temp.: -10 to +70°C	-30	+30	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>	Standard Specifications	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—	1.5 ≤ f <sub>o</sub> ≤ 80MHz	-0.6	+6.0	V	
Supply Voltage	V <sub>cc</sub>	80 < f <sub>o</sub> ≤ 125MHz	-0.3	+4.0	V	
Current Consumption (Maximum Loaded/ 1.6 < V <sub>cc</sub> ≤ 2.0V)	I <sub>cc</sub>	1.5 ≤ f <sub>o</sub> ≤ 24MHz	—	2.5	mA	
		24 < f <sub>o</sub> ≤ 40MHz	—	3.5		
		40 < f <sub>o</sub> ≤ 60MHz	—	5.0		
		60 < f <sub>o</sub> ≤ 80MHz	—	6.0		
		80 < f <sub>o</sub> ≤ 125MHz	—	11.0		
Current Consumption (Maximum Loaded/ 2.0 < V <sub>cc</sub> ≤ 2.8V)	I <sub>cc</sub>	1.5 ≤ f <sub>o</sub> ≤ 24MHz	—	3.0	mA	
		24 < f <sub>o</sub> ≤ 40MHz	—	4.5		
		40 < f <sub>o</sub> ≤ 60MHz	—	5.5		
		60 < f <sub>o</sub> ≤ 80MHz	—	6.5		
		80 < f <sub>o</sub> ≤ 125MHz	—	14.0		
Current Consumption (Maximum Loaded/ 2.8 < V <sub>cc</sub> ≤ 3.63V)	I <sub>cc</sub>	1.5 ≤ f <sub>o</sub> ≤ 24MHz	—	3.5	mA	
		24 < f <sub>o</sub> ≤ 40MHz	—	5.0		
		40 < f <sub>o</sub> ≤ 60MHz	—	6.0		
		60 < f <sub>o</sub> ≤ 80MHz	—	8.0		
		80 < f <sub>o</sub> ≤ 125MHz	—	17.0		
Stand-by Current	I <sub>std</sub>		—	10	μA	
Symmetry	SYM	@50%V <sub>cc</sub>	45	55	%	
Rise/ Fall Time (10% V <sub>cc</sub> to 90% V <sub>cc</sub> Maximum Loaded)	tr/ tf	1.6 ≤ V <sub>cc</sub> ≤ 2.0V/ 1.5 < f <sub>o</sub> ≤ 80MHz	—	6.5	ns	
		2.0 < V <sub>cc</sub> ≤ 2.8V/ 1.5 < f <sub>o</sub> ≤ 80MHz	—	5.0		
		2.8 < V <sub>cc</sub> ≤ 3.63V/ 1.5 < f <sub>o</sub> ≤ 80MHz	—	4.5		
		1.6 ≤ V <sub>cc</sub> ≤ 3.63V/ 80 < f <sub>o</sub> ≤ 125MHz	—	4.0		
Low Level Output Voltage	V <sub>OL</sub>	I <sub>oL</sub> = 4mA	—	10%V <sub>cc</sub>	V	
High Level Output Voltage	V <sub>OH</sub>	I <sub>oH</sub> = -4mA	90%V <sub>cc</sub>	—	V	
Output Load	L <sub>CMOS</sub>	CMOS Output	—	15	pF	
Low Level Input Voltage	V <sub>IL</sub>		—	30%V <sub>cc</sub>	V	
High Level Input Voltage	V <sub>IH</sub>		70%V <sub>cc</sub>	—	V	
Disable Time	t <sub>dis</sub>		—	100	ns	
Enable Time	t <sub>ena</sub>		—	5	ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	J <sub>Sigma</sub>	Measured with Wavecrest SIA-3000	1.5 ≤ f <sub>o</sub> ≤ 80MHz	—	8	ps
			80 < f <sub>o</sub> ≤ 125MHz	—	4	
Peak to Peak Jitter	J <sub>PK-PK</sub>	Measured with Wavecrest SIA-3000	1.5 ≤ f <sub>o</sub> ≤ 80MHz	—	80	ps
			80 < f <sub>o</sub> ≤ 125MHz	—	40	

Note: All electrical characteristics are defined at the maximum load and operating temperature range. Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)





CMOS/ 2.5V to 3.3V/ 2.5×2.0mm



RoHS Compliant

**Features**

- Miniature ceramic package  
2.5 (L) × 2.0 (W) × 0.7 (H) mm (Typ.)
- Highly reliable with seam welding
- CMOS output
- Supply voltage 2.5/ 3.3V  
Wide operating voltage range 2.25 to 3.63V
- Low current consumption
- High output frequency 160MHz

**Table 1**

Freq. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	-10 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$	-40 to +85	Please contact us for available frequencies.
F	$\pm 100$		
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

**How to Order**

KC2520B 125.000 C 2 □ E 00  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (2.5V, 3.3V Compatible)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Specifications		Units	
			Min.	Max.		
Output Frequency Range	fo	fo>125MHz	125	160	MHz	
Frequency Tolerance	f <sub>tol</sub>	Over all conditions : initial tolerance, operating temperature range, rated power supply voltage change, load change, aging (1year @25°C), shock and vibration	Op. Temp. : -40 ~ +85°C	-100	+100	$\times 10^{-6}$
			Op. Temp. : -10 to +70°C/ -40 to +85°C/ -40 to +105°C	-50	+50	
			Op. Temp. : -10 ~ +70°C	-30	+30	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>	Standard Specifications	-10	+70	°C	
		Extend (Option)	-40	+85		
			-40	+105		
Max. Supply Voltage	—		-0.3	+4.0	V	
Supply Voltage	V <sub>CC</sub>		+2.25	+3.63	V	
Current Consumption (Maximum Loaded/ 2.25≤V <sub>CC</sub> ≤2.75V)	I <sub>CC</sub>	125<fo≤160MHz	—	25	mA	
Current Consumption (Maximum Loaded/ 2.75≤V <sub>CC</sub> ≤3.63V)		125<fo≤160MHz	—	27		
Stand-by Current	I <sub>std</sub>		—	10	μA	
Symmetry	SYM	@50% V <sub>CC</sub>	45	55	%	
Rise/ Fall Time (10% V <sub>CC</sub> to 90% V <sub>CC</sub> Maximum Loaded)	tr/ tf	125<fo≤160MHz	—	2.5	ns	
Low Level Output Voltage	V <sub>OL</sub>	I <sub>OL</sub> = 4mA	—	10% V <sub>CC</sub>	V	
High Level Output Voltage	V <sub>OH</sub>	I <sub>OH</sub> = -4mA	90% V <sub>CC</sub>	—		
Output Load	L <sub>CMOS</sub>	CMOS Output	—	15	pF	
Low Level Input Voltage	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V	
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>CC</sub>	—		
Disable Time	t <sub>dis</sub>		—	100	ns	
Enable Time	t <sub>ena</sub>		—	5	ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	J <sub>Sigma</sub>	Measured with Wavecrest SIA-3000	—	3	ps	
Peak to Peak Jitter	J <sub>PK-PK</sub>	125<fo≤160MHz	—	25		

Note: All electrical characteristics are defined at the maximum load and operating temperature range.  
Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



CMOS/ 1.8V to 3.3V/ 2.5×2.0mm for Automotive



RoHS Compliant

**Features**

- Miniature ceramic package  
2.5 (L) × 2.0 (W) × 0.7 (H) mm (Typ.)
- Highly reliable with seam welding
- CMOS output
- Supply voltage 1.8/ 2.5/ 3.3V  
Wide operating voltage range 1.6 to 3.63V
- Low current consumption
- AEC-Q100/ 200 qualified

**Table 1**

Freq. Tol. Code	Freq. Tol. × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
F	±100	-40 to +85	Please contact us for available frequencies.
G	± 50	-40 to +85	
6	± 50	-40 to +105	Standard specifications
X	±100	-40 to +125	

**How to Order**

**KC2520M 25.0000 C 1 □ E SH**  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V, 2.5V, 3.3V Compatible)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "SH")

Packaging (Tape & Reel 2000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Specifications		Units	
			Min.	Max.		
Output Frequency Range	fo		1.5	60	MHz	
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Aging (1 year @25°C), Shock and vibration	Op.Temp.: -40 to +85°C -40 to +125°C	-100	+100	×10 <sup>-6</sup>
			Op.Temp.: -40 to +85°C -40 to +105°C	-50	+50	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>		-40	+125	°C	
Max. Supply Voltage	—	1.5 ≤ fo ≤ 60MHz	-0.6	+6.5	V	
Supply Voltage	V <sub>cc</sub>		+1.6	+3.63	V	
Current Consumption (Maximum Loaded/ 1.6 ≤ V <sub>cc</sub> ≤ 2.0V)	I <sub>cc</sub>	1.5 ≤ fo ≤ 24MHz	—	2.5	mA	
		24 < fo ≤ 40MHz	—	3.0		
		40 < fo ≤ 60MHz	—	4.5		
Current Consumption (Maximum Loaded/ 2.0 < V <sub>cc</sub> ≤ 2.8V)	I <sub>cc</sub>	1.5 ≤ fo ≤ 24MHz	—	3.0		
		24 < fo ≤ 40MHz	—	4.0		
		40 < fo ≤ 60MHz	—	5.0		
Current Consumption (Maximum Loaded/ 2.8 < V <sub>cc</sub> ≤ 3.63V)	I <sub>cc</sub>	1.5 ≤ fo ≤ 24MHz	—	3.5		
		24 < fo ≤ 40MHz	—	5.0		
		40 < fo ≤ 60MHz	—	6.5		
Stand-by Current	I <sub>std</sub>		—	10	μA	
Symmetry	SYM	@50%V <sub>cc</sub>	45	55	%	
		1.6 ≤ V <sub>cc</sub> ≤ 2.0V	—	6.5		
Rise/ Fall Time (10% V <sub>cc</sub> to 90% V <sub>cc</sub> Maximum Loaded)	tr/ tf	2.0 < V <sub>cc</sub> ≤ 2.8V	—	5.5	ns	
		2.8 < V <sub>cc</sub> ≤ 3.63V	—	4.5		
			—	—		
Low Level Output Voltage	V <sub>OL</sub>	I <sub>OL</sub> = 4mA	—	10%V <sub>cc</sub>	V	
High Level Output Voltage	V <sub>OH</sub>	I <sub>OH</sub> = -4mA	90%V <sub>cc</sub>	—	V	
Output Load	L <sub>CMOS</sub>	CMOS Output	—	15	pF	
Low Level Input Voltage	V <sub>IL</sub>		—	30%V <sub>cc</sub>	V	
High Level Input Voltage	V <sub>IH</sub>		70%V <sub>cc</sub>	—	V	
Disable Time	t <sub>dis</sub>		—	100	ns	
Enable Time	t <sub>ena</sub>		—	5	ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	J <sub>Sigma</sub>	Measured with Wavecrest SIA-3000	—	8	ps	
Peak to Peak Jitter	J <sub>PK-PK</sub>		—	80	ps	

Note: All electrical characteristics are defined at the maximum load and operating temperature range.  
Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)





CMOS/ 1.8V/ 2.5×2.0mm



RoHS Compliant

### Features

- Miniature ceramic package  
2.5 (L) × 2.0 (W) × 0.7 (H) mm (Typ.)
- High Stability Output Frequency  
±10×10<sup>-6</sup> (-10 to +70°C)  
±15×10<sup>-6</sup> (-40 to +85°C)
- CMOS output
- Supply voltage V<sub>CC</sub> = 1.8V  
Low Power Supply Consumption

### Applications

- Wi-Fi, Bluetooth® etc.

### How to Order

KC2520C 40.0000 C 1 □ E 00  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)

Table 1

Freq. Tol. Code	× 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
Y	±10	-10 to +70	Please contact us for available frequencies.
K	±20	-40 to +85	Standard specifications
L	±15		


### Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	f <sub>o</sub>		1.5	54	MHz	
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-15	+15	×10 <sup>-6</sup>
			Op. Temp.: -40 to +85°C	-20	+20	
			Op. Temp.: -10 to +70°C	-10	+10	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>		-10	+70	°C	
			-40	+85		
Max. Supply Voltage	—		-0.3	+4.0	V	
Supply Voltage	V <sub>CC</sub>		+1.6	+2.0	V	
Current Consumption (Maximum Loaded)	I <sub>CC</sub>	CL ≤ 15pF	1.5 ≤ f <sub>o</sub> < 24MHz	—	4	mA
			24 ≤ f <sub>o</sub> ≤ 54MHz	—	4.5	
Stand-by Current	I <sub>std</sub>		—	5	μA	
Symmetry	SYM	@50% V <sub>CC</sub>	45	55	%	
Rise/ Fall Time (10% V <sub>CC</sub> to 90% V <sub>CC</sub> Maximum Loaded)	t <sub>r</sub> / t <sub>f</sub>		—	4	ns	
Low Level Output Voltage	V <sub>OL</sub>	I <sub>OL</sub> = 4mA	—	10% V <sub>CC</sub>	V	
High Level Output Voltage	V <sub>OH</sub>	I <sub>OH</sub> = -4mA	90% V <sub>CC</sub>	—	V	
CMOS Load	L <sub>CMOS</sub>	CMOS Output	—	15	pF	
Input Voltage Range	V <sub>IN</sub>		0	V <sub>CC</sub>	V	
Low Level Input Voltage	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V	
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>CC</sub>	—	V	
Disable Time	t <sub>dis</sub>		—	100	ns	
Enable Time	t <sub>ena</sub>		—	5	ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	J <sub>Sigma</sub>	Measured with Wavcrest SIA-3000	—	8	ps	
Peak to Peak Jitter	J <sub>PK-PK</sub>		—	80	ps	

Note: All electrical characteristics are defined at the maximum load and operating temperature range.  
Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)





CMOS/ 2.5V to 3.3V/ 2.5×2.0mm



RoHS Compliant

### Features

- Miniature ceramic package  
2.5 (L) × 2.0 (W) × 0.7 (H) mm (Typ.)
- High Stability Output Frequency  
±10×10<sup>-6</sup> (-10 to +70°C)  
±15×10<sup>-6</sup> (-40 to +85°C)
- CMOS output
- Supply voltage V<sub>CC</sub> = 2.5V/ 3.3V Compatible
- Low Power Supply Consumption
- Wide Operating Voltage Range 2.25 to 3.63V

### Applications

- Wi-Fi, Bluetooth® etc.

### How to Order

KC2520C 40.0000 C 2 □ E 00  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (2.5V, 3.3V Compatible)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)

Table 1

Freq. Tol. Code	× 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
Y	±10	-10 to +70	Please contact us for available frequencies.
K	±20	-40 to +85	
L	±15		Standard specifications


### Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	f <sub>o</sub>		1.5	54	MHz	
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-15	+15	×10 <sup>-6</sup>
			Op. Temp.: -40 to +85°C	-20	+20	
			Op. Temp.: -10 to +70°C	-10	+10	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>		-10	+70	°C	
			-40	+85		
Max. Supply Voltage	—		-0.3	+4.0	V	
Supply Voltage	V <sub>CC</sub>		+2.25	+3.63	V	
Current Consumption	I <sub>CC</sub>	CL = 15pF @2.5V	1.5 ≤ f <sub>o</sub> < 24MHz	—	3.0	mA
			24 ≤ f <sub>o</sub> ≤ 40MHz	—	3.5	
		CL = 15pF @3.3V	40 < f <sub>o</sub> ≤ 54MHz	—	4.5	
			1.5 ≤ f <sub>o</sub> < 24MHz	—	3.5	
		24 ≤ f <sub>o</sub> ≤ 40MHz	—	5.0		
		40 < f <sub>o</sub> ≤ 54MHz	—	6.0		
Stand-by Current	I <sub>std</sub>		—	5	μA	
Symmetry	SYM	@50% V <sub>CC</sub>	45	55	%	
Rise/ Fall Time (10% V <sub>CC</sub> to 90% V <sub>CC</sub> Maximum Loaded)	tr/ tf		—	4	ns	
Low Level Output Voltage	V <sub>OL</sub>	I <sub>OL</sub> = 4mA	—	10% V <sub>CC</sub>	V	
High Level Output Voltage	V <sub>OH</sub>	I <sub>OH</sub> = -4mA	90% V <sub>CC</sub>	—	V	
CMOS Load	L <sub>CMOS</sub>	CMOS Output	—	15	pF	
Input Voltage Range	V <sub>IN</sub>		0	V <sub>CC</sub>	V	
Low Level Input Voltage	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V	
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>CC</sub>	—	V	
Disable Time	t <sub>dis</sub>		—	100	ns	
Enable Time	t <sub>ena</sub>		—	5	ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	J <sub>Sigma</sub>	Measured with Wavecrest SIA-3000	—	8	ps	
Peak to Peak Jitter	J <sub>PK-PK</sub>		—	80	ps	

Note: All electrical characteristics are defined at the maximum load and operating temperature range.  
Please contact us for inquiry about operating temperature range, available frequencies and other conditions


### Dimensions

(Unit: mm)




### Recommended Land Pattern

(Unit: mm)



CMOS/ 2.5V/ 3.2×2.5mm



RoHS Compliant

**Features**

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage  $V_{CC} = 2.5V$   
Lower voltage available
- $\pm 25 \times 10^{-6}$  available

**Table 1**

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	-10 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$		
6	$\pm 50$		

**How to Order**

**KC3225A 25.0000 C 2 □ E 00**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	$f_o$		1.5	125	MHz	
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	$\times 10^{-6}$
			Op. Temp.: -10 to +70°C/ -40 to +85°C/ -40 to +105°C	-50	+50	
			Op. Temp.: -10 to +70°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
Storage Temperature Range	$T_{stg}$		-55	+125	°C	
Operating Temperature Range	$T_{use}$	Standard Specifications	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-0.5	+7.0	V	
Supply Voltage	$V_{CC}$	Freq. Tol.Code: 0, S, F	+2.25	+2.75	V	
		Freq. Tol.Code: U, G, 6	+2.38	+2.62		
Current Consumption (Maximum Loaded)	$I_{CC}$	1.5 $\leq f_o \leq 26$ MHz	—	4	mA	
		26 $< f_o \leq 50$ MHz	—	6		
		50 $< f_o \leq 67.5$ MHz	—	9		
		67.5 $< f_o \leq 95$ MHz	—	14		
		95 $< f_o \leq 125$ MHz	—	18		
Stand-by Current	$I_{std}$		—	10	$\mu A$	
Symmetry	SYM	@50% $V_{CC}$	45	55	%	
Rise/ Fall Time (10% $V_{CC}$ to 90% $V_{CC}$ Maximum Loaded)	$t_r / t_f$	1.5 $\leq f_o \leq 67.5$ MHz	—	6	ns	
		67.5 $< f_o \leq 125$ MHz	—	4		
Low Level Output Voltage	$V_{OL}$	$I_{OL} = 4$ mA	—	10% $V_{CC}$	V	
High Level Output Voltage	$V_{OH}$	$I_{OH} = -4$ mA	90% $V_{CC}$	—	V	
CMOS Load	$L_{CMOS}$	CMOS Output	—	15	pF	
Input Voltage Range	$V_{IN}$		0	$V_{CC}$	V	
Low Level Input Voltage	$V_{IL}$		—	30% $V_{CC}$	V	
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$	—	V	
Disable Time	$t_{dis}$		—	150	ns	
Enable Time	$t_{ena}$		—	5	ms	
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	$J_{Sigma}$	Measured with Wavecrest SIA-3000	1.5 $\leq f_o \leq 60$ MHz	—	8	ps
			60 $< f_o \leq 125$ MHz	—	5	
Peak to Peak Jitter	$J_{PK-PK}$	Measured with Wavecrest SIA-3000	1.5 $\leq f_o \leq 60$ MHz	—	80	ps
			60 $< f_o \leq 125$ MHz	—	40	

Note: All electrical characteristics are defined at the maximum load and operating temperature range. Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)






# Clock Oscillators Surface Mount Type

## KC3225A-C3 Series



CMOS/ 3.3V/ 3.2×2.5mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage  $V_{CC} = 3.3V$
- $\pm 25 \times 10^{-6}$  available

Table 1

Freq. Tol. Code	Tolerance $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	-10 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC3225A 25.0000 C 3 □ E 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)


### Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	$f_o$		1.5	125	MHz	
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	$\times 10^{-6}$
			Op. Temp.: -10 to +70°C/ -40 to +85°C/ -40 to +105°C	-50	+50	
			Op. Temp.: -10 to +70°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
Storage Temperature Range	$T_{stg}$		-55	+125	°C	
Operating Temperature Range	$T_{use}$	Standard Specifications	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-40	+105		
Supply Voltage	$V_{CC}$	Freq. Tol.Code: 0, S, F	+2.97	+3.63	V	
		Freq. Tol.Code: U, G, 6	+3.14	+3.46	V	
Current Consumption (Maximum Loaded)	$I_{CC}$	1.5 ≤ $f_o$ ≤ 26MHz	—	6	mA	
		26 < $f_o$ ≤ 50MHz	—	8		
		50 < $f_o$ ≤ 67.5MHz	—	12		
		67.5 < $f_o$ ≤ 95MHz	—	20		
		95 < $f_o$ ≤ 125MHz	—	25		
Stand-by Current	$I_{std}$		—	10	μA	
Symmetry	SYM	@50% $V_{CC}$	45	55	%	
Rise/ Fall Time (10% $V_{CC}$ to 90% $V_{CC}$ Maximum Loaded)	$t_r/ t_f$	1.5 ≤ $f_o$ ≤ 67.5MHz	—	5	ns	
		67.5 < $f_o$ ≤ 125MHz	—	3		
Low Level Output Voltage	$V_{OL}$	$I_{OL} = 4mA$	—	10% $V_{CC}$	V	
High Level Output Voltage	$V_{OH}$	$I_{OH} = -4mA$	90% $V_{CC}$	—	V	
CMOS Load	$L_{CMOS}$	CMOS Output	—	15	pF	
Input Voltage Range	$V_{IN}$		0	$V_{CC}$	V	
Low Level Input Voltage	$V_{IL}$		—	30% $V_{CC}$	V	
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$	—	V	
Disable Time	$t_{dis}$		—	150	ns	
Enable Time	$t_{ena}$		—	5	ms	
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	$J_{Sigma}$	Measured with Wavecrest SIA-3000	1.5 ≤ $f_o$ ≤ 60MHz	—	8	ps
			60 < $f_o$ ≤ 125MHz	—	5	
Peak to Peak Jitter	$J_{PK-PK}$	Measured with Wavecrest SIA-3000	1.5 ≤ $f_o$ ≤ 60MHz	—	80	ps
			60 < $f_o$ ≤ 125MHz	—	40	

Note: All electrical characteristics are defined at the maximum load and operating temperature range. Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)



CMOS/ 1.8V to 5.0V/ 5.0×3.2mm



RoHS Compliant

**Features**

- Wide operating voltage range 1.6 to 5.5V
- ±25×10<sup>-6</sup> available
- Highly reliable with seam welding
- Miniature ceramic package
- CMOS output

**Table 1**

Freq. Code	Tol. × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
F	±100	-40 to +85	Please contact us for available frequencies.
G	± 50		
6	± 50	-40 to +105	

**How to Order**

**KC5032A 25.0000 C M □ E 00**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
  - ② Output Frequency
  - ③ Output Type (CMOS)
  - ④ Supply Voltage (1.8V, 2.5V, 3.3V, 5V Compatible)
  - ⑤ Frequency Tolerance (See Table 1)
  - ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
  - ⑦ Individual Specification (STD Specification is "00")
- Packaging (Tape & Reel 1000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	f <sub>o</sub>		1.8	50	MHz	
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	×10 <sup>-6</sup>
			Op. Temp.: -10 to +70°C/ -40 to +85°C/ -40 to +105°C	-50	+50	
			Op. Temp.: -10 to +70°C	-30	+30	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>	Standard Specification	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-40	+105		
Supply Voltage	V <sub>CC</sub>		-0.6	+6.5	V	
Current Consumption (Loaded) (1.6<V <sub>CC</sub> ≤2.0V)	I <sub>CC</sub>	1.8≤f <sub>o</sub> ≤20MHz	—	3.5	mA	
		20<f <sub>o</sub> ≤40MHz	—	4.5		
		40<f <sub>o</sub> ≤50MHz	—	5.0		
Current Consumption (Loaded) (2.0<V <sub>CC</sub> ≤2.8V)	I <sub>CC</sub>	1.8≤f <sub>o</sub> ≤20MHz	—	4.0	mA	
		20<f <sub>o</sub> ≤40MHz	—	5.0		
		40<f <sub>o</sub> ≤50MHz	—	6.0		
Current Consumption (Loaded) (2.8<V <sub>CC</sub> ≤3.63V)	I <sub>CC</sub>	1.8≤f <sub>o</sub> ≤20MHz	—	5.0	mA	
		20<f <sub>o</sub> ≤40MHz	—	6.0		
		40<f <sub>o</sub> ≤50MHz	—	7.0		
Current Consumption (Loaded) (3.63<V <sub>CC</sub> ≤5.5V)	I <sub>CC</sub>	1.8≤f <sub>o</sub> ≤20MHz	—	7.0	mA	
		20<f <sub>o</sub> ≤40MHz	—	8.0		
		40<f <sub>o</sub> ≤50MHz	—	9.5		
Stand-by Current	I <sub>std</sub>		—	10	μA	
Symmetry	SYM	@50% V <sub>CC</sub>	45	55	%	
		1.6≤V <sub>CC</sub> ≤2V	—	8		
Rise/ Fall Time (10% V <sub>CC</sub> to 90% V <sub>CC</sub> Maximum Loaded)	tr/ tf	2<V <sub>CC</sub> ≤2.8V	—	7	ns	
		2.8<V <sub>CC</sub> ≤3.63V	—	6		
		4.5≤V <sub>CC</sub> ≤5.5V	—	5		
			—	5		
Low Level Output Voltage	V <sub>OL</sub>	I <sub>OL</sub> = 4mA	—	10% V <sub>CC</sub>	V	
High Level Output Voltage	V <sub>OH</sub>	I <sub>OH</sub> = -4mA	90% V <sub>CC</sub>	—	V	
Output Load	L <sub>CMOS</sub>	1.6≤V <sub>CC</sub> ≤5.5V	—	15	pF	
Input Voltage Range	V <sub>IN</sub>		0	V <sub>CC</sub>	V	
Low Level Input Voltage	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V	
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>CC</sub>	—	V	
Disable Time	t <sub>dis</sub>		—	150	ns	
Enable Time	t <sub>ena</sub>		—	5	ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	J <sub>Sigma</sub>	Measured with Wavecrest SIA-3000	1.8≤f <sub>o</sub> ≤40MHz	—	8	ps
			40<f <sub>o</sub> ≤50MHz	—	5	
Peak to Peak Jitter	J <sub>PK-PK</sub>	Measured with Wavecrest SIA-3000	1.8≤f <sub>o</sub> ≤40MHz	—	80	ps
			40<f <sub>o</sub> ≤50MHz	—	50	

Note: All electrical characteristics are defined at the maximum load and operating temperature range. Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)






# Clock Oscillators Surface Mount Type KC5032A-C1 Series (High Frequency)



CMOS/ 1.8V to 3.3V/ 5.0×3.2mm



RoHS Compliant

## Features

- Wide operating voltage range 1.6 to 3.3V
- $\pm 25 \times 10^{-6}$  available
- Highly reliable with seam welding
- Miniature ceramic package
- CMOS output

Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	-10 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$	-40 to +85	
6	$\pm 50$	-40 to +105	

## How to Order

KC5032A 100.000 C 1 □ E 00  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V, 2.5V, 3.3V Compatible)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)


## Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	fo	fo>50MHz	50	135	MHz	
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	$\times 10^{-6}$
			Op. Temp.: -10 to +70°C/ -40 to +105°C	-50	+50	
			Op. Temp.: -10 to +70°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
Storage Temperature Range	T <sub>stg</sub>	Standard Specification	-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>	Standard Specification	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-0.3	+4.0	V	
Supply Voltage	V <sub>cc</sub>		+1.6	+3.63	V	
Current Consumption (Loaded) (1.6<V <sub>cc</sub> ≤2.0V)	I <sub>cc</sub>	50<fo≤85MHz	—	10	mA	
		85<fo≤105MHz	—	15		
		105<fo≤135MHz	—	16		
Current Consumption (Loaded) (2.0<V <sub>cc</sub> ≤2.8V)	50<fo≤85MHz	—	14			
	85<fo≤105MHz	—	17			
	105<fo≤135MHz	—	18			
Current Consumption (Loaded) (2.8<V <sub>cc</sub> ≤3.63V)	50<fo≤85MHz	—	17			
	85<fo≤105MHz	—	19			
	105<fo≤135MHz	—	22			
Stand-by Current	I <sub>std</sub>		—	10	μA	
Symmetry	SYM	@50% V <sub>cc</sub>	45	55	%	
Rise/ Fall Time (10% V <sub>cc</sub> to 90% V <sub>cc</sub> Maximum Loaded)	tr/ tf	1.6≤V <sub>cc</sub> ≤2V	—	3.5	ns	
		2<V <sub>cc</sub> ≤2.8V	—	3.0		
		2.8<V <sub>cc</sub> ≤3.63V	—	2.5		
Low Level Output Voltage	V <sub>OL</sub>		—	10% V <sub>cc</sub>	V	
High Level Output Voltage	V <sub>OH</sub>		90% V <sub>cc</sub>	—	V	
Output Load	L <sub>CMOS</sub>	1.6≤V <sub>cc</sub> ≤3.63V	—	15	pF	
Input Voltage Range	V <sub>IN</sub>		0	V <sub>cc</sub>	V	
Low Level Input Voltage	V <sub>IL</sub>		—	30% V <sub>cc</sub>	V	
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>cc</sub>	—	V	
Disable Time	t <sub>dis</sub>		—	150	ns	
Enable Time	t <sub>ena</sub>		—	5	ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	J <sub>Sigma</sub>	Measured with Wavecrest SIA-3000	50<fo≤100MHz	—	5	ps
			100<fo≤135MHz	—	4	
Peak to Peak Jitter	J <sub>PK-PK</sub>		50<fo≤100MHz	—	40	ps
			100<fo≤135MHz	—	30	

Note: All electrical characteristics are defined at the maximum load and operating temperature range.  
Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


## Dimensions

(Unit: mm)



## Recommended Land Pattern

(Unit: mm)







# Clock Oscillators Surface Mount Type

## KC5032A-C5 Series



CMOS/ 5.0V/ 5.0×3.2mm



RoHS Compliant

### Features

- ±25×10<sup>-6</sup> available
- Highly reliable with seam welding
- Miniature ceramic package
- CMOS output
- Supply voltage V<sub>cc</sub> = 5.0V

Table 1

Freq. Tol. Code	Tolerance × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
F	±100	-40 to +85	Please contact us for available frequencies.
G	± 50		
6	± 50	-40 to +105	

### How to Order

KC5032A 25.0000 C 5 □ E 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)


### Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	f <sub>o</sub>		1.8	50	MHz	
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	×10 <sup>-6</sup>
			Op. Temp.: -10 to +70°C/ -40 to +85°C/ -40 to +105°C	-50	+50	
			Op. Temp.: -10 to +70°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>	Standard Specification	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-0.6	+6.5	V	
Supply Voltage	V <sub>cc</sub>		+4.5	+5.5	V	
Current Consumption (Loaded)	I <sub>cc</sub>	1.8≤f <sub>o</sub> ≤20MHz	—	12	mA	
		20<f <sub>o</sub> ≤40MHz	—	17		
		40<f <sub>o</sub> ≤50MHz	—	20		
Stand-by Current	I <sub>std</sub>		—	10	μA	
Symmetry	SYM	@50% V <sub>cc</sub>	45	55	%	
Rise/ Fall Time (10% V <sub>cc</sub> to 90% V <sub>cc</sub> Maximum Loaded)	tr/ tf	1.8≤f <sub>o</sub> ≤26MHz	—	10	ns	
		26<f <sub>o</sub> ≤50MHz	—	8		
Low Level Output Voltage	V <sub>oL</sub>	I <sub>oL</sub> = 4mA	—	10% V <sub>cc</sub>	V	
High Level Output Voltage	V <sub>oH</sub>	I <sub>oH</sub> = -4mA	90% V <sub>cc</sub>	—	V	
Output Load	L <sub>CMOS</sub>	CMOS Output	—	50	pF	
Input Voltage Range	V <sub>IN</sub>		0	V <sub>cc</sub>	V	
Low Level Input Voltage	V <sub>IL</sub>		—	30% V <sub>cc</sub>	V	
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>cc</sub>	—	V	
Disable Time	t <sub>dis</sub>		—	150	ns	
Enable Time	t <sub>ena</sub>		—	5	ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	J <sub>Sigma</sub>	Measured with Wavecrest SIA-3000	1.8≤f <sub>o</sub> ≤40MHz	—	8	ps
			40<f <sub>o</sub> ≤50MHz	—	5	
Peak to Peak Jitter	J <sub>PK-PK</sub>	Measured with Wavecrest SIA-3000	1.8≤f <sub>o</sub> ≤40MHz	—	80	ps
			40<f <sub>o</sub> ≤50MHz	—	50	

Note: All electrical characteristics are defined at the maximum load and operating temperature range.  
 Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


### Dimensions

(Unit: mm)




### Recommended Land Pattern

(Unit: mm)



CMOS/ 3.3V/ 5.0×3.2mm



RoHS Compliant

**Features**

- Built-in Spread Spectrum function
- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage Vcc = 3.3V
- External control pad for Modulation Selectable (For initial testing purpose only)

**Table 1**

Spread Type			
Center Spread		Down Spread	
Code	Spread %	Code	Spread %
C2	±0.5%	D2	-1.0%
C4	±1.0%	D4	-2.0%
C6	±1.5%	D6	-3.0%
C0*	External Control*	D0*	External Control*

\* For initial testing purpose only

**How to Order**

KC5032E 25.0000 C 3 F E □□  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (±100ppm)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Spread Type and Spread Percent or Individual Specification (See Table 1)

Packaging (Tape & Reel 1000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	fo		14.31818	166	MHz	
Frequency Tolerance	f_tol	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration Op. Temp.: -40 to +85°C	-100	+100	×10 <sup>-6</sup>	
Storage Temperature Range	T_stg		-55	+125	°C	
Operating Temperature Range	T_use		-40	+85	°C	
Max. Supply Voltage	—		-0.5	+4.6	V	
Supply Voltage	Vcc		+2.97	+3.63	V	
Current Consumption (Maximum Loaded)	Icc	fo≤40MHz	—	20	mA	
		40<fo≤100MHz	—	25		
		100<fo≤166MHz	—	35		
Stand-by Current	I_std		—	30	µA	
Symmetry	SYM	@50% Vcc	45	55	%	
Rise/ Fall Time (10% Vcc to 90% Vcc Maximum Loaded)	tr/ tf	14.31818≤fo≤40MHz	—	10	ns	
		40<fo≤100MHz	—	5		
		100<fo≤166MHz	—	3		
Low Level Output Voltage	VoL	IoL = 13mA (fo<40MHz), IoL = 19mA (40≤fo<100MHz) IoL = 44mA (100≤fo≤166MHz)	—	10% Vcc	V	
High Level Output Voltage	VoH	IoH = -13mA (fo<40MHz), IoH = -19mA (40≤fo<100MHz) IoH = -44mA (100≤fo≤166MHz)	90% Vcc	—	V	
CMOS Load	L_CMOS	CMOS Output	—	15	pF	
Input Voltage Range	VIN		0	Vcc	V	
Low Level Input Voltage	VIL		—	30% Vcc	V	
High Level Input Voltage	VIH		70% Vcc	—	V	
Disable Time	t_dis		—	200	ns	
Enable Time	t_ena		—	10	ms	
Start-up Time	t_str	@Minimum operating voltage to be 0 sec.	—	20	ms	
Peak to Peak Jitter (Cycle to Cycle Jitter)	JPK-PK	Measured with @50%Vcc 10,000 cyc. min. Lecroy Wavepro 950	14.31818≤fo<40MHz	—	±250	ps
			40≤fo<80MHz	—	±175	
			80≤fo≤166MHz	—	±150	

Note: All electrical characteristics are defined at the maximum load and operating temperature range.  
Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)





CMOS/ 1.8V/ 7.0×5.0mm



RoHS Compliant

**Features**

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage Vcc = 1.8V  
Lower voltage available
- ±25×10<sup>-6</sup>, ±20×10<sup>-6</sup> available

**Table 1**

Stability Code	× 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
W	± 20		
F	±100	-40 to +85	Please contact us for available frequencies.
G	± 50		
6	± 50		

**How to Order**

KC7050A 25.0000 C 1 □ E 00  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	fo		1.8	39.99	MHz	
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	×10 <sup>-6</sup>
			Op. Temp.: -10 to +70°C/ -40 to +85°C/-40 to +105°C	-50	+50	
			Op. Temp.: -10 to +70°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
			Op. Temp.: -10 to +70°C	-20	+20	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>	Standard Specifications	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-0.5	+3.6	V	
Supply Voltage	V <sub>cc</sub>	Freq. Tol.Code: 0, S, F	+1.71	+1.89	V	
		Freq. Tol.Code: U, G, W, 6	+1.75	+1.85		
Current Consumption (Maximum Loaded)	I <sub>cc</sub>	1.8≤fo≤25MHz	—	3	mA	
		25<fo≤39.99MHz	—	4		
Stand-by Current	I <sub>std</sub>		—	10	μA	
Symmetry	SYM	@50% V <sub>cc</sub>	45	55	%	
Rise/ Fall Time (10% V <sub>cc</sub> to 90% V <sub>cc</sub> Maximum Loaded)	tr/ tf		—	9	ns	
Low Level Output Voltage	V <sub>OL</sub>	I <sub>OL</sub> = 2.8mA	—	10% V <sub>cc</sub>	V	
High Level Output Voltage	V <sub>OH</sub>	I <sub>OH</sub> = -2.8mA	90% V <sub>cc</sub>	—	V	
CMOS Load	L <sub>CMOS</sub>	CMOS Output	—	15	pF	
Input Voltage Range	V <sub>IN</sub>		0	V <sub>cc</sub>	V	
Low Level Input Voltage	V <sub>IL</sub>		—	30% V <sub>cc</sub>	V	
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>cc</sub>	—	V	
Disable Time	t <sub>dis</sub>		—	150	ns	
Enable Time	t <sub>ena</sub>		—	5	ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	J <sub>Sigma</sub>	Measured with Wavcrest SIA-3000	—	8	ps	
Peak to Peak Jitter	J <sub>PK-PK</sub>		—	80	ps	

Note: All electrical characteristics are defined at the maximum load and operating temperature range.  
Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



CMOS/ 2.5V/ 7.0×5.0mm



RoHS Compliant

**Features**

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage  $V_{CC} = 2.5V$   
Lower voltage available
- $\pm 25 \times 10^{-6}$ ,  $\pm 20 \times 10^{-6}$  available

**How to Order**

**KC7050A 25.0000 C 2 □ E 00**  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

**Table 1**

Stability Code	Stability $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	-10 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
W	$\pm 20$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$		
6	$\pm 50$		


**Specifications**

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	$f_o$		1.8	125	MHz	
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	$\times 10^{-6}$
			Op. Temp.: -10 to +70°C/ -40 to +85°C/ -40 to +105°C	-50	+50	
			Op. Temp.: -10 to +70°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
			Op. Temp.: -10 to +70°C	-20	+20	
Storage Temperature Range	$T_{stg}$		-55	+125	°C	
Operating Temperature Range	$T_{use}$	Standard Specifications	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-0.5	+7.0	V	
Supply Voltage	$V_{CC}$	Freq. Tol.Code: 0, S, F	+2.25	+2.75	V	
		Freq. Tol.Code: U, G, 6	+2.38	+2.62		
		Freq. Tol.Code: W	+2.43	+2.57		
Current Consumption (Maximum Loaded)	$I_{CC}$	1.8 $\leq f_o \leq 20$ MHz	—	5	mA	
		20 $< f_o \leq 40$ MHz	—	10		
		40 $< f_o \leq 60$ MHz	—	15		
		60 $< f_o \leq 85$ MHz	—	20		
		85 $< f_o \leq 100$ MHz	—	22		
		100 $< f_o \leq 125$ MHz	—	27		
Stand-by Current	$I_{std}$		—	10	$\mu A$	
Symmetry	SYM	@50% $V_{CC}$	45	55	%	
Rise/ Fall Time (10% $V_{CC}$ to 90% $V_{CC}$ Maximum Loaded)	$t_r / t_f$	1.8 $\leq f_o \leq 40$ MHz	—	7	ns	
		40 $< f_o \leq 85$ MHz	—	4		
		85 $< f_o \leq 125$ MHz	—	3		
Low Level Output Voltage	$V_{OL}$	$I_{OL} = 4mA / 8mA$ (40MHz $< f_o$ )	—	10% $V_{CC}$	V	
High Level Output Voltage	$V_{OH}$	$I_{OH} = -4mA / -8mA$ (40MHz $< f_o$ )	90% $V_{CC}$	—	V	
CMOS Load	$L_{CMOS}$	CMOS Output	—	15	pF	
Input Voltage Range	$V_{IN}$		0	$V_{CC}$	V	
Low Level Input Voltage	$V_{IL}$		—	30% $V_{CC}$	V	
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$	—	V	
Disable Time	$t_{dis}$		—	150	ns	
Enable Time	$t_{ena}$		—	5	ms	
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	$J_{Sigma}$	Measured with Wavecrest SIA-3000	1.8 $\leq f_o < 40$ MHz	—	8	ps
			40 $\leq f_o \leq 100$ MHz	—	5	
			100 $< f_o \leq 125$ MHz	—	4	
Peak to Peak Jitter	$J_{PK-PK}$	Measured with Wavecrest SIA-3000	1.8 $\leq f_o < 40$ MHz	—	80	ps
			40 $\leq f_o < 100$ MHz	—	40	
			100 $\leq f_o \leq 125$ MHz	—	30	

Note: All electrical characteristics are defined at the maximum load and operating temperature range. Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)





# Clock Oscillators Surface Mount Type

## KC7050A-C3 Series



CMOS/ 3.3V/ 7.0×5.0mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage  $V_{CC} = 3.3V$
- $\pm 25 \times 10^{-6}$ ,  $\pm 20 \times 10^{-6}$  available

Table 1

Stability Code	Stability $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	-10 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
W	$\pm 20$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC7050A 25.0000 C 3 □ E 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)


### Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	$f_o$		1.8	170	MHz	
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	$\times 10^{-6}$
			Op. Temp.: -10 to +70°C/ -40 to +85°C/ -40 to +105°C	-50	+50	
			Op. Temp.: -10 to +70°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
			Op. Temp.: -10 to +70°C	-20	+20	
Storage Temperature Range	$T_{stg}$		-55	+125	°C	
Operating Temperature Range	$T_{use}$	Standard Specifications	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	-	$f_o < 135\text{MHz}$	-0.5	+7.0	V	
		$f_o \geq 135\text{MHz}$	-0.5	+5.0		
Supply Voltage	$V_{CC}$	Freq. Tol.Code: 0, S, F	+2.97	+3.63	V	
		Freq. Tol.Code: U, G, 6	+3.14	+3.46		
		Freq. Tol.Code: W	+3.20	+3.40		
Current Consumption (Maximum Loaded)	$I_{CC}$	$1.8 \leq f_o \leq 20\text{MHz}$	-	10	mA	
		$20 < f_o \leq 40\text{MHz}$	-	15		
		$40 < f_o \leq 60\text{MHz}$	-	30		
		$60 < f_o \leq 100\text{MHz}$	-	35		
		$100 < f_o \leq 135\text{MHz}$	-	45		
		$135 < f_o \leq 170\text{MHz}$	-	60		
Stand-by Current	$I_{std}$		-	10	$\mu\text{A}$	
Symmetry	SYM	@50% $V_{CC}$	45	55	%	
Rise/ Fall Time (10% $V_{CC}$ to 90% $V_{CC}$ Maximum Loaded)	$t_r / t_f$	$1.8 \leq f_o \leq 26\text{MHz}$	-	10	ns	
		$26 < f_o \leq 45\text{MHz}$	-	8		
		$45 < f_o \leq 100\text{MHz}$	-	5		
		$100 < f_o \leq 170\text{MHz}$	-	2.5		
Low Level Output Voltage	$V_{OL}$	$I_{OL} = 8\text{mA}$	-	10% $V_{CC}$	V	
High Level Output Voltage	$V_{OH}$	$I_{OH} = -8\text{mA}$	90% $V_{CC}$	-	V	
CMOS Load	$L_{CMOS}$	CMOS Output	-	15	pF	
Input Voltage Range	$V_{IN}$		0	$V_{CC}$	V	
Low Level Input Voltage	$V_{IL}$		-	30% $V_{CC}$	V	
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$	-	V	
Disable Time	$t_{dis}$		-	150	ns	
Enable Time	$t_{ena}$		-	5	ms	
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	-	10	ms	
1 Sigma Jitter	$J_{Sigma}$	Measured with Wavecrest SIA-3000	$1.8 \leq f_o < 40\text{MHz}$	-	8	ps
			$40 \leq f_o \leq 100\text{MHz}$	-	5	
			$100 < f_o \leq 170\text{MHz}$	-	4	
Peak to Peak Jitter	$J_{PK-PK}$	Measured with Wavecrest SIA-3000	$1.8 \leq f_o < 40\text{MHz}$	-	80	ps
			$40 \leq f_o \leq 100\text{MHz}$	-	40	
			$100 < f_o \leq 170\text{MHz}$	-	30	

Note: All electrical characteristics are defined at the maximum load and operating temperature range. Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)





CMOS/ 5.0V/ 7.0×5.0mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage  $V_{CC} = 5.0V$

Table 1

Stability Code	Stability $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	-10 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC7050A 25.0000 C 5 □ D 00

① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (5.0V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Disable)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)


### Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range	$f_o$		1.8	50	MHz	
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	$\times 10^{-6}$
			Op. Temp.: -10 to +70°C/ -40 to +85°C/ -40 to +105°C	-50	+50	
			Op. Temp.: -10 to +70°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
Storage Temperature Range	$T_{stg}$		-55	+125	°C	
Operating Temperature Range	$T_{use}$	Standard Specifications	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-0.5	+7.0	V	
Supply Voltage	$V_{CC}$	Freq. Tol.Code: 0, S, F	+4.5	+5.5	V	
		Freq. Tol.Code: U, G, 6	+4.75	+5.25		
Current Consumption (Maximum Loaded)	$I_{CC}$	$1.8 \leq f_o \leq 20MHz$	—	25	mA	
		$20 < f_o \leq 40MHz$	—	35		
		$40 < f_o \leq 50MHz$	—	50		
Disable Current	$I_{dis}$		—	20	mA	
Symmetry	SYM	@50% $V_{CC}$	45	55	%	
Rise/ Fall Time (10% $V_{CC}$ to 90% $V_{CC}$ Maximum Loaded)	$t_r / t_f$	$1.8 \leq f_o \leq 26MHz$	—	10	ns	
		$26 < f_o \leq 50MHz$	—	8		
Low Level Output Voltage	$V_{OL}$	$I_{OL} = 16mA$	—	10% $V_{CC}$	V	
High Level Output Voltage	$V_{OH}$	$I_{OH} = -16mA$	90% $V_{CC}$	—	V	
CMOS Load	$L_{CMOS}$	CMOS Output	—	50	pF	
Input Voltage Range	$V_{IN}$		0	$V_{CC}$	V	
Low Level Input Voltage	$V_{IL}$		—	0.8	V	
High Level Input Voltage	$V_{IH}$		2.2	—	V	
Disable Time	$t_{dis}$		—	100	ns	
Enable Time	$t_{ena}$		—	100	ns	
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	—	10	ms	
1 Sigma Jitter	$J_{Sigma}$	Measured with Wavecrest SIA-3000	$1.8 \leq f_o < 40MHz$	—	8	ps
			$40 \leq f_o \leq 50MHz$	—	5	
Peak to Peak Jitter	$J_{PK-PK}$	Measured with Wavecrest SIA-3000	$1.8 \leq f_o < 40MHz$	—	80	ps
			$40 \leq f_o \leq 50MHz$	—	40	

Note: All electrical characteristics are defined at the maximum load and operating temperature range. Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)





CMOS/ 5.0V/ 7.0×5.0mm



RoHS Compliant

**Features**

- Surface mount type suitable for auto pick-and-place
- Reflow compatible
- CMOS, TTL IC direct drive is possible
- With tri-state function
- Broad frequency range 80MHz (PLL circuit is built in)
- Supply voltage Vcc = 5.0V available

**How to Order**

**KC7050B 80.0000 C 5 Z B QZ**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage 5 = 5.0V
- ⑤ Frequency Tolerance (See Table 3)
- ⑥ Symmetry/ INH Function (40/ 60%, Stand-by)
- ⑦ Individual Specification (STD Specification is "QZ")

**Table 3**

Freq. Tol. Code	× 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
Z	± 50	-10 to +85	80MHz

"Designated for MFP3N, Communication LSI for CC-Link Remote Device"


**Specifications**

Item	Symbol	Conditions	Specifications		Units
			Min.	Max.	
Output Frequency Range	f <sub>o</sub>		80		MHz
Frequency Tolerance (Overall)	f <sub>tol</sub>		-50	+50	×10 <sup>-6</sup>
Storage Temperature Range	T <sub>stg</sub>		-20	+85	°C
Operating Temperature Range	T <sub>use</sub>		-10	+85	°C
Max. Supply Voltage	—		-0.5	+6	V
Supply Voltage	V <sub>CC</sub>	5.0V Typ.	+4.75	+5.25	V
Current Consumption	I <sub>CC</sub>		—	50	mA
Stand-by Current	I <sub>std</sub>		—	40	μA
Symmetry	SYM	@50% V <sub>CC</sub>	40	60	%
Rise/ Fall Time	tr/ tf		—	5	ns
Low Level Output Voltage	V <sub>OL</sub>		—	10% V <sub>CC</sub>	V
High Level Output Voltage	V <sub>OH</sub>	@5.0 V	90% V <sub>CC</sub>	—	V
CMOS Load	L <sub>CMOS</sub>	CMOS Output	—	15	pF
Input Voltage Range	V <sub>IN</sub>		V <sub>SS</sub>	V <sub>CC</sub>	V
Low Level Input Voltage	V <sub>IL</sub>		—	0.8	V
High Level Input Voltage	V <sub>IH</sub>		2.2	—	V
Disable Time	t <sub>dis</sub>		—	100	ns
Enable Time	t <sub>ena</sub>		—	100	μs
Start-up Time	t <sub>str</sub>		—	10	ms

Note: All electrical characteristics are defined at the maximum load and operating temperature range. Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)






# Clock Oscillators Surface Mount Type

## KC3225L-P2/ KC3225L-P3 Series



LV-PECL/ 3.3V or 2.5V/ 3.2x2.5mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- LV-PECL output
- Supply voltage  $V_{CC} = 3.3V, 2.5V$
- $\pm 25 \times 10^{-6}$  available
- Low Phase Noise

### Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	0 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$	-40 to +85	Please contact us for available frequencies.
F	$\pm 100$		
G	$\pm 50$		
6	$\pm 50$		

### How to Order

KC3225L 125.000 P □ □ J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function  
J : 45/ 55%, Stand-by
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)

### Specifications


Item	Symbol	Conditions	Specifications		Units	
			KC3225L-P2	KC3225L-P3		
Output Frequency Range <sup>Note1</sup>	fo		25 to 175		MHz	
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	$\pm 50/ -40$ to +105°C		ppm	
			$\pm 100/ -40$ to +85°C			
			$\pm 50/ -40$ to +85°C			
			$\pm 50/ 0$ to +70°C			
			$\pm 30/ 0$ to +70°C			
Storage Temperature Range	T <sub>stg</sub>		-55 to +125		°C	
Operating Temperature Range	T <sub>use</sub>	Standard Specifications	0 to +70/ -40 to +85		°C	
		Extend (Option)	-40 to +105			
Max. Supply Voltage	—		-0.5 to +5.0		V	
Supply Voltage	V <sub>CC</sub>		+2.375 to +2.625	+2.97 to +3.63	V	
Current Consumption	I <sub>CC</sub>	$\leq 156.25\text{MHz}$	60 max.		mA	
		156.25MHz<	70 max.			
Stand-by Current	I <sub>std</sub>		20 max.		μA	
Symmetry	SYM	50ohm @crossing point	50±5		%	
Rise/ Fall Time (20% V <sub>CC</sub> to 80% V <sub>CC</sub> Maximum Loaded)	tr/ tf	50ohm	0.6 max.		ns	
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		V <sub>CC</sub> -1.810 to V <sub>CC</sub> -1.620		V	
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		V <sub>CC</sub> -1.025 to V <sub>CC</sub> -0.880		V	
Output Load	RL		50		ohm	
Input Voltage Range	V <sub>IN</sub>		0 to V <sub>CC</sub>			
Low Level Input Voltage	V <sub>IL</sub>		30% V <sub>CC</sub> max.		V	
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>CC</sub> min.		V	
Disable Time	t <sub>dis</sub>		150 max.		ns	
Enable Time	t <sub>ena</sub>		10 max.		ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	10 max.		ms	
Deterministic Jitter	DJ		2 max.		ps	
1 Sigma Jitter	J <sub>sigma</sub>	Measured with Wavecrest SIA-3000	4 max.		ps	
Peak to Peak Jitter	J <sub>PK-PK</sub>		30 max.		ps	
Phase Jitter	J <sub>Phase</sub>	@156.25MHz V <sub>CC</sub> = 3.3V	BW : 12kHz to 20MHz	0.3max.		ps
		@156.25MHz V <sub>CC</sub> = 3.3V				
Phase Noise	—	@156.25MHz V <sub>CC</sub> = 3.3V	@10Hz offset	Typ. -77		dBc/ Hz
			@100Hz offset	Typ. -103		
			@1kHz offset	Typ. -133		
			@10kHz offset	Typ. -143		
			@100kHz offset	Typ. -149		
			@1MHz offset	Typ. -149		
			@10MHz offset	Typ. -154		

Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions. Note2: DC characteristic


### Dimensions

(Unit: mm)




### Recommended Land Pattern

(Unit: mm)



LV-PECL/ 3.3V or 2.5V/ 5.0×3.2mm



RoHS Compliant

**Features**

- Miniature ceramic package
- Highly reliable with seam welding
- LV-PECL output
- Supply voltage Vcc = 3.3V, 2.5V
- ±25×10<sup>-6</sup> available
- Low Phase Noise

**Table 1**

Freq. Tol. Code	Tolerance × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
0	± 50	0 to +70	Standard specifications
S	± 30		
U	± 25	-40 to +85	Please contact us for available frequencies.
F	±100		
G	± 50		
6	± 50	-40 to +105	

**How to Order**

**KC5032L 100.000 P □ G J 00**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by) J: Low Phase Noise
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

**Specifications**

Item	Symbol	Conditions	Specifications		Units	
			KC5032L-P2	KC5032L-P3		
Output Frequency Range <sup>Note1</sup>	f <sub>o</sub>		25 to 170		MHz	
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	±50/ -40 to +105°C		ppm	
			±100/ -40 to +85°C			
			±50/ -40 to +85°C			
			±50/ 0 to +70°C			
			±30/ 0 to +70°C			
Storage Temperature Range	T <sub>stg</sub>		-55 to +125		°C	
Operating Temperature Range	T <sub>use</sub>	Standard Specifications Extend (Option)	0 to +70/ -40 to +85		°C	
			-40 to +105			
Max. Supply Voltage	—		-0.3 to +4.0		V	
Supply Voltage	V <sub>cc</sub>		+2.25 to +2.75	+2.97 to +3.63	V	
Current Consumption	I <sub>cc</sub>	≤156.25MHz 156.25MHz<	60 max. 70 max.		mA	
Stand-by Current	I <sub>std</sub>		20 max.		µA	
Symmetry	SYM	50ohm @crossing point	50±5		%	
Rise/ Fall Time (20% V <sub>cc</sub> to 80% V <sub>cc</sub> Maximum Loaded)	tr/ tf	50ohm	0.6 max. (V <sub>cc</sub> : 2.25 to 2.75V) 0.4 max. (V <sub>cc</sub> : 2.97 to 3.63V)		ns	
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		V <sub>cc</sub> -1.810 to V <sub>cc</sub> -1.620		V	
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		V <sub>cc</sub> -1.025 to V <sub>cc</sub> -0.880		V	
Output Load	RL		50		ohm	
Input Voltage Range	V <sub>IN</sub>		0 to V <sub>cc</sub>		V	
Low Level Input Voltage	V <sub>IL</sub>		30% V <sub>cc</sub> max.		V	
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>cc</sub> min.		V	
Disable Time	t <sub>dis</sub>		150 max.		ns	
Enable Time	t <sub>ena</sub>		10 max.		ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	10 max.		ms	
Deterministic Jitter	DJ	Measured with Wavecrest SIA-3000	2 max.		ps	
1 Sigma Jitter	J <sub>Sigma</sub>		4 max.		ps	
Peak to Peak Jitter	J <sub>PK-PK</sub>		30 max.		ps	
Phase Jitter	J <sub>Phase</sub>	@156.25MHz V <sub>cc</sub> = 3.3V	BW : 12kHz to 20MHz	0.3max.		ps
		@156.25MHz V <sub>cc</sub> = 3.3V	@10Hz offset	Typ. -77		dBc/ Hz
@100Hz offset	Typ. -103					
@1kHz offset	Typ. -133					
@10kHz offset	Typ. -143					
@100kHz offset	Typ. -149					
@1MHz offset	Typ. -149					
@10MHz offset	Typ. -154					


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)






# Clock Oscillators Surface Mount Type

## KC5032P-P2/ KC5032P-P3 Series



LV-PECL/ 3.3V or 2.5V/ 5.0×3.2mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- LV-PECL output
- Supply voltage  $V_{CC} = 3.3V, 2.5V$
- $\pm 25 \times 10^{-6}$  available
- Low Phase Noise

Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	0 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$	-40 to +85	Please contact us for available frequencies.
F	$\pm 100$		
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC5032P 125.000 P □ □ J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function  
J : 45/ 55%, Stand-by
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Specifications		Units
			KC5032P-P2	KC5032P-P3	
Output Frequency Range <sup>Note1</sup>	$f_o$		25 to 175		MHz
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	$\pm 50/ -40$ to $+105^\circ C$		ppm
			$\pm 100/ -40$ to $+85^\circ C$		
			$\pm 50/ -40$ to $+85^\circ C$		
			$\pm 50/ 0$ to $+70^\circ C$		
			$\pm 30/ 0$ to $+70^\circ C$		
Storage Temperature Range	$T_{stg}$		-55 to +125		°C
Operating Temperature Range	$T_{use}$	Standard Specifications	0 to +70/ -40 to +85		°C
		Extend (Option)	-40 to +105		
Max. Supply Voltage	—		-0.5 to +5.0		V
Supply Voltage	$V_{CC}$		+2.375 to +2.625	+2.97 to +3.63	V
Current Consumption	$I_{CC}$		70 max.		mA
Stand-by Current	$I_{std}$		20 max.		$\mu A$
Symmetry	SYM	50ohm @crossing point	50±5		%
Rise/ Fall Time (20% $V_{CC}$ to 80% $V_{CC}$ Maximum Loaded)	$t_r/ t_f$	50ohm	0.6 max.		ns
Low Level Output Voltage <sup>Note2</sup>	$V_{OL}$		$V_{CC} - 1.810$ to $V_{CC} - 1.620$		V
High Level Output Voltage <sup>Note2</sup>	$V_{OH}$		$V_{CC} - 1.025$ to $V_{CC} - 0.880$		V
Output Load	RL		50		ohm
Input Voltage Range	$V_{IN}$		0 to $V_{CC}$		V
Low Level Input Voltage	$V_{IL}$		30% $V_{CC}$ max.		V
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$ min.		V
Disable Time	$t_{dis}$		150 max.		ns
Enable Time	$t_{ena}$		10 max.		ms
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	10 max.		ms
Deterministic Jitter	DJ	Measured with Wavecrest SIA-3000	2 max.		ps
1 Sigma Jitter	$J_{\sigma}$		4 max.		ps
Peak to Peak Jitter	$J_{PK-PK}$		30 max.		ps
Phase Jitter	$J_{Phase}$	@156.25MHz $V_{CC} = 3.3V$	BW : 12kHz to 20MHz	0.3 max.	ps


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)





# Clock Oscillators Surface Mount Type

## KC7050P-P2/ KC7050P-P3 Series



LV-PECL/ 3.3V or 2.5V/ 7.0×5.0mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- LV-PECL output
- Supply voltage  $V_{CC} = 3.3V, 2.5V$
- $\pm 25 \times 10^{-6}$  available
- Low Phase Noise

Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	0 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$	-40 to +85	Please contact us for available frequencies.
F	$\pm 100$		
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC7050P 125.000 P □ □ J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function  
J : 45/ 55%, Stand-by
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Specifications		Units
			KC7050P-P2	KC7050P-P3	
Output Frequency Range <sup>Note1</sup>	$f_o$		25 to 175		MHz
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	$\pm 50/ -40$ to $+105^\circ\text{C}$		ppm
			$\pm 100/ -40$ to $+85^\circ\text{C}$		
			$\pm 50/ -40$ to $+85^\circ\text{C}$		
			$\pm 50/ 0$ to $+70^\circ\text{C}$		
			$\pm 30/ 0$ to $+70^\circ\text{C}$		
Storage Temperature Range	$T_{stg}$		-55 to +125		°C
Operating Temperature Range	$T_{use}$	Standard Specifications	0 to +70/ -40 to +85		°C
		Extend (Option)	-40 to +105		
Max. Supply Voltage	—		-0.5 to +5.0		V
Supply Voltage	$V_{CC}$		+2.375 to +2.625	+2.97 to +3.63	V
Current Consumption	$I_{CC}$		70 max.		mA
Stand-by Current	$I_{std}$		20 max.		$\mu\text{A}$
Symmetry	SYM	50ohm @crossing point	50 $\pm$ 5		%
Rise/ Fall Time (20% $V_{CC}$ to 80% $V_{CC}$ Maximum Loaded)	tr/ tf	50ohm	0.6 max.		ns
Low Level Output Voltage <sup>Note2</sup>	$V_{OL}$		$V_{CC}-1.810$ to $V_{CC}-1.620$		V
High Level Output Voltage <sup>Note2</sup>	$V_{OH}$		$V_{CC}-1.025$ to $V_{CC}-0.880$		V
Output Load	RL		50		ohm
Input Voltage Range	$V_{IN}$		0 to $V_{CC}$		
Low Level Input Voltage	$V_{IL}$		30% $V_{CC}$ max.		V
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$ min.		V
Disable Time	$t_{dis}$		150 max.		ns
Enable Time	$t_{ena}$		10 max.		ms
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	10 max.		ms
Deterministic Jitter	DJ	Measured with Wavecrest SIA-3000	2 max.		ps
1 Sigma Jitter	J $\sigma$		4 max.		ps
Peak to Peak Jitter	J $_{PK-PK}$		30 max.		ps
Phase Jitter	J $_{Phase}$	@156.25MHz $V_{CC} = 3.3V$	BW : 12kHz to 20MHz	0.3 max.	ps


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)





LV-PECL or LVDS/ 3.3V or 2.5V/ 5.0×3.2mm



RoHS Compliant

**Features**

- High frequency to 900MHz
- LV-PECL output or LVDS output
- Miniature ceramic package
- Compact and low profile (5.0×3.2×1.2mm max.)
- Low current consumption

**Applications**

- WDM/ Networking

**Table 1**

Freq. Code	Tol. × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
G	±50	-40 to +85	Please contact us for available frequencies.

**How to Order**

KC5032R 622.080 □ □ G D 00  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (P : LV-PECL or L : LVDS)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Disable)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

**Specifications**

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range <sup>Note1</sup>	f <sub>o</sub>		10	900	MHz
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration Op. Temp.: -40 to +85°C	-50	+50	×10 <sup>-6</sup>
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C
Operating Temperature Range	T <sub>use</sub>		-40	+85	°C
Max. Supply Voltage	—		-0.5	+4.2	V
Supply Voltage	V <sub>cc</sub>		+2.25 +2.97	+2.75 +3.63	V
Current Consumption	I <sub>cc</sub>	LV-PECL Output (2.25≤V <sub>cc</sub> ≤2.75V) LV-PECL Output (2.97<V <sub>cc</sub> <3.63V) LVDS Output (2.25≤V <sub>cc</sub> ≤2.75V, 2.97≤V <sub>cc</sub> ≤3.63V)	—	80 100 40	mA
Symmetry	SYM	LV-PECL Output 50ohm @crossing point LVDS Output 100ohm @crossing point	45	55	%
Rise/ Fall Time (20% to 80% Output Level)	t <sub>r</sub> / t <sub>f</sub>	LV-PECL Output 50ohm LVDS Output 100ohm	—	0.4 0.6	ns
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		—	V <sub>cc</sub> -1.620	V
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>	LV-PECL Output	V <sub>cc</sub> -1.025	—	V
Output Load	—		—	50	ohm
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		Typ. 1.1V	0.9	V
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		Typ. 1.43V	—	V
Differential Output Voltage <sup>Note2</sup>	V <sub>OD</sub>		Typ. 330mV	175	mV
Differential Output Voltage Error <sup>Note2</sup>	dV <sub>OD</sub>	LVDS Output dV <sub>OD</sub> =  V <sub>OD1</sub> -V <sub>OD2</sub>	—	50	mV
Offset Voltage	V <sub>OS</sub>		Typ. 1.25V	1.125	V
Offset Voltage Error	dV <sub>OS</sub>		—	50	mV
Output Load	—		—	100	ohm
Low Level Input Voltage <sup>Note2</sup>	V <sub>IL</sub>		—	30% V <sub>cc</sub>	V
High Level Input Voltage <sup>Note2</sup>	V <sub>IH</sub>		70% V <sub>cc</sub>	—	V
Disable Time	t <sub>dis</sub>		—	200	ns
Enable Time	t <sub>ena</sub>		—	2	ms
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms
Phase Jitter	J <sub>Phase</sub>	@622.08MHz BW : 12kHz to 20MHz	—	Typ. 3.0	ps
Phase Noise	—	@622.08MHz	@10Hz offset	Typ. -40	dBc/ Hz
			@100Hz offset	Typ. -70	
			@1kHz offset	Typ. -95	
			@10kHz offset	Typ. -105	
			@100kHz offset	Typ. -105	
			@1MHz offset	Typ. -125	
			@10MHz offset	Typ. -135	


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)





# Clock Oscillators Surface Mount Type

## KC5032G Series Dual Selectable



LV-PECL or LVDS/ 3.3V or 2.5V/ 5.0×3.2mm



RoHS Compliant

### Features

- High frequency to 900MHz
- Dual frequency selectable
- LV-PECL output or LVDS output
- Miniature ceramic package
- Compact and low profile (5.0×3.2×1.2mm max.)
- Low current consumption

### Applications

- WDM/ Networking

### Table 1

Freq. Tol. Code	× 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
G	±50	-40 to +85	Please contact us for available frequencies.

### How to Order

KC5032G 622A644 □ □ G D 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency/ Selection Frequency
- ③ Output Type (P : LV-PECL or L : LVDS)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Disable)
- ⑦ Individual Standard (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications


Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range <sup>Note1</sup>	f1	Primary Output/ #2 "H"-Level or Open	10	900	MHz	
	f2	Secondary Output/ #2 "L"-Level	10	900		
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration Op. Temp.: -40 to +85°C	-50	+50	×10 <sup>-6</sup>	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>		-40	+85	°C	
Max. Supply Voltage	—		-0.5	+4.2	V	
Supply Voltage	V <sub>cc</sub>		+2.25	+2.75	V	
			+2.97	+3.63		
			—	—		
Current Consumption	I <sub>cc</sub>	LV-PECL Output (2.25≤V <sub>cc</sub> ≤2.75V)	—	80	mA	
		LV-PECL Output (2.97<V <sub>cc</sub> <3.63V)	—	100		
		LVDS Output (2.25≤V <sub>cc</sub> ≤2.75V, 2.97≤V <sub>cc</sub> ≤3.63V)	—	40		
Symmetry	SYM	LV-PECL Output 50ohm @crossing point	45	55	%	
		LVDS Output 100ohm @crossing point	45	55		
Rise/ Fall Time (20% to 80% Output Level)	tr/ tf	LV-PECL Output 50ohm LVDS Output 100ohm	—	0.4	ns	
			—	0.6		
Low Level Output Voltage	V <sub>OL</sub>		—	V <sub>cc</sub> -1.620	V	
High Level Output Voltage	V <sub>OH</sub>	LV-PECL Output	V <sub>cc</sub> -1.025	—	V	
Output Load	—		50		ohm	
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>	LVDS Output	Typ. 1.1V	—	V	
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		Typ. 1.43V	—	1.6	V
Differential Output Voltage <sup>Note2</sup>	V <sub>OD</sub>		Typ. 330mV	175	454	mV
Differential Output Voltage Error <sup>Note2</sup>	dV <sub>OD</sub>		dV <sub>OD</sub> =  V <sub>OD1</sub> -V <sub>OD2</sub>	—	50	mV
Offset Voltage	V <sub>OS</sub>		Typ. 1.25V	1.125	1.375	V
Offset Voltage Error	dV <sub>OS</sub>		dV <sub>OS</sub> =  V <sub>OS1</sub> -V <sub>OS2</sub>	—	50	mV
Output Load	—			100		ohm
Low Level Input Voltage <sup>Note2</sup>	V <sub>IL</sub>		—	30% V <sub>cc</sub>	V	
High Level Input Voltage <sup>Note2</sup>	V <sub>IH</sub>		70% V <sub>cc</sub>	—	V	
Disable Time	t <sub>dis</sub>		—	200	ns	
Enable Time	t <sub>ena</sub>		—	2	ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
Phase Jitter	J <sub>Phase</sub>	@622.08MHz	BW : 12kHz to 20MHz	Typ. 3.0		ps
			@10Hz offset	Typ. -40		
			@100Hz offset	Typ. -70		
			@1kHz offset	Typ. -95		
			@10kHz offset	Typ. -105		
			@100kHz offset	Typ. -105		
			@1MHz offset	Typ. -125		
			@10MHz offset	Typ. -135		
Phase Noise	—	@622.08MHz	BW : 12kHz to 20MHz	Typ. 3.0		dBc/ Hz
			@10Hz offset	Typ. -40		
			@100Hz offset	Typ. -70		
			@1kHz offset	Typ. -95		
			@10kHz offset	Typ. -105		
			@100kHz offset	Typ. -105		
			@1MHz offset	Typ. -125		
			@10MHz offset	Typ. -135		

Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions. Note2: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)






# Clock Oscillators Surface Mount Type

## KC7050L-P2/ KC7050L-P3 Series



LV-PECL/ 3.3V or 2.5V/ 7.0×5.0mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- LV-PECL output
- Supply voltage  $V_{CC} = 3.3V, 2.5V$
- $\pm 25 \times 10^{-6}$  available
- Low Phase Noise

### Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	0 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC7050L 100.000 P   J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by) J : Low Phase Noise
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Specifications		Units	
			KC7050L-P2	KC7050L-P3		
Output Frequency Range <sup>Note1</sup>	$f_o$		25 to 170		MHz	
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	$\pm 50/ -40$ to +105°C		ppm	
			$\pm 100/ -40$ to +85°C			
			$\pm 50/ -40$ to +85°C			
			$\pm 50/ 0$ to +70°C			
			$\pm 30/ 0$ to +70°C			
Storage Temperature Range	$T_{stg}$		-55 to +125		°C	
Operating Temperature Range	$T_{use}$	Standard Specifications	0 to +70/ -40 to +85		°C	
		Extend (Option)	-40 to +105			
Max. Supply Voltage	—		-0.3 to +4.0		V	
Supply Voltage	$V_{CC}$		+2.25 to +2.75	+2.97 to +3.63	V	
Current Consumption	$I_{CC}$	$\leq 156.25\text{MHz}$	60 max.		mA	
		$156.25\text{MHz} <$	70 max.			
Stand-by Current	$I_{std}$		20 max.		$\mu\text{A}$	
Symmetry	SYM	50ohm @crossing point	50 $\pm$ 5		%	
Rise/ Fall Time (20% $V_{CC}$ to 80% $V_{CC}$ Maximum Loaded)	$tr/ tf$	50ohm	0.6 max. ( $V_{CC}: 2.25$ to $2.75\text{V}$ ) 0.4 max. ( $V_{CC}: 2.97$ to $3.63\text{V}$ )		ns	
Low Level Output Voltage <sup>Note2</sup>	$V_{OL}$		$V_{CC} - 1.810$ to $V_{CC} - 1.620$		V	
High Level Output Voltage <sup>Note2</sup>	$V_{OH}$		$V_{CC} - 1.025$ to $V_{CC} - 0.880$		V	
Output Load	$R_L$		50		ohm	
Input Voltage Range	$V_{IN}$		0 to $V_{CC}$		V	
Low Level Input Voltage	$V_{IL}$		30% $V_{CC}$ max.		V	
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$ min.		V	
Disable Time	$t_{dis}$		150 max.		ns	
Enable Time	$t_{ena}$		10 max.		ms	
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	10 max.		ms	
Deterministic Jitter	DJ	Measured with Wavecrest SIA-3000	2 max.		ps	
1 Sigma Jitter	$J_{\sigma}$		4 max.		ps	
Peak to Peak Jitter	$J_{PK-PK}$		30 max.		ps	
Phase Jitter	$J_{Phase}$	@156.25MHz $V_{CC} = 3.3V$	BW : 12kHz to 20MHz	0.3max.		ps
		@156.25MHz $V_{CC} = 3.3V$	@10Hz offset	Typ. -77		
			@100Hz offset	Typ. -103		
			@1kHz offset	Typ. -133		
			@10kHz offset	Typ. -143		
			@100kHz offset	Typ. -149		
			@1MHz offset	Typ. -149		
@10MHz offset	Typ. -154					


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


### Dimensions

(Unit: mm)




### Recommended Land Pattern

(Unit: mm)





LV-PECL/ 3.3V/ 7.0x5.0mm



RoHS Compliant

**Features**

- High frequency to 900MHz
- LV-PECL output
- Miniature ceramic package
- Highly reliable with seam welding
- for WDM, Networking Applications

**Table 1**

Freq. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
G	$\pm 50$	-40 to +85	Please contact us for available frequencies.

**How to Order**

KC7050R 622.080 P 3 G D 00  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Disable)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

**Specifications**

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range <sup>Note1</sup>	fo		10	900	MHz
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration Op. Temp.: -40 to +85°C	-50	+50	$\times 10^{-6}$
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C
Operating Temperature Range	T <sub>use</sub>		-40	+85	°C
Max. Supply Voltage	—		-0.5	+4.2	V
Supply Voltage	V <sub>CC</sub>		+2.97	+3.63	V
Current Consumption	I <sub>CC</sub>		—	100	mA
Disable Current	I <sub>DE</sub>		—	30	mA
Symmetry	SYM	50ohm @crossing point	45	55	%
Rise/ Fall Time (20% to 80% Output Level)	tr/ tf	50ohm	—	0.4	ns
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		—	V <sub>CC</sub> -1.620	V
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		V <sub>CC</sub> -1.025	—	V
Output Load	—	LV-PECL Output	50		ohm
Low Level Input Voltage <sup>Note2</sup>	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V
High Level Input Voltage <sup>Note2</sup>	V <sub>IH</sub>		70% V <sub>CC</sub>	—	V
Disable Time	t <sub>dis</sub>		—	200	ns
Enable Time	t <sub>ena</sub>		—	2	ms
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms
Phase Jitter	J <sub>Phase</sub>	@622.08MHz	BW : 12kHz to 20MHz Typ. 3.0		ps
Phase Noise	—	@622.08MHz	@10Hz offset	Typ. -40	dBc/ Hz
			@100Hz offset	Typ. -70	
			@1kHz offset	Typ. -95	
			@10kHz offset	Typ. -105	
			@100kHz offset	Typ. -105	
			@1MHz offset	Typ. -125	
			@10MHz offset	Typ. -135	


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)






# Clock Oscillators Surface Mount Type KC7050G-P3 Series Dual Selectable



LV-PECL/ 3.3V/ 7.0x5.0mm



RoHS Compliant

## Features

- High frequency to 900MHz
- Dual frequency selectable
- LV-PECL output
- Miniature ceramic package
- Highly reliable with seam welding
- for WDM, Networking Applications

## Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
G	$\pm 50$	-40 to +85	Please contact us for available frequencies.

## How to Order

KC7050G 622A644 P 3 G D 00  
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency/ Selection Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Disable)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

## Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range <sup>Note1</sup>	f1	Primary Output/ #2 "H"-Level or Open	10	900	MHz
	f2	Secondary Output/ #2 "L"-Level	10	900	MHz
Frequency Tolerance	f_tol	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration Op. Temp.: -40 to +85°C	-50	+50	$\times 10^{-6}$
Storage Temperature Range	T_stg		-55	+125	°C
Operating Temperature Range	T_use		-40	+85	°C
Max. Supply Voltage	—		-0.5	+4.2	V
Supply Voltage	V <sub>CC</sub>		+2.97	+3.63	V
Current Consumption	I <sub>CC</sub>		—	100	mA
Symmetry	SYM	50ohm @crossing point	45	55	%
Rise/ Fall Time (20% to 80% Output Level)	tr/ tf	50ohm	—	0.4	ns
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		—	V <sub>CC</sub> -1.620	V
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		V <sub>CC</sub> -1.025	—	V
Output Load	—	LV-PECL Output	50		ohm
Low Level Input Voltage	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>CC</sub>	—	V
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms
Phase Jitter	J <sub>Phase</sub>	@622.08MHz	BW : 12kHz to 20MHz		ps
Phase Noise	—	@622.08MHz	@10Hz offset		dBc/ Hz
			@100Hz offset		
			@1kHz offset		
			@10kHz offset		
			@100kHz offset		
			@1MHz offset		
			@10MHz offset		
		Typ. 3.0			
		Typ. -40			
		Typ. -70			
		Typ. -95			
		Typ. -105			
		Typ. -105			
		Typ. -125			
		Typ. -135			


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


## Dimensions

(Unit: mm)



## Recommended Land Pattern

(Unit: mm)



LVDS/ 3.3V or 2.5V/ 3.2×2.5mm



RoHS Compliant

**Features**

- Miniature ceramic package
- Highly reliable with seam welding
- LVDS output
- Supply voltage Vcc = 3.3V, 2.5V
- ±25×10<sup>-6</sup> available
- Low Phase Noise

**Table 1**

Freq. Tol. Code	Tol. × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
0	± 50	0 to +70	Standard specifications
S	± 30		
U	± 25		
F	±100	-40 to +85	Please contact us for available frequencies.
G	± 50		
6	± 50		

**How to Order**

**KC3225L 125.000 L □ □ J 00**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LVDS)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function  
 J : 45/ 55%, Stand-by
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)

**Specifications**


Item	Symbol	Conditions	Specifications		Units		
			KC3225L-L2	KC3225L-L3			
Output Frequency Range <sup>Note1</sup>	f <sub>o</sub>		25 to 175		MHz		
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	±50/ -40 to +105°C		ppm		
			±100/ -40 to +85°C				
			±50/ -40 to +85°C				
			±50/ 0 to +70°C				
			±30/ 0 to +70°C				
Storage Temperature Range	T <sub>stg</sub>		-55 to +125		°C		
			0 to +70/ -40 to +85		°C		
Operating Temperature Range	T <sub>use</sub>	Standard Specifications Extend (Option)	-40 to +105		°C		
Max. Supply Voltage	—		-0.5 to +5.0		V		
Supply Voltage	V <sub>cc</sub>		+2.375 to +2.625	+2.97 to +3.63	V		
Current Consumption	I <sub>cc</sub>		50 max.		mA		
Stand-by Current	I <sub>std</sub>		20 max.		µA		
Symmetry	SYM	100ohm @crossing point	50±5		%		
Rise/ Fall Time (20% V <sub>cc</sub> to 80% V <sub>cc</sub> Maximum Loaded)	tr/ tf	100ohm	0.6 max.		ns		
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		0.9 min. Typ.:1.1		V		
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		1.6 max. Typ.:1.43		V		
Differential Output Voltage <sup>Note2</sup>	V <sub>OD</sub>		247 to 454 Typ.:330		mV		
Differential Output Voltage Error <sup>Note2</sup>	dV <sub>OD</sub>	dV <sub>OD</sub> =  V <sub>OD1</sub> - V <sub>OD2</sub>	50 max.		mV		
Offset Voltage	V <sub>OS</sub>		1.125 to 1.375		V		
Offset Voltage Error	dV <sub>OS</sub>	dV <sub>OS</sub> =  V <sub>OS1</sub> - V <sub>OS2</sub>	50 max.		mV		
Output Load	RL	LVDS Output	100		ohm		
Input Voltage Range	V <sub>IN</sub>		0 to V <sub>cc</sub>		V		
Low Level Input Voltage	V <sub>IL</sub>		30% V <sub>cc</sub> max.		V		
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>cc</sub> min.		V		
Disable Time	t <sub>dis</sub>		200 max.		ns		
Enable Time	t <sub>ena</sub>		10 max.		ms		
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	10 max.		ms		
Deterministic Jitter	DJ	Measured with Wavecrest SIA-3000	2 max.		ps		
1 Sigma Jitter	J <sub>sigma</sub>		4 max.		ps		
Peak to Peak Jitter	J <sub>PK-PK</sub>		30 max.		ps		
Phase Jitter	J <sub>Phase</sub>	@156.25MHz V <sub>cc</sub> = 3.3V	BW : 12kHz to 20MHz	0.3 max.		ps	
				@10Hz offset			Typ. -77
				@100Hz offset			Typ. -103
				@1kHz offset			Typ. -133
				@10kHz offset			Typ. -143
				@100kHz offset			Typ. -149
				@1MHz offset			Typ. -149
@10MHz offset		Typ. -154					

Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions. Note2: DC characteristic


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



LVDS/ 3.3V or 2.5V/ 5.0×3.2mm



RoHS Compliant

**Features**

- Miniature ceramic package
- Highly reliable with seam welding
- LVDS output
- Supply voltage Vcc = 3.3V, 2.5V
- ±25×10<sup>-6</sup> available
- Low Phase Noise

**Table 1**

Freq. Tol. Code	Tol. × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
0	± 50	0 to +70	Standard specifications
S	± 30		
U	± 25		
F	±100	-40 to +85	Please contact us for available frequencies.
G	± 50		
6	± 50	-40 to +105	

**How to Order**

**KC5032L 100.000 L □ □ J 00**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LVDS)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by) J: Low Phase Noise
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

**Specifications**


Item	Symbol	Conditions	Specifications		Units	
			KC5032L-L2	KC5032L-L3		
Output Frequency Range <sup>Note1</sup>	f <sub>o</sub>		25 to 170		MHz	
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	±50/ -40 to +105°C		ppm	
			±100/ -40 to +85°C			
			±50/ -40 to +85°C			
			±50/ 0 to +70°C			
			±30/ 0 to +70°C			
Storage Temperature Range	T <sub>stg</sub>		-55 to +125		°C	
Operating Temperature Range	T <sub>use</sub>	Standard Specifications	0 to +70/ -40 to +85		°C	
		Extend (Option)	-40 to +105			
Max. Supply Voltage	—		-0.3 to +4.0		V	
Supply Voltage	V <sub>CC</sub>		+2.25 to +2.75	+2.97 to +3.63	V	
Current Consumption	I <sub>CC</sub>		50 max.		mA	
Stand-by Current	I <sub>std</sub>		20 max.		µA	
Symmetry	SYM	100ohm @crossing point	50±5		%	
Rise/ Fall Time (20% Vcc to 80% Vcc Maximum Loaded)	tr/ tf	100ohm	0.4 max.		ns	
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		0.9 min. Typ.: 1.1		V	
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		1.6 max. Typ.: 1.43		V	
Differential Output Voltage <sup>Note2</sup>	V <sub>OD</sub>		247 to 454 Typ.: 330		mV	
Differential Output Voltage Error <sup>Note2</sup>	dV <sub>OD</sub>	dV <sub>OD</sub> =  V <sub>OD1</sub> - V <sub>OD2</sub>	50 max.		mV	
Offset Voltage	V <sub>OS</sub>		1.125 to 1.375		V	
Offset Voltage Error	dV <sub>OS</sub>	dV <sub>OS</sub> =  V <sub>OS1</sub> - V <sub>OS2</sub>	50 max.		mV	
Output Load	RL	LVDS Output	100		ohm	
Input Voltage Range	V <sub>IN</sub>		0 to V <sub>CC</sub>		V	
Low Level Input Voltage	V <sub>IL</sub>		30% V <sub>CC</sub> max.		V	
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>CC</sub> min.		V	
Disable Time	t <sub>dis</sub>		200 max.		ns	
Enable Time	t <sub>ena</sub>		10 max.		ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	10 max.		ms	
Deterministic Jitter	DJ		2 max.		ps	
1 Sigma Jitter	J <sub>Sigma</sub>	Measured with Wavecrest SIA-3000	4 max.		ps	
Peak to Peak Jitter	J <sub>PK-PK</sub>		30 max.		ps	
Phase Jitter	J <sub>Phase</sub>	@156.25MHz V <sub>CC</sub> = 3.3V	BW : 12kHz to 20MHz	0.3 max.		ps
		@156.25MHz V <sub>CC</sub> = 3.3V				
Phase Noise	—	@156.25MHz V <sub>CC</sub> = 3.3V	@10Hz offset	Typ. -77		dBc/ Hz
			@100Hz offset	Typ. -103		
			@1kHz offset	Typ. -133		
			@10kHz offset	Typ. -143		
			@100kHz offset	Typ. -149		
			@1MHz offset	Typ. -149		
@10MHz offset	Typ. -154					

Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions. Note2: DC characteristic


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)






# Clock Oscillators Surface Mount Type

## KC5032P-L2/ KC5032P-L3 Series



LVDS/ 3.3V or 2.5V/ 5.0×3.2mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- LVDS output
- Supply voltage  $V_{CC} = 3.3V, 2.5V$
- $\pm 25 \times 10^{-6}$  available
- Low Phase Noise

### Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	0 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$	-40 to +85	Please contact us for available frequencies.
F	$\pm 100$		
G	$\pm 50$	-40 to +105	
6	$\pm 50$		

### How to Order

KC5032P 125.000 L □ □ J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LVDS)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function  
J : 45/ 55%, Stand-by
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Specifications		Units
			KC5032P-L2	KC5032P-L3	
Output Frequency Range <sup>Note1</sup>	$f_o$		25 to 175		MHz
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	$\pm 50/ -40$ to $+105^\circ\text{C}$		ppm
			$\pm 100/ -40$ to $+85^\circ\text{C}$		
			$\pm 50/ -40$ to $+85^\circ\text{C}$		
			$\pm 50/ 0$ to $+70^\circ\text{C}$		
			$\pm 30/ 0$ to $+70^\circ\text{C}$		
Storage Temperature Range	$T_{stg}$	Standard Specifications	-55 to +125		°C
			Extend (Option)		
Operating Temperature Range	$T_{use}$	Extend (Option)	0 to +70/ -40 to +85		°C
Max. Supply Voltage	—		-40 to +105		
Supply Voltage	$V_{CC}$		+2.375 to +2.625	+2.97 to +3.63	V
Current Consumption	$I_{CC}$		-0.5 to +5.0		V
Stand-by Current	$I_{std}$		50 max.		mA
Symmetry	SYM	100ohm @crossing point	20 max.		$\mu\text{A}$
Rise/ Fall Time (20% $V_{CC}$ to 80% $V_{CC}$ Maximum Loaded)	tr/ tf	100ohm	50 $\pm$ 5		%
Low Level Output Voltage <sup>Note2</sup>	$V_{OL}$		0.6 max.		ns
High Level Output Voltage <sup>Note2</sup>	$V_{OH}$		0.9 min. Typ.:1.1		V
Differential Output Voltage <sup>Note2</sup>	$V_{OD}$		1.6 max. Typ.:1.43		V
Differential Output Voltage Error <sup>Note2</sup>	$dV_{OD}$	$dV_{OD} =  V_{OD1} - V_{OD2} $	247 to 454 Typ.:330		mV
Offset Voltage	$V_{OS}$		50 max.		mV
Offset Voltage Error	$dV_{OS}$	$dV_{OS} =  V_{OS1} - V_{OS2} $	1.125 to 1.375		V
Output Load	RL	LVDS Output	50 max.		mV
Input Voltage Range	$V_{IN}$		100		ohm
Low Level Input Voltage	$V_{IL}$		0 to $V_{CC}$		V
High Level Input Voltage	$V_{IH}$		30% $V_{CC}$ max.		V
Disable Time	$t_{dis}$		70% $V_{CC}$ min.		V
Enable Time	$t_{ena}$		200 max.		ns
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	10 max.		ms
Deterministic Jitter	DJ	Measured with Wavecrest SIA-3000	10 max.		ms
1 Sigma Jitter	$J_{\sigma}$		2 max.		ps
Peak to Peak Jitter	$J_{PK-PK}$		4 max.		ps
Phase Jitter	$J_{Phase}$	@156.25MHz $V_{CC} = 3.3V$	BW : 12kHz to 20MHz	30 max.	ps
				0.3 max.	ps


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


### Dimensions

(Unit: mm)




### Recommended Land Pattern

(Unit: mm)



LVDS/ 3.3V or 2.5V/ 7.0×5.0mm



RoHS Compliant

**Features**

- Miniature ceramic package
- Highly reliable with seam welding
- LVDS output
- Supply voltage Vcc = 3.3V, 2.5V
- ±25×10<sup>-6</sup> available
- Low Phase Noise

**Table 1**

Freq. Tol. Code	Tol. × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
0	± 50	0 to +70	Standard specifications
S	± 30		
U	± 25		
F	±100	-40 to +85	Please contact us for available frequencies.
G	± 50		
6	± 50	-40 to +105	

**How to Order**

**KC7050L 100.000 L** □ □ **J 00**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LVDS)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by) J : Low Phase Noise
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Specifications		Units
			KC7050L-L2	KC7050L-L3	
Output Frequency Range <sup>Note1</sup>	f <sub>o</sub>		25 to 170		MHz
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	±50/ -40 to +105°C		ppm
			±100/ -40 to +85°C		
			±50/ -40 to +85°C		
			±50/ 0 to +70°C		
			±30/ 0 to +70°C		
Storage Temperature Range	T <sub>stg</sub>		-55 to +125		°C
Operating Temperature Range	T <sub>use</sub>	Standard Specifications	0 to +70/ -40 to +85		°C
		Extend (Option)	-40 to +105		
Max. Supply Voltage	—		-0.3 to +4.0		V
Supply Voltage	V <sub>cc</sub>		+2.25 to +2.75	+2.97 to +3.63	V
Current Consumption	I <sub>cc</sub>		50 max.		mA
Stand-by Current	I <sub>std</sub>		20 max.		µA
Symmetry	SYM	100ohm @crossing point	50±5		%
Rise/ Fall Time (20% V <sub>cc</sub> to 80% V <sub>cc</sub> Maximum Loaded)	tr/ tf	100ohm	0.4 max.		ns
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		0.9 min. Typ.: 1.1		V
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		1.6 max. Typ.: 1.43		V
Differential Output Voltage <sup>Note2</sup>	V <sub>OD</sub>		247 to 454 Typ.: 330		mV
Differential Output Voltage Error <sup>Note2</sup>	dV <sub>OD</sub>	dV <sub>OD</sub> =  V <sub>OD1</sub> - V <sub>OD2</sub>	50 max.		mV
Offset Voltage	V <sub>OS</sub>		1.125 to 1.375		V
Offset Voltage Error	dV <sub>OS</sub>	dV <sub>OS</sub> =  V <sub>OS1</sub> - V <sub>OS2</sub>	50 max.		mV
Output Load	RL	LVDS Output	100		ohm
Input Voltage Range	V <sub>IN</sub>		0 to V <sub>cc</sub>		V
Low Level Input Voltage	V <sub>IL</sub>		30% V <sub>cc</sub> max.		V
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>cc</sub> min.		V
Disable Time	t <sub>dis</sub>		200 max.		ns
Enable Time	t <sub>ena</sub>		10 max.		ms
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	10 max.		ms
Deterministic Jitter	DJ		2 max.		ps
1 Sigma Jitter	J <sub>sigma</sub>	Measured with Wavecrest SIA-3000	4 max.		ps
Peak to Peak Jitter	J <sub>PK-PK</sub>		30 max.		ps
Phase Jitter	J <sub>Phase</sub>	@156.25MHz V <sub>cc</sub> = 3.3V	BW : 12kHz to 20MHz	0.3 max.	ps
Phase Noise	—	@156.25MHz V <sub>cc</sub> = 3.3V	@10Hz offset	Typ. -77	dBc/ Hz
			@100Hz offset	Typ. -103	
			@1kHz offset	Typ. -133	
			@10kHz offset	Typ. -143	
			@100kHz offset	Typ. -149	
			@1MHz offset	Typ. -149	
@10MHz offset	Typ. -154				


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions. Note2: DC characteristic

**Dimensions**



**Recommended Land Pattern**





# Clock Oscillators Surface Mount Type

## KC7050P-L2/ KC7050P-L3 Series



LVDS/ 3.3V or 2.5V/ 7.0×5.0mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- LVDS output
- Supply voltage  $V_{CC} = 3.3V, 2.5V$
- $\pm 25 \times 10^{-6}$  available
- Low Phase Noise

### Table 1

Freq. Tol. Code	Tolerance $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	0 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$	-40 to +105	
6	$\pm 50$		

### How to Order

KC7050P 125.000 L □ □ J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LVDS)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function  
J : 45/ 55%, Stand-by
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Specifications		Units
			KC7050P-L2	KC7050P-L3	
Output Frequency Range <sup>Note1</sup>	$f_o$		25 to 175		MHz
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	$\pm 50/ -40$ to $+105^\circ\text{C}$		ppm
			$\pm 100/ -40$ to $+85^\circ\text{C}$		
			$\pm 50/ -40$ to $+85^\circ\text{C}$		
			$\pm 50/ 0$ to $+70^\circ\text{C}$		
			$\pm 30/ 0$ to $+70^\circ\text{C}$		
Storage Temperature Range	$T_{stg}$	Standard Specifications	-55 to +125		°C
			Extend (Option)		
Operating Temperature Range	$T_{use}$	Standard Specifications	0 to +70/ -40 to +85		°C
		Extend (Option)	-40 to +105		
Max. Supply Voltage	—		-0.5 to +5.0		V
Supply Voltage	$V_{CC}$		+2.375 to +2.625	+2.97 to +3.63	V
Current Consumption	$I_{CC}$		50 max.		mA
Stand-by Current	$I_{std}$		20 max.		$\mu\text{A}$
Symmetry	SYM	100ohm @crossing point	50 $\pm$ 5		%
Rise/ Fall Time (20% $V_{CC}$ to 80% $V_{CC}$ Maximum Loaded)	tr/ tf	100ohm	0.6 max.		ns
Low Level Output Voltage <sup>Note2</sup>	$V_{OL}$		0.9 min. Typ.:1.1		V
High Level Output Voltage <sup>Note2</sup>	$V_{OH}$		1.6 max. Typ.:1.43		V
Differential Output Voltage <sup>Note2</sup>	$V_{OD}$		247 to 454 Typ.:330		mV
Differential Output Voltage Error <sup>Note2</sup>	$dV_{OD}$	$dV_{OD} =  V_{OD1} - V_{OD2} $	50 max.		mV
Offset Voltage	$V_{OS}$		1.125 to 1.375		V
Offset Voltage Error	$dV_{OS}$	$dV_{OS} =  V_{OS1} - V_{OS2} $	50 max.		mV
Output Load	RL	LVDS Output	100		ohm
Input Voltage Range	$V_{IN}$		0 to $V_{CC}$		V
Low Level Input Voltage	$V_{IL}$		30% $V_{CC}$ max.		V
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$ min.		V
Disable Time	$t_{dis}$		200 max.		ns
Enable Time	$t_{ena}$		10 max.		ms
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	10 max.		ms
Deterministic Jitter	DJ	Measured with Wavecrest SIA-3000	2 max.		ps
1 Sigma Jitter	$J_{\sigma}$		4 max.		ps
Peak to Peak Jitter	$J_{PK-PK}$		30 max.		ps
Phase Jitter	$J_{Phase}$	@156.25MHz $V_{CC} = 3.3V$	BW : 12kHz to 20MHz	0.3max.	ps


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)






# Clock Oscillators Surface Mount Type

## KC3225L-H2/ KC3225L-H3 Series



HCSL/ 3.3V or 2.5V/ 3.2×2.5mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- HCSL output
- Supply voltage  $V_{CC} = 3.3V, 2.5V$
- $\pm 25 \times 10^{-6}$  available
- Low Phase Noise

Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	0 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC3225L 100.000 H   J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (HCSL)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function  
J : 45/ 55%, Stand-by
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Specifications				Units	
			KC3225L-H2		KC3225L-H3			
			Min.	Max.	Min.	Max.		
Output Frequency Range <sup>Note1</sup>	$f_o$		100	140	100	140	MHz	
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	-50	+50	-50	+50	$\times 10^{-6}$	
Storage Temperature Range	$T_{stg}$		-55	+125	-55	+125	°C	
Operating Temperature Range	$T_{use}$		0	+70	0	+70	°C	
			-40	+85	-40	+85		
			-40	+105	-40	+105		
Max. Supply Voltage	—		-0.3	+4.0	-0.3	+4.0	V	
Supply Voltage	$V_{CC}$		2.375	2.625	2.97	3.63	V	
Current Consumption	$I_{CC}$		—	50	—	50	mA	
Stand-by Current	$I_{std}$		—	20	—	20	$\mu A$	
Symmetry	SYM	50ohm @crossing point	45	55	45	55	%	
Rise/ Fall Time 0.175V to 0.525V	$t_r / t_f$	50ohm	—	0.5	—	0.5	ns	
Low Level Output Voltage <sup>Note2</sup>	$V_{OL}$		-0.15	+0.15	-0.15	+0.15	V	
High Level Output Voltage <sup>Note2</sup>	$V_{OH}$		+0.66	+0.85	+0.66	+0.85	V	
Output Load	RL	HCSL Output	50		50		ohm	
Low Level Input Voltage	$V_{IL}$		—	30% $V_{CC}$	—	30% $V_{CC}$	V	
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$	—	70% $V_{CC}$	—	V	
Disable Time	$t_{dis}$		—	200	—	200	ns	
Enable Time	$t_{ena}$		—	10	—	10	ms	
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	—	10	—	10	ms	
Deterministic Jitter	DJ	Measured with Wavecrest SIA-3000	—	2	—	2	ps	
1sigma Jitter	J $\Sigma$		—	4	—	4	ps	
Peak to Peak Jitter	J $_{PK-PK}$		—	30	—	30	ps	
Phase Jitter	$J_{Phase}$	@100MHz $V_{CC} = 3.3V$	BW : 12kHz to 20MHz	—	0.5	—	0.5	ps
		@100MHz $V_{CC} = 3.3V$						
Phase Noise	—	@100MHz $V_{CC} = 3.3V$	@10Hz offset	Typ. -77		dBc/ Hz		
			@100Hz offset	Typ. -107				
			@1kHz offset	Typ. -130				
			@10kHz offset	Typ. -142				
			@100kHz offset	Typ. -149				
			@1MHz offset	Typ. -150				
		@10MHz offset	Typ. -152					


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)






# Clock Oscillators Surface Mount Type

## KC5032L-H2/ KC5032L-H3 Series



HCSL/ 3.3V or 2.5V/ 5.0×3.2mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- HCSL output
- Supply voltage  $V_{CC} = 3.3V, 2.5V$
- $\pm 25 \times 10^{-6}$  available
- Low Phase Noise

Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	0 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC5032L 100.000 H   J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (HCSL)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by) J: Low Phase Noise
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Specifications				Units
			KC5032L-H2		KC5032L-H3		
			Min.	Max.	Min.	Max.	
Output Frequency Range <sup>Note1</sup>	$f_o$		100	140	100	140	MHz
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	-50	+50	-50	+50	$\times 10^{-6}$
Storage Temperature Range	$T_{stg}$		-55	+125	-55	+125	°C
Operating Temperature Range	$T_{use}$		0	+70	0	+70	°C
			-40	+85	-40	+85	
			-40	+105	-40	+105	
Max. Supply Voltage	—		-0.3	+4.0	-0.3	+4.0	V
Supply Voltage	$V_{CC}$		2.375	2.625	2.97	3.63	V
Current Consumption	$I_{CC}$		—	50	—	50	mA
Stand-by Current	$I_{std}$		—	20	—	20	$\mu A$
Symmetry	SYM	50ohm @crossing point	45	55	45	55	%
Rise/ Fall Time 0.175V to 0.525V	$t_r/ t_f$	50ohm	—	0.5	—	0.5	ns
Low Level Output Voltage <sup>Note2</sup>	$V_{OL}$		-0.15	+0.15	-0.15	+0.15	V
High Level Output Voltage <sup>Note2</sup>	$V_{OH}$		+0.66	+0.85	+0.66	+0.85	V
Output Load	$R_L$	HCSL Output	50		50		ohm
Low Level Input Voltage	$V_{IL}$		—	30% $V_{CC}$	—	30% $V_{CC}$	V
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$	—	70% $V_{CC}$	—	V
Disable Time	$t_{dis}$		—	200	—	200	ns
Enable Time	$t_{ena}$		—	10	—	10	ms
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	—	10	—	10	ms
Deterministic Jitter	DJ		—	2	—	2	ps
1sigma Jitter	J <sub>Sigma</sub>	Measured with Wavecrest SIA-3000	—	4	—	4	ps
Peak to Peak Jitter	J <sub>PK-PK</sub>		—	30	—	30	ps
Phase Jitter	J <sub>Phase</sub>		@100MHz $V_{CC} = 3.3V$ BW : 12kHz to 20MHz	—	0.5	—	0.5
Phase Noise	—	@100MHz $V_{CC} = 3.3V$	@10Hz offset	Typ. -77		dBc/ Hz	
			@100Hz offset	Typ. -107			
			@1kHz offset	Typ. -130			
			@10kHz offset	Typ. -142			
			@100kHz offset	Typ. -149			
			@1MHz offset	Typ. -150			
		@10MHz offset	Typ. -152				


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)






# Clock Oscillators Surface Mount Type

## KC5032P-H2/ KC5032P-H3 Series



HCSL/ 3.3V or 2.5V/ 5.0×3.2mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- HCSL output
- Supply voltage  $V_{CC} = 3.3V, 2.5V$
- $\pm 25 \times 10^{-6}$  available
- Low Phase Noise

### Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	0 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC5032P 100.000 H   J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (HCSL)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Specifications				Units
			KC5032P-H2		KC5032P-H3		
			Min.	Max.	Min.	Max.	
Output Frequency Range <sup>Note1</sup>	fo		25	175	25	175	MHz
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	-50	+50	-50	+50	$\times 10^{-6}$
Storage Temperature Range	T <sub>stg</sub>		-55	+125	-55	+125	°C
Operating Temperature Range	T <sub>use</sub>		0	+70	0	+70	°C
			-40	+85	-40	+85	
			-40	+105	-40	+105	
Max. Supply Voltage	—		-0.3	+4.0	-0.3	+4.0	V
Supply Voltage	V <sub>CC</sub>		2.375	2.625	2.97	3.63	V
Current Consumption	I <sub>CC</sub>		—	50	—	50	mA
Stand-by Current	I <sub>std</sub>		—	20	—	20	μA
Symmetry	SYM	50ohm @crossing point	45	55	45	55	%
Rise/ Fall Time 0.175V to 0.525V	tr/ tf	50ohm	—	0.5	—	0.5	ns
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		-0.15	+0.15	-0.15	+0.15	V
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		+0.66	+0.85	+0.66	+0.85	V
Output Load	RL	HCSL Output	50		50		ohm
Low Level Input Voltage	V <sub>IL</sub>		—	30% V <sub>CC</sub>	—	30% V <sub>CC</sub>	V
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>CC</sub>	—	70% V <sub>CC</sub>	—	V
Disable Time	t <sub>dis</sub>		—	200	—	200	ns
Enable Time	t <sub>ena</sub>		—	10	—	10	ms
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	—	10	ms
Deterministic Jitter	DJ		—	2	—	2	ps
1sigma Jitter	J <sub>Sigma</sub>	Measured with Wavecrest SIA-3000	—	4	—	4	ps
Peak to Peak Jitter	J <sub>PK-PK</sub>		—	30	—	30	ps
Phase Jitter	J <sub>Phase</sub>		@100MHz V <sub>CC</sub> = 3.3V	—	0.5	—	0.5
Phase Noise	—	@100MHz V <sub>CC</sub> = 3.3V	BW : 12kHz to 20MHz	Typ. -77		dBc/ Hz	
			@10Hz offset	Typ. -107			
			@100Hz offset	Typ. -130			
			@1kHz offset	Typ. -142			
			@10kHz offset	Typ. -149			
			@100kHz offset	Typ. -150			
@1MHz offset	Typ. -152						


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)






# Clock Oscillators Surface Mount Type

## KC7050L-H2/ KC7050L-H3 Series



HCSL/ 3.3V or 2.5V/ 7.0×5.0mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- HCSL output
- Supply voltage  $V_{CC} = 3.3V, 2.5V$
- $\pm 25 \times 10^{-6}$  available
- Low Phase Noise

### Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	0 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC7050L 100.000 H   J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (HCSL)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by) J : Low Phase Noise
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Specifications				Units	
			KC7050L-H2		KC7050L-H3			
			Min.	Max.	Min.	Max.		
Output Frequency Range <sup>Note1</sup>	$f_o$		100	140	100	140	MHz	
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	-50	+50	-50	+50	$\times 10^{-6}$	
Storage Temperature Range	$T_{stg}$		-55	+125	-55	+125	°C	
Operating Temperature Range	$T_{use}$		0	+70	0	+70	°C	
			-40	+85	-40	+85		
			-40	+105	-40	+105		
Max. Supply Voltage	—		-0.3	+4.0	-0.3	+4.0	V	
Supply Voltage	$V_{CC}$		2.375	2.625	2.97	3.63	V	
Current Consumption	$I_{CC}$		—	50	—	50	mA	
Stand-by Current	$I_{std}$		—	20	—	20	$\mu A$	
Symmetry	SYM	50ohm @crossing point	45	55	45	55	%	
Rise/ Fall Time 0.175V to 0.525V	$t_r / t_f$	50ohm	—	0.5	—	0.5	ns	
Low Level Output Voltage <sup>Note2</sup>	$V_{OL}$		-0.15	+0.15	-0.15	+0.15	V	
High Level Output Voltage <sup>Note2</sup>	$V_{OH}$		+0.66	+0.85	+0.66	+0.85	V	
Output Load	RL	HCSL Output	50		50		ohm	
Low Level Input Voltage	$V_{IL}$		—	30% $V_{CC}$	—	30% $V_{CC}$	V	
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$	—	70% $V_{CC}$	—	V	
Disable Time	$t_{dis}$		—	200	—	200	ns	
Enable Time	$t_{ena}$		—	10	—	10	ms	
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	—	10	—	10	ms	
Deterministic Jitter	DJ	Measured with Wavecrest SIA-3000	—	2	—	2	ps	
1sigma Jitter	J $\sigma$		—	4	—	4	ps	
Peak to Peak Jitter	J $PK-PK$		—	30	—	30	ps	
Phase Jitter	J $Phase$	@100MHz $V_{CC} = 3.3V$	BW : 12kHz to 20MHz	—	0.5	—	0.5	ps
Phase Noise	—	@100MHz $V_{CC} = 3.3V$	@10Hz offset	Typ. -77		dBc/ Hz		
			@100Hz offset	Typ. -107				
			@1kHz offset	Typ. -130				
			@10kHz offset	Typ. -142				
			@100kHz offset	Typ. -149				
			@1MHz offset	Typ. -150				
			@10MHz offset	Typ. -152				


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)





# Clock Oscillators Surface Mount Type

## KC7050P-H2/ KC7050P-H3 Series



HCSL/ 3.3V or 2.5V/ 7.0×5.0mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- HCSL output
- Supply voltage  $V_{CC} = 3.3V, 2.5V$
- $\pm 25 \times 10^{-6}$  available
- Low Phase Noise

Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	0 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
F	$\pm 100$	-40 to +85	Please contact us for available frequencies.
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC7050P 100.000 H   J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (HCSL)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Specifications				Units
			KC7050P-H2		KC7050P-H3		
			Min.	Max.	Min.	Max.	
Output Frequency Range <sup>Note1</sup>	$f_o$		25	175	25	175	MHz
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	-50	+50	-50	+50	$\times 10^{-6}$
Storage Temperature Range	$T_{stg}$		-55	+125	-55	+125	°C
Operating Temperature Range	$T_{use}$		0	+70	0	+70	°C
			-40	+85	-40	+85	
			-40	+105	-40	+105	
Max. Supply Voltage	—		-0.3	+4.0	-0.3	+4.0	V
Supply Voltage	$V_{CC}$		2.375	2.625	2.97	3.63	V
Current Consumption	$I_{CC}$		—	50	—	50	mA
Stand-by Current	$I_{std}$		—	20	—	20	$\mu A$
Symmetry	SYM	50ohm @crossing point	45	55	45	55	%
Rise/ Fall Time 0.175V to 0.525V	$t_r / t_f$	50ohm	—	0.5	—	0.5	ns
Low Level Output Voltage <sup>Note2</sup>	$V_{OL}$		-0.15	+0.15	-0.15	+0.15	V
High Level Output Voltage <sup>Note2</sup>	$V_{OH}$		+0.66	+0.85	+0.66	+0.85	V
Output Load	RL	HCSL Output	50		50		ohm
Low Level Input Voltage	$V_{IL}$		—	30% $V_{CC}$	—	30% $V_{CC}$	V
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$	—	70% $V_{CC}$	—	V
Disable Time	$t_{dis}$		—	200	—	200	ns
Enable Time	$t_{ena}$		—	10	—	10	ms
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	—	10	—	10	ms
Deterministic Jitter	DJ		—	2	—	2	ps
1sigma Jitter	J $\sigma$	Measured with Wavecrest SIA-3000	—	4	—	4	ps
Peak to Peak Jitter	J $PK-PK$		—	30	—	30	ps
Phase Jitter	J $Phase$		@100MHz $V_{CC} = 3.3V$ BW : 12kHz to 20MHz	—	0.5	—	0.5
Phase Noise	—	@100MHz $V_{CC} = 3.3V$	@10Hz offset	Typ. -77		dBc/ Hz	
			@100Hz offset	Typ. -107			
			@1kHz offset	Typ. -130			
			@10kHz offset	Typ. -142			
			@100kHz offset	Typ. -149			
			@1MHz offset	Typ. -150			
		@10MHz offset	Typ. -152				


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)






# Voltage Controlled Crystal Oscillators (VCXO)

## Surface Mount Type KV3225L Series



LV-PECL/ 3.3V/ 7.0x5.0mm



RoHS Compliant

### Features

- Miniature ceramic package
- LV-PECL output
- High frequency to 170MHz
- Low Phase Noise

Table 1

Freq. Code	Tol. × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
0	±50	-10 to +70	Standard specifications
S	±30	-10 to +70	Please contact us for available frequencies.
G	±50	-40 to +85	

### How to Order

**KV3225L** **100.000** **P** **3** **□** **J** **00**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function/ APR (45/ 55%, Disable/ APR50) J : Low Phase Noise
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range <sup>Note1</sup>	fo		100	170	MHz	
Frequency Tolerance <sup>Note2</sup>	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	×10 <sup>-6</sup>
			Op. Temp.: -10 to +70°C	-30	+30	
Absolute Pull Range	APR	Standard specifications	±50	—	×10 <sup>-6</sup>	
		Extend (Option)	±100	—		
Frequency Aging	f <sub>age</sub>	Per 20years @25°C	-20	+20	×10 <sup>-6</sup>	
Control Voltage	V <sub>C</sub>		0	+3.3	V	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>	Standard specifications	0	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-0.3	+5.0	V	
Supply Voltage	V <sub>CC</sub>		+2.97	+3.63	V	
Current Consumption	I <sub>CC</sub>		—	85	mA	
Disable Current	I <sub>dis</sub>		—	5	mA	
Symmetry	SYM	50ohm @crossing point	45	55	%	
Rise/ Fall Time (20% to 80% Output Level)	tr/ tf	50ohm	—	0.7	ns	
Low Level Output Voltage <sup>Note3</sup>	V <sub>OL</sub>		—	V <sub>CC</sub> -1.620	V	
High Level Output Voltage <sup>Note3</sup>	V <sub>OH</sub>		V <sub>CC</sub> -1.025	—	V	
Output Load	—	LV-PECL Output	—	50	ohm	
Input Voltage Range	V <sub>IN</sub>		0	+3.3	V	
Low Level Input Voltage <sup>Note3</sup>	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V	
High Level Input Voltage <sup>Note3</sup>	V <sub>IH</sub>		70% V <sub>CC</sub>	—	V	
Input Resistance	—		10	—	M ohm	
Disable Time	t <sub>dis</sub>		—	200	ns	
Enable Time	t <sub>ena</sub>		—	20	µs	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
Phase Jitter	J <sub>Phase</sub>	@122.88MHz	BW : 12kHz to 20MHz	—	0.3	ps
			@10Hz offset	Typ. -71	dBc/ Hz	
			@100Hz offset	Typ. -102		
			@1kHz offset	Typ. -128		
			@10kHz offset	Typ. -146		
			@100kHz offset	Typ. -152		
			@1MHz offset	Typ. -156		
	@10MHz offset	Typ. -157				

Note : All electrical characteristics are defined at the maximum load and operating temperature range.


Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: Please contact us for the Frequency tolerance of -40 to +85°C.

Note3: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)





# Voltage Controlled Crystal Oscillators (VCXO)

## Surface Mount Type KV5032L Series



LV-PECL/ 3.3V/ 5.0×3.2mm



RoHS Compliant

### Features

- High frequency to 170MHz
- LV-PECL output
- Miniature ceramic package
- Low Phase Noise

Table 1

Freq. Code	Tol. × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
O	±50	-10 to +70	Standard specifications
S	±30	-10 to +70	Please contact us for available frequencies.
G	±50	-40 to +85	

### How to Order

**KV5032L** **100.000** **P** **3** **□** **J** **00**

① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function/ APR (45/ 55%, Disable/ APR50) J : Low Phase Noise
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range <sup>Note1</sup>	f <sub>o</sub>		100	170	MHz	
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	×10 <sup>-6</sup>
			Op. Temp.: -10 to +70°C	-30	+30	
Absolute Pull Range	APR	Standard Specifications	±50	—	×10 <sup>-6</sup>	
		Extend (Option)	±100	—		
Frequency Aging	f <sub>age</sub>	Per 20years @25°C	-20	+20	×10 <sup>-6</sup>	
Control Voltage	V <sub>C</sub>		0	+3.3	V	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>	Standard Specifications	0	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-0.3	+5.0	V	
Supply Voltage	V <sub>CC</sub>		+2.97	+3.63	V	
Current Consumption	I <sub>CC</sub>		—	85	mA	
Disable Current	I <sub>dis</sub>		—	5	mA	
Symmetry	SYM	50ohm @crossing point	45	55	%	
Rise/ Fall Time (20% to 80% Output Level)	tr/ tf	50ohm	—	0.7	ns	
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		—	V <sub>CC</sub> -1.620	V	
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		V <sub>CC</sub> -1.025	—	V	
Output Load	—	LV-PECL Output	—	50	ohm	
Input Voltage Range	V <sub>IN</sub>		0	+3.3	V	
Low Level Input Voltage <sup>Note2</sup>	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V	
High Level Input Voltage <sup>Note2</sup>	V <sub>IH</sub>		70% V <sub>CC</sub>	—	V	
Input Resistance	—		10	—	Mohm	
Disable Time	t <sub>dis</sub>		—	200	ns	
Enable Time	t <sub>ena</sub>		—	20	ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
Phase Jitter	J <sub>Phase</sub>	@122.88MHz	BW : 12kHz to 20MHz	—	0.3	ps
		@122.88MHz	@10Hz offset	Typ. -71	dBc/ Hz	
			@100Hz offset	Typ. -102		
			@1kHz offset	Typ. -128		
			@10kHz offset	Typ. -146		
			@100kHz offset	Typ. -152		
			@1MHz offset	Typ. -156		
@10MHz offset	Typ. -157					


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)





# Voltage Controlled Crystal Oscillators (VCXO)

## Surface Mount Type KV5032D-C3 Series



CMOS/ 3.3V/ 5.0×3.2mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage  $V_{CC} = 3.3V$
- Excellent Jitter performance

Table 1

Freq. Tol. Code	Freq. Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	-10 to +70	Standard specifications
S	$\pm 30$	-10 to +70	Please contact us for available frequencies.
G	$\pm 50$	-40 to +85	

### How to Order

KV5032D 24.576 C 3 □ D 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function/ Input Resistance (45/ 55%, Disable)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications


Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range <sup>Note1</sup>	$f_o$		1.5	170	MHz	
Frequency Tolerance	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	$\times 10^{-6}$
			Op. Temp.: -10 to +70°C	-30	+30	
Absolute Pull Range	APR	$1.5 \leq f_o \leq 30\text{MHz}$ $30 < f_o \leq 170\text{MHz}$	$\pm 100$ $\pm 50$	—	$\times 10^{-6}$	
Control Voltage	$V_c$		0	+3.3	V	
Storage Temperature Range	$T_{stg}$		-55	+125	°C	
Operating Temperature Range	$T_{use}$	Standard Specifications	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—	$1.5 \leq f_o \leq 80\text{MHz}$ $80 < f_o \leq 170\text{MHz}$	-0.5 -0.5	+7 +5	V	
Supply Voltage	$V_{CC}$		+2.97	+3.63	V	
Current Consumption	$I_{CC}$	$1.5 \leq f_o \leq 80\text{MHz}$	—	15	mA	
		$80 < f_o \leq 170\text{MHz}$	—	35		
Disable Current	$I_{dis}$	$1.5 \leq f_o \leq 80\text{MHz}$	—	10	mA	
		$80 < f_o \leq 170\text{MHz}$	—	50		
Symmetry	SYM	@50% $V_{CC}$	45	55	%	
Rise/ Fall Time (10% $V_{CC}$ to 90% $V_{CC}$ )	$t_r / t_f$	$1.5 \leq f_o \leq 30\text{MHz}$	—	8	ns	
		$30 < f_o \leq 80\text{MHz}$	—	5		
		$80 < f_o \leq 170\text{MHz}$	—	4		
Low Level Output Voltage	$V_{OL}$		—	10% $V_{CC}$	V	
High Level Output Voltage	$V_{OH}$		90% $V_{CC}$	—	V	
Output Load	$L_{CMOS}$	CMOS Output	—	15	pF	
Input Voltage Range	$V_{IN}$		0	+3.3	V	
Low Level Input Voltage	$V_{IL}$		—	30% $V_{CC}$	V	
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$	—	V	
Input Resistance	—	Code ⑥ : D	100	—	k ohm	
		Code ⑥ : G or N	5	—	Mohm	
Disable Time	$t_{dis}$		—	100	ns	
Enable Time	$t_{ena}$	$1.5 \leq f_o \leq 80\text{MHz}$	—	100	ns	
		$80 < f_o \leq 170\text{MHz}$	—	2		
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	—	10	ms	
Phase Jitter	$J_{Phase}$	@155.52MHz	BW : 12kHz to 20MHz	—	1.0	ps
Phase Noise	—	@155.52MHz	@10Hz offset	Typ. -55	dBc/ Hz	
			@100Hz offset	Typ. -85		
			@1kHz offset	Typ. -115		
			@10kHz offset	Typ. -130		
			@100kHz offset	Typ. -145		
			@1MHz offset	Typ. -150		
			@10MHz offset	Typ. -155		

Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)






# Voltage Controlled Crystal Oscillators (VCXO)

## Surface Mount Type KV7050L Series



LV-PECL/ 3.3V/ 7.0x5.0mm



RoHS Compliant

### Features

- Miniature ceramic package
- LV-PECL output
- High frequency to 170MHz
- Low Phase Noise

Table 1

Freq. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
O	$\pm 50$	-10 to +70	Standard specifications
S	$\pm 30$	-10 to +70	Please contact us for available frequencies.
G	$\pm 50$	-40 to +85	

### How to Order

KV7050L 100.000 P 3  J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function/ APR (45/ 55%, Disable/ APR5) J : Low Phase Noise
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range <sup>Note1</sup>	fo		100	170	MHz	
Frequency Tolerance <sup>Note2</sup>	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	$\times 10^{-6}$
			Op. Temp.: -10 to +70°C	-30	+30	
Absolute Pull Range	APR	Standard specifications Extend (Option)	$\pm 50$ $\pm 100$	—	$\times 10^{-6}$	
Frequency Aging	f <sub>age</sub>	Per 20years @25°C	-20	+20	$\times 10^{-6}$	
Control Voltage	V <sub>c</sub>		0	+3.3	V	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>	Standard specifications	0	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-0.3	+5.0	V	
Supply Voltage	V <sub>CC</sub>		+2.97	+3.63	V	
Current Consumption	I <sub>CC</sub>		—	85	mA	
Disable Current	I <sub>dis</sub>		—	5	mA	
Symmetry	SYM	50ohm @crossing point	45	55	%	
Rise/ Fall Time (20% to 80% Output Level)	tr/ tf	50ohm	—	0.7	ns	
Low Level Output Voltage <sup>Note3</sup>	V <sub>OL</sub>		—	V <sub>CC</sub> -1.620	V	
High Level Output Voltage <sup>Note3</sup>	V <sub>OH</sub>		V <sub>CC</sub> -1.025	—	V	
Output Load	—	LV-PECL Output	—	50	ohm	
Input Voltage Range	V <sub>IN</sub>		0	+3.3	V	
Low Level Input Voltage <sup>Note3</sup>	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V	
High Level Input Voltage <sup>Note3</sup>	V <sub>IH</sub>		70% V <sub>CC</sub>	—	V	
Input Resistance	—		10	—	M ohm	
Disable Time	t <sub>dis</sub>		—	200	ns	
Enable Time	t <sub>ena</sub>		—	20	μs	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
Phase Jitter	J <sub>Phase</sub>	@122.88MHz	—	0.3	ps	
Phase Noise	—	@122.88MHz	BW : 12kHz to 20MHz	—	dBc/ Hz	
			@10Hz offset	Typ. -71		
			@100Hz offset	Typ. -102		
			@1kHz offset	Typ. -128		
			@10kHz offset	Typ. -146		
			@100kHz offset	Typ. -152		
			@1MHz offset	Typ. -156		
@10MHz offset	Typ. -157					

Note : All electrical characteristics are defined at the maximum load and operating temperature range.


Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: Please contact us for the Frequency tolerance of -40 to +85°C.

Note3: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)



CMOS/ 3.3V/ 5.0V/ 7.0×5.0mm



RoHS Compliant

**Features**

- Surface mount type suitable for auto pick-and-place
- Reflow soldering compatible
- Supply voltage Vcc = 5.0/ 3.3V available
- for DTV, DVD Applications

**How to Order**

**KV7050A 27.0000 C □ S C 00**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage 5 = 5.0V, 3 = 3.3V
- ⑤ Frequency Tolerance (S =  $\pm 30 \times 10^{-6}$ )
- ⑥ Symmetry (40/ 60%)
- ⑦ Individual Specification (STD Specification is "00")


**Specifications**

Item	Symbol	Specifications		Units
		KV7050Axx.xxxxC5SC00 (VC-FXO-35F)	KV7050Axx.xxxxC3SC00 (VC-FXO-35FL)	
Output Frequency Range	f <sub>o</sub>	8 to 30	8 to 30	MHz
Frequency Tolerance (Overall)	f <sub>tol</sub>	±30		×10 <sup>-6</sup>
Storage Temperature Range	T <sub>stg</sub>	-35 to +85		°C
Operating Temperature Range	T <sub>use</sub>	-10 to +70		°C
Max. Supply Voltage	—	7 max.		V
Supply Voltage	V <sub>cc</sub>	5±5%	3.3±5%	V
Current Consumption	I <sub>cc</sub>	25 max.	20 max.	mA
Symmetry	SYM	40 to 60@50%V <sub>cc</sub>		%
Rise/ Fall Time	tr/ tf	10 max.	15 max.	ns
Low Level Output Voltage	V <sub>OL</sub>	0.5 max.		V
High Level Output Voltage	V <sub>OH</sub>	90% V <sub>cc</sub> min.		V
CMOS Load	L <sub>CMOS</sub>	15		pF
Start-up Time	t <sub>str</sub>	10 max.		ms
Voltage Control Range	f <sub>cont</sub>	±50 min.	±50 min.	×10 <sup>-6</sup>
Frequency Deviation	f <sub>cont</sub>	2.5V±2.5V	1.65V±1.65V	V

Note: All electrical characteristics are defined at the maximum load and operating temperature range.  
 Please contact us for inquiry about operating temperature range, available frequencies and other conditions.


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)





# Voltage Controlled Crystal Oscillators (VCXO)

## Surface Mount Type KV7050B-C3 Series



CMOS/ 3.3V/ 7.0x5.0mm



RoHS Compliant

### Features

- Miniature ceramic package
- CMOS output
- High frequency to 170MHz
- Highly reliable with seam welding
- Supply voltage  $V_{CC} = 3.3V$
- Excellent Jitter performance

Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	-10 to +70	Standard specifications
S	$\pm 30$	-10 to +70	Please contact us for available frequencies.
G	$\pm 50$	-40 to +85	

### How to Order

KV7050B 24.576 C 3 □ □ 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
  - ② Output Frequency
  - ③ Output Type (CMOS)
  - ④ Supply Voltage (3.3V)
  - ⑤ Frequency Tolerance (See Table 1)
  - ⑥ Symmetry/ INH Function/ Input Resistance  
 D:  $1.5 \leq f_o \leq 70MHz$   
 N:  $70 \leq f_o \leq 170MHz$
  - ⑦ Individual Specification (STD Specification is "00")
- Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range <sup>Note1</sup>	$f_o$		1.5	170	MHz	
Frequency Tolerance <sup>Note2</sup>	$f_{tol}$	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -10 to +70°C / -40 to +85°C	-50	+50	$\times 10^{-6}$
			Op. Temp.: -10 to +70°C	-30	+30	
Absolute Pull Range	APR	$1.5 \leq f_o \leq 30MHz$ $30 < f_o \leq 170MHz$	$\pm 100$ $\pm 50$	—	$\times 10^{-6}$	
Control Voltage	$V_c$		0	+3.3	V	
Storage Temperature Range	$T_{stg}$		-55	+125	°C	
Operating Temperature Range	$T_{use}$	Standard Specifications	-10	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—	$1.5 \leq f_o \leq 80MHz$ $80 < f_o \leq 170MHz$	-0.5	+7.0	V	
Supply Voltage	$V_{CC}$		+2.97	+3.63	V	
Current Consumption	$I_{CC}$	$1.5 \leq f_o \leq 80MHz$	—	15	mA	
		$80 < f_o \leq 170MHz$	—	30		
Disable Current	$I_{dis}$	$1.5 \leq f_o \leq 80MHz$	—	10	mA	
		$80 < f_o \leq 170MHz$	—	15		
Symmetry	SYM	@50% $V_{CC}$	45	55	%	
Rise/ Fall Time (10% $V_{CC}$ to 90% $V_{CC}$ )	$t_r / t_f$	$1.5 \leq f_o \leq 30MHz$	—	8	ns	
		$30 < f_o \leq 80MHz$	—	5		
		$80 < f_o \leq 170MHz$	—	2.5		
Low Level Output Voltage	$V_{OL}$		—	10% $V_{CC}$	V	
High Level Output Voltage	$V_{OH}$		90% $V_{CC}$	—	V	
Output Load	L <sub>CMOS</sub>	CMOS Output	—	15	pF	
Input Voltage Range	$V_{IN}$		0	+3.3	V	
Low Level Input Voltage	$V_{IL}$		—	30% $V_{CC}$	V	
High Level Input Voltage	$V_{IH}$		70% $V_{CC}$	—	V	
Input Resistance	—	Code ⑥ : D	100	—	k ohm	
		Code ⑥ : G or N	5	—	Mohm	
Disable Time	$t_{dis}$	$1.5 \leq f_o \leq 30MHz$	—	100	ns	
		$30 \leq f_o \leq 170MHz$	—	200		
Enable Time	$t_{ena}$	$1.5 \leq f_o \leq 80MHz$	—	100	ns	
		$80 < f_o \leq 170MHz$	—	2		
Start-up Time	$t_{str}$	@Minimum operating voltage to be 0 sec.	—	10	ms	
Phase Jitter	$J_{Phase}$	@155.52MHz	BW : 12kHz to 20MHz	—	0.4	ps
			@10Hz offset	Typ. -70		
Phase Noise	—	@155.52MHz	@100Hz offset	Typ. -102	dBc/ Hz	
			@1kHz offset	Typ. -128		
			@10kHz offset	Typ. -147		
			@100kHz offset	Typ. -158		
			@1MHz offset	Typ. -160		
			@10MHz offset	Typ. -161		


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: Please contact us for the Frequency tolerance of -40 to +85°C.


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)






# Voltage Controlled Crystal Oscillators (VCXO)

## Surface Mount Type KV7050C-P3 Series



LV-PECL/ 3.3V/ 7.0x5.0mm



RoHS Compliant

### Features

- Miniature ceramic package
- LV-PECL output
- High frequency to 170MHz
- Highly reliable with seam welding
- Low Phase Noise

Table 1

Freq. Tol. Code	Freq. Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	-10 to +70	Standard specifications
S	$\pm 30$	-10 to +70	Please contact us for available frequencies.
G	$\pm 50$	-40 to +85	Please contact us for available frequencies.

### How to Order

KV7050C 155.520 P 3  J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function/ APR (45/ 55%, Disable, APR50)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range <sup>Note1</sup>	fo		80	170	MHz	
Frequency Tolerance <sup>Note2</sup>	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Shock and vibration	Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	$\times 10^{-6}$
			Op. Temp.: -10 to +70°C	-30	+30	
Absolute Pull Range	APR	Standard Specifications Extend (Option)	$\pm 50$ $\pm 100$	—	$\times 10^{-6}$	
Frequency Aging	f <sub>age</sub>	Per 20years @25°C	-15	+15	$\times 10^{-6}$	
Control Voltage	V <sub>c</sub>		0	+3.3	V	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>	Standard Specifications	0	+70	°C	
		Extend (Option)	-40	+85		
Max. Supply Voltage	—		-0.3	+5.0	V	
Supply Voltage	V <sub>CC</sub>		+2.97	+3.63	V	
Current Consumption	I <sub>CC</sub>		—	85	mA	
Disable Current	I <sub>dis</sub>		—	5	mA	
Symmetry	SYM	50ohm@crossing point	45	55	%	
Rise/ Fall Time (20% to 80% Output Level)	tr/ tf	50ohm	—	0.7	ns	
Low Level Output Voltage <sup>Note3</sup>	V <sub>OL</sub>		—	V <sub>CC</sub> -1.620	V	
High Level Output Voltage <sup>Note3</sup>	V <sub>OH</sub>		V <sub>CC</sub> -1.025	—	V	
Output Load	—	LV-PECL Output	—	50	ohm	
Input Voltage Range	V <sub>IN</sub>		0	+3.3	V	
Low Level Input Voltage <sup>Note3</sup>	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V	
High Level Input Voltage <sup>Note3</sup>	V <sub>IH</sub>		70% V <sub>CC</sub>	—	V	
Input Resistance	—		10	—	Mohm	
Disable Time	t <sub>dis</sub>		—	200	ns	
Enable Time	t <sub>ena</sub>		—	2	ms	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
Phase Jitter	J <sub>Phase</sub>	@122.88MHz	BW : 12kHz to 20MHz	—	0.3	ps
			@10Hz offset	Typ. -71	dBc/ Hz	
			@100Hz offset	Typ. -102		
			@1kHz offset	Typ. -128		
			@10kHz offset	Typ. -146		
			@100kHz offset	Typ. -152		
			@1MHz offset	Typ. -156		
			@10MHz offset	Typ. -157		

Note : All electrical characteristics are defined at the maximum load and operating temperature range.


Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: Please contact us for the Frequency tolerance of -40 to +85°C.

Note3: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)





# Voltage Controlled Crystal Oscillators (VCXO)

## Surface Mount Type KV5032R Series



LV-PECL or LVDS/ 3.3V or 2.5V/ 5.0×3.2mm



RoHS Compliant

### Features

- High frequency to 900MHz
- LV-PECL output or LVDS output
- Miniature ceramic package
- Compact and low profile (5.0×3.2×1.2mm max.)
- Low current consumption

### Applications

- WDM/ Networking

Table 1

Freq. Code	Tol. × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
G	±50	-40 to +85	Please contact us for available frequencies.

### How to Order

KV5032R 622.080 □ □ G D 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (P : LV-PECL or L : LVDS)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Disable)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications


Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range <sup>Note1</sup>	f <sub>o</sub>		10	900	MHz
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration			
Absolute Pull Range	APR		±100	—	×10 <sup>-6</sup>
Control Voltage	V <sub>c</sub>		0	+3.3	V
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C
Operating Temperature Range	T <sub>use</sub>		-40	+85	°C
Max. Supply Voltage	—		-0.5	+4.2	V
Supply Voltage	V <sub>cc</sub>		+2.25 +2.97	+2.75 +3.63	V
Linearity	—	V <sub>c</sub> = 0V to +3.3V	-10	10	%
Current Consumption	I <sub>cc</sub>	LV-PECL Output (2.25≤V <sub>cc</sub> ≤2.75V) LV-PECL Output (2.97≤V <sub>cc</sub> ≤3.63V) LVDS Output (2.25≤V <sub>cc</sub> ≤2.75V, 2.77≤V <sub>cc</sub> ≤3.63V)	— — —	80 100 40	mA
Symmetry	SYM	LV-PECL Output 50ohm @crossing point LVDS Output 100ohm @crossing point	45 45	55 55	%
Rise/ Fall Time (20% to 80% Output Level)	t <sub>r</sub> / t <sub>f</sub>	LV-PECL Output 50ohm LVDS Output 100ohm	— —	0.4 0.6	ns
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		—	V <sub>cc</sub> -1.620	V
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>	LV-PECL Output	V <sub>cc</sub> -1.025	—	V
Output Load	—		—	50	ohm
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		0.9	—	V
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		—	1.6	V
Differential Output Voltage <sup>Note2</sup>	V <sub>OD</sub>		175	454	mV
Differential Output Voltage Error <sup>Note2</sup>	dV <sub>OD</sub>	LVDS Output	—	50	mV
Offset Voltage	V <sub>OS</sub>		1.125	1.375	V
Offset Voltage Error	dV <sub>OS</sub>		—	50	mV
Output Load	—		—	100	ohm
Low Level Input Voltage <sup>Note2</sup>	V <sub>IL</sub>		—	30% V <sub>cc</sub>	V
High Level Input Voltage <sup>Note2</sup>	V <sub>IH</sub>		70% V <sub>cc</sub>	—	V
Input Resistance	—		150	—	k ohm
Disable Time	t <sub>dis</sub>		—	200	ns
Enable Time	t <sub>ena</sub>		—	2	ms
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms
Phase Jitter	J <sub>Phase</sub>	@622.08MHz	BW : 12kHz to 20MHz		ps
Phase Noise	—	@622.08MHz	@10Hz offset		Typ. 3.0
			@100Hz offset		Typ. -40
			@1kHz offset		Typ. -70
			@10kHz offset		Typ. -95
			@100kHz offset		Typ. -105
			@1MHz offset		Typ. -105
			@10MHz offset		Typ. -125

Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions. Note2: DC characteristic


### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)



LV-PECL or LVDS/ 3.3V or 2.5V/ 5.0×3.2mm



RoHS Compliant

**Features**

- High frequency to 900MHz
- Dual frequency selectable
- LV-PECL output or LVDS output
- Miniature ceramic package
- Compact and low profile (5.0×3.2×1.2mm max.)
- Low current consumption

**Applications**

- WDM/ Networking

**Table 1**

Freq. Tol. Code	× 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
G	±50	-40 to +85	Please contact us for available frequencies.

**How to Order**

**KV5032G 622A644** □ □ **G F 00**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency/ Selection Frequency
- ③ Output Type (P : LV-PECL or L : LVDS)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

**Specifications**


Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range <sup>Note1</sup>	f1	Primary Output/ #2 "H" -Level or Open	10	900	MHz	
	f2	Secondary Output/ #2 "L" -Level	10	900		
Frequency Tolerance	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration Op. Temp.: -40 to +85°C	-50	+50	×10 <sup>-6</sup>	
Absolute Pull Range	APR		±100	—	×10 <sup>-6</sup>	
Control Voltage	V <sub>C</sub>		0	+3.3	V	
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C	
Operating Temperature Range	T <sub>use</sub>		-40	+85	°C	
Max. Supply Voltage	—		-0.5	+4.2	V	
Supply Voltage	V <sub>CC</sub>		+2.25	+2.75	V	
			+2.97	+3.63		
Linearity	—	V <sub>C</sub> = 0V to +3.3V	-10	10	%	
Current Consumption	I <sub>CC</sub>	LV-PECL Output (2.25≤V <sub>CC</sub> ≤2.75V)	—	80	mA	
		LV-PECL Output (2.97≤V <sub>CC</sub> ≤3.63V)	—	100		
		LVDS Output (2.25≤V <sub>CC</sub> ≤2.75V, 2.77≤V <sub>CC</sub> ≤3.63V)	—	40		
Symmetry	SYM	LV-PECL Output 50ohm @crossing point	45	55	%	
		LVDS Output 100ohm @crossing point	45	55		
Rise/ Fall Time (20% to 80% Output Level)	tr/ tf	LV-PECL Output 50ohm LVDS Output 100ohm	—	0.4	ns	
			—	0.6		
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>	LV-PECL Output	—	V <sub>CC</sub> -1.620	V	
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		V <sub>CC</sub> -1.025	—	V	
Output Load	—		50		ohm	
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>	LVDS Output	Typ. 1.1V	0.9	—	V
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		Typ. 1.43V	—	1.6	V
Differential Output Voltage <sup>Note2</sup>	V <sub>OD</sub>		Typ. 330mV	175	454	mV
Differential Output Voltage Error <sup>Note2</sup>	dV <sub>OD</sub>		dV <sub>OD</sub> =  V <sub>OD1</sub> -V <sub>OD2</sub>	—	50	mV
Offset Voltage	V <sub>OS</sub>		Typ. 1.25V	1.125	1.375	V
Offset Voltage Error	dV <sub>OS</sub>		dV <sub>OS</sub> =  V <sub>OS1</sub> -V <sub>OS2</sub>	—	50	mV
Output Load	—			100		ohm
Low Level Input Voltage <sup>Note2</sup>	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V	
High Level Input Voltage <sup>Note2</sup>	V <sub>IH</sub>		70% V <sub>CC</sub>	—	V	
Input Resistance	—		150	—	k ohm	
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms	
Phase Jitter	J <sub>Phase</sub>	@622.08MHz	BW : 12kHz to 20MHz		ps	
			Typ. 3.0			
Phase Noise	—	@622.08MHz	@10Hz offset	Typ. -40		dBc/ Hz
			@100Hz offset	Typ. -70		
			@1kHz offset	Typ. -95		
			@10kHz offset	Typ. -105		
			@100kHz offset	Typ. -105		
			@1MHz offset	Typ. -125		
			@10MHz offset	Typ. -135		

Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions. Note2: DC characteristic


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)





# Voltage Controlled Crystal Oscillators (VCXO)

## Surface Mount Type KV7050R-P3 Series



LV-PECL/ 3.3V/ 7.0x5.0mm



RoHS Compliant

### Features

- High frequency to 900MHz
- LV-PECL output
- Miniature ceramic package
- for WDM, Networking Applications

Table 1

Freq. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
G	$\pm 50$	-40 to +85	Please contact us for available frequencies.

### How to Order

KV7050R 622.080 P 3 G D 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Disable)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range <sup>Note1</sup>	fo		10	900	MHz
Frequency Tolerance @Vc = +1.65V	f_tol	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration Op. Temp.: -40 to +85°C	-50	+50	$\times 10^{-6}$
Absolute Pull Range	APR		$\pm 100$	—	$\times 10^{-6}$
Control Voltage	Vc		0	+3.3	V
Storage Temperature Range	T_stg		-55	+125	°C
Operating Temperature Range	T_use		-40	+85	°C
Max. Supply Voltage	—		-0.5	+4.2	V
Supply Voltage	Vcc		+2.97	+3.63	V
Linearity	—	Vc = 0V to +3.3V	-10	+10	%
Current Consumption	Icc		—	100	mA
Symmetry	SYM	50ohm @crossing point	45	55	%
Rise/ Fall Time (20% to 80% Output Level)	tr/ tf	50ohm	—	0.4	ns
Low Level Output Voltage <sup>Note2</sup>	VOL		—	Vcc-1.620	V
High Level Output Voltage <sup>Note2</sup>	VOH		Vcc-1.025	—	V
Output Load	—	LV-PECL Output	—	50	ohm
Low Level Input Voltage	VIL		—	30% Vcc	V
High Level Input Voltage	VIH		70% Vcc	—	V
Input Resistance	—		150	—	k ohm
Disable Time	t_dis		—	200	ns
Enable Time	t_ena		—	2	ms
Start-up Time	t_str	@Minimum operating voltage to be 0 sec.	—	10	ms
Phase Jitter	JPhase	@622.08MHz	BW : 12kHz to 20MHz Typ. 3.0		ps
Phase Noise	—	@622.08MHz	@10Hz offset Typ. -40		dBc/ Hz
			@100Hz offset Typ. -70		
			@1kHz offset Typ. -95		
			@10kHz offset Typ. -105		
			@100kHz offset Typ. -105		
			@1MHz offset Typ. -125		
			@10MHz offset Typ. -135		


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


### Dimensions

(Unit: mm)




### Recommended Land Pattern

(Unit: mm)



LV-PECL/ 3.3V/ 7.0×5.0mm



RoHS Compliant

**Features**

- High frequency to 900MHz
- Dual Selectable
- LV-PECL output
- Miniature ceramic package
- for WDM, Networking Applications

**Table 1**

Freq. Tol. Code	Tol. × 10 <sup>-6</sup>	Operating Temperature Range (°C)	Note
G	±50	-40 to +85	Please contact us for available frequencies.

**How to Order**

**KV7050G 622A644 P 3 G F 00**  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency/ Selection Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry (45/ 55%)
- ⑦ Individual Specification (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

**Specifications**

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range <sup>Note1</sup>	f1	Primary Output/ #2 "H"-Level or Open	10	900	MHz
	f2	Secondary Output/ #2 "L"-Level	10	900	MHz
Frequency Tolerance @V <sub>c</sub> = +1.65V	f <sub>tol</sub>	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	-50	+50	×10 <sup>-6</sup>
Absolute Pull Range	APR		±100	—	×10 <sup>-6</sup>
Control Voltage	V <sub>c</sub>		0	+3.3	V
Storage Temperature Range	T <sub>stg</sub>		-55	+125	°C
Operating Temperature Range	T <sub>use</sub>		-40	+85	°C
Max. Supply Voltage	—		-0.5	+4.2	V
Supply Voltage	V <sub>CC</sub>		+2.97	+3.63	V
Linearity	—	V <sub>c</sub> = 0V to +3.3V	-10	+10	%
Current Consumption	I <sub>CC</sub>		—	100	mA
Symmetry	SYM	50ohm @crossing point	45	55	%
Rise/ Fall Time (20% to 80% Output Level)	tr/ tf	50ohm	—	0.4	ns
Low Level Output Voltage <sup>Note2</sup>	V <sub>OL</sub>		—	V <sub>CC</sub> -1.620	V
High Level Output Voltage <sup>Note2</sup>	V <sub>OH</sub>		V <sub>CC</sub> -1.025	—	V
Output Load	—	LV-PECL Output	50		ohm
Low Level Input Voltage	V <sub>IL</sub>		—	30% V <sub>CC</sub>	V
High Level Input Voltage	V <sub>IH</sub>		70% V <sub>CC</sub>	—	V
Input Resistance	—		TYP	1	Mohm
Start-up Time	t <sub>str</sub>	@Minimum operating voltage to be 0 sec.	—	10	ms
Phase Jitter	J <sub>Phase</sub>	@622.08MHz	BW : 12kHz to 20MHz		ps
Phase Noise	—	@622.08MHz	@10Hz offset		Typ. -40
			@100Hz offset		Typ. -70
			@1kHz offset		Typ. -95
			@10kHz offset		Typ. -105
			@100kHz offset		Typ. -105
			@1MHz offset		Typ. -125
			@10MHz offset		Typ. -135


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



1.6×1.2mm



RoHS Compliant

**Features**

- Ultra-miniature SMD type (1.65×1.25×0.55mm)
- Freq. temp. characteristics:  
: ±2.0×10<sup>-6</sup>/ -30 to +85°C  
: ±0.5×10<sup>-6</sup>/ -30 to +85°C (for GPS)
- 1.68 to 3.63V drive available
- Reflow compatible
- Operating Temp. -40 to +105°C (Option)
- Disable Function (Option)
- AEC-Q200 qualified

**Applications**

- Mobile Communications, W-LAN
- Low power radio communications
- GPS Unit

**How to Order**

KT1612A 26000 □ □ □ □ □ □ □ □ XX  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series
  - ② Output Frequency
  - ③ Freq. Temp. Chrst.
  - ④ Lower Operating Temp.
  - ⑤ Upper Operating Temp.
  - ⑥ Supply Voltage
  - ⑦ Voltage Control Function
  - ⑧ Individual Specification
- |           |      |           |      |
|-----------|------|-----------|------|
| <b>18</b> | 1.8V | <b>28</b> | 2.8V |
| <b>30</b> | 3.0V | <b>33</b> | 3.3V |
- |          |                       |
|----------|-----------------------|
| <b>A</b> | ±0.5×10 <sup>-6</sup> |
| <b>B</b> | ±1.0×10 <sup>-6</sup> |
| <b>C</b> | ±1.5×10 <sup>-6</sup> |
| <b>D</b> | ±2.0×10 <sup>-6</sup> |
- |                    |        |
|--------------------|--------|
| <b>T</b>           | TCXO   |
| <b>Spec. Code*</b> | VCTCXO |
- |          |       |
|----------|-------|
| <b>C</b> | -30°C |
| <b>E</b> | -20°C |
| <b>G</b> | -10°C |
- |          |       |
|----------|-------|
| <b>W</b> | +85°C |
| <b>V</b> | +80°C |
| <b>U</b> | +75°C |

Packaging (Tape & Reel 18000 pcs./ reel)

**Specifications**


Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	f <sub>o</sub>		10	52	MHz
Frequency Tolerance	f <sub>tol</sub>	vs Temperature	-0.5/ -2	+0.5/ +2	×10 <sup>-6</sup>
		vs Load	-0.2	+0.2	
		vs Voltage	-0.2	+0.2	
Frequency Aging	f <sub>age</sub>	Per Year	-1	+1	×10 <sup>-6</sup>
Storage Temperature Range	T <sub>stg</sub>		-40	+85	°C
Operating Temperature Range	T <sub>use</sub>		-30	+85	°C
Voltage Control Range	f <sub>cont</sub>	Positive	±8	±15	×10 <sup>-6</sup>
Supply Voltage	V <sub>CC</sub>		1.68	3.63	V
Output Level	V <sub>pp</sub>	Clipped Sine*, Load: 10k ohm // 10pF	0.8	-	Vp-p
Current Consumption	I <sub>CC</sub>		-	2	mA
Harmonics	-		-	-5	dBc

\* : A DC-cut capacitor is not embedded in this crystal oscillator. Connect a DC-cut capacitor (≥1nF) to the line-out terminal of the oscillator.


\* Please contact us for other specifications.

**Dimensions**

(Unit: mm)




**Test Circuit**



**Recommended Land Pattern**

(Unit: mm)



2.0×1.6mm



RoHS Compliant

**Features**

- Miniature SMD type (2.0×1.6×0.8mm)
- Freq. temp. characteristics:  
: ±2.0×10<sup>-6</sup>/ -30 to +85°C  
: ±0.5×10<sup>-6</sup>/ -30 to +85°C (for GPS)
- 1.68 to 3.63V available
- Reflow compatible
- Operating Temp. -40 to +105°C (Option)
- Ultra low supply current 800µA typ. Conditions of 26MHz and 1.0Vp-p (Option)
- Disable Function (Option)
- AEC-Q200 qualified
- AEC-Q100 qualified (Option)

**Applications**

- Mobile Communications, W-LAN
- Low power radio communications
- GPS Unit

**How to Order**

KT2016K 26000 □ □ □ □ □ □ □ □ XX  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series
  - ② Output Frequency
  - ③ Freq. Temp. Chrst.
  - ④ Lower Operating Temp.
  - ⑤ Upper Operating Temp.
  - ⑥ Supply Voltage
  - ⑦ Voltage Control Function
  - ⑧ Individual Specification
- |           |      |           |      |
|-----------|------|-----------|------|
| <b>18</b> | 1.8V | <b>28</b> | 2.8V |
| <b>30</b> | 3.0V | <b>33</b> | 3.3V |
- |          |                       |
|----------|-----------------------|
| <b>A</b> | ±0.5×10 <sup>-6</sup> |
| <b>B</b> | ±1.0×10 <sup>-6</sup> |
| <b>C</b> | ±1.5×10 <sup>-6</sup> |
| <b>D</b> | ±2.0×10 <sup>-6</sup> |
- |          |       |
|----------|-------|
| <b>C</b> | -30°C |
| <b>E</b> | -20°C |
| <b>G</b> | -10°C |
- |          |       |
|----------|-------|
| <b>W</b> | +85°C |
| <b>V</b> | +80°C |
| <b>U</b> | +75°C |
- |                    |        |
|--------------------|--------|
| <b>T</b>           | TCXO   |
| <b>Spec. Code*</b> | VCTCXO |
- \* Please contact us for Spec. Code.

Packaging (Tape & Reel 15000 pcs./ reel)

**Specifications**


Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	f <sub>o</sub>		10	60	MHz
Frequency Tolerance	f <sub>tol</sub>	vs Temperature	-0.5/ -2	+0.5/ +2	×10 <sup>-6</sup>
		vs Load	-0.2	+0.2	
		vs Voltage	-0.2	+0.2	
Frequency Aging	f <sub>age</sub>	Per Year	-1	+1	×10 <sup>-6</sup>
Storage Temperature Range	T <sub>stg</sub>		-40	+85	°C
Operating Temperature Range	T <sub>use</sub>		-30	+85	°C
Voltage Control Range	f <sub>cont</sub>	Positive	±8	±15	×10 <sup>-6</sup>
Supply Voltage	V <sub>CC</sub>		1.68	3.63	V
Output Level	V <sub>pp</sub>	Clipped Sine*, Load: 10k ohm // 10pF	0.8	-	Vp-p
Current Consumption	I <sub>CC</sub>		-	2	mA
Harmonics	-		-	-5	dBc

\* : A DC-cut capacitor is not embedded in this crystal oscillator. Connect a DC-cut capacitor (≥1nF) to the line-out terminal of the oscillator.


\* Please contact us for other specifications.

**Dimensions**

(Unit: mm)




**Test Circuit**




**Recommended Land Pattern**

(Unit: mm)



2.5×2.0mm



RoHS Compliant

### Features

- Miniature SMD type (2.5×2.0×0.8mm)
- Freq. temp. characteristics:  
: ±2.0×10<sup>-6</sup>/ -30 to +85°C  
: ±0.5×10<sup>-6</sup>/ -30 to +85°C (for GPS)
- 1.68 to 3.63V drive available
- Reflow compatible
- Operating Temp. -40 to +105°C (Option)
- Ultra low supply current 800µA typ.  
Conditions of 26MHz and 1.0Vp-p (Option)
- Disable Function (Option)
- AEC-Q200 qualified
- AEC-Q100 qualified (Option)

### Applications

- Mobile Communications, W-LAN
- Low power radio communications
- GPS Unit

### How to Order

KT2520K 26000 □ □ □ □ □ □ □ □ XX  
① ② ③ ④ ⑤ ⑥ ⑦ ⑧

① Series

② Output Frequency

③ Freq. Temp. Chrst.

A	±0.5×10 <sup>-6</sup>
B	±1.0×10 <sup>-6</sup>
C	±1.5×10 <sup>-6</sup>
D	±2.0×10 <sup>-6</sup>

④ Lower Operating Temp.

C	-30°C
E	-20°C
G	-10°C

⑤ Upper Operating Temp.

W	+85°C
V	+80°C
U	+75°C

⑥ Supply Voltage

18	1.8V	28	2.8V
30	3.0V	33	3.3V

⑦ Voltage Control Function

T	TCXO
Spec. Code*	VCTCXO

\* Please contact us for Spec. Code.

⑧ Individual Specification

Packaging (Tape & Reel 12000 pcs./ reel)

### Specifications


Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	f <sub>o</sub>		10	60	MHz
Frequency Tolerance	f <sub>tol</sub>	vs Temperature	-0.5/ -2	+0.5/ +2	×10 <sup>-6</sup>
		vs Load	-0.2	+0.2	
		vs Voltage	-0.2	+0.2	
Frequency Aging	f <sub>age</sub>	Per Year	-1	+1	×10 <sup>-6</sup>
Storage Temperature Range	T <sub>stg</sub>		-40	+85	°C
Operating Temperature Range	T <sub>use</sub>		-30	+85	°C
Voltage Control Range	f <sub>cont</sub>	Positive	±8	±15	×10 <sup>-6</sup>
Supply Voltage	V <sub>CC</sub>		1.68	3.63	V
Output Level	V <sub>pp</sub>	Clipped Sine*, Load: 10k ohm // 10pF	0.8	—	Vp-p
Current Consumption	I <sub>CC</sub>		—	2	mA
Harmonics	—		—	-5	dBc

\* : A DC-cut capacitor is not embedded in this crystal oscillator. Connect a DC-cut capacitor (≥1nF) to the line-out terminal of the oscillator.


\* Please contact us for other specifications.

### Dimensions

(Unit: mm)




### Test Circuit




### Recommended Land Pattern

(Unit: mm)





5.0×3.2mm



RoHS Compliant

**Features**

- High stability and high reliability
- 2.3 to 3.63V drive available
- Clipped sine wave or CMOS level output
- Low phase noise

**Applications**

- 5G, Smallcell, Stratum3
- SONET/ SDH/ Ethernet

**How to Order**

KT5032F 20000 □ A □ 33 T xx  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series
- ② Output Frequency
- ③ Frequency Tolerance
- ④ Lower Operating Temp.
- ⑤ Upper Operating Temp.

	③	④	⑤
<b>KAW</b>	±0.28×10 <sup>-6</sup>	-40°C	+85°C
<b>KAY</b>	±0.28×10 <sup>-6</sup>	-40°C	+105°C
<b>AAV</b>	±0.10×10 <sup>-6</sup>	-40°C	+105°C

⑥ Supply Voltage	⑦ Voltage Control Function
<b>33</b>	3.3V
<b>T</b>	TCXO
<b>Spec. Code*</b>	VCTCXO

\* Please contact us for Spec. Code.

- ⑧ Individual Specification

Packaging (Tape & Reel 1000 pcs./ reel)


**Specifications**

Item	Symbol	Conditions	Min.	Max.	Units	
<b>Output Frequency Range</b>	f <sub>o</sub>	Standard Frequency: 10, 19.2, 20, 24.576, 26, 30.72, 38.88, 40	10	40	MHz	
<b>Frequency Tolerance</b>	f <sub>tol</sub>	vs Temperature (-10 to +105°C) [±(fmax-fmin)/ 2fo]	-0.1	+0.1	×10 <sup>-6</sup>	
		vs Temperature (-40 to +85°C/ +105°C) [±(fmax-fmin)/ 2fo]	-0.28	+0.28		
		vs Voltage	-0.1	+0.1		
<b>Supply Voltage</b>	V <sub>CC</sub>		+2.3	+3.63	V	
<b>Current Consumption</b>	I <sub>CC</sub>	CMOS Output	—	6	mA	
<b>Frequency Aging</b>	f <sub>age</sub>	20years aging @40°C Including temp characteristics, initial tolerance, rated power supply voltage change and load change.	-4.6	+4.6	×10 <sup>-6</sup>	
<b>Voltage Control Range</b>	f <sub>cont</sub>	Positive *100k ohm min	±5	±20	×10 <sup>-6</sup>	
<b>Output Level</b>	V <sub>pp</sub>	Clipped Sine*, Load: 10k ohm // 10pF	0.8	—	Vp-p	
<b>Low Level Output Voltage</b>	V <sub>OL</sub>	CMOS, Load: 15pF I <sub>OL</sub> = 4mA	—	10% V <sub>CC</sub>	V	
<b>High Level Output Voltage</b>	V <sub>OH</sub>	CMOS, Load: 15pF I <sub>OH</sub> = -4mA	90% V <sub>CC</sub>	—	V	
<b>Rise / Fall Time (10%V<sub>CC</sub> to 90%V<sub>CC</sub>)</b>	tr/ tf	CMOS, Load: 15pF	—	8	ns	
<b>Symmetry</b>	SYM	50% V <sub>CC</sub>	45	55	%	
<b>Phase Noise</b>	—	@20MHz	@10Hz offset	—	-90	dBc/ Hz
			@100Hz offset	—	-120	
			@1kHz offset	—	-140	
			@10kHz offset	—	-150	
			@100kHz offset	—	-150	

\* : A DC-cut capacitor is not embedded in this crystal oscillator. In case of clipped sine output, connect a DC-cut capacitor (≥1nF) to the line-out terminal of the oscillator.  
 \* Please contact us for other specifications.


**Dimensions**

(Unit: mm)




**Recommended Land Pattern**

(Unit: mm)



7.0×5.0mm



RoHS Compliant

**Features**

- High stability and high reliability
- 2.7 to 5.5V drive available
- Clipped sine wave or CMOS level output
- Low phase noise
- Disable Function (KT7050A)

**Applications**

- 5G, Smallcell, Stratum3
- SONET/ SDH/ Ethernet

**How to Order**

KT7050 □ 20000 □ A □ 33 T xx  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series
- ② Land Type
- ③ Output Frequency
- ④ Freq. Temp. Chrst.
- ⑤ Lower Operating Temp.
- ⑥ Upper Operating Temp.

	④	⑤	⑥
<b>KAW</b>	±0.28×10 <sup>-6</sup>	-40°C	+85°C
<b>KAY</b>	±0.28×10 <sup>-6</sup>	-40°C	+105°C
<b>AAV</b>	±0.10×10 <sup>-6</sup>	-40°C	+105°C

⑦ Supply Voltage	⑧ Voltage Control Function
<b>33</b>	<b>T</b>
3.3V	TCXO
	<b>Spec. Code*</b>
	VCTCXO

\*Please contact us for Spec. Code.

- ⑨ Individual Specification

Packaging (Tape & Reel 1000 pcs./ reel)



- Compliant to the GR1244-Core & GR253-Core
- Recommended in Microsemi's ZLAN-68 app. note for Stratum3 applications based on tests performed by Kyocera.

**Specifications**



Item	Symbol	Conditions	Min.	Max.	Units	
<b>Output Frequency Range</b>	fo	Standard Frequency: 10, 19.2, 20, 24.576, 26, 30.72, 38.88, 40 vs Temperature (-10 to +105°C) [±(fmax-fmin)/ 2fo]	10	40	MHz	
<b>Frequency Tolerance</b>	f <sub>tol</sub>	vs Temperature (-40 to +85°C/ +105°C) [±(fmax-fmin)/ 2fo] vs Voltage	-0.1	+0.1	×10 <sup>-6</sup>	
<b>Supply Voltage</b>	V <sub>CC</sub>		-0.1	+0.1		
<b>Current Consumption</b>	I <sub>CC</sub>	CMOS Output	+2.7	+5.5	V	
<b>Frequency Aging</b>	f <sub>age</sub>	20years aging @40°C Including temp characteristics, initial tolerance, rated power supply voltage change and load change.	-	6	mA	
<b>Voltage Control Range</b>	f <sub>cont</sub>	Positive *100k ohm min	-4.6	+4.6	×10 <sup>-6</sup>	
<b>Output Level</b>	V <sub>pp</sub>	Clipped Sine, Load: 10k ohm // 10pF	±5	±20	×10 <sup>-6</sup>	
<b>Low Level Output Voltage</b>	V <sub>OL</sub>	CMOS, Load: 15pF I <sub>OL</sub> = 4mA	0.8	-	Vp-p	
<b>High Level Output Voltage</b>	V <sub>OH</sub>	CMOS, Load: 15pF I <sub>OH</sub> = -4mA	-	10% V <sub>CC</sub>	V	
<b>Rise / Fall Time (10%V<sub>CC</sub> to 90%V<sub>CC</sub>)</b>	tr/ tf	CMOS, Load: 15pF	90% V <sub>CC</sub>	-	V	
<b>Symmetry</b>	SYM	50% V <sub>CC</sub>	-	8	ns	
<b>Phase Noise</b>	-	@20MHz	@10Hz offset	-	-90	dBc/ Hz
			@100Hz offset	-	-120	
			@1kHz offset	-	-140	
			@10kHz offset	-	-150	
			@100kHz offset	-	-150	

\* Please contact us for other specifications.

**Dimensions**



**Recommended Land Pattern** (Unit: mm)





## 1. Shock & Drop • Vibration

Do not inflict excessive shock and mechanical vibration that exceeds the norm, such as hitting or mistakenly dropping, when transporting and mounting on a board. There are cases when pieces of crystal break, and pieces that are used become damaged, and become inoperable. When a shock or vibration that exceeds the norm has been inflicted, make sure to check the characteristics.

## 2. Cleaning

Since a crystal piece can be broken by resonance when a crystal device is cleaned by ultrasonic cleaning, be careful when carrying out ultrasonic cleaning.


## 3. Soldering conditions

To maintain the product reliability, please follow recommended conditions.

### Standard soldering iron conditions

	Clock Oscillators
Soldering iron	280°C to 340°C
Time	3+1/ -0 sec. max.

### Reflow conditions (Example)



Recommended reflow Conditions vary depending upon products. Please check with the respective specification for details.

## 4. Mounting Precautions

The lead of the device and the pattern of the board is soldered on the surface. Since extreme deformation of the board tears off the pattern, tears off the lead metal, cracks the solder and damages the sealed part of the device and there are cases in which performance deteriorates and operation fails, use it within the stipulated bending conditions. Due to the small cracks in the board resulting from mounting, please pay sufficient attention when attaching a device at the position where the warping of the board is great.

When using an automatic loading machine, as far as possible, select a type that has a small impact and use it while confirming that there is no damage.

Surface mount devices are NOT flow soldering compatible.

## 5. Storage Condition

Since the long hour high temperature and low temperature storage, as well as the storage at high humidity are causes of deterioration in frequency accuracy and solderability.






Parts should be stored in temperature range of -5 to +40°C, humidity 40 to 60% RH, and avoid direct sunlight. Then use within 6 months.



## 6. In order to use clock oscillators

- (1) The miniature oscillator for the clock utilizes a CMOS IC and incorporates a protective circuit against static electricity. However, exercise care in the same manner as for a normal CMOS IC.
- (2) Internal capacitor is not provided in the power supply section (+DC-GND). \*  
To serve as overimpressed voltage and overcurrent protective device, place a bypass capacitor (0.01μF) as near as possible to the (+DC-GND) terminal. However, the capacitance value is meant as a guideline. Depending on the capacitor type, frequency characteristics vary. Accordingly, use a capacitor that matches the frequency characteristics.  
\* KC7050S series has Bypass Capacitor between Vcc and GND.
- (3) Applying reverse voltage could result in damage to internal parts. Take care not to connect terminals incorrectly.
- (4) Please do not use oscillators under unfavorable condition such as beyond specified range in catalog or specification sheet.
- (5) Please keep oscillators away from water, salt water or harmful gas.
- (6) KC7050S series should be stored in humidity-controlled area after the package is unsealed, in temperature +25±5°C, under humidity of 65%RH, and should be mounted on PCB within 7 days.


## Clock Timing Chart






## Test Circuits

### CMOS Output Test Circuits




Note) Maximum load (Includes capacitances of fixture and probe)


### HCSL Output Test Circuits




### LV-PECL (3.3V/ XO) Output Test Circuits



### LV-PECL (2.5V/ XO) Output Test Circuits




### LVDS (3.3V/ XO) Output Test Circuits




Note) RL=50Ω

### LVDS (2.5V/ XO) Output Test Circuits




Note) RL=50Ω

### CMOS (VCXO 4pad) Output Test Circuits



Note) Maximum load (Includes capacitances of fixture and probe)

### CMOS (VCXO 6pad) Output Test Circuits



Note) Maximum load (Includes capacitances of fixture and probe)




Tape & Reel Specifications

■ Clock Oscillators

■ Temperature Compensated Crystal Oscillators (TCXO)

		KC2016B KC2016K MC2016K	KC2520B KC2520C KC2520K MC2520M MC2520K	KC3225A KC3225K KC3225L MC3225K KV3225L	KC5032A KC5032E KC5032F KC5032G KC5032K KC5032L KC5032P KC5032R MC5032K KV5032D KV5032F KV5032G KV5032L KV5032R	KC7050A KC7050G KC7050K KC7050L KC7050P KC7050R MC7050K KV7050B KV7050C KV7050G KV7050L KV7050R	KC7050B KV7050A	KT1612	KT2016	KT2520	KT3225	KT5032	KT7050	
T A P E	A	2.0±0.05	2.0±0.05	2.0±0.05	1.5+0.1/-0	2.0±0.1	2.0±0.1	2.0±0.05	2.0±0.05	2.0±0.05	2.0±0.05	2.0±0.05	2.0±0.1	
	B	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.05	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	
	C	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.55±0.1	φ1.5±0.1	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.5+0.1/-0	φ1.55±0.05	φ1.5+0.1/-0	
	D	4.0±0.1	4.0±0.1	4.0±0.1	8.0±0.1	8.0±0.1	8.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	4.0±0.1	8.0±0.1	8.0±0.1	
	E	3.5±0.05	3.5±0.05	3.5±0.05	5.5±0.05	7.5±0.1	7.5±0.1	3.5±0.05	3.5±0.05	3.5±0.05	3.5±0.05	5.5±0.05	7.5±0.1	
	F	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	1.75±0.1	
	G	8.0±0.2	8.0±0.2	8.0±0.2	12.0±0.3	16.0±0.3	16.0±0.2	8.0±0.2	8.0±0.2	8.0±0.3/-0.2	8.0±0.3	12.0±0.2	16.0±0.3/-0.1	
	H	φ1.05±0.1	φ1.1±0.1	φ1.5+0.1/0	φ1.5+0.1/0	φ1.55	φ1.55±0.1	φ0.5±0.05	φ1.0+0.1/-0	φ1.1±0.1	φ1.5+0.1/-0	φ1.55±0.05	φ1.55±0.05	
	J	2.25±0.1	2.7±0.1	3.5±0.05	5.5±0.1	8.18	7.4±0.1	1.85±0.1	2.4±0.05	2.9±0.1	3.5±0.1	5.9±0.1	8.21±0.1	
	L	1.85±0.1	2.2±0.1	2.8±0.05	3.7±0.1	5.56	5.4±0.1	1.45±0.1	2.0±0.05	2.4±0.1	2.8±0.1	3.7±0.1	5.78±0.1	
	N	0.95±0.1	1.0±0.1	1.1±0.05	1.4±0.1	2.16±0.1	2.0±0.1	0.65±0.05	0.9±0.05	1.15±0.1	1.1±0.1	2.0±0.1	2.16±0.1	
	O	0.2±0.05	0.2±0.05	0.25±0.05	0.3±0.05	0.3±0.05	0.3±0.05	0.2±0.05	0.25±0.05	0.25±0.05	0.25±0.05	0.3±0.05	0.3±0.05	
	R E E L	P	φ180+0/-3	φ180+0/-3	φ180+0/-3	φ180+0/-3	φ254±2	φ180+0/-3	φ330+0/-2	φ330+0/-2	φ330+0/-2	φ330+0/-2	φ254±2.0	φ254±2.0
		Q	φ60+1/-0	φ60+1/-0	φ60+1/-0	φ60+1/-0	φ100±1	φ60+1/-0	φ100±1.0	φ100±1.0	φ100±1.0	φ100±1.0	φ100±1.0	φ100+1.0/-0
R		φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.3	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2	φ13±0.2	
S		φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	φ21±0.8	
U		2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	2.0±0.5	
W		9.0+0.3/-0	9.0+0.3/-0	9.0±0.3	13.0±0.3	17.5±0.5	17±0.2	9.4+1.0/-0.5	9.4+1.0/-0.5	9.4+1.0/-0.5	9.4+1.0/-0.5	13.5±1.0	16.4+1.0/-0	
Qty.		2000	2000	2000	1000	1000	1000	18000	15000	12000	12000	1000	1000	

(Unit: mm)



## Notes for Using the Catalog

1. Specifications described in this catalog are for references. Products specifications shall be based on written documents agreed by each party.
2. Contents in this catalog are subject to change without notice. It is recommended to confirm the latest information at the time of usage. Also, Kyocera Electronic Components Catalog is revised once a year. We may not be able to accept requests based on old catalogs.
3. Products in this catalog are intended to be used in general electronic equipment such as office equipment, audio and visual equipment, communication equipment, measurement instrument and home appliances. It is absolutely recommended to consult with our sales representatives in advance upon planning to use our products in applications which require extremely high quality and reliability such as aircraft and aerospace equipment, traffic systems, safety systems, power plant and medical equipment including life maintenance systems.
4. Even though we strive for improvements of quality and reliability of products, it is requested to design with enough safety margin in equipment or systems in order not to threaten human lives directly or damage human bodies or properties by an accidental result of products.
5. It is requested to design based on guaranteed specifications for such as maximum ratings, operating voltage and operating temperature. It is not the scope of our guarantee for unsatisfactory results due to misuse or inadequate usage of products in the catalog.
6. Operation summaries and circuit examples in this catalog are intended to explain typical operation and usage of the product. It is recommended to perform circuit and assembly design considering surrounding conditions upon using products in this catalog.
7. Technical information described in this catalog is meant to explain typical operations and applications of products, and it is not intended to guarantee or license intellectual properties or other industrial rights of the third party or Kyocera.
8. Trademarks, logos and brand names used in this catalog are owned by Kyocera or the corresponding third party.
9. Certain products in this catalog are subject to the Foreign Exchange and Foreign Trade Control Act of Japan, and require the license from Japanese Government upon exporting the restricted products and technical information under the law.  
Besides, it is requested not to use products and technical information in the catalog for the development and/or manufacture of weapons of mass destruction or other conventional weapons, nor to provide them to any third party with the possibility of having such purposes.
10. It is prohibited to reprint and reproduce a part or whole of this catalog without permission.
11. Contents described herein are as of March 2018.



The information contained in this catalog is current as of March 2018.

Duplication or reproduction of any part of this catalog without approval is prohibited.

© 2018 KYOCERA Corporation