TERMINAL BLOCK

CONTENT PAGE

Overview ---- 1–2

Wire Protector System ---- 3–18




TA ···· 4
VA ···· 5
TB ···· 5
TC ···· 6
TD ···· 7
TE/TF ···· 7
T3 ···· 8
T5 ···· 8
T4 ···· 9
TK ···· 9
TL ···· 10
VY ···· 10
TQ ···· 11
T9 ···· 11
TR ···· 12–13
KH ···· 14
TM ···· 15
EN ···· 15
KY ···· 16
KZ ···· 17
EC ···· 18
E7 ···· 18

Rising Clamp System ---- 19–59



VN ···· 20–21
ER ···· 20–21
VQ ···· 20–21
ED ···· 22–23
YO ···· 22–23
YP ···· 22–23
YQ ···· 24–25
TV ···· 24–25
YA ···· 26
T2 ···· 27
TP ···· 28
ES ···· 29
TZ ···· 29
V3 ···· 30
TO ···· 30
YC ···· 31
EK ···· 31
TI ···· 32–33
TU ···· 32–33
YD ···· 32–33
VI ···· 34–35
VJ ···· 36–38
EQ ···· 39
YF ···· 39
YE ···· 40
YR ···· 41
YG ···· 41
YS ···· 42–43
YL ···· 42–43
YM ···· 44
EB ···· 45
YB ···· 46
YN ···· 46
YH ···· 47
YT ···· 47
YI ···· 48
T7 ···· 49–50
KQ ···· 49–50
KO ···· 51
VV ···· 51
VP ···· 52–53
EJ ···· 54–55
EI ···· 54–55
E4 ···· 54–55
V4 ···· 54–55
VT ···· 56
TG ···· 56
E6 ···· 57–58
KP ···· 57–58
K6 ···· 59
K7 ···· 59

Screw Pluggable System ---- 60–152



TH ···· 61–62
TT ···· 61–62
EH ···· 63
TX ···· 63
KR ···· 64
TY ···· 64
VG ···· 65–66
EO ···· 65–66
EP ···· 65–66
EX ···· 65–66
OP ···· 67–68
KG ···· 67–68
E2 ···· 69
VD ···· 69
TJ ···· 70–72
EZ ···· 73
VR ···· 74
VB ···· 75
ET ···· 76
EV ···· 77
TS ···· 78–81
VM ···· 82–84
EM ···· 85–86
EL ···· 87–88
VE ···· 89–90
OQ ···· 91–96
VS ···· 97
VK ···· 98–99
VC ···· 100–101
EW ···· 102–103
EU ···· 104–105
NC ···· 106–107
KE ···· 108–111
K3 ···· 112–113
VL ···· 114–117
VF ···· 118–120
VO ···· 121–122
V7 ···· 123–126
KL ···· 127–128
V5 ···· 129–130
V9 ···· 131–132
KI ···· 133–134
KV ···· 135–136
AO ···· 137
AR ···· 137
V8 ···· 138–139
KK ···· 140
KF ···· 141
VH ···· 141
KT ···· 142–143
KS ···· 142–143
VZ ···· 144
VX ···· 145–146
KU ···· 147–148
KX ···· 149
K4 ···· 150
EY ···· 150
K5 ···· 151
KJ ···· 152
FW ···· 152


CONTENT PAGE

Spring Clamp Pluggable System ---- 153–174



HI ···· 154–156
HN ···· 157–158
HP ···· 157–158
HW ···· 159–161
H4 ···· 162–163
H5 ···· 164–166
NB ···· 167–168
KD ···· 169–171
ND ···· 172
VW ···· 173
HN ···· 173
NF ···· 174

Spring Clamp System ---- 175–212




HA ···· 176–178
NA ···· 176–178
HX ···· 179
HB ···· 180–181
H6 ···· 182
H7 ···· 183
TN ···· 184
HC ···· 185
NE ···· 186–187
HE ···· 186–187
HD ···· 188–189
HG ···· 188–189
HT ···· 190–191
HV ···· 190–191
HF ···· 192
HH ···· 192
HM ···· 193–195
HQ ···· 196–197
HR ···· 198–199
HS ···· 200–201
H3 ···· 202
H2 ···· 203–204
H8 ···· 203–204
HY ···· 205
HL ···· 205
DS240 ···· 206–207
NH ···· 206–207
NI ···· 206–207
H9 ···· 208
NA ···· 208
NJ ···· 209
NK ···· 210
NP ···· 211
NQ ···· 211
NM ···· 212

Accessories ---- 213–222



AN ···· 214
AM ···· 214
AP ···· 215
AE ···· 215
AF ···· 216
AG ···· 216
AU ···· 217
AI ···· 217
AL ···· 218
AJ ···· 219
AK ···· 219
AS ···· 220
AT ···· 220
AD ···· 221
ANAA ···· 221
AH ···· 222

Barrier Terminal Blocks ---- 223–246



YK (30/40/50/60/70/90) ···· 224–231
YK (21/31/32/41/42/51/61 Series) ···· 232–239
YK (11/22/33/44/55/88 Series) ···· 240–245
YK (66/77) ···· 246

Cross Reference List ---- 247–280

DINKLE ···· 247–258
PHOENIX ···· 259–273
WEIDMULLER ···· 274–280

TERMINAL BLOCKS

OVERVIEW

FCI's PCB signal and power Terminal Blocks are available in both pluggable and fixed configurations. They come in different pitch and wire sizes for signal and power solutions.

The proven rising-cage-clamp technology ensures long-life, reliable connections, especially for demanding applications in industrial, instrumentation and communications environments.



FEATURES & BENEFITS

- Robust and solid design
- Modular system, 2 up to 24 positions
- Pitch-sizes: 2.50mm, 2.54mm, 3.50mm, 3.81mm, 4.50mm, 5.00mm, 5.08mm, 6.35mm, 7.50mm, 7.62mm, 9.52mm, 10.00mm, 10.16mm, 12.70mm, 15.00mm, 19.00mm
- Signal and Power, current ratings from 2A up to 125A
- Various product configurations
- Locking flange feature
- Latching feature, prevent miss-match
- End-to-end stackable
- Through mount soldering
- High performance rising-cage-clamp contact system and spring-clamp-contact
- High durability, 200 mating cycles

TARGET MARKETS / APPLICATIONS


- Industrial & Instrumentation and Medical
  - Embedded control units
  - Measurement equipment
  - Medical Instrumentation
  - Power Supplies
  - Security
  - HVAC
  - Lighting
- Communications


TERMINAL BLOCKS


FCI's PCB signal and power Terminal Blocks are available in both pluggable and fixed configurations. They both utilize proven high performance Rising-cage-clamp technology that ensures a perfect connection time after time.

FCI supports its high reliability Terminal Blocks with excellent customer service, standard products delivered from stock, fast sample service and easy access to product information at www.fci.com/terminalblocks.

PLUGGABLE









FIXED







TMBPDTFAMILY1113A4


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

WIRE PROTECTOR SYSTEM

OVERVIEW


For wire protector system, the wire guard is pushed down by turning the screw clock-wise. The terminal is fixed in the housing and there is no lift system.






Wire protector systems are used to prevent damage from rising clamps or screw terminals. Wire protector terminals secure the wires with a flat surface instead of a screw-like surface. This prevents the wires from being twisted. They are intended for use in light duty environments.

WIRE PROTECTOR SYSTEM




TA

Pitch 5.0mm
2-Interlock/Polyamide
Poles 2p/3p
TAxx016100J0G*
Number of poles




Electrical:	UL	VDE
Voltage rating:	250V	250V
Current rating:	16A	16A
Wire range:	0.5 - 2.5mm²	
Solid wire(AWG):	14-26	
Stranded wire(AWG):	14-26	
Torque:	2.6Lb-In	0.5Nm
Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.5KV	2KV
Safety Approval:		




TA

Pitch 5.08mm
1-Interlock
Poles 2p/3p
TAxx416300J0G*
Number of poles




Electrical:	UL
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14-22
Stranded wire(AWG):	14-22
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	



TA

Pitch 7.5mm
1-Interlock
Poles 2p/3p
TAxx2161BBJ0G*
Number of poles



Electrical:	UL
Voltage rating:	250V
Current rating:	16A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	14-22
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.5KV
Safety Approval:	

PART NUMBERS

TA (5.0) — XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Tail length | XXXXX | X

End Stackable
For 5.0 Pitch
02 to 24 2 to 24 contacts
For 10.0 Pitch
02 to 12 2 to 12 contacts
For 7.5 Pitch
02 to 16 2 to 16 contacts
For 15.0 Pitch
02 to 08 2 to 8 contacts

Pitch:
0 5.00/.197"
1 10.00/.394"
2 7.5/.295"
3 15.00/.950"

Screw & Clamp:
0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color:
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Tail length:
0 4.4mm
1 3.8mm
2 3.5mm

XXXXX:
00J0 2 Interlock (only for 5.0 & 10.0 pitch) (Steel screw plating Cr^{3+})
BBJ0 1 Interlock (only for 7.5 & 15.0 pitch) (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X:
G RoHS compliant (lead<4%) In copper Alloy

TA (5.08) — XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Tail length | XXXXX | X

End Stackable
For 5.08 Pitch
02 to 24 2 to 24 contacts
For 10.16 Pitch
02 to 12 2 to 12 contacts

Pitch:
4 5.08/.20" (1-lock)
5 10.16/.40" (1-lock)

Screw & Clamp:
0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color:
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Tail length:
1 3.8mm
3 4.0mm


XXXXX:
00J0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.


X:
G RoHS compliant (lead<4%) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


WIRE PROTECTOR SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14-22
Stranded wire(AWG):	14-22
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cRUus







Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14-22
Stranded wire(AWG):	14-22
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cRUus





Electrical:	UL
Voltage rating:	250V
Current rating:	16A
Wire range:	
Solid wire(AWG):	14
Stranded wire(AWG):	
Torque(Lb-In) :	2.6
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.5KV
Safety Approval:	RU





Electrical:	UL
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14-22
Stranded wire(AWG):	14-22
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cRUus

PART NUMBERS

VA — XX Number of contacts | X Pitch | X Screw & Clamp | X Color | 0 | XXXX XX

End Stackable

For 5.0 Pitch
02 to 24 2 to 24 contacts

For 10.0 Pitch
02 to 12 2 to 12 contacts

For 7.5 Pitch
02 to 16 2 to 16 contacts

For 15.0 Pitch
02 to 08 2 to 8 contacts

Pitch	
0	5.00/.197"
1	10.00/.394"
2	7.5/.295"
3	15.00/.950"

Screw & Clamp	
0	"-/+"Combination type W/Brass Machined Clamp
1	"-"Slot type W/Brass Machined Clamp

Color	
0	Black
5	Green (RAL 6018/T)
6	Blue
8	Grey (RAL 7035/D)
C	Green (RAL 6018/U)

XXXX	
00J0	Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.

X	
G	RoHS compliant (lead<4%) In copper Alloy

TB — XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Tail length | XXXX XX

End Stackable

For 5.0 & 5.08 Pitch
02 to 24 2 to 24 contacts

For 10.0 & 10.16 Pitch
02 to 12 2 to 12 contacts

Pitch	
0	5.00/.197"
1	10.00/.394"
2	5.08/.20"
3	10.16/.40"

Screw & Clamp	
0	"-/+"Combination type W/Brass Machined Clamp
1	"-"Slot type W/Brass Machined Clamp


Color	
0	Black
5	Green (RAL 6018/T)
6	Blue
8	Grey (RAL 7035/D)
C	Green (RAL 6018/U)


Tail length	
0	4.4mm
1	3.8mm
2	3.5mm

XXXX	
00J0	Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.


X	
G	RoHS compliant (lead<4%) In copper Alloy


WIRE PROTECTOR SYSTEM







Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	15A	17.5A
Wire range:	0.5 - 1.5mm²	
Solid wire(AWG):	14 - 22	
Stranded wire(AWG):	14-22	
Torque :	2.6Lb-In	0.4Nm
Screw:	M2.6	
Wire strip length:	5~6mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	VDE







Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14 - 22
Stranded wire(AWG):	14 - 22
Torque (Lb-In):	2.6
Screw:	M2.6
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	15A	17.5A
Wire range:	0.5 - 1.5mm²	
Solid wire(AWG):	14-22	
Stranded wire(AWG):	14-22	
Torque :	2.6Lb-In	0.4Nm
Screw:	M2.6	
Wire strip length:	5~6mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	VDE






Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14-22
Stranded wire(AWG):	14-22
Torque(Lb-In) :	2.6
Screw:	M2.6
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS







For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


WIRE PROTECTOR SYSTEM







Electrical:	cULus
Voltage rating:	250V
Current rating:	16A
Wire range:	
Solid wire(AWG):	14
Stranded wire(AWG):	16
Torque(Lb-In) :	2.6
Screw:	M2.6
Wire strip length:	5~6mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus







Electrical:	UL
Voltage rating:	125V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	18-26
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.25KV
Safety Approval:	cULus





Electrical:	UL
Voltage rating:	125V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	18-26
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.25KV
Safety Approval:	cULus





Electrical:	UL
Voltage rating:	125V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.25KV
Safety Approval:	UL

PART NUMBERS

TD


XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Tail length	XXXXX
End Stackable For 5.0 Pitch 02 to 24 2 to 24 contacts For 10.0 Pitch 02 to 12 2 to 12 contacts	0 5.00/.197" 1 10.00/.394"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 4.4mm 1 3.8mm 2 3.5mm	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy

TE/TF


XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Tail length	XXXXX
End Stackable For 3.5 Pitch 02 to 24 2 to 24 contacts For 7.0 Pitch 02 to 12 2 to 12 contacts	0 3.50/.138" 1 7.00/.276"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	Stackable 0 4.4mm 1 3.8mm 2 3.5mm Solid block (Only TE) 3 4.4mm 4 3.8mm 5 3.5mm	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy

WIRE PROTECTOR SYSTEM

T5



Pitch 3.5mm
Solid block
Poles 2p~24p
T5xx015000J0G*
Number of poles




Electrical:	UL
Voltage rating:	125V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Torque(Lb-In) :	1.7

Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.25KV
Safety Approval:	cULus

T3




Pitch 5.0mm
2-Interlock/Polyamide
Poles 2p/3p
T3xx045100J0G*
Number of poles




Electrical:	UL	TUV
Voltage rating:	300V	250V
Current rating:	8A	12A
Wire range:		0.2-2.5mm
Solid wire(AWG):	14-26	
Stranded wire(AWG):	14-26	
Torque :	3.5Lb-In	0.4Nm

Screw:	M2.5	
Wire strip length:	5~6mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cUL	TUV

T3




Pitch 5.0mm - Solid block
(180D wire inlet)
Poles 4P~24P
T3xx045400J0G*
Number of poles




Electrical:	UL	TUV
Voltage rating:	300V	250V
Current rating:	8A	12A
Wire range:		0.2-2.5mm
Solid wire(AWG):	14-26	
Stranded wire(AWG):	14-26	
Torque :	3.5Lb-In	0.4Nm

Screw:	M2.5	
Wire strip length:	5~6mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	TUV

T3



Pitch 5.0mm
(90D wire inlet)
Poles 2p/3p
T3xx045300J0G*
Number of poles



Electrical:	UL	TUV
Voltage rating:	300V	250V
Current rating:	8A	12A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	14-26	
Stranded wire(AWG):	14-26	
Torque :	3.5Lb-In	0.4Nm

Screw:	M2.5	
Wire strip length:	5~6mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	TUV

PART NUMBERS

T3

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Tail length	XXXXX
End Stackable For 5.0 Pitch 02 to 24 2 to 24 contacts For 10.0 Pitch 02 to 12 2 to 12 contacts	0 5.00/.197" 1 10.00/.394"	4 "-/+"Combination type W/Brass stamping clamp 5 "-"Slot type W/Brass stamping clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D)	1 Stackable 4.0mm 3 Stackable (90D wire inlet) 4 Solidblock (180D 4.0mm)	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy


T5


XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Tail length	XXXXX
Solid Block For 3.5 Pitch 02 to 24 2 to 24 contacts For 7.0 Pitch 02 to 12 2 to 12 contacts	0 3.5/.138" 1 7.00/.276"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D)	0 3.5mm	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.


WIRE PROTECTOR SYSTEM






Electrical:	UL	VDE
Voltage rating:	300V	450V
Current rating:	10A	17.5A
Wire range:	0.75 - 4.0mm²	
Solid wire(AWG):	12-20	
Stranded wire(AWG):	12-20	
Torque :	3.5Lb-In	0.4Nm


Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE






Electrical:	UL
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-20
Stranded wire(AWG):	12-20
Torque(Lb-In) :	3.5


Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	UL
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-20
Stranded wire(AWG):	12-20
Torque(Lb-In) :	3.5

Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	UL
Voltage rating:	250V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5

Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus

PART NUMBERS


T4


XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Tail length	X X X X	X
Solid Block For 5.0 Pitch 02 to 24 2 to 24 contacts For 10.0 Pitch 02 to 12 2 to 12 contacts For 7.5 Pitch 02 to 16 2 to 16 contacts For 15.0 Pitch 02 to 08 2 to 08 contacts	0 5.00/.197" 1 10.00/.394" 2 7.5/.295" 3 15.0/.591"	4 "-/+"Combination type W/Brass stamping clamp 5 "-"Slot type W/Brass stamping clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D)	0 4.4mm 1 3.0mm 2 4.4mm (Connector though type) 3 3.0mm (Connector though type)	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy


TK


XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Tail length	X X X X	X
Solid Block For 5.0 Pitch 02 to 24 2 to 24 contacts For 10.0 Pitch 02 to 12 2 to 12 contacts	0 5.00/.197" 1 10.00/.394"	4 "-/+"Combination type W/Brass stamping clamp 5 "-"Slot type W/Brass stamping clamp	8 Grey (RAL 7035/D)	0 4.7mm 1 40°	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy


WIRE PROTECTOR SYSTEM














Electrical:	UL
Voltage rating:	250V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14-22
Stranded wire(AWG):	14-22
Torque(Lb-In) :	3.5
Screw:	M2.6
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14-22
Stranded wire(AWG):	14-22
Torque(Lb-In) :	3.5
Screw:	M2.6
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

TL

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Special Design	XXXXX
Solid Block For 5.0 Pitch 02 to 24 2 to 24 contacts For 10.0 Pitch 02 to 12 2 to 12 contacts	0 5.00/.97" 1 10.00/.394"	4 "-/+"Combination type W/Brass Machined Clamp 5 "-"Slot type W/Brass Machined Clamp	8 Grey (RAL 7035/D)	0 4.0mm A 21° B 40° C 52° D 90° E Special bending-pin 2,4,6:no bending F 45°	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy


VY


XX Number of contacts	X Pitch	X Screw & Terminal	X Color	X Body type	XXXXX
End Stackable For 5.0 Pitch 02 to 24 2 to 24 contacts For 10.0 Pitch 02 to 12 2 to 12 contacts	0 5.00/.197" 1 10.00/.394"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 Polyamide 4.8mm 1 Polyamide 3.8mm C High Temperature 4.5mm	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

WIRE PROTECTOR SYSTEM









Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14-22
Stranded wire(AWG):	14-22
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	14-24
Torque(Lb-In) :	3.2
Screw:	M2.6
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

TQ — XX Number of contacts | X Pitch | X Screw & Clamp | X Color | 0 | XXXX | X


- Solid Block
  - For 5.0 Pitch: 02 to 24 — 2 to 24 contacts
  - For 10.0 Pitch: 02 to 12 — 2 to 12 contacts
- Pitch: 0 5.00/.197" | 1 10.00/.394"
- Screw & Clamp: 0 "-/+"Combination type W/Brass Machined Clamp | 1 "-"Slot type W/Brass Machined Clamp
- Color: 0 Black | 5 Green (RAL 6018/T) | 6 Blue | 8 Grey (RAL 7035/D) | C Green (RAL 6018/U)
- XXXX: 00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- X: G RoHS compliant (lead<4%) In copper Alloy

T9 — XX Number of contacts | X Pitch | X Screw & Terminal | X Color | 0 | XXXX | X


- End Stackable
  - For 5.08 Pitch: 02 to 24 — 2 to 24 contacts
  - For 10.16 Pitch: 02 to 12 — 2 to 12 contacts
- Pitch: 2 5.08/.20" | 3 10.16/.396"
- Screw & Terminal: 0 "-/+"Combination type W/Brass Machined Clamp | 1 "-"Slot type W/Brass Machined Clamp
- Color: 5 Green | 8 Grey (RAL 7035/D)
- XXXX: 00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- X: G RoHS compliant (lead<4%) In copper Alloy

WIRE PROTECTOR SYSTEM

TR




Pitch 3.81mm
Vertical (180D wire inlet)
Poles 1p~24p
TRxx355100J0G* (Row spacing 7.62mm)
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Torque(Lb-In) :	2.0
Screw:	M2
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TR




Pitch 3.81mm
Vertical (90D wire inlet)
Poles 1p~24p
TRxx355000J0G* (Row spacing 7.62mm)
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Torque(Lb-In) :	2.0
Screw:	M2
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TR




Pitch 5.0mm
Horizontal
(180D wire inlet)
Poles 1p~24p
TRxx055100J0G* (Row spacing 5.0mm)
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	2.4
Screw:	M2.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TR




Pitch 5.0mm
Vertical
(90D wire inlet)
Poles 1p~24p
TRxx055000J0G* (Row spacing 5.0mm)
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	2.4
Screw:	M2.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TR




Pitch 5.0mm
Horizontal
(180D wire inlet)
Poles 1p~24p
TRxx0551A0J0G* (Row spacing 10.0mm)
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	2.4
Screw:	M2.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TR




Pitch 7.5mm
Vertical
(90D wire inlet)
Poles 1p~16p
TRxx255000J0G* (Row spacing 5.0mm)
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	2.4
Screw:	M2.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TR




Pitch 7.5mm
Horizontal
(180D wire inlet)
Poles 1p~16p
TRxx255100J0G* (Row spacing 5.0mm)
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	2.4
Screw:	M2.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TR



Pitch 7.5mm
Horizontal
(180D wire inlet)
Poles 1p~16p
TRxx2551A0J0G* (Row spacing 10.0mm)
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	2.4
Screw:	M2.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

WIRE PROTECTOR SYSTEM

TR




Pitch 10.0mm
Horizontal
(180D wire inlet)
Poles 1p~12p
TRxx155100J0G* (Row spacing 5.0mm)
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	2.4
Screw:	M2.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TR




Pitch 10.0mm
Vertical
(90D wire inlet)
Poles 1p~12p
TRxx155000J0G* (Row spacing 5.0mm)
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	2.4
Screw:	M2.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TR



Pitch 10.0mm
Horizontal
(180D wire inlet)
Poles 1p~12p
TRxx1551A0J0G* (Row spacing 10.0mm)
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	2.4
Screw:	M2.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

TR | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X P.C.B Mounting | X X X X X

XX Number of contacts

End Stackable
For 3.81 & 5.0 Pitch
01 to 24 1 to 24 contacts

For 7.5 Pitch
01 to 16 1 to 16 contacts

For 10.0 Pitch
01 to 12 1 to 12 contacts

X Pitch

0 5.00/.197"
1 10.00/.394"
2 7.5/.2952"
3 3.81/.15"

X Screw & Clamp

4 "-/+"Combination type W/Steel Stamping Clamp
5 "-"Slot type W/Steel Stamping Clamp

X Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

X P.C.B Mounting

0 Vertical (90D wire inlet)
1 Horizontal (180D wire inlet)

X X X X

00J0 Standard
(Row spacing 7.62mm&5.0mm)
(Steel screw plating Cr^{3+})


A0J0
(Row spacing 10.0mm)


Any special item by customer request, please contact sales department.

X


G RoHS compliant (lead<4%) In copper Alloy


WIRE PROTECTOR SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	30A
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	10-24
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	15-16mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	30A
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	10-24
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	15-16mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	300V
Current rating:	30A
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	10-24
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	15-16mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	30A
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	10-24
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	15-16mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS




WIRE PROTECTOR SYSTEM

TM




Type/Stackable
Poles 3p/4p/5p
TMxx190000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	400V	450V
Current rating:	10A	24A
Wire range:	0.34~2.5mm²	
Solid wire(AWG):	14-22	
Stranded wire(AWG):	14-22	
Torque :	3.5Lb-In	0.5Nm
Screw:	M3	
Wire strip length:	7~8mm	
Withstanding Voltage:	1.8KV	2.5KV
Safety Approval:	cULus	VDE

EN



Pitch 12.5mm
Solid Block
Poles 2p~6p
ENxx048000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	57A
Wire range:	
Solid wire(AWG):	6-22
Stranded wire(AWG):	6-22
Torque(Lb-In) :	13
Screw:	M4
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

TM


XX Number of contacts	X Screw & Clamp	X Body Color	X Fuse Holder Color	X Earth Screw	X X X X	X
Solid Block 03 to 05 3 to 5 contacts	0 "-/+"Combination type W/Brass Machined 1 "-"Slot type W/Brass Machined	8 Dark grey 9 White	0 Black	0 W/O Earth screw 1 With Earth screw (M3*14) 2 With Earth screw (M3*18)	00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy

EN


XX Number of contacts	X Pitch	X Screw & Clamp	X Color	0	X X X X	X
Solid Block 02 to 12 2 to 12 contacts	0 12.5/.492"	4 "-/+"Combination type W/Steel Stamping Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D)		00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy

WIRE PROTECTOR SYSTEM

KY




Pitch 5.0mm
Poles 2p/3p
Horizontal (180D wire inlet) Square hole
KYxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V / 250V
Current rating:	15A / 17.5A
Wire range:	
Solid wire(AWG):	12-24 / 0.2-2.5mm^2
Stranded wire(AWG):	12-24 / 0.2-2.5mm^2
Torque(Lb-In) :	3.0 / 0.34Nm
Screw:	M2.6
Wire strip length:	5-6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

KY




Pitch 5.0mm
Poles 2p/3p
Vertical (90D wire inlet) Square hole
KYxx015100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V / 250V
Current rating:	15A / 17.5A
Wire range:	
Solid wire(AWG):	12-24 / 0.2-2.5mm^2
Stranded wire(AWG):	12-24 / 0.2-2.5mm^2
Torque(Lb-In) :	3.0 / 0.34Nm
Screw:	M2.6
Wire strip length:	5-6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

KY




Pitch 5.0mm
Poles 2p/3p
Horizontal (180D wire inlet) Round hole
KYxx015200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V / 250V
Current rating:	15A / 17.5A
Wire range:	
Solid wire(AWG):	12-24 / 0.2-2.5mm^2
Stranded wire(AWG):	12-24 / 0.2-2.5mm^2
Torque(Lb-In) :	3.0 / 0.34Nm
Screw:	M2.6
Wire strip length:	5-6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

KY



Pitch 5.0mm
Poles 2p/3p
Vertical (90D wire inlet) Round hole
KYxx015300J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V / 250V
Current rating:	15A / 17.5A
Wire range:	
Solid wire(AWG):	12-24 / 0.2-2.5mm
Stranded wire(AWG):	12-24 / 0.2-2.5mm
Torque(Lb-In) :	3.0 / 0.34Nm
Screw:	M2.6
Wire strip length:	5-6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

PART NUMBERS

KY | XX Number of contacts | X Pitch | X Screw & Terminal | X Color | X Body type | X X X X | X

XX Number of contacts

End Stackable

For 5.0 Pitch
02 to 24 2 to 24 contacts

For 10.0 Pitch
02 to 12 2 to 12 contacts

X Pitch

0 5.00/.197"
1 10.00/.394"

X Screw & Terminal

0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

X Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

X Body type

0 Horizontal(180D) Square hole
1 Vertical(90D) Square hole
2 Horizontal(180D) Round hole
3 Vertical(90D) Round hole

X X X X

00J 0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.


X


G RoHS compliant (lead<4%) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


WIRE PROTECTOR SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Torque(Lb-In) :	2.3
Screw:	M2.0
Wire strip length:	4-5mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Torque(Lb-In) :	2.3
Screw:	M2.0
Wire strip length:	4-5mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Torque(Lb-In) :	3.5
Screw:	M2.6
Wire strip length:	5-6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Torque(Lb-In) :	2.4
Screw:	M2.6
Wire strip length:	5-6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

KZ | XX Number of contacts | X Pitch | X Screw & Terminal | X Color | X Cage type | XXXXX | X

Number of contacts

End Stackable

For 3.5 Pitch
02 to 24 2 to 24 contacts

For 7.0 Pitch
02 to 12 2 to 12 contacts

Pitch

1 3.5/.138"
2 7.0/.276"
7 5.0/.197"
8 10.0/.394"

Screw & Terminal

0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Cage type

0 Square hole
1 Round hole

XXXXX

00J0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X


G RoHS compliant (lead<4%) In copper Alloy

WIRE PROTECTOR SYSTEM

EC



Pitch 3.5mm
Poles 2p-16p
SMT type (W/O Pillar)
EC**xx**1000B0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Torque(Lb-In) :	2.0
Screw:	M2.0
Wire strip length:	5-6mm
Withstanding Voltage:	1.3KV
Safety Approval:	(cULus) pending

EC



Pitch 3.5mm
Poles 2p-16p
SMT type (With Pillar)
EC**xx**1001B0J0G *
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Torque(Lb-In) :	2.0
Screw:	M2.0
Wire strip length:	5-6mm
Withstanding Voltage:	1.3KV
Safety Approval:	(cULus) pending

E7



Pitch 5.0mm
Poles 2p-20p
W/O Interlock
E7**xx**015000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14-22
Stranded wire(AWG):	14-22
Torque(Lb-In) :	3.5
Screw:	M2.6
Wire strip length:	5-6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

EC

XX Number of contacts	X Pitch	X Screw & Terminal	X Color	X Body type	X X X X	X
Solid Block For 3.5 Pitch 02 to 16 2 to 16 contacts For 7.0 Pitch 02 to 12 2 to 12 contacts	1 3.5/.138" 2 7.0/.276"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black	0 W/O Pillar & With cover 1 With Pillar & With cover	B0J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy

E7

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Body type	X X X X	X
Solid Block 02 to 20 2-20 contacts	0 5.0/.197" 1 10.0/.394"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 Solid Block	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

TMBWIREPRSYS0214A4

"*" means FCI Standard item, any other non-standard item, please consult FCI for up-to-date information.


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

RISING CLAMP SYSTEM

OVERVIEW

For rising clamp system, the clamp is lifted by turning the screw clock-wise. The wire is clamped between the clamp and the terminal. It is a more robust and secure wire connection.







Single-piece rising clamp terminal block connectors are commonly used in applications where there is restricted access. They are ideal for highly active environments because they are designed to withstand activity and vibrations.

RISING CLAMP SYSTEM

VN




Pitch 2.54mm
Solid Block
Poles 2p~24p
VNxxA15000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	6A
Wire range:	
Solid wire(AWG):	18-30
Stranded wire(AWG):	18-30
Torque(Lb-In) :	1.3
Screw:	M1.6
Wire strip length:	4~5mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

ER




Pitch 3.5mm
Vertical
(90D Wiire inlet)
Poles 2p/3p
ERxx015100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

ER




Pitch 3.5mm
Poles 2p~3p
ERxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

VQ




Pitch 3.5mm
Dip solder/Solid Block
Poles 2p~24p
VQxx115000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-30
Stranded wire(AWG):	16-30
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VQ




Pitch 3.81mm
Dip solder/Solid Block
Poles 2p~24p
VQxx315000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-30
Stranded wire(AWG):	16-30
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VQ




Pitch 3.5mm
Press fit/Solid Block
Poles 2p~24p
VQxx115100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-30
Stranded wire(AWG):	16-30
Torque(Lb-In) :	1.7
Diameter of metal-plated hole:	Ø1.0
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VQ



Pitch 3.81mm
Press fit/Solid Block
Poles 2p~24p
VQxx315100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-30
Stranded wire(AWG):	16-30
Torque(Lb-In) :	1.7
Diameter of metal-plated hole:	Ø1.0
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

RISING CLAMP SYSTEM

PART NUMBERS









RISING CLAMP SYSTEM

ED




Pitch 3.81mm
Solid block
Poles 2p~24p
EDxx315000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	2.17
Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YO




Pitch 3.5mm
1st-Level/Solid Block
Poles 2p~24p
YOxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque :	1.7Lb-in
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YO




Pitch 3.81mm
1st-Level/Solid Block
Poles 2p~24p
YOxx215000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque :	1.7Lb-in
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YP




Pitch 3.5mm
2nd-Level/Solid Block
Poles 2p~24p (Insert hole:1.6x1.6mm)
YPxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YP



Pitch 3.81mm
2nd-Level/Solid Block
Poles 2p~24p (Insert hole:1.6x1.6mm)
YPxx215000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YP



Pitch 3.81mm
High Type (2nd-Level/Solid Block)
Poles 2p~24p (Insert hole:2.1x2.2mm)
YPxx2150A0J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

RISING CLAMP SYSTEM

PART NUMBERS

ED — XX Number of contacts · X Pitch · X Screw & Clamp · X Color · 0 · X X X X X

- Solid Block
  - For 3.81 Pitch: 02 to 24 — 2 to 24 contacts
  - For 7.62 Pitch: 02 to 12 — 2 to 12 contacts
- 3 3.81/.15"
- 4 7.62/.30"
- 0 "-/+"Combination type W/Brass Machined Clamp
- 1 "-"Slot type W/Brass Machined Clamp
- 0 Black
- 5 Green (RAL 6018/T)
- 6 Blue
- 8 Grey (RAL 7035/D)
- C Green (RAL 6018/U)
- 00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

YO — XX Number of contacts · X Pitch · X Screw & Clamp · X Color · X Tail length · X X X X X


- Solid Block
  - For 3.5/3.81 Pitch: 02 to 24 — 2 to 24 contacts
  - For 7.0/7.62 Pitch: 02 to 12 — 2 to 12 contacts
- 0 3.50/.138"
- 1 7.00/.275"
- 2 3.81/.15"
- 3 7.62/.30"
- 0 "-/+"Combination type W/Brass Machined Clamp
- 1 "-"Slot type W/Brass Machined Clamp
- 0 Black
- 5 Green (RAL 6018/T)
- 6 Blue
- 8 Grey (RAL 7035/D)
- 0 3.7mm
- 00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

YP — XX Number of contacts · X Pitch · X Screw & Clamp · X Color · X Tail length · X Special Insulator · X X X X


- Solid Block
  - For 3.5/3.81 Pitch: 02 to 24 — 2 to 24 contacts
  - For 7.0/7.62 Pitch: 02 to 12 — 2 to 12 contacts
- 0 3.50/.138"
- 1 7.00/.275"
- 2 3.81/.15"
- 3 7.62/.30"
- 0 "-/+"Combination type W/Brass Machined Clamp
- 1 "-"Slot type W/Brass Machined Clamp
- 0 Black
- 5 Green (RAL 6018/T)
- 6 Blue
- 8 Grey (RAL 7035/D)
- 0 3.7mm
- 0 Standard
- A High type (only pitch3.81/7.62)
- 0J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

RISING CLAMP SYSTEM

YQ




Pitch 3.5mm-L
Double level (YO+YP)
Poles 2*2p~2*24p (Insert hole:1.6x1.6mm)
YQxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YQ




Pitch 3.5mm-R
Double level (YO+YP)
Poles 2*2p~2*24p (Insert hole:1.6x1.6mm)
YQxx215000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YQ



Pitch 3.81mm-L
Double level (YO+YP)
Poles 2*2p~2*24p (Insert hole:1.6x1.6mm)
YQxx415000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YQ




Pitch 3.81mm-L
Double level (ED+YP) High type
Poles 2*2p~2*24p (Insert hole:2.1x2.2mm)
YQxx4150A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YQ



Pitch 3.81mm-R
Double level (YO+YP)
Poles 2*2p~2*24p (Insert hole:1.6x1.6mm)
YQxx615000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YQ




Pitch 3.81mm-R
Double level (ED+YP) High type
Poles 2*2p~2*24p (Insert hole:2.1x2.2mm)
YQxx6150A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TV




Pitch 3.5mm
Solid Block
Poles 2p~24p
TVxx115000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TV



Pitch 3.81mm
Solid Block
Poles 2p~24p
TVxx315000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

RISING CLAMP SYSTEM

TV



Pitch 5.0mm
Solid Block
Poles 2p~24p
TVxx515000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-26
Stranded wire(AWG):	14-26
Torque(Lb-In) :	3.5
Screw:	M3.0
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

PART NUMBERS

YQ — XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Tail length | X Special Insulator | XXX X

Solid Block

For 3.5/3.81 Pitch
04 to 48 2*2-24 contacts

For 7.0/7.62 Pitch
04 to 24 2*2-12 contacts

Pitch:
0 3.50/.138"(Left)
1 7.00/.275"(Left)
2 3.50/.138"(Right)
3 7.00/.275"(Right)
4 3.81/.15"(Left)
5 7.62/.30"(Left)
6 3.81/.15"(Right)
7 7.62/.30"(Right)

Screw & Clamp:
0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color:
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)

Tail length:
0 3.7mm

Special Insulator:
0 Standard
A High type (only pitch3.81/7.62)

XXX:
0J0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X:
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

TV — XX Number of contacts | X Pitch | X Screw & Clamp | X Color | 0 | XXXX X

Solid Block

For 3.5 & 3.81 & 5.0 Pitch
02 to 24 2 to 24 contacts

For 7.0 & 7.62 & 10.0 Pitch
02 to 12 2 to 12 contacts

Pitch:
1 3.50/.138"
2 7.0/.276"
3 3.81/.15"
4 7.62/.30"
5 5.0/.197"
6 10.0/.394"


Screw & Clamp:
0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp


Color:
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)


XXXX:
00J0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.


X:
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

RISING CLAMP SYSTEM











Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus



Electrical:	cULus
Voltage rating:	150V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus



Electrical:	cULus
Voltage rating:	150V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

PART NUMBERS

YA | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Tail length | X X X X X

Number of contacts

End Stackable

For 3.5/3.81 Pitch
06 to 72 3*2-24 contacts

For 7.0/7.62 Pitch
06 to 36 3*2-12 contacts

Solid Block Only

For only 3.81 Pitch
15 3*5 contacts

Pitch

0 3.5/.138"
1 7.0/.275"
2 3.81/.15"
3 7.62/.30"

Screw & Clamp

0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)

Tail length

0 3.5mm (only 15 pole solid block)
1 3.5mm (stackable)

X X X X

00J0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.


X


G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


RISING CLAMP SYSTEM














Electrical:	UL
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	

Electrical:	UL
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	

Electrical:	UL
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	

PART NUMBERS

T2 | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Insulator type | XXXXX | X

XX Number of contacts
End Stackable
For 5.0 & 5.08 Pitch
02 to 24 2 to 24 contacts
For 10.0 & 10.16 Pitch
02 to 12 2 to 12 contacts

X Pitch
0 5.00/.197"
1 10.00/.394"
2 5.08/0.20"
3 10.16/0.40"

X Screw & Clamp
0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp


X Color
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)


X Insulator type
0 Stackable
1 Solid block

XXXXX
00J 0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.


X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy


RISING CLAMP SYSTEM





Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

TP | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body type | X X X X | X

Number of contacts
End Stackable
For 5.0 & 5.08 Pitch
02 to 24 2 to 24 contacts
For 10.0 & 10.16 Pitch
02 to 12 2 to 12 contacts

Pitch
0 5.00/.197"
1 10.00/.394"

Screw & Clamp
0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Body type
0 Stackable
1 Solid block
(Only pitch 5.0 24P)

X X X X
00J0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.


X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

RISING CLAMP SYSTEM

ES




Pitch 5.0mm
Poles 2p/3p
ESxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14-30
Stranded wire(AWG):	14-30
Torque(Lb-In) :	4.3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TZ



Pitch 5.0mm
Solid Block
Poles 2p~24p (With Cover/2P~7P)
TZxx0101B0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	6A
Wire range:	
Solid wire(AWG):	14-30
Stranded wire(AWG):	14-30
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TZ



Pitch 3.5mm
Poles 2p-16p
SMT type (W/O Pillar)
TZxx2103B0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-30
Stranded wire(AWG):	16-30
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	4~5mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

TZ



Pitch 3.5mm
Poles 2p-16p
SMT type (With Pillar)
TZxx2101B0J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-30
Stranded wire(AWG):	16-30
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	4~5mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

PART NUMBERS

ES

XX	X	X	X	0	X X X X X
Number of contacts	Pitch	Screw & Clamp	Color		

End Stackable

For 5.00 Pitch
02 to 24 2 to 24 contacts

For 10.0 Pitch
02 to 12 2 to 12 contacts

- 0 5.00/.197"
- 1 10.0/.394"

- 0 "-/+"Combination type W/Brass Machined Clamp
- 1 "-"Slot type W/Brass Machined Clamp

- 0 Black
- 5 Green (RAL 6018/T)
- 6 Blue
- 8 Grey (RAL 7035/D)

- 00J0 Standard (Steel screw plating Cr^{3+})
  Any special item by customer request, please contact sales department.

- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

TZ

XX	X	X	X	X	X X X X X
Number of contacts	Pitch	Screw & Clamp	Color	Body type	

Solid Block

For 3.5 & 5.0 Pitch
02 to 24 2 to 24 contacts

For 10.0 Pitch
02 to 12 2 to 12 contacts

- 0 5.00/.197"
- 1 10.00/.394"
- 2 3.5/.138"

- 0 "-/+"Combination type W/Brass Machined Clamp
- 1 "-"Slot type W/Brass Machined Clamp


- 0 Black


- 0 With Pillar & W/O cover
- 1 With Pillar & With cover
- 2 W/O Pillar & W/O cover (only Pitch 3.5)
- 3 W/O Pillar & With cover (only Pitch 3.5)


- B0J0 Standard (Steel screw plating Cr^{3+})
  Any special item by customer request, please contact sales department.


- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy


RISING CLAMP SYSTEM




















Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	

Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	

Electrical:	UL	VDE
Voltage rating:	300V	250V
Current rating:	10A	10A
Wire range:	0.5 - 1.5mm²	
Solid wire(AWG):	16-26	
Stranded wire(AWG):	16-26	
Torque :	3.5Lb-In.	0.4N.m
Screw:	M3	
Wire strip length:	5~6mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:		

Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

PART NUMBERS

V3

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Contact direction	X X X X X
Solid Block For 5.0 Pitch 03 3 contacts For 10.0 Pitch 02 2 contacts	0 5.00/.197" 1 10.0/.394"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7004/P) C Green (RAL 6018/U)	0 Left 1 Right	00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy


TO


XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Body type	X X X X X
End Stackable For 5.0 Pitch 02 to 24 2 to 24 contacts For 10.0 Pitch 02 to 12 2 to 12 contacts	0 5.00/.197" 1 10.00/.394	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	1 Solid Block Type (Tail length 3.8mm) 2 Stackable Type (Tail length 3.8mm)	00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


RISING CLAMP SYSTEM





Electrical:	UL
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Torque(Lb-In) :	3.5
Screw:	M3.0
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cRUus





Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cRUus

PART NUMBERS

YC

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Tail length	X X X X X

End Stackable

For 5.08 Pitch
02 to 24 2 to 24 contacts

For 10.16 Pitch
02 to 12 2 to 12 contacts

Pitch
2 5.08/.20"
3 10.16/.40"

Screw & Clamp
0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)

Tail length
0 3.5mm

X X X X X
00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

EK

XX Number of contacts	X Pitch	X Screw & Terminal body	X Color	0	X X X X X

End Stackable

For 5.08 Pitch
02 to 24 2 to 24 contacts

For 10.16 Pitch
02 to 12 2 to 12 contacts


Pitch
2 5.08/.2"
3 10.16/.4"


Screw & Terminal body
0 "-/+" Combination type W/Brass Machined Clamp
1 "-" slot type W/Brass Machined Clamp

Color
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)


X X X X X
00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy


RISING CLAMP SYSTEM







Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	16A	10A
Wire range:	0.34-4.0mm²	
Solid wire(AWG):	12-22	
Stranded wire(AWG):	12-22	
Torque :	3.5Lb-In.	0.4N.m
Screw:	M2.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	VDE







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	UL	VDE
Voltage rating:	300V	450V
Current rating:	10A	10A
Wire range:	0.34-4.0mm²	
Solid wire(AWG):	12-22	
Stranded wire(AWG):	12-22	
Torque :	3.5Lb-In.	0.4N.m
Screw:	M2.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	UL	VDE







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	UL
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	UL






Electrical:	UL
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	UL


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

RISING CLAMP SYSTEM


PART NUMBERS










RISING CLAMP SYSTEM







Electrical:	cULus	FIMKO
Voltage rating:	300V	300V
Current rating:	16A	17.5A
Wire range:		0.5-1.5mm²
Solid wire(AWG):	12-28	
Stranded wire(AWG):	12-28	
Torque :	3.5Lb-In	0.5N.m
Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	FI







Electrical:	cULus	FIMKO
Voltage rating:	300V	300V
Current rating:	16A	17.5A
Wire range:		0.5-1.5mm²
Solid wire(AWG):	12-28	
Stranded wire(AWG):	12-28	
Torque :	3.5Lb-In	0.5N.m
Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	FI







Electrical:	cULus	FIMKO
Voltage rating:	300V	300V
Current rating:	16A	17.5A
Wire range:		0.5-1.5mm²
Solid wire(AWG):	12-28	
Stranded wire(AWG):	12-28	
Torque :	3.5Lb-In	0.5N.m
Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	FI







Electrical:	cULus	FIMKO
Voltage rating:	300V	300V
Current rating:	16A	17.5A
Wire range:		0.5-1.5mm²
Solid wire(AWG):	12-28	
Stranded wire(AWG):	12-28	
Torque :	3.5Lb-In	0.5N.m
Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	FI







Electrical:	cULus
Voltage rating:	300V
Current rating:	16A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	16A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus	FIMKO
Voltage rating:	300V	300V
Current rating:	16A	17.5A
Wire range:		0.5-1.5mm²
Solid wire(AWG):	12-28	
Stranded wire(AWG):	12-28	
Torque :	3.5Lb-In	0.5N.m
Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	FI






Electrical:	cULus	FIMKO
Voltage rating:	300V	300V
Current rating:	16A	17.5A
Wire range:		0.5-1.5mm²
Solid wire(AWG):	12-28	
Stranded wire(AWG):	12-28	
Torque :	3.5Lb-In	0.5N.m
Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	FI

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.


RISING CLAMP SYSTEM

PART NUMBERS




RISING CLAMP SYSTEM

VJ



Pitch 5.0mm
Horizontal
(180D wire inlet)
Poles 2p/3p


VJxx015200J0G*
Number of poles



Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m


Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

VJ



Pitch 5.0mm
Horizontal-Solid block
(180D wire inlet)
Poles 4p~24p


VJxx015500J0G*
Number of poles



Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m


Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

VJ



Pitch 5.0mm
Vertical
(90D wire inlet)
Poles 2p/3p


VJxx015000J0G*
Number of poles



Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m


Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

VJ



Pitch 5.0mm
Vertical-Solid block
(90D wire inlet)
Poles 4p~24p


VJxx015300J0G*
Number of poles



Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	20A	24A
Wire range:		0.2-2.54mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m


Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

VJ



Pitch 5.08mm
Horizontal
(180D wire inlet)
Poles 2p/3p


VJxx215200J0G*
Number of poles



Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m


Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

VJ



Pitch 5.08mm
Horizontal-Solid block
(180D wire inlet)
Poles 4p~24p


VJxx215500J0G*
Number of poles



Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m


Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

VJ



Pitch 5.08mm
Vertical
(90D wire inlet)
Poles 2p/3p


VJxx215000J0G*
Number of poles



Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m


Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

VJ



Pitch 5.08mm
Vertical-Solid block
(90D wire inlet)
Poles 4p~24p

VJxx215300J0G*
Number of poles



Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m


Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

RISING CLAMP SYSTEM

VJ




Pitch 7.5mm
Horizontal
(180D wire inlet)
Poles 2p/3p
VJxx415200J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	750V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	3KV
Safety Approval:	cULus	VDE

VJ




Pitch 7.5mm
Horizontal - Solid block
(180D wire inlet)
Poles 4p~16p
VJxx415500J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	750V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	3KV
Safety Approval:	cULus	VDE

VJ




Pitch 7.5mm
Vertical
(90D wire inlet)
Poles 2p/3p
VJxx415000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	750V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	3KV
Safety Approval:	cULus	VDE

VJ




Pitch 7.5mm
Vertical - Solid block
(90D wire inlet)
Poles 4p~16p
VJxx415300J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	750V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	3KV
Safety Approval:	cULus	VDE

VJ




Pitch 7.62mm
Horizontal
(180D wire inlet)
Poles 2p/3p
VJxx615200J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	750V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	3KV
Safety Approval:	cULus	VDE

VJ




Pitch 7.62mm
Horizontal - Solid block
(180D wire inlet)
Poles 4p~16p
VJxx615500J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	750V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	3KV
Safety Approval:	cULus	VDE

VJ




Pitch 7.62mm
Vertical
(90D wire inlet)
Poles 2p/3p
VJxx615000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	750V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	3KV
Safety Approval:	cULus	VDE

VJ



Pitch 7.62mm
Vertical - Solid block
(90D wire inlet)
Poles 4p~16p
VJxx615300J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	750V
Current rating:	20A	24A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-30	
Stranded wire(AWG):	12-30	
Torque :	3.5Lb-in	0.5N.m


Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	3KV
Safety Approval:	cULus	VDE

RISING CLAMP SYSTEM

PART NUMBERS




RISING CLAMP SYSTEM




EQ

Pitch 5.0mm - 90D
Solid block
Poles 2p~24p
EQxx058000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus




EQ

Pitch 5.0mm - 180D
Solid block
Poles 2~24p
EQXX058100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus




YF

Pitch 5.0mm
3rd-level
Poles 2p/3p
YFxx015000J0G*
Number of poles




Electrical:	UL
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	UL



YF

Pitch 5.08mm
3rd-level
Poles 2p/3p
YFxx215000J0G*
Number of poles



Electrical:	UL
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	UL

PART NUMBERS


EQ


XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Wire Entry	X X X X X
Solid Block For 5.0 Pitch 02 to 24 2 to 24 contacts For 10.0 Pitch 02 to 12 2 to 12 contacts	0 5.00/.197" 1 10.0/.394"	0 "-/+"Combination type W/Brass Machined clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D)	0 90D Wire inlet (Vertical) 1 180D Wire inlet (Horizontal)	00J 0 Standard (Steel screw plating Cr^{2+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

YF


XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Tail length	X X X X X
End Stackable For 5.0 & 5.08 Pitch 02 to 24 2 to 24 contacts For 10.0 & 10.16 Pitch 02 to 12 2 to 12 contacts	0 5.00/.197" 1 10.00/.394" 2 5.08/0.20" 3 10.16/0.40"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D)	0 3.5mm	00J 0 Standard (Steel screw plating Cr^{2+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy


RISING CLAMP SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus


PART NUMBERS




For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


RISING CLAMP SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending





Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending





Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

PART NUMBERS

YR — XX Number of contacts | X Pitch | X Screw & Clamp | X Color | 0 | X X X X X

Solid Block

For 5.0 & 5.08 Pitch
02 to 24 2 to 24 contacts

For 10.0 & 10.16 Pitch
02 to 12 2 to 12 contacts

Pitch	
0	5.0/.197"
1	10.0/.394"
2	5.08/.20"
3	10.16/.40"

Screw & Clamp	
0	"-/+"Combination type W/Brass Machined Clamp
1	"-"Slot type W/Brass Machined Clamp

Color	
0	Black
5	Green (RAL 6018/T)
6	Blue
8	Grey (RAL 7035/D)
C	Green (RAL 6018/U)

XXXX	
00J0	Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.

X	
G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy

YG — XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body type | X X X X X

Solid Block

For 5.0 & 5.08 Pitch
02 to 24 2 to 24 contacts

For 10.0 & 10.16 Pitch
02 to 12 2 to 12 contacts

Pitch	
0	5.0/.197"
1	10.0/.394"
2	5.08/.20"
3	10.16/.40"

Screw & Clamp	
0	"-/+"Combination type W/Brass Machined Clamp
1	"-"Slot type W/Brass Machined Clamp

Color	
0	Black
5	Green (RAL 6018/T)
6	Blue
8	Grey (RAL 7035/D)
C	Green (RAL 6018/U)


Body type	
1	W/O cover

XXXX	
00J0	Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.


X	
G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy

RISING CLAMP SYSTEM

YS




Pitch 5.0mm
Double Level
Poles 4p(2*2),6p(2*3)
YSxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Torque(Lb-In) :	3.5
Screw:	M3.0
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YS




Pitch 5.08mm
Double Level
Poles 4p(2*2),6p(2*3)
YSxx215000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Torque(Lb-In) :	3.5
Screw:	M3.0
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YL




Pitch 5.0mm-L
Double level(YD+YE)
Poles 4p(2*2),6p(2*3)
YLxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YL




Pitch 5.0mm-R
Double level(YD+YE)
Poles 4p(2*2),6p(2*3)
YLxx215000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YL




Pitch 5.08mm - Left
Double level (YD+YE)
Poles 4p(2*2),6p(2*3)
YLxx415000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YL




Pitch 5.08mm - Right
Double level (YD+YE)
Poles 4p(2*2),6p(2*3)
YLxx615000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

YL



Pitch 5.08mm - Right
Double level (Solid block)
Poles 4P(2*2p)/6P(2*3p)
YLxx615100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	5.0
Screw:	M3.0
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.


RISING CLAMP SYSTEM


PART NUMBERS








RISING CLAMP SYSTEM




















Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

YM | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Tail length | X X X X X

End Stackable

For 5.0 & 5.08 Pitch
04 to 48 2*2 to 24 contacts

For 10.0 & 10.16 Pitch
04 to 24 2*2 to 12 contacts

Pitch
- 0 5.0/.197"(Left)
- 1 10.0/.394"(Left)
- 2 5.0/.197"(Right)
- 3 10.0/.394"(Right)
- 4 5.08/.20"(Left)
- 5 10.16/.40"(Left)
- 6 5.08/.20"(Right)
- 7 10.16/.40"(Right)

Screw & Clamp
- 0 "-/+"Combination type W/Brass Machined Clamp
- 1 "-"Slot type W/Brass Machined Clamp

Color
- 0 Black
- 5 Green (RAL 6018/T)
- 6 Blue
- 8 Grey (RAL 7035/D)
- C Green (RAL 6018/U)

Tail length
- 0 3.5mm


X X X X
00J 0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.


RISING CLAMP SYSTEM




Pitch 5.0mm - Interlace
Poles 2*2p/2*3p
EBxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	




Pitch 5.0mm - Parallel
Poles 2*2p/2*3p
EBxx015300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	




Pitch 5.08mm - Interlace
Poles 2*2p/2*3p
EBxx215000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	



Pitch 5.08mm - Parallel
Poles 2*2p/2*3p
EBxx215300J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	

PART NUMBERS

EB | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body type | X X X X X

End Stackable

For 5.0 & 5.08 Pitch
04 to 48 2*2 to 24 contacts

For 10.0 & 10.16 Pitch
04 to 24 2*2 to 12 contacts

Pitch	
0	5.0/.197"
1	10.0/.394"
2	5.08/.20"
3	10.16/.40"

Screw & Clamp	
0	"-/+"Combination type W/Brass Machined Clamp
1	"-"Slot type W/Brass Machined Clamp


Color	
0	Black
5	Green (RAL 6018/T)
6	Blue
8	Grey (RAL 7035/D)
C	Green (RAL 6018/U)


Body type	
0	With cover (solder pin staggered by half pin spacing)
1	W/O cover (solder pin staggered by half pin spacing)
3	W/O cover (solder pin in line)


00J 0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.


X	
G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy


RISING CLAMP SYSTEM














Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	14-24
Torque(Lb-In) :	3.5
Screw:	M3.0
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

YB

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Tail length	X X X X	X
End Stackable For 5.08 Pitch 06 to 72 3*2 to 24 contacts For 10.16 Pitch 06 to 36 3*2 to 12 contacts	2 5.08/.20" 3 10.16/.40"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D)	0 3.5mm	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy


YN


XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Tail length	X X X X	X
End Stackable For 5.0 & 5.08 Pitch 06 to 72 3*2 to 24 contacts For 10.0 & 10.16 Pitch 06 to 36 3*2 to 12 contacts	0 5.0/.197" 1 10.0/.394" 2 5.08/.20" 3 10.16/.40"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 3.5mm	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


RISING CLAMP SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire:	AWG 12-24
Stranded wire:	AWG 12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

YH — XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body type | X X X X X


- **XX Number of contacts**
  - End Stackable
  - For 5.0 / 5.08 Pitch: 06 to 72 — 3*2 to 24 contacts
  - For 10.0 / 10.16 Pitch: 06 to 36 — 3*2 to 12 contacts
- **X Pitch**
  - 0 5.0/.197"
  - 1 10.0/.394"
  - 2 5.08/.20"
  - 3 10.16/.40"
- **X Screw & Clamp**
  - 0 "-/+"Combination type W/Brass Machined Clamp
  - 1 "-"Slot type W/Brass Machined Clamp
- **X Color**
  - 0 Black
  - 5 Green (RAL 6018/T)
  - 6 Blue
  - 8 Grey (RAL 7035/D)
  - C Green (RAL 6018/U)
- **X Body type**
  - 1 W/O cover
- **X X X X X**
  - 00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- **X**
  - G RoHS compliant (lead<4%) In copper Alloy
  - H RoHS compliant (lead<1000ppm) In copper Alloy

YT — XX Number of contacts | X Pitch | X Screw & Clamp | X Color | 0 | X X X X X


- **XX Number of contacts**
  - End Stackable
  - For 5.0 / 5.08 Pitch: 08 to 96 — 4*2 to 24 contacts
  - For 10.0 / 10.16 Pitch: 08 to 48 — 4*2 to 12 contacts
- **X Pitch**
  - 0 5.0/.197"
  - 1 10.0/.394"
  - 2 5.08/.20"
  - 3 10.16/.40"
- **X Screw & Clamp**
  - 0 "-/+"Combination type W/Brass Machined Clamp
  - 1 "-"Slot type W/Brass Machined Clamp
- **X Color**
  - 0 Black
  - 5 Green (RAL 6018/T)
  - 6 Blue
  - 8 Grey (RAL 7035/D)
  - C Green (RAL 6018/U)
- **X X X X X**
  - 00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- **X**
  - G RoHS compliant (lead<4%) In copper Alloy
  - H RoHS compliant (lead<1000ppm) In copper Alloy

RISING CLAMP SYSTEM

YI




Pitch 5.0mm
Poles 4*2p/4*3p
YIxx015100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

YI



Pitch 5.08mm
Poles 4*2p/4*3p
YIxx215100J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

PART NUMBERS

YI | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body type | XXXXX | X

Number of contacts

End Stackable

For 5.0 / 5.08 Pitch
08 to 96 4*2 to 24 contacts

For 10.0 / 10.16 Pitch
08 to 48 4*2 to 12 contacts

Pitch

0 5.0/.197"
1 10.0/.394"
2 5.08/.20"
3 10.16/.40"

Screw & Clamp

0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Body type

1 W/O cover


XXXXX


00J 0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X


G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy


RISING CLAMP SYSTEM







Electrical:	cULus	TUV
Voltage rating:	300V	450V
Current rating:	30A	41A
Wire range:		0.2-6mm^2
Solid wire(AWG):	10-26	
Stranded wire(AWG):	10-26	
Torque :	6.9Lb-In	0.85Nm
Screw:	M3.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		







Electrical:	cULus	TUV
Voltage rating:	300V	450V
Current rating:	30A	41A
Wire range:		0.2-6mm^2
Solid wire(AWG):	10-26	
Stranded wire(AWG):	10-26	
Torque :	6.9Lb-In	0.85Nm
Screw:	M3.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		







Electrical:	cULus	TUV
Voltage rating:	300V	450V
Current rating:	30A	41A
Wire range:		0.2-6mm^2
Solid wire(AWG):	10-26	
Stranded wire(AWG):	10-26	
Torque :	6.9Lb-In	0.85Nm
Screw:	M3.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		







Electrical:	cULus	TUV
Voltage rating:	300V	450V
Current rating:	30A	41A
Wire range:		0.2-6mm^2
Solid wire(AWG):	10-26	
Stranded wire(AWG):	10-26	
Torque :	6.9Lb-In	0.85Nm
Screw:	M3.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		





Electrical:	cULus	TUV
Voltage rating:	300V	450V
Current rating:	30A	41A
Wire range:		0.2-6mm^2
Solid wire(AWG):	10-26	
Stranded wire(AWG):	10-26	
Torque :	6.9Lb-In	0.85Nm
Screw:	M3.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		







Electrical:	cULus
Voltage rating:	300V
Current rating:	64A
Wire range:	
Solid wire(AWG):	6-22
Stranded wire(AWG):	6-22
Torque(Lb-In) :	19
Screw:	M4.5
Wire strip length:	11~12mm
Withstanding Voltage:	1.6KV
Safety Approval:	

RISING CLAMP SYSTEM


PART NUMBERS








Disclaimer
Please note that the above information is subject to change without notice.


RISING CLAMP SYSTEM




















Electrical:	cULus
Voltage rating:	600V
Current rating:	30A
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	10-24
Torque(Lb-In) :	5.5
Screw:	M3.5
Wire strip length:	7~8mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus

Electrical:	cULus
Voltage rating:	300V
Current rating:	30A
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	10-24
Torque(Lb-In) :	5.5
Screw:	M3.5
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

Electrical:	cULus
Voltage rating:	300V
Current rating:	30A
Wire range:	
Solid wire(AWG):	10-30
Stranded wire(AWG):	10-30
Torque(Lb-In) :	5.2
Screw:	M3.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

Electrical:	cULus
Voltage rating:	300V
Current rating:	30A
Wire range:	
Solid wire(AWG):	10-30
Stranded wire(AWG):	10-30
Torque(Lb-In) :	5.2
Screw:	M3.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS


KO

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Contact type	X X X X	X
End Stackable 02 to 16 2 to 16 contacts	2 9.52/.374"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 Back single row 1 Solder pins staggered by half pin spacing	00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

VV


XX Number of contacts	X Pitch	X Screw & Clamp	X Color	0	X X X X	X
End Stackable For 6.35 & 9.52 Pitch 04 to 32 2*2 to 16 contacts For 12.7 & 19.04 Pitch 04 to 16 2*2 to 8 contacts	0 6.35/.25" 1 12.7/.5" 2 9.52/.375" 3 19.04/.75"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D)		00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

RISING CLAMP SYSTEM




VP

Pitch 10.16mm
Single tail type
Poles 2p/3p
VPxx658400J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	650V
Current rating:	65A	57A
Wire range:		
Solid wire:	AWG 6-20/0.5-16mm²	
Stranded wire:	AWG 6-20/0.5-10mm²	
Torque :	19Lb-In/1.2N.m	

Screw:	M4.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV/8KV
Safety Approval:	cULus




VP

Pitch 10.16mm
Double Parallel tail type
Poles 2p/3p
VPxx658500J0G* A type (Solder pitch 5.08mm)
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	250V
Current rating:	65A	57A
Wire range:		
Solid wire:	AWG 6-20/0.5-16mm²	
Stranded wire:	AWG 6-20/0.5-10mm²	
Torque :	19Lb-In/1.2N.m	

Screw:	M4.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV/4KV
Safety Approval:	cULus




VP

Pitch 10.16mm
Double Parallel tail type
Poles 2p/3p
VPxx658800J0G* B type (Solder pitch 4.0mm)
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	250V
Current rating:	65A	57A
Wire range:		
Solid wire:	AWG 6-20/0.5-16mm²	
Stranded wire:	AWG 6-20/0.5-10mm²	
Torque :	19Lb-In/1.2N.m	

Screw:	M4.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV/4KV
Safety Approval:	cULus




VP

Pitch 10.16mm
Double Interlace tail type
Poles 2p/3p
VPxx658700J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	65A	76A
Wire range:		
Solid wire:	AWG 6-20/16mm²	
Stranded wire:	AWG 6-20/16mm²	
Torque (Lb-In):	19Lb-In/1.2N.m	

Screw:	M4.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV/6KV
Safety Approval:	cULus




VP

Pitch 12.7mm
Single tail type
Poles 2p/3p
VPxx855400J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	65A	76A
Wire range:		
Solid wire:	AWG 6-20/16mm²	
Stranded wire:	AWG 6-20/16mm²	
Torque:	19Lb-In/1.2N.m	

Screw:	M4.5
Wire strip length:	10~11mm
Withstanding Voltage:	2.2KV 6KV
Safety Approval:	cULus




VP

Pitch 12.7mm
Double tail type
Poles 2p/3p
VPxx858500J0G* A type (Solder pitch 5.08mm)
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	65A	76A
Wire range:		
Solid wire:	AWG 6-20/16mm²	
Stranded wire:	AWG 6-20/16mm²	
Torque :	19Lb-In/1.2N.m	

Screw:	M4.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV/6KV
Safety Approval:	cULus




VP

Pitch 12.7mm
Double tail Parallel type
Poles 2p/3p
VPxx858800J0G* B type (Solder pitch 4.0mm)
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	65A	76A
Wire range:		
Solid wire:	AWG 6-20/16mm²	
Stranded wire:	AWG 6-20/16mm²	
Torque:	19Lb-In/1.2N.m	

Screw:	M4.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV/6KV
Safety Approval:	cULus



VP

Pitch 12.7mm
Double tail Interlace type
Poles 2p/3p
VPxx858700J0G* B type (Solder pitch 4.0mm)
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	65A	76A
Wire range:		
Solid wire:	AWG 6-20/16mm²	
Stranded wire:	AWG 6-20/16mm²	
Torque :	19Lb-In/1.2N.m	

Screw:	M4.5
Wire strip length:	10~11mm
Withstanding Voltage:	2.2KV/6KV
Safety Approval:	cULus

Disclaimer
Please note that the above information is subject to change without notice.

RISING CLAMP SYSTEM

PART NUMBERS




RISING CLAMP SYSTEM

EJ




Pitch 19.0mm
Poles 1p
EJ01D15100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	600V
Current rating:	100A
Wire range:	
Solid wire(AWG):	3-18
Stranded wire(AWG):	3-18
Torque(Lb-In) :	30
Screw:	M5
Wire strip length:	12~15mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus

EI




Pitch 15.0mm
Solid block
Poles 2p~10p
EIxxC15300J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	125A	125A
Wire range:		35 mm²
Solid wire(AWG):	2-20	
Stranded wire(AWG):	2-20	
Torque(Lb-In) :	36.5	
Screw:	M5	
Wire strip length:	12~15mm	
Withstanding Voltage:	2.2KV	8KV
Safety Approval:	cULus	

EI



Pitch 15.0mm - With Flange
Solid block
Poles 2p~10p
EIxxC15310J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	125A	125A
Wire range:		35 mm²
Solid wire(AWG):	2-20	
Stranded wire(AWG):	2-20	
Torque(Lb-In) :	36.5	
Screw:	M5	
Wire strip length:	12~15mm	
Withstanding Voltage:	2.2KV	8KV
Safety Approval:	cULus	

E4



Solid Block
Poles 2p/3p/4p/6p
E4xx018000J0G*
Number of poles




poles	a(mm)	b(mm)
2pole	20	
3pole	31	11
4pole	38	18
6pole	52	32

Electrical:	cULus
Voltage rating:	300V
Current rating:	30A
Wire range:	
Solid wire(AWG):	10-26
Stranded wire(AWG):	10-26
Torque(Lb-In) :	9
Screw:	M3.5
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V4



Solid Block
Poles 2p~5p
V4xx018000J0G*
Number of poles



Poles	a(mm)	b(mm)
2pole	29.0	
3pole	46.0	17.0
4pole	57.0	28.0
5pole	68.0	39.0


Electrical:	cULus
Voltage rating:	600V
Current rating:	65A
Wire range:	
Solid wire(AWG):	6-22
Stranded wire(AWG):	6-22
Torque(Lb-In) :	8.7
Screw:	M4
Wire strip length:	6~7mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


RISING CLAMP SYSTEM

PART NUMBERS














RISING CLAMP SYSTEM




















Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	

Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	15A	10A
Wire range:		0.34-4.0mm²
Solid wire(AWG):	12-24	
Stranded wire(AWG):	12-24	
Torque :	3.5Lb-In	0.4N.m
Screw:	M2.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	VDE

Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	15A	10A
Wire range:		0.34-4.0mm²
Solid wire(AWG):	12-24	
Stranded wire(AWG):	12-24	
Torque:	3.5Lb-In	0.4N.m
Screw:	M2.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	VDE

PART NUMBERS

VT

XX Number of contacts | X Pitch | X Screw & Clamp | X Color | 0 | X X X X | X

- **XX Number of contacts**: End Stackable; 01 to 12 — 1 to 12 contacts
- **X Pitch**: 2 — 5.08/.20"
- **X Screw & Clamp**: 1 — "-"Slot type W/Brass Machined Clamp
- **X Color**: 0 Black; 5 Green (RAL 6018/T); 6 Blue; 8 Grey (RAL 7035/D); C Green (RAL 6018/U)
- **X X X X**: 00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- **X**: G RoHS compliant (lead<4%) In copper Alloy; H RoHS compliant (lead<1000ppm) In copper Alloy

TG


XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Tail length | X Special Insulator | X X X | X


- **XX Number of contacts**: End Stackable; For 5.0 & 5.08 Pitch 02 to 24 — 2 to 24 contacts; For 10.0 & 10.16 Pitch 02 to 12 — 2 to 12 contacts
- **X Pitch**: 0 5.00/.197"; 1 10.00/.394"; 5 5.08/.20"; 6 10.16/.40"
- **X Screw & Clamp**: 0 "-/+"Combination type W/Brass Machined Clamp; 1 "-"Slot type W/Brass Machined Clamp
- **X Color**: 0 Black; 5 Green (RAL 6018/T); 6 Blue; 8 Grey (RAL 7035/D); C Green (RAL 6018/U)
- **X Tail length**: 0 4.5mm; 3 3.2mm
- **X Special Insulator**: B Stackable (long-interlock); C Solid block (long-interlock) (Only pitch 5.0mm)
- **X X X**: 0J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- **X**: G RoHS compliant (lead<4%) In copper Alloy; H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


RISING CLAMP SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.0
Screw:	M3.0
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.0
Screw:	M3.0
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.0
Screw:	M3.0
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.0
Screw:	M3.0
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.0
Screw:	M3.0
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.0
Screw:	M3.0
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	600V
Current rating:	30A
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	10-24
Torque (Lb-In):	5.3
Screw:	M3.5
Wire strip length:	8~9mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	30A
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	10-24
Torque (Lb-In):	5.3
Screw:	M3.5
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus


RISING CLAMP SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	30A
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	10-24
Torque (Lb-In):	5.3
Screw:	M3.5
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	600V
Current rating:	65A
Wire range:	
Solid wire(AWG):	6-20
Stranded wire(AWG):	6-20
Torque (Lb-In):	11.7
Screw:	M4.5
Wire strip length:	10~11mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	65A
Wire range:	
Solid wire(AWG):	6-20
Stranded wire(AWG):	6-20
Torque (Lb-In):	11.7
Screw:	M4.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	65A
Wire range:	
Solid wire(AWG):	6-20
Stranded wire(AWG):	6-20
Torque (Lb-In):	11.7
Screw:	M4.5
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

E6 | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Direction of pin | XXXXX

- **Number of contacts**: Solid Block; 02 to 04 — 2 to 4 contacts
- **Pitch**: 0 — 5.00/.197"
- **Screw & Clamp**: 0 "-/+"Combination type W/Brass Machined Clamp; 1 "-"Slot type W/Brass Machined Clamp
- **Color**: 0 Black; 5 Green (RAL 6018/T); 6 Blue; 8 Grey (RAL 7035/D); C Green (RAL 6018/U)
- **Direction of pin**: 0 Right; 1 Left
- **XXXXX**: 00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- **X**: G RoHS compliant (lead<4%) In copper Alloy; H RoHS compliant (lead<1000ppm) In copper Alloy

KP | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Contact type | XXXXX


- **Number of contacts**: End Stackable; For 6.35 Pitch: 01 to 16 — 1 to 16 contacts; For 10.16 Pitch: 01 to 12 — 1 to 12 contacts
- **Pitch**: 0 6.35/.25"; 2 10.16/.4"
- **Screw & Clamp**: 0 "-/+"Combination type W/Brass Machined Clamp; 1 "-"Slot type W/Brass Machined Clamp
- **Color**: 0 Black; 5 Green (RAL 6018/T); 6 Blue; 8 Grey (RAL 7035/D); C Green (RAL 6018/U)
- **Contact type**: 0 Solder pins staggered by half pin spacing; 1 Back single row; 2 Front single row
- **XXXXX**: 00J0 W/O cover; 10J0 With cover; Any special item by customer request, please contact sales department.
- **X**: G RoHS compliant (lead<4%) In copper Alloy; H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

RISING CLAMP SYSTEM

K6



Pitch 4.5mm
Poles 2~24p
K6xx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Torque(Lb-In) :	2.7
Screw:	M3.0
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

K7



Pitch 7.5mm - Right
Poles 3p
K7xx038000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	4.3
Screw:	M3.0
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

K7



Pitch 7.5mm - Left
Poles 3p
K7xx038100J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	4.3
Screw:	M3.0
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

PART NUMBERS

K6

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	0	XXXXX	X

End Stackable
For 4.5 Pitch
02 to 24 2 to 24 contacts
For 9.0 Pitch
02 to 12 2 to 12 contacts

0 4.5/.177"
1 9.00/.354"

0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

00J 0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

K7

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Direction of pin	XXXXX	X

Solid Block
03 3 contacts

0 7.5/.295"

2 "-/+"Combination type W/Zinc Alloy Clamp (square hole)
3 "-"Slot type W/Zinc Alloy Clamp (square hole)

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

0 Right
1 Left

00J 0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

"*" means FCI Standard item, any other non-standard item, please consult FCI for up-to-date information.

TMBRISCLPSYS0214A4


Notes

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

SCREW PLUGGABLE SYSTEM

OVERVIEW

For screw pluggable system, the plug uses the screw structure to contact.






Screw pluggable terminal block connectors are used primarily in wire-to-board situations. Designed to be connected or detached with ease, the plug uses its screw structure to protect and fix the wire to the contact.

SCREW PLUGGABLE SYSTEM

TH



Pitch 3.5mm
Poles 2p/3p
THxx215000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TH



Pitch 3.5mm
Solid Block
Poles 4p~24p
THxx215100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TH




Pitch 3.81mm
Poles 2p/3p
THxx415000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TH



Pitch 3.81mm
Solid Block
Poles 4p~24p
THxx415100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TH



Pitch 5.0mm
Poles 2p/3p
THxx016000J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	15A	12A	15A
Wire range:	0.34 - 1.5mm²		
Solid wire(AWG):	14-22		
Stranded wire(AWG):	14-22		
Torque :	3.5Lb-In.	0.4N.m	0.4N.m
Screw:	M2.6		
Wire strip length:	5~6mm		
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus		

TH



Pitch 5.0mm
Solid Block
Poles 2p~24p
THxx010100J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	15A	12A	15A
Wire range:	0.34 - 1.5mm²		
Solid wire(AWG):	14-22		
Stranded wire(AWG):	14-22		
Torque :	3.5Lb-In.	0.4N.m	0.4N.m
Screw:	M2.6		
Wire strip length:	5~6mm		
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus		

TT



Pitch 3.5mm
Poles 2p/3p/4p
TTxx215000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

TT



Pitch 3.81mm
Poles 2p/3p/4p
TTxx415000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

TT



Pitch 5.0mm
Poles 2p/3p
TTxx018000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-22
Stranded wire(AWG):	16-22
Torque(Lb-In) :	1.7
Screw:	M3
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TT



Pitch 5.0mm
Solid Block
Poles 4p~24p
TTxx018100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-22
Stranded wire(AWG):	16-22
Torque(Lb-In) :	1.7
Screw:	M3
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

PART NUMBERS






SCREW PLUGGABLE SYSTEM

EH



Pitch 3.5mm
Poles 2p/3p
EHxx216000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.1
Screw:	M2
Wire strip length:	5~6mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

TX



Pitch 5.0mm (Round hole)
Solid Block (TX/EX L=12.9mm)
Poles 2p~12p
TXxx010000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Torque(Lb-In) :	3.5
Screw:	M3
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TX



Pitch 5.0mm (Square hole)
Poles 2p~12p
TXxx030000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Torque(Lb-In) :	3.5
Screw:	M3.0
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

EH

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	0	XXXXX

Number of contacts

End Stackable

For 3.5 Pitch
02 to 24 2 to 24 contacts

For 7.0 Pitch
02 to 12 2 to 12 contacts

Pitch

2 3.5/.138"
3 7.0/.276"

Screw & Clamp

0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

XXXXX

00J 0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X

G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

TX

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	0	XXXXX

Number of contacts

Solid Block

For 5.0 Pitch
02 to 12 2 to 12 contacts

For 10.0 Pitch
02 to 06 2 to 06 contacts

Pitch

0 5.00/.197"
1 10.00/.394"

Screw & Clamp

0 "-/+"Combination type W/Brass Machined Clamp (round hole)
1 "-"Slot type W/Brass Machined Clamp (round hole)

Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

XXXXX

00J 0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X

G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

KR



Pitch 5.0mm - without hook
Poles 2P~24P
KRxx010000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-26
Stranded wire(AWG):	14-26
Torque(Lb-In) :	3.5
Screw:	M2.6
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

KR



Pitch 5.0mm - with hook
Poles 2P~24P
KRxx010100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-26
Stranded wire(AWG):	14-26
Torque(Lb-In) :	3.5
Screw:	M2.6
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TY



Pitch 5.0mm
Solid Block
Poles 2p~24p
TYxx010000J0G*
Number of poles



Electrical:	cULus	TUV
Voltage rating:	300V	300V
Current rating:	10A	10A
Wire range:	0.2 -2.5mm²	
Solid wire(AWG):	14-26	
Stranded wire(AWG):	14-26	
Torque:	3.5Lb-In	0.4N.m
Screw:	M2.6	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	TÜV

PART NUMBERS

KR

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Body Type	X X X X	X

XX Number of contacts

Solid Block

For 5.0 Pitch
02 to 24 2 to 24 contacts

For 10.0 Pitch
02 to 12 2 to 12 contacts

X Pitch

0 5.0/.197"
1 10.0/.394"

X Screw & Clamp

0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

X Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

X Body Type

0 W/O Hook
1 With Hook

X X X X

00J 0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X

G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

TY

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Male pin	X X X X	X

XX Number of contacts

Solid Block

For 5.0 Pitch
02 to 24 2 to 24 contacts

For 10.0 Pitch
02 to 12 2 to 12 contacts

X Pitch

0 5.00/.197"
1 10.00/.394"

X Screw & Clamp

0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

X Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

X Male pin

0 Two beam contact (with male Φ 1.0)
1 Six finger contact (with male Φ 1.0)
2 With flat jumper (Two beam contact)
3 With round jumper (Two beam contact)

X X X X

00J 0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X


G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

SCREW PLUGGABLE SYSTEM

VG



Pitch 5.0mm
Solid Block
Poles 2p~24p
VGxx010000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-26
Stranded wire(AWG):	14-26
Torque(Lb-In) :	3.5
Screw:	M2.6
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

EO



Pitch 5.0mm - Solid block
Poles 2p~12p
EO withTwo beam contact /EP□1.0mm
EOwithSix beam contact/EX L=16.0mm
EOxx010000J0G/EOxx010200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Torque(Lb-In) :	4.5
Screw:	M3
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

EO




Pitch 5.0mm
High type
Poles 2p-24p
EOxx0102A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Torque(Lb-In) :	4.5
Screw:	M3
Wire strip length:	5-6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

EP



Pitch 5.0mm
Poles 2p~24p
(EO/EP□1.0mm)
EPxx000000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

EX



Pitch 5.0mm
(Match TX 5.0)
Poles 2p~24p
EXxx000000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

EX



Pitch 5.0mm
(Match EO 5.0 High type)
Poles 2p~24p
EXxx0001A0J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

PART NUMBERS

VG

XX	X	X	X	0	X X X X	X
Number of contacts	Pitch	Screw & Clamp	Color			

- **Number of contacts**: Solid Block — For 5.0 Pitch: 02 to 24 (2 to 24 contacts); For 10.0 Pitch: 02 to 12 (2 to 12 contacts)
- **Pitch**: 0 5.00/.197" | 1 10.00/.394"
- **Screw & Clamp**: 0 "-/+"Combination type W/Brass Machined Clamp | 1 "-"Slot type W/Brass Machined Clamp
- **Color**: 0 Black | 5 Green (RAL 6018/T) | 6 Blue | 8 Grey (RAL 7035/D) | C Green (RAL 6018/U)
- **X X X X**: 00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- **X**: G RoHS compliant (lead<4%) In copper Alloy | H RoHS compliant (lead<1000ppm) In copper Alloy

EO

XX	X	X	X	X	X X X X	X
Number of contacts	Pitch	Screw & Clamp	Color	Body Type		

- **Number of contacts**: Solid Block — For 5.0 Pitch: 02 to 12 (2 to 12 contacts); For 10.0 Pitch: 02 to 06 (2 to 6 contacts)
- **Pitch**: 0 5.0/.197" | 1 10.00/.394"
- **Screw & Clamp**: 0 "-/+"Combination type W/Brass Machined Clamp | 1 "-"Slot type W/Brass Machined Clamp
- **Color**: 0 Black | 5 Green (RAL 6018/T) | 6 Blue | 8 Grey (RAL 7035/D)
- **Body Type**: 0 Two beam contact (Hole Dim 1.9mm) (with EP □ 1.0mm) | 2 Six finger contact (Hole Dim 1.9mm) (with EXΦ 1.3mm L=16.0mm)
- **X X X X**: 00J 0 Standard; A0J 0 High type (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- **X**: G RoHS compliant (lead<4%) In copper Alloy | H RoHS compliant (lead<1000ppm) In copper Alloy

EP

XX	X	X	X	0	X X X X	X
Number of contacts	Pitch	Pin length	Pin plating			

- **Number of contacts**: Solid Block — For 5.0 Pitch: 02 to 24 (2 to 24 contacts); For 10.0 Pitch: 02 to 12 (2 to 12 contacts)
- **Pitch**: 0 5.0/.197" | 1 10.00/.394"
- **Pin length**: 0 13.75mm pin(□1.0*1.0)
- **Pin plating**: 0 Tin plated
- **X X X X**: 00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.
- **X**: G RoHS compliant (lead<4%) In copper Alloy | H RoHS compliant (lead<1000ppm) In copper Alloy

EX

XX	X	X	X	X	X X X X	X
Number of contacts	Pitch	Pin plating	Color	Pin length		


- **Number of contacts**: Solid Block — For 5.0 Pitch: 02 to 24 (2 to 24 contacts); For 10.0 Pitch: 02 to 12 (2 to 12 contacts)
- **Pitch**: 0 5.00/.197" | 1 10.00/.394"
- **Pin plating**: 0 Tin plating | 1 G/F plating
- **Color**: 0 Black | 2 Red (RAL3001/D) | 5 Green (RAL6018/T) | 8 Grey (RAL7035/D)
- **Pin length**: 0 12.9mm pin (for Tx series) (UpΦ1.3, Down Φ 1.0) | 1 16.0mm pin (for Eo series) (UpΦ 1.3, Down Φ 1.0) | 2 16.0mm pin (for Eo series) (UpΦ 1.4, Down Φ 1.0)
- **X X X X**: 00J 0 Standard; A0J 0 Match EO High type. Any special item by customer request, please contact sales department.
- **X**: G RoHS compliant (lead<4%) In copper Alloy | H RoHS compliant (lead<1000ppm) In copper Alloy

SCREW PLUGGABLE SYSTEM

OP



Pitch 3.5mm
Poles 2p~24p
(EH/OPΦ1.0mm)
OPxx2B0100J0G*
Number of poles




(See how to order pageH18)

Electrical:	cULus
Voltage rating:	150V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

OP



Pitch 3.5mm
Poles 2p~24p
OPxx220000J0G*
Number of poles




(See how to order pageH18)

Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

OP



Pitch 3.81mm
Poles 2p~24p
OPxx420000J0G*
Number of poles




(See how to order pageH18)

Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

OP



Pitch 5.0mm
Poles 2p~24p
OPxx000000J0G*
Number of poles




(See how to order pageH17)

Electrical:	UL	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	15A	12A	15A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Torque :			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			

OP



Pitch 5.0mm - Bend PIN
Poles 2p~24p
OPxx0F0000J0G*
Number of poles




(See how to order pageH17)

Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

OP



Pitch 8.0mm
Poles 2p~20p
OPxx630000J0G*
Number of poles




(See how to order pageH18)

Electrical:	UL
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

KG



Pitch 5.0 (with TH5.0 and TT 5.0)
Poles 2p-24p
KGxx008000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	( )pending

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

PART NUMBERS

OP — XX Number of contacts | X Pitch | X Pin length | X Pin plating | X Material of body | XXXXX

Solid Block

For 3.5 & 3.81 Pitch
02 to 24 2 to 24 contacts
For 8.0 Pitch
02 to 20 2 to 20 contacts
For 7.0 & 7.62 Pitch
02 to 12 2 to 12 contacts
For 16.0 Pitch
02 to 10 2 to 10 contacts

Pitch:
2 3.5/.138"
3 7.0/.276"
4 3.81/.15"
5 7.62/.30"
6 8.0/.315"
7 16.0/.63"

Pin length:
2 L=12.5mm(UpΦ1.3 DownΦ1.0) (DIMA=3.5)
B L=10.0mm(ΦI.0) (DIMA=3.5) (Only pitch:3.5 used for EH)
3 L=11.5mm(ΦI.3)(DIMA=1.9) (Only pitch:8.0)

Pin plating:
0 Tin
1 Gold plating 10u"
2 Gold flash

Material of body:
0 PA66
1 PA46

00J 0 Standard
Any special item by customer request, please contact sales department.

G RoHS compliant (lead<4%) In copper Alloy

OP — XX Number of contacts | X Pitch | X Pin length | X Pin plating | X Material of body | XXXXX

Solid Block

For 5.0 Pitch
02 to 24 2 to 24 contacts

For 10.0 Pitch
02 to 12 2 to 12 contacts

Pitch:
0 5.00/.197"
1 10.00/.394"

Pin length:
0 L=12.5mm(ΦI.3) (DIMA=3.5)
1 L=13.0mm(UpΦ1.3 DownΦ1.0) (DIMA=4.3)
2 L=12.5mm(UpΦ1.3 DownΦ1.0) (DIMA=3.5)
3 L=11.5mm(ΦI.3) (DIMA=1.9)
4 L=14.2mm(ΦI.3) (DIMA=2.9)
5 L=17.5mm(ΦI.3) (DIMA=3.5)
6 L=20.0mm(ΦI.3) (DIMA=3.5)
7 L=18.0mm(UpΦ1.3 DownΦI.0) (DIMA=3.5)
8 L=16.2mm(UpΦ1.3 DownΦI.0) (DIMA=3.5)
9 L=16.5mm(ΦI.3) (DIMA=3.5)
A L= 21.0mm(Φ I.1) (DIMA=4.4)
C L= 12.7mm(Φ I.1) (DIMA=4.4)
D L= 16.3mm(Φ I.1) (DIMA=4.4)
F L=12.5*8.8mm Bend pin(ΦI.3)
J L= 13.0mm pin(ΦI.3) (DIMA=3.5)
H L= 25.5mm pin(ΦI.3) (DIMA=3.5)
G L= 17.9mm pin(ΦI.10) (DIMA=4.4)
K L= 12.0mm pin(UPΦ1.30 DownΦ1.0) (Round pin)
M L= 11.8mm pin(ΦI.1) (DIMA=4.0)

Pin plating:
0 Tin
1 Gold plating 10u"
2 Gold flash

Material of body:
0 PA66
1 PA46

00J 0 Standard
Any special item by customer request, please contact sales department.

G RoHS compliant (lead<4%) In copper Alloy

KG — XX Number of contacts | 0 | 0 | X Color | 0 | XXXXX

Solid Block

For 5.0 Pitch
02 to 24 2 to 24 contacts

For 10.0 Pitch
02 to 12 2 to 12 contacts

Color:
0 Black
5 Green (RAL 6018/T)
6 Blue (RAL 5015/A)
8 Grey (RAL 7035/D)

00J 0 Standard
Any special item by customer request, please contact sales department.


G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

SCREW PLUGGABLE SYSTEM

E2




Pitch 3.5mm
Poles 2p~24p
E2xx113000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-28
Stranded wire(AWG):	14-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	6-7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VD




Pitch 3.81mm
Poles 2p~24p
VDxx315000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VD



Pitch 3.81mm
Poles 2p~24p
With Flange
VDxx315200J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

E2

XX Number of contacts	X Pitch	X Screw &Clamp	X Color	X Body Type	XXXXX	X
Solid Block For 3.5 Pitch 02 to 24 2 to 24 contacts For 7.0 Pitch 02 to 12 2 to 12 contacts	1 3.5/.138" 2 7.0/.276"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 3 Orange 5 Green (RAL 6018/T) 6 Blue (RAL5015/A) 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 W/O Flange	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

VD


XX Number of contacts	X Pitch	X Screw&Clamp	X Color	X Body Type	XXXXX	X
Solid Block For 3.81 Pitch 02 to 24 2 to 24 contacts For 7.62 Pitch 02 to 12 2 to 12 contacts	3 3.81/.15" 4 7.62/.30"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 W/O Flange 2 With Flange	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

TJ



Pitch 3.5mm
Stackable
Poles 2p~24p
TJxx1115300J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		1.5mm²
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	3.0Lb-In.	0.2N.m

Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

TJ




Pitch 3.5mm - With Flange
Poles 2p~24p
TJxx115200J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		1.5mm²
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	3.0Lb-In.	0.2N.m

Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

TJ



Pitch 3.81mm
Stackable
Poles 2p~24p
TJxx315300J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		1.5mm²
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	3.0Lb-In	0.2N.m

Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

TJ




Pitch 3.81mm - With Flange
Poles 2p~24p
TJxx315200J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		1.5mm²
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	3.0Lb-In.	0.2N.m

Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

TJ




Pitch 3.5/3.81 mm
With Handle
Poles 2p~24p
TJxxx15400J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		1.5mm²
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	3.0Lb-In	0.2N.m

Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

TJ



Pitch 5.0/5.08 mm
With Handle
Poles 2p~24p
TJxxx15400J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m

Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV 2.5KV 2.5KV
Safety Approval:	cULus VDE TÜV

TJ



Pitch 5.0mm
Contact on down side
Poles 2p~24p
TJxx715000J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m

Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV 2.5KV 2.5KV
Safety Approval:	cULus VDE TÜV

TJ



Pitch 5.0mm - With Flange
Contact on down side
Poles 2p~24p
TJxx715200J0G*
Number of poles



Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m


Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV 2.5KV 2.5KV
Safety Approval:	cULus VDE TÜV

SCREW PLUGGABLE SYSTEM

TJ



Pitch 5.0mm
Contact on up side
Poles 2p~24p
TJxx715600J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	5
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TJ



Pitch 5.0mm - With Flange
Contact on up side
Poles 2p~24p
TJxx715700J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	5
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TJ



Pitch 5.08mm
Contact on down side
Poles 2p~24p
TJxx515300J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m
Screw:	M3		
Wire strip length:	7~8mm		
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus	VDE	TÜV

TJ



Pitch 5.08mm - With Flange
Contact on down side
Poles 2p~24p
TJxx515200J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m
Screw:	M3		
Wire strip length:	7~8mm		
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus	VDE	TÜV

TJ



Pitch 5.08mm
Contact on up side
Poles 2p~24p
TJxx515600J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	5
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TJ




Pitch 5.08mm - With Flange
Contact on up side
Poles 2p~24p
TJxx515700J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	5
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	

TJ



Pitch 7.5mm
Poles 2p~16p
TJxxA15000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	5
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TJ



Pitch 7.5mm - With Flange
Poles 2p~16p
TJxxA15200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	5
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

TJ



Pitch 7.62mm
Poles 2p~16p
TJxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	5
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

TJ



Pitch 7.62mm - With Flange
Poles 2p~16p
TJxx015200J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	5
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

TJ (3.5/3.81/5.08)


XX Number of contacts	X Pitch	X Screw &Clamp	X Color	X Body Type	XXXXX	X
Solid Block 02 to 24 2 to 24 contacts	1 3.5/.138" 3 3.81/.15" 5 5.08/.20"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue (RAL 5015/A) 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	2 With Flange 3 W/O Flange 4 W/O Flange (With Handle) 5 With Flange (With Handle) 6 W/O Flange (Contact on up side only 5.08) 7 With Flange (Contact on up side only 5.08)	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

TJ (5.0/7.5/7.62)


XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Body Type	XXXXX	X
Solid Block For 5.0 Pitch 02 to 24 2 to 24 contacts For 7.5 & 7.62 Pitch 02 to 16 2 to 16 contacts	0 7.62/.30" 7 5.0/.197" A 7.5/.295"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 W/O Flange 2 With Flange 4 W/O Flange (With handle only 5.0) 5 With Flange (With Handle only 5.0) 6 W/O Flange (Contact on up side only 5.0) 7 With Flange	00J0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

SCREW PLUGGABLE SYSTEM

EZ



Pitch 5.0mm
Poles 2p~24p
EZxx715000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cRUus

EZ




Pitch 5.0mm - With Flange
Poles 2p~24p
EZxx715200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cRUus

EZ




Pitch 5.08mm
Poles 2p~24p
EZxx515000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cRUus

EZ



Pitch 5.08mm - With Flange
Poles 2p~24p
EZxx515200J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cRUus

PART NUMBERS

EZ | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body Type | XXXXX | X

Solid Block

For 5.0 & 5.08 Pitch
02 to 24 2 to 24 contacts

For 10.0 & 10.16 Pitch
02 to 12 2 to 12 contacts

Pitch

7	5.0/.197"
5	5.08/.20"
8	10.0/.394"
6	10.16/.40"

Screw & Clamp

0	"-/+"Combination type W/Brass Machined Clamp
1	"-"Slot type W/Brass Machined Clamp

Color

0	Black
5	Green (RAL 6018/T)
6	Blue
8	Grey (RAL 7035/D)
C	Green (RAL 6018/U)

Body Type

0	W/O Flange
2	With Flange

XXXXX

00J0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X

G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

VR



Pitch 5.08mm
Contact on down side
Poles 2p~24p
VRxx515000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-30
Stranded wire(AWG):	14-30
Torque(Lb-In) :	2
Screw:	M2
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VR



Pitch 5.08mm - With Flange
Contact on down side
Poles 2p~24p
VRxx515200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-30
Stranded wire(AWG):	14-30
Torque(Lb-In) :	2
Screw:	M2
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VR



Pitch 5.08mm
Contact on up side
Poles 2p~24p
VRxx515100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-30
Stranded wire(AWG):	14-30
Torque(Lb-In) :	2
Screw:	M2
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VR



Pitch 5.08mm - WIth Flange
Contact on up side
Poles 2p~24p
VRxx515300J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-30
Stranded wire(AWG):	14-30
Torque(Lb-In) :	2
Screw:	M2
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

VR | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body Type | XXXXX | X

Number of contacts
Solid Block

For 5.08 Pitch
02 to 24 2 to 24 contacts

For 10.16 Pitch
02 to 12 2 to 12 contacts

Pitch
5 5.08/.20"
6 10.16/.40"

Screw & Clamp
0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Body Type
0 W/O Flange (Contact on down side)
1 W/O Flange (Contact on up side)
2 With Flange (Contact on down side)
3 With Flange (Contact on up side)

XXXXX
00J 0 Standard (Steel screw plating Cr^{6+})
Any special item by customer request, please contact sales department.


X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

SCREW PLUGGABLE SYSTEM

VB



Pitch 7.62mm
Poles 2p~16p
VBxx015000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	400V
Current rating:	20A	20A
Wire range:		
Solid wire:	AWG10-30/0.2-4mm²	
Stranded wire:	AWG10-30/0.25-4mm²	
Torque :	4.5Lb-In/0.5N.m	

Screw:	M3	
Wire strip length:	7~8mm	
Withstanding Voltage:	1.6KV	6KV
Safety Approval:		

VB



Pitch 7.62mm - With Flange
Poles 2p~16p
VBxx015200J0G*
Number of poles



Electrical:	cULus	IEC
Voltage rating:	300V	400V
Current rating:	20A	20A
Wire range:		
Solid wire:	AWG10-30/0.2-4mm²	
Stranded wire:	AWG10-30/0.25-4mm²	
Torque :	4.5Lb-In/0.5N.m	

Screw:	M3	
Wire strip length:	7~8mm	
Withstanding Voltage:	1.6KV	6KV
Safety Approval:		

PART NUMBERS

VB | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body type | XXXXX | X

Solid Block

For 7.62 Pitch
02 to 16 2 to 16 contacts

For 15.24 Pitch
02 to 08 2 to 8 contacts

- 0 7.62/.30"
- 1 15.24/.60"

- 0 "-/+"Combination type W/Brass Machined Clamp
- 1 "-"Slot type W/Brass Machined Clamp

- 0 Black
- 5 Green (RAL 6018/T)
- 6 Blue
- 8 Grey (RAL 7035/D)
- C Green (RAL 6018/U)

- 0 W/O Flange
- 2 With Flange

00J 0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

ET



Pitch 7.62mm
Poles 2p~16p
ETxx025000J0G*
Number of poles




Electrical:	cULus	TUV
Voltage rating:	300V/600V	800V
Current rating:	32A/41A	32A
Wire range:		0.2-6mm^2
Solid wire:	AWG8-24	
Stranded wire:	AWG8-24	
Torque :	7Lb-In	0.8N.m
Screw:	M3.5	
Wire strip length:	10~11mm	
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	TÜV

ET



Pitch 7.62mm - With Flange
Poles 2p~16p
ETxx025200J0G*
Number of poles




Electrical:	cULus	TUV
Voltage rating:	300V/600V	800V
Current rating:	32A/41A	32A
Wire range:		0.2-6mm^2
Solid wire:	AWG8-24	
Stranded wire:	AWG8-24	
Torque :	7Lb-In	0.8N.m
Screw:	M3.5	
Wire strip length:	10~11mm	
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	TÜV

ET



Pitch 7.62mm
With Flange (With Handle)
Poles 3p/4p
ETxx025300J0G*
Number of poles



Poles	a(mm)	b(mm)
3pole	38.10	15.24
4pole	45.72	22.86

Electrical:	cULus	TUV
Voltage rating:	300V/600V	800V
Current rating:	32A/41A	32A
Wire range:		0.2-6mm^2
Solid wire:	AWG8-24	
Stranded wire:	AWG8-24	
Torque :	7Lb-In	0.8N.m
Screw:	M3.5	
Wire strip length:	10~11mm	
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	TÜV

PART NUMBERS

ET | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body type | X X X X X

Solid Block

For 7.62 Pitch
02 to 16 2 to 16 contacts

For 15.24 Pitch
02 to 08 2 to 8 contacts

Pitch

0 7.62/.30"
1 15.24/.60"

Screw & Clamp

0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp
2 "*" Combination type W/Brass Machined Clamp

Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Body type

Used for VC series
Two tails type (300V 32A)
0 W/O Flange
2 With Flange (W/O Handle)
3 With Flange & With Handle (only 3p & 4p)
Three tails type (300V 41A)
E W/O Flange
G With Flange (W/O Handle)

Used for KT series (600V 41A)
A W/O Flange
C With Flange (W/O Handle)
D With Flange & With Handle (only 3p&4p)

X X X X

00J 0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X


G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

SCREW PLUGGABLE SYSTEM

EV



Pitch 10.16mm
Poles 2p~12p
EVxx615000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		0.5-16mm²
Solid wire(AWG):	6-20	
Stranded wire(AWG):	6-20	
Torque :	10.4Lb-In	1.2N.m
Screw:	M4.5	
Wire strip length:	13~14mm	
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	

EV



Pitch 10.16mm - With Flange
Poles 2p~12p
EVxx615100J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		0.5-16mm²
Solid wire(AWG):	6-20	
Stranded wire(AWG):	6-20	
Torque :	10.4Lb-In	1.2N.m
Screw:	M4.5	
Wire strip length:	13~14mm	
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	

EV



Pitch 10.16mm
With Flange (With Handle)
Poles 3p/4p
EVxx615200J0G*
Number of poles



Poles	a(mm)	b(mm)
3pole	48.24	20.32
4pole	58.40	30.48

Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		0.5-16mm²
Solid wire(AWG):	20	
Stranded wire(AWG):	6-20	
Torque :	10.4Lb-In	1.2N.m
Screw:	M4.5	
Wire strip length:	13~14mm	
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	

PART NUMBERS

EV | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body type | X X X X X

Solid Block

For 10.16 Pitch
02 to 12 2 to 12 contacts

For 20.32 Pitch
02 to 06 2 to 6 contacts

6	10.16/.40"
7	20.32/.80"

0	"-/+"Combination type W/Brass Machined Clamp
1	"-"Slot type W/Brass Machined Clamp

0	Black
5	Green (RAL 6018/T)
6	Blue
8	Grey (RAL 7035/D)
C	Green (RAL 6018/U)

0	W/O Flange
1	With Flange (W/O Handle)
2	With Flange (With Handle) (only 3p&4p)

00J 0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.


G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

TS



Pitch 3.5mm
Hook on entry side
Poles 2p~24p
TSXX115A00J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	8A	10A
Wire range:		1.5mm²
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	1.7Lb-In	0.2N.m

Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

TS



Pitch 3.5mm - With Flange
Hook on entry side
Poles 2p~24p
TSXX115C00J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	8A	10A
Wire range:		1.5mm²
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	1.7Lb-In	0.2N.m

Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

TS



Pitch 3.5mm
Hook on back side
Poles 2p~24p
TSXX115B00J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	8A	10A
Wire range:		1.5mm²
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	1.7Lb-In	0.2N.m

Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

TS




Pitch 3.5mm - With Flange
Hook on back side
Poles 2p~24p
TSXX115D00J0G
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	8A	10A
Wire range:		1.5mm²
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	1.7Lb-In	0.2N.m

Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

TS



Pitch 3.81mm
Hook on entry side
Poles 2p~24p
TSXX315A00J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	8A	10A
Wire range:		1.5mm²
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	1.7Lb-In	0.2N.m

Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

TS



Pitch 3.81mm - With Flange
Hook on entry side
Poles 2p~24p
TSXX315C00J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	8A	10A
Wire range:		1.5mm²
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	1.7Lb-In	0.2N.m

Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

TS



Pitch 3.81mm
Hook on back side
Poles 2p~24p
TSXX315B00J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	8A	10A
Wire range:		
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	1.7Lb-In	0.2N.m

Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

TS



Pitch 3.81mm - With Flange
Hook on back side
Poles 2p~24p
TSXX315D00J0G*
Number of poles



Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	8A	10A
Wire range:		
Solid wire(AWG):	16-28	
Stranded wire(AWG):	16-28	
Torque :	1.7Lb-In	0.2N.m


Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV 2.5KV
Safety Approval:	cULus VDE

SCREW PLUGGABLE SYSTEM

TS



Pitch 5.0mm
Hook on entry side
Poles 2p~24p
TSxx715A00J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m

Screw:		M3	
Wire strip length:		7~8mm	
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			

TS



Pitch 5.0mm - With Flange
Hook on entry side
Poles 2p~24p
TSxx715C00J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m

Screw:		M3	
Wire strip length:		7~8mm	
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			

TS



Pitch 5.0mm
Hook on back side
Poles 2p~24p
TSxx715B00J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m

Screw:		M3	
Wire strip length:		7~8mm	
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			

TS



Pitch 5.0mm - With Flange
Hook on back side
Poles 2p~24p
TSxx715D00J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m

Screw:		M3	
Wire strip length:		7~8mm	
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			

TS



Pitch 5.08mm
Hook on entry side
Poles 2p~24p
TSxx515A00J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m

Screw:		M3	
Wire strip length:		7~8mm	
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			

TS



Pitch 5.08mm - With Flange
Hook on entry side
Poles 2p~24p
TSxx515C00J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m

Screw:		M3	
Wire strip length:		7~8mm	
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			

TS



Pitch 5.08mm
Hook on back side
Poles 2p~24p
TSxx515B00J0G*
Number of poles




Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m

Screw:		M3	
Wire strip length:		7~8mm	
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			

TS



Pitch 5.08mm - With Flange
Hook on back side
Poles 2p~24p
TSxx515D00J0G*
Number of poles



Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:		2.5mm²/0.34-2.5mm²	
Solid wire(AWG):	12-24		
Stranded wire(AWG):	12-24		
Torque :	5Lb-In	0.5N.m	0.56N.m


Screw:		M3	
Wire strip length:		7~8mm	
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

TS



Pitch 7.5mm
Hook on entry side
Poles 2p~16p
TSxxA15A00J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	15A	15A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-24	
Stranded wire(AWG):	12-24	
Torque(Lb-In) :	3.5 Lb-In	0.4N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV

TS



Pitch 7.5mm - With Flange
Hook on entry side
Poles 2p~16p
TSxxA15C00J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	15A	15A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-24	
Stranded wire(AWG):	12-24	
Torque(Lb-In) :	3.5 Lb-In	0.4N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV

TS



Pitch 7.5mm
Hook on back side
Poles 2p~16p
TSxxA15B00J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	15A	15A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-24	
Stranded wire(AWG):	12-24	
Torque(Lb-In) :	3.5 Lb-In	0.4N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV

TS



Pitch 7.5mm - With Flange
Hook on back side
Poles 2p~16p
TSxxA15D00J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	15A	15A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-24	
Stranded wire(AWG):	12-24	
Torque(Lb-In) :	3.5 Lb-In	0.4N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV

TS



Pitch 7.62mm
Hook on entry side
Poles 2p~16p
TSxx015A00J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	15A	15A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-24	
Stranded wire(AWG):	12-24	
Torque(Lb-In) :	3.5 Lb-In	0.4N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV

TS



Pitch 7.62mm - With Flange
Hook on entry side
Poles 2p~16p
TSxx015C00J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	15A	15A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-24	
Stranded wire(AWG):	12-24	
Torque(Lb-In) :	3.5 Lb-In	0.4N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV

TS



Pitch 7.62mm
Hook on back side
Poles 2p~16p
TSxx015B00J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	15A	15A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-24	
Stranded wire(AWG):	12-24	
Torque(Lb-In) :	3.5 Lb-In	0.4N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV

TS



Pitch 7.62mm - With Flange
Hook on back side
Poles 2p~16p
TSxx015D00J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	15A	15A
Wire range:		0.2-2.5mm²
Solid wire(AWG):	12-24	
Stranded wire(AWG):	12-24	
Torque(Lb-In) :	3.5 Lb-In	0.4N.m

Screw:	M3	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV

SCREW PLUGGABLE SYSTEM

PART NUMBERS



For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

VM



Pitch 3.5mm
Poles 2p~24p
VMxx155000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VM




Pitch 3.5mm - With Flange
Poles 2p~24p
VMxx155200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VM



Pitch 3.81mm
Poles 2p~24p
VMxx355000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VM




Pitch 3.81mm - With Flange
Poles 2p~24p
VMxx355200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Torque(Lb-In) :	1.7
Screw:	M2
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VM



Pitch 5.0mm
Poles 2p~24p
VMxx755000J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	300V
Current rating:	20A	20A
Wire range:	0.34-2.5mm²	
Solid wire(AWG):	12-22	
Stranded wire(AWG):	12-22	
Torque :	3.5Lb-In	0.4N.m
Screw:	M2.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	TÜV

VM




Pitch 5.0mm - With Flange
Poles 2p~24p
VMxx755200J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	300V
Current rating:	20A	20A
Wire range:	0.34-2.5mm²	
Solid wire(AWG):	12-22	
Stranded wire(AWG):	12-22	
Torque :	3.5Lb-In	0.4N.m
Screw:	M2.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	TÜV

VM



Pitch 5.08mm
Poles 2p~24p
VMxx555000J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	300V
Current rating:	20A	20A
Wire range:	0.34-2.5mm²	
Solid wire(AWG):	12-22	
Stranded wire(AWG):	12-22	
Torque :	3.5Lb-In	0.4N.m
Screw:	M2.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	TÜV

VM




Pitch 5.08mm - With Flange
Poles 2p~24p
VMxx555200J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	300V
Current rating:	20A	20A
Wire range:	0.34-2.5mm²	
Solid wire(AWG):	12-22	
Stranded wire(AWG):	12-22	
Torque :	3.5Lb-In	0.4N.m
Screw:	M2.5	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	TÜV

SCREW PLUGGABLE SYSTEM

VM



Pitch 5.08mm
Low profile
Poles 2p~24p
VMxx555100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VM



Pitch 5.08mm - With Flange
Low profile
Poles 2p~24p
VMxx555300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VM



Pitch 7.5mm
Low profile
Poles 2p~16p
VMxxA55100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VM




Pitch 7.5mm - With Flange
Low profile
Poles 2p~16p
VMxxA55300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VM



Pitch 7.62mm
Low profile
Poles 2p~16p
VMxx055100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VM



Pitch 7.62mm - With Flange
Low profile
Poles 2p~16p
VMxx055300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	3.5
Screw:	M2.5
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

PART NUMBERS




SCREW PLUGGABLE SYSTEM

EM



Pitch 5.0mm
Poles 2p~24p
EMxx715000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

EM



Pitch 5.0mm - With Flange
Poles 2p~24p
EMxx715200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

EM



Pitch 5.08mm
Poles 2p~24p
EMxx515000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

EM



Pitch 5.08mm - With Flange
Poles 2p~24p
EMxx515200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

EM



Pitch 7.5mm
Poles 2p~16p
EMxxA15000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

EM



Pitch 7.5mm - With Flange
Poles 2p~16p
EMxxA15200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

EM



Pitch 7.62mm
Poles 2p~16p
EMxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

EM



Pitch 7.62mm - With Flange
Poles 2p~16p
EMxx015200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-22
Stranded wire(AWG):	12-22
Torque(Lb-In) :	4
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM

PART NUMBERS





SCREW PLUGGABLE SYSTEM







Electrical:	cULus	VDE
Voltage rating:	300V	160V
Current rating:	10A	13A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		







Electrical:	cULus	VDE
Voltage rating:	300V	160V
Current rating:	10A	13A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		







Electrical:	cULus	VDE
Voltage rating:	300V	160V
Current rating:	10A	13A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		







Electrical:	cULus	VDE
Voltage rating:	300V	160V
Current rating:	10A	13A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		





Electrical:	cULus	VDE
Voltage rating:	300V	160V
Current rating:	10A	13A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		






Electrical:	cULus	VDE
Voltage rating:	300V	160V
Current rating:	10A	13A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM

PART NUMBERS





SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM

PART NUMBERS





SCREW PLUGGABLE SYSTEM







Electrical:	cULus	
Voltage rating:	150V	
Current rating:	4A	
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.3KV	
Safety Approval:	cULus	







Electrical:	cULus	
Voltage rating:	150V	
Current rating:	4A	
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.3KV	
Safety Approval:	cULus	







Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE







Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE







Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE







Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE





Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE







Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM







Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		







Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			






Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			


SCREW PLUGGABLE SYSTEM







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			





Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	20A	15A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:		







Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	20A	15A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:		

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM







Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	20A	15A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV







Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	20A	15A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV







Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	20A	15A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV







Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	20A	15A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV







Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	20A	15A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV







Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	20A	15A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV






Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	20A	15A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV






Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	20A	15A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV

SCREW PLUGGABLE SYSTEM




OQ

Pitch 7.62mm
With Flange
Right-angle
Poles 2p~16p
OQxx055100J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	20A	15A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV




OQ

Pitch 7.62mm
Open Right-angle
Poles 2p~16p
OQxx005100J0G*
Number of poles




Electrical:	cULus	TÜV
Voltage rating:	300V	750V
Current rating:	20A	15A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	6.0KV
Safety Approval:	cULus	TÜV




OQ

Pitch 3.5mm - Vertical
With latch holder
Poles 2p~24p
OQxx125003J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE




OQ

Pitch 3.5mm
Right-angle
With latch holder
Poles 2p~24p
OQxx125103J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	10A	10.5A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE




OQ

Pitch 5.08mm - Vertical
With latch holder
Poles 2p~24p
OQxx545003J0G*
Number of poles




Electrical:	cULus	VDE	TUV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Torque(Lb-In) :			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus	VDE	TÜV




OQ

Pitch 5.08mm - Right-angle
With latch holder
Poles 2p~24p
OQxx545103J0G*
Number of poles




Electrical:	cULus	VDE	TUV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Torque(Lb-In) :			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus	VDE	TÜV




OQ

Pitch 5.0mm - Right-angle
With Latch holder
Poles 2p-24p
OQxx715103J0G*




Electrical:	cULus	VDE	TUV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Torque(Lb-In) :			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus	VDE	TÜV



OQ

Pitch 5.0mm
With Latch holder Vertical
Poles 2p-24p
OQxx715003J0G*




Electrical:	cULus	VDE	TUV
Voltage rating:	300V	300V	300V
Current rating:	20A	20A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Torque(Lb-In) :			
Screw:			
Wire strip length:			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus	VDE	TÜV



OQ

Pitch 3.5/3.81 mm
With Cover SMT type
Poles 2p~16p
OQxxx500D0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM

PART NUMBERS













SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

VS | XX Number of contacts | X Pitch | X Body Type | X Color | X P.C.B Mounting | XXXXX

Number of contacts
- Solid Block
- For 5.08 Pitch
  02 to 24 2 to 24 contacts
- For 10.16 Pitch
  02 to 12 2 to 12 contacts

Pitch
- 5 5.08/.20"
- 6 10.16/.40"

Body Type
- 1 Close
- 2 With Flange

Color
- 0 Black
- 5 Green (RAL 6018/T)
- 6 Blue
- 8 Grey (RAL 7035/D)
- C Green (RAL 6018/U)

P.C.B Mounting
- 0 Vertical
- 1 Right angle


XXXXX
- 00J0 Standard
- Any special item by customer request, please contact sales department.


X
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM







Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	8A	10A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE







Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	8A	10A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE







Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	8A	10A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE







Electrical:	cULus	VDE
Voltage rating:	300V	300V
Current rating:	8A	10A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	15A	17A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus	VDE	TÜV







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	15A	17A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus	VDE	TÜV






Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	15A	17A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus	VDE	TÜV







Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	15A	17A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus	VDE	TÜV


SCREW PLUGGABLE SYSTEM





Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	15A	17A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus	VDE	TÜV





Electrical:	cULus	VDE	TÜV
Voltage rating:	300V	300V	300V
Current rating:	15A	17A	20A
Wire range:			
Solid wire(AWG):			
Stranded wire(AWG):			
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:	cULus	VDE	TÜV

PART NUMBERS

VK | XX Number of contacts | X Pitch | X Body Type | X Color | 0 | X X X X | X

Number of contacts

Solid Block

For 3.5 & 3.81 & 5.0 & 5.08 Pitch
02 to 24 2 to 24 contacts

For 7.0 & 7.62 & 10.0 & 10.16 Pitch
02 to 12 2 to 12 contacts

Pitch

1	3.5/.138"
3	3.81/.15"
5	5.08/.20"
7	5.00/.197"
2	7.0/.276"
4	7.62/.30"
6	10.16/.40"
8	10.0/.394"

Body Type

0	Open (only 5.0/ 5.08mm pitch)
1	Close
2	With Flange

Color

0	Black
5	Green (RAL 6018/T)
6	Blue
8	Grey (RAL 7035/D)
C	Green (RAL 6018/U)

X X X X

00J 0 Standard

Any special item by customer request, please contact sales department.

X


G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

VC




Pitch 7.62mm
Right-angle (Two tail A type)
Poles 2p~16p
VCxx005000J0G*
Number of poles




Electrical:	cULus	TUV
Voltage rating:	300V	800V
Current rating:	32A	32A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	VDE

VC




Pitch 7.62mm
Flange with Nut (Right-angle)
Poles 2p~16p (Two tail A type)
VCxx015000J0G*
Number of poles




Electrical:	cULus	TUV
Voltage rating:	300V	800V
Current rating:	32A	32A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	VDE

VC




Pitch 7.62mm
Vertical (Two tail A type)
Poles 2p~16p
VCxx005100J0G*
Number of poles




Electrical:	cULus	TUV
Voltage rating:	300V	800V
Current rating:	32A	32A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	VDE

VC




Pitch 7.62mm
Flange with Nut (Vertical)
Poles 2p~16p (Two tail A type)
VCxx015100J0G*
Number of poles




Electrical:	cULus	TUV
Voltage rating:	300V	800V
Current rating:	32A	32A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	VDE

VC




Pitch 7.62mm
Feed-through header with slip-on connection
Poles 2p~16p
VCxx025100J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	800V
Current rating:	32A	32A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	

VC




Pitch 7.62mm
Close Vertical
Poles 2p~16p (Three tail B type)
VCxx0051A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	32A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VC



Pitch 7.62mm
With Flange
Vertical
Poles 2p~16p (Three tail B type)
VCxx0151A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	32A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VC



Pitch 7.62mm
Close Right-angle (PCB down)
Poles 2p~16p (Three tail B type)
VCxx0050C0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	32A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

SCREW PLUGGABLE SYSTEM

VC



Pitch 7.62mm
Close Right-angle (PCB up)
Poles 2p~16p (Three tail B type)
VCxx0050B0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	32A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

VC



Pitch 7.62mm
With Flange
Right-angle (PCB down)
Poles 2p~16p (Three tail B type)
VCxx0150C0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	32A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

VC



Pitch 7.62mm
With Flange
Right-angle (PCB up)
Poles 2p~16p (Three tail B type)
VCxx0150B0J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	32A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

PART NUMBERS

VC | XX Number of contacts | X Pitch | X Body type | X Color | X Tail type | X X X X X

Solid Block

For 7.62 Pitch
02 to 16 2 to 16 contacts

For 15.24 Pitch
02 to 08 2 to 08 contacts

Pitch
0 7.62/.30"
1 15.24/.60"

Body type
0 W/O Flange
1 Flange with Nut

Color
0 Black
5 Green (RAL 6018/T)
6 Blue (RAL5015/A)
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Tail type
0 Right angle (Two tail type)
1 Vertical (Two tail type)
A Vertical (Three tail type)
B Right angle (Three tail type) (PCB Up)
C Right angle (Three tail type) (PCB Down)

X X X X
00J 0 Standard
Any special item by customer request, please contact sales department.

X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

VC | XX Number of contacts | X Pitch | X Body type | X Color | X Tail type | X X X X X

Solid Block

For 7.62 Pitch
02 to 16 2 to 16 contacts

For 15.24 Pitch
02 to 08 2 to 08 contacts

Pitch
0 7.62/.30"
1 15.24/.60"

Body type
2 With Flange (Only feed-through head with slip-on connection)

Color
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Tail type
1 Vertical


X X X X
00J 0 Standard
Any special item by customer request, please contact sales department.

X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM




Pitch 10.16mm
Close Vertical
Poles 2p~12p
EWxx615000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	




Pitch 10.16mm
With Flange Vertical
Poles 2p~12p
EWxx625000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	




Pitch 10.16mm
Close Right-angle (PCB down)
Poles 2p~12p
EWxx615100J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	




Pitch 10.16mm
Close Right-angle (PCB UP)
Poles 2p~12p
EWxx615200J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	




Pitch 10.16mm
With Flange
Right-angle (PCB down)
Poles 2p~12p
EWxx625100J0G*
Number of poles



Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	



Pitch 10.16mm
With Flange
Right-angle (PCB UP)
Poles 2p~12p
EWxx625200J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	


SCREW PLUGGABLE SYSTEM

PART NUMBERS





SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending






Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending


SCREW PLUGGABLE SYSTEM




Pitch 3.5mm (Right)
Poles 4p
EU04108000J0G*




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending




Pitch 3.5mm (Left)
Poles 4p
EU04108100J0G*




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending




Pitch 3.5mm (Right)
Poles 5p
EU05108000J0G*



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending



Pitch 3.5mm (Left)
Poles 5p
EU05108100J0G*



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

PART NUMBERS

EU | XX Number of contacts | X Pitch | 0 | X Color | X Direction of pin | X X X X X

Solid Block

For 5.0 Pitch
02 to 04 2 to 4 contacts

For 3.5 Pitch
03 to 05 3 to 5 contacts

1	3.5/.138"
7	5.0/.197"

0	Black
5	Green (RAL 6018/T)
6	Blue
8	Grey (RAL 7035/D)
C	Green (RAL 6018/U)

0	Right
1	Left

00J0 Standard

Any special item by customer request, please contact sales department.


G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

NC




Pitch 5.0mm - Right-angle
Poles 2p~24p
NCxx718100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NC




Pitch 5.0 mm - Vertical
Poles 2p~24p
NCxx718000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NC




Pitch 5.0mm - Right-angle
With hook holder
(100% protected against mismating)
Poles 2p~24p
NCxx728100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NC



Pitch 5.0mm - Vertical
With hook holder
(100% protected against mismating)
Poles 2p~24p
NCxx728000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NC



Pitch 7.5mm - Right-angle
Poles 2p~16p
NCxxA18100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

NC




Pitch 7.5mm - Vertical
Poles 2p~16p
NCxxA18000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

NC



Pitch 7.5mm - Right-angle
With hook holder
(100% protected against mismating)
Poles 2p~16p
NCxxA28100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

NC




Pitch 7.5mm - Vertical
With hook holder
(100% protected against mismating)
Poles 2p~16p
NCxxA28000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending


SCREW PLUGGABLE SYSTEM

PART NUMBERS





SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	300V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus


SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus


SCREW PLUGGABLE SYSTEM





Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

KE | XX Number of contacts | X Pitch | X Body Type | X Color | X PCB Mounting | XXXXX

Number of contacts
Solid Block
For 3.5 & 3.81 Pitch
04 to 48 2*2 to 24 contacts
For 7.0 & 7.62 Pitch
04 to 24 2*2 to 12 contacts

Pitch
1 3.5/.138"
2 7.00/.275"
3 3.81/.15"
4 7.62/.30"

Body Type
1 Close
2 With Flange
3 With Latch holder

Color
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey
C Green (RAL 6018/U)

PCB Mounting
0 Vertical
1 Right-angle

XXXXX
00J 0 THR Type
A0J 0 DIP Type
Any special item by customer request, please contact sales department.

X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

KE | XX Number of contacts | X Pitch | X Body Type | X Color | X PCB Mounting | XXXXX

Number of contacts
Solid Block
For 5.0 & 5.08 Pitch
04 to 48 2*2 to 24 contacts
For 10.0 & 10.16 Pitch
04 to 24 2*2 to 12 contacts

Pitch
5 5.08/.20"
6 10.16/.40"
7 5.0/.197"
8 10.0/.394"

Body Type
1 Close
2 With Flange
3 With Latch holder
4 Open (only 5.0 pitch)

Color
THR type
0 Black
Dip type
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey
C Green (RAL 6018/U)

PCB Mounting
THR type
0 Vertical
1 Right-angle
Dip type
2 Vertical
3 Right-angle

XXXXX
00J 0 Standard
Any special item by customer request, please contact sales department.

X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

K3



Pitch 3.5mm
W/O Flange
Right-angle
Poles 3*2p-3*24p
K3xx1151A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	(cULus)Pending

K3



Pitch 3.5mm
With Flange
Right-angle
Poles 3*2p-3*24p
K3xx1251A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	(cULus)Pending

K3



Pitch 3.5mm
With latch
Right-angle
Poles 3*2p-3*24p
K3xx1351A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	(cULus)Pending

K3



Pitch 3.5mm
W/O Flange
Vertical
Poles 3*2p-3*24p
K3xx1150A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	(cULus)Pending

K3



Pitch 3.5mm
With Flange
Vertical
Poles 3*2p-3*24p
K3xx1250A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	(cULus)Pending

K3




Pitch 3.5mm
With Latch
Vertical
Poles 3*2p-3*24p
K3xx1350A0J0G*
Number of poles



Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	(cULus)Pending


SCREW PLUGGABLE SYSTEM


PART NUMBERS




Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	150V
Current rating:	4A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.30KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	150V
Current rating:	4A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.30KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus


SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

SCREW PLUGGABLE SYSTEM

PART NUMBERS




For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

VF




Pitch 3.81mm
Close Vertical
Poles 2*2p~2*24p
VFxx315000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF




Pitch 3.81mm
With Flange
Vertical
Poles 2*2p~2*24p
VFxx325000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF




Pitch 3.81mm
Close Right-angle
Poles 2*2p~2*24p
VFxx315100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF



Pitch 3.81mm
With Flange
Right-angle
Poles 2*2p~2*24p
VFxx325100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF




Pitch 5.0mm
Open Vertical
Poles 2*2p~2*24p
VFxx705000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF



Pitch 5.0mm
Open Right-angle
Poles 2*2p~2*24p
VFxx705100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF




Pitch 5.0mm
Close Vertical
Poles 2*2p~2*24p
VFxx715000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF




Pitch 5.0mm
With Flange
Vertical
Poles 2*2p~2*24p
VFxx725000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

SCREW PLUGGABLE SYSTEM

VF




Pitch 5.0mm
Close Right-angle
Poles 2*2p~2*24p
VFxx715100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF




Pitch 5.0mm
With Flange
Right-angle
Poles 2*2p~2*24p
VFxx725100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF




Pitch 5.08mm
Open Vertical
Poles 2*2p~2*24p
VFxx505000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF




Pitch 5.08mm
Open Right-angle
Poles 2*2p~2*24p
VFxx505100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF




Pitch 5.08mm
Close Vertical
Poles 2*2p~2*24p
VFxx515000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF




Pitch 5.08mm
With Flange
Vertical
Poles 2*2p~2*24p
VFxx525000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF




Pitch 5.08mm
Close Right-angle
Poles 2*2p~2*24p
VFxx515100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VF



Pitch 5.08mm
With Flange
Right-angle
Poles 2*2p~2*24p
VFxx525100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM

PART NUMBERS





SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM

PART NUMBERS





SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus


SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SCREW PLUGGABLE SYSTEM

PART NUMBERS





SCREW PLUGGABLE SYSTEM







Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	







Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	







Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	







Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	





Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	






Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

PART NUMBERS




SCREW PLUGGABLE SYSTEM

V5



Pitch 3.81mm
Bottom cover fixed type
Poles 2p~24p
V5xx315000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	14-28
Stranded wire(AWG):	14-28
Torque(Lb-In) :	2.2
Screw:	M2
Wire strip length:	6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V5



Pitch 3.81mm - With Flange
Bottom cover fixed type
Poles 2p~24p
V5xx315100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	14-28
Stranded wire(AWG):	14-28
Torque(Lb-In) :	2.2
Screw:	M2
Wire strip length:	6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V5



Pitch 3.81mm
Dinrail holder A type
Poles 3p~24p
V5xx315200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	14-28
Stranded wire(AWG):	14-28
Torque(Lb-In) :	2.2
Screw:	M2
Wire strip length:	6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V5



Pitch 3.81mm - With Flange
Dinrail holder A type
Poles 3p~24p
V5xx315300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	14-28
Stranded wire(AWG):	14-28
Torque(Lb-In) :	2.2
Screw:	M2
Wire strip length:	6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V5



Pitch 5.08mm
Bottom cover fixed type
Poles 2p~24p
V5xx515000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.2
Screw:	M3
Wire strip length:	6- 7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V5



Pitch 5.08mm - With Flange
Bottom cover fixed type
Poles 2p~24p
V5xx515100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.2
Screw:	M3
Wire strip length:	6- 7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V5



Pitch 5.08mm
Dinrail holder A type
Poles 2p~24p
V5xx515200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.2
Screw:	M3
Wire strip length:	6- 7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V5



Pitch 5.08mm - With Flange
Dinrail holder A type
Poles 2p~24p
V5xx515300J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.2
Screw:	M3
Wire strip length:	6- 7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

V5



Pitch 5.08mm
Dinrail holder B type
Poles 2p~24p
V5xx515400J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.2
Screw:	M3
Wire strip length:	6- 7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V5



Pitch 5.08mm - With Flange
Dinrail holder B type
Poles 2p~24p
V5xx515500J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.2
Screw:	M3
Wire strip length:	6- 7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

V5 | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body type | X X X X | X

Number of contacts
Solid Block

For 3.81 & 5.08 Pitch
02 to 24 2 to 24 contacts

For 7.62 & 10.16 Pitch
02 to 12 2 to 12 contacts

Pitch
3 3.81/.15"
5 5.08/.20"
4 7.62/.30"
6 10.16/.40"

Screw & Clamp
0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Body type
0 W/O Flange (Bottom cover fixed type)
1 With Flange (Bottom cover fixed type)
2 W/O Flange (Dinrail holder A type)
3 With Flange (Dinrail holder A type)
4 W/O Flange (Dinrail holder B type)
5 With Flange (Dinrail holder B type)

X X X X
00J 0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.


X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

SCREW PLUGGABLE SYSTEM

V9



Pitch 5.08mm
Bottom cover fixed type
Poles 2p~24p
V9xx515000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.2
Screw:	M3
Wire strip length:	6- 7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V9



Pitch 5.08mm - With Flange
Bottom cover fixed type
Poles 2p~24p
V9xx515100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.2
Screw:	M3
Wire strip length:	6- 7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V9



Pitch 5.08mm
Dinrail holder A type
Poles 2p~24p
V9xx515200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.2
Screw:	M3
Wire strip length:	6- 7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V9



Pitch 5.08mm - With Flange
Dinrail holder A type
Poles 2p~24p
V9xx515300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.2
Screw:	M3
Wire strip length:	6- 7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V9



Pitch 5.08mm
Dinrail holder B type
Poles 2p~24p
V9xx515400J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5.2
Screw:	M3
Wire strip length:	6- 7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V9



Pitch 5.08mm - With Flange
Dinrail holder B type
Poles 2p~24p
V9xx515500J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-30
Stranded wire(AWG):	12-30
Torque(Lb-In) :	5
Screw:	M3
Wire strip length:	6- 7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

PART NUMBERS




SCREW PLUGGABLE SYSTEM

KI



Pitch 3.81mm
Poles 2p~24p
KIxx305000J0G*
Match with AO 3.81 type PIN
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	

KI



Pitch 3.81mm - With Flange
Poles 2p~24p
KIxx305200J0G*
Match with AO 3.81 type PIN
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	

KI



Pitch 3.81mm
with high profile
Poles 2p~24p
KIxx305100J0G*
Match with AO 3.81 type PIN
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	

KI



Pitch 3.81mm - With Flange
with high profile
Poles 2p~24p
KIxx305300J0G*
Match with AO3.81 type PIN
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.32KV
Safety Approval:	

KI



Pitch 5.08mm
Poles 2p~24p
KIxx505000J0G*
Match with AO 5.08 type PIN
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

KI




Pitch 5.08mm - With Flange
Poles 2p~24p
KIxx505200J0G*
Match with AO 5.08 type PIN
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

KI



Pitch 5.08mm
with high profile
Poles 2p~24p
KIxx505100J0G*
Match with AO 5.08 type PIN
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

KI



Pitch 5.08mm - With Flange
with high profile
Poles 2p~24p
KIxx505300J0G*
Match with AO 5.08 type PIN
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

PART NUMBERS




SCREW PLUGGABLE SYSTEM

KV



Pitch 5.08mm
With Hook & Low profile
Poles: 2p~24p
KVxx505000J0G*
Match with AR 5.08 type PIN
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

KV



Pitch 5.08mm
Flange with screw & Low profile
Poles: 2p~24p
KVxx505100J0G*
Match with AR 5.08 type PIN
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

KV



Pitch 5.08mm
Flange with nut & Low profile
Poles: 2p~24p
KVxx505200J0G*
Match with AR 5.08 type PIN
Number of poles




Electrical:	cULs
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

KV



Pitch 5.08mm
With Hook & High profile
Poles: 2p~24p
KVxx505300J0G*
Match with AR 5.08 type PIN
Number of poles




Electrical:	cULs
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

KV



Pitch 5.08mm
Flange with screw & High profile
Poles: 2p~24p
KVxx505400J0G*
Match with AR 5.08 type PIN
Number of poles




Electrical:	cULs
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

KV



Pitch 5.08mm
Flange with nut & High profile
Poles: 2p~24p
KVxx505500J0G*
Match with AR 5.08 type PIN
Number of poles




Electrical:	cULs
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks





Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

PART NUMBERS



SCREW PLUGGABLE SYSTEM

AO	AO	AO	AR
			
Match with KI 3.81 AO00000000J0G* With wire range (0.5-1.0mm^2)	Match with KI 5.08 AO00001000J0G* With wire range (0.5-1.0mm^2)	Match with KI 5.08 AO00002000J0G* With wire range (1.5-2.5mm^2)	Match with KV 5.08 AR00000000J0G* With wire range (1.5-2.5mm^2)
			
Used Wire range :0.5~1.0mm^2	Used Wire range :0.5~1.0mm^2	Used Wire range :1.5~2.5mm^2	Used Wire range :1.5~2.5mm^2
Stranded wire(AWG): 18-20	Stranded wire(AWG):18-20	Stranded wire(AWG):14-16	Stranded wire(AWG):14-20
Currents of 6A to 8A	Currents of up to 10A	Currents of up to 12A	Currents of up to 12A
Wire strip length:4.0mm	Wire strip length: 4.0mm	Wire strip length: 4.0mm	Wire strip length: 4.0mm
Core diameter including insulation:0.18 mm ...0.25 mm	Core diameter including insulation:1.8 mm ... 2.1 mm	Core diameter including insulation:2.11 mm ... 3.1 mm	Core diameter including insulation:2.11 mm ... 3.1 mm

PART NUMBERS

AO

00	0	0	X	0	X X X X	X
			Contact			

- 0 wire range (0.5-1.0 mm^2) (pitch3.81)
- 1 wire range (0.5-1.0 mm^2) (pitch5.08)
- 2 wire range (1.5-2.5 mm^2) (pitch5.08)

- 00J 0 Standard
- Any special item by customer request, please contact sales department.

- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

AR

00	0	0	X	0	X X X X	X
			Contact			

- 0 wire range (1.5-2.5 mm^2) (pitch5.08)

- 00J 0 Standard
- Any special item by customer request, please contact sales department.

- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

V8



Pitch 3.81mm
Poles 2p~24p
V8xx315000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	14-30
Stranded wire(AWG):	14-30
Torque(Lb-In) :	2
Screw:	M2
Wire strip length:	7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V8



Pitch 3.81mm
Flange with Nut - With Flange
Poles 2p~24p
V8xx315100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	14-30
Stranded wire(AWG):	14-30
Torque(Lb-In) :	2
Screw:	M2
Wire strip length:	7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V8



Pitch 3.81mm - With Flange
Flange with Screw
Poles 2p~24p
V8xx315200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	14-30
Stranded wire(AWG):	14-30
Torque(Lb-In) :	2
Screw:	M2
Wire strip length:	7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V8



Pitch 5.08mm
Poles 2p~24p
V8xx515000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	4.0
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V8



Pitch 5.08mm
Flange with Nut
Poles 2p~24p
V8xx515100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	4.0
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V8



Pitch 5.08mm - With Flange
Flange with screw
Poles 2p~24p
V8xx515200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	4.0
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V8



Pitch 7.62mm
Poles 2p~16p
V8xx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	4.0
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

V8



Pitch 7.62mm
Flange with Nut
Poles 2p~16p
V8xx015100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	4.0
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus


SCREW PLUGGABLE SYSTEM

V8



Pitch 7.62mm
Flange with Screw
Poles 2p~16p
V8xx015200J0G*
Number of poles





Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	4.0
Screw:	M3
Wire strip length:	7-8mm
Withstanding Voltage:	1.6KV
Safety Approval:	

PART NUMBERS

V8 | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body Type | X X X X | X

Number of contacts
Solid Block

For 3.81 & 5.08 Pitch
02 to 24 2 to 24 contacts

For 7.62 Pitch
02 to 16 2 to 16 contacts

Pitch
3 3.81/.15"
5 5.08/.20"
0 7.62/.30"

Screw & Clamp
0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Body Type
0 W/O Flange
1 Flange with Nut
2 Flange with screw

X X X X
00J0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

KK



Pitch 10.16mm
Poles 2P~12P
KKxx615000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire:	6-20AWG/0.5-16mm²	
Stranded wire:	6-20AWG/0.5-16mm²	
Torque :	18Lb-In/1.2N.m	
Screw:	M4.5	
Wire strip length:	13 - 14mm	
Withstanding Voltage:	1.6KV	8KV
Safety Approval:		

KK



Pitch 10.16mm - Flange with screw
Poles 2P~12P
KKxx615100J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire:	6-20AWG/0.5-16mm²	
Stranded wire:	6-20AWG/0.5-16mm²	
Torque :	18Lb-In/1.2N.m	
Screw:	M4.5	
Wire strip length:	13 - 14mm	
Withstanding Voltage:	1.6KV	8KV
Safety Approval:		

KK



Pitch 10.16mm - Flange with Screw (with handle)
Poles 3P/4P
KKxx615200J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire:	6-20AWG/0.5-16mm²	
Stranded wire:	6-20AWG/0.5-16mm²	
Torque :	18Lb-In/1.2N.m	
Screw:	M4.5	
Wire strip length:	13 - 14mm	
Withstanding Voltage:	1.6KV	8KV
Safety Approval:		

KK



Pitch 10.16mm - Flange with Nut
Poles 2~12P
KKxx615300J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire:	6-20AWG/0.5-16mm²	
Stranded wire:	6-20AWG/0.5-16mm²	
Torque :	18Lb-In/1.2N.m	
Screw:	M4.5	
Wire strip length:	13 - 14mm	
Withstanding Voltage:	1.6KV	8KV
Safety Approval:		

KK



Pitch 10.16mm - Flange with Nut (with handle)
Poles 3P/4P
KKxx615400J0G*
Number of poles



Electrical:	cULus	IEC
Voltage rating:	300V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire:	6-20AWG/0.5-16mm²	
Stranded wire:	6-20AWG/0.5-16mm²	
Torque :	18Lb-In/1.2N.m	
Screw:	M4.5	
Wire strip length:	13 - 14mm	
Withstanding Voltage:	1.6KV	8KV
Safety Approval:		

PART NUMBERS

KK | XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body type | X X X X X

XX — Number of contacts

Solid Block

For 10.16 Pitch
02 to 12 2 to 12 contacts

For 20.32 Pitch
02 to 06 2 to 06 contacts

X — Pitch

6 10.16/.40"
7 20.32/.80"

X — Screw & Clamp

0 "-/+"Combination type W/Brass Machined Clamp

1 "-"Slot type W/Brass Machined Clamp

X — Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

X — Body type

0 W/O Flange
1 Flange with screw (W/O handle)
2 Flange with screw (With handle) (only 3p & 4p)
3 Flange with Nut (W/O handle)
4 Flange with Nut (With handle) (only 3p & 4p)

X X X X — Plating

00J0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X — RoHS

G RoHS compliant (lead<4%) In copper Alloy


H RoHS compliant (lead<1000ppm) In copper Alloy

SCREW PLUGGABLE SYSTEM

KF



Pitch 3.5mm
Poles 2p~24p
KFxx105000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
With P.C.B thickness :	1.6±0.2mm
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

KF



Pitch 5.0mm
Poles 2p~24p
KFxx705000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
With P.C.B thickness :	1.6±0.2mm
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

KF



Pitch 7.5mm
Poles 2p~16p
KFxxA050000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
With P.C.B thickness:	1.6±0.2mm
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	

VH



Pitch 5.08mm
Poles 2p~24p
VHxx515000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	

VH



Pitch 5.08mm - With Flange
Poles 2p~24p
VHxx515200J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	4.3
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	

PART NUMBERS

KF

XX	X	0	X	0	X X X X	X
Number of contacts	Pitch		Color			

Solid Block

For 3.5 & 5.0 Pitch
02 to 24 2 to 24 contacts

For 7.5 Pitch
02 to 16 2 to 16 contacts

1 3.5/.138"
7 5.0/.197"
A 7.5/.295"

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

00J 0 Standard

Any special item by customer request, please contact sales department.

G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

VH

XX	X	X	X	X	X X X X	X
Number of contacts	Pitch	Screw & Clamp	Color	Body Type		

Solid Block

For 5.08 Pitch
02 to 24 2 to 24 contacts

For 10.16 Pitch
02 to 12 2 to 12 contacts

5 5.08/.20"
6 10.16/.40"

0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

0 W/O Flange
2 With Flange

00J 0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

KT



Pitch 7.62mm
Poles 2p~16p
KTxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	600V
Current rating:	41A
Wire range:	
Solid wire(AWG):	8-24
Stranded wire(AWG):	8-24
Torque(Lb-In) :	9
Screw:	M3.5
Wire strip length:	10-11mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus

KT



Pitch 7.62mm
With Flange screw type
Poles 2p~16p
KTxx015400J0G*
Number of poles




Electrical:	cULus
Voltage rating:	600V
Current rating:	41A
Wire range:	
Solid wire(AWG):	8-24
Stranded wire(AWG):	8-24
Torque(Lb-In) :	9
Screw:	M3.5
Wire strip length:	10-11mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus

KT




Pitch 7.62mm
With Flange screw type & With Handle
Poles 3p~4p
KTxx015500J0G*
Number of poles




Electrical:	cULus
Voltage rating:	600V
Current rating:	41A
Wire range:	
Solid wire(AWG):	8-24
Stranded wire(AWG):	8-24
Torque(Lb-In) :	9
Screw:	M3.5
Wire strip length:	10-11mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus

KT



Pitch 7.62mm
With Flange nut type
Poles 2p~16p
KTxx015200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	600V
Current rating:	41A
Wire range:	
Solid wire(AWG):	8-24
Stranded wire(AWG):	8-24
Torque(Lb-In) :	9
Screw:	M3.5
Wire strip length:	10-11mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus

KT




Pitch 7.62mm
With Flange nut type & With Handle
Poles 3p~4p
KTxx015300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	600V
Current rating:	41A
Wire range:	
Solid wire(AWG):	8-24
Stranded wire(AWG):	8-24
Torque(Lb-In) :	9
Screw:	M3.5
Wire strip length:	10-11mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus

KS



Pitch 7.62mm - Vertical
Poles 2P/16P
KSxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	41A
Wire range:	
Solid wire:	
Stranded wire:	
Torque :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

KS




Pitch 7.62mm - Vertical
With Flange
Poles 2p~16p
KSxx025000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	41A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
With P.C.B thickness :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

KS



Pitch 7.62mm Right-angle
PCB Down
Poles 2p~16p
KSxx015100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	41A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
With P.C.B thickness :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

SCREW PLUGGABLE SYSTEM

KS



Pitch 7.62mm Right-angle
PCB Up
Poles 2p~16p
KSxx015200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	41A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
With P.C.B thickness:	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

KS



Pitch 7.62mm Right-angle
With Flange PCB Down
Poles 2p~16p
KSxx025100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	41A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

KS



Pitch 7.62mm Right-angle
With Flange PCB Up
Poles 2p~16p
KSxx025200J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	41A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

KT

XX Number of contacts	X Pitch	X Screw & Clamp	X Color	X Body Type	XXXXX
Solid Block For 7.62 Pitch 02 to 16 2 to 16 contacts For 15.24 Pitch 02 to 08 2 to 8 contacts	0 7.62/.30" 1 15.24/.60"	0 "-/+"Combination type W/Brass Machined Clamp 1 "-"Slot type W/Brass Machined Clamp 2 "*"Slot type W/Brass Machined Clamp	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 W/O Flange 2 With Flange nut 3 With Flange nut & With handle (only 3P & 4P) 4 With Flange screw 5 With Flange screw & With handle (only 3P & 4P)	00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

KS


XX Number of contacts	X Pitch	X Body Type	X Color	X Tail Type	XXXXX
Solid Block For 7.62 Pitch 02 to 16 2 to 16 contacts For 15.24 Pitch 02 to 08 2 to 8 contacts	0 7.62/.30" 1 15.24/.60"	1 W/O Flange 2 W/Flange	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 Vertical 1 Right angle (PCB down) 2 Right angle (PCB Up)	00J 0 Standard (Steel screw plating Cr^{3+}) Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

VZ




Pitch 3.81mm
Poles 2p~24p
VZxx305000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

VZ



Pitch 5.08mm
Poles 2p~24p
VZxx505000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

VZ | XX Number of contacts | X Pitch | 0 | X Color | 0 | X X X X | X

Solid Block

For 3.81 & 5.08 Pitch
02 to 24 2 to 24 contacts

For 7.62 & 10.16 Pitch
02 to 12 2 to 12 contacts

3	3.81/.15"
4	7.62/.30"
5	5.08/.20"
6	10.16/.40"


0	Black
5	Green (RAL 6018/T)
6	Blue
8	Grey (RAL 7035/D)
C	Green (RAL 6018/U)


00J 0 Standard

Any special item by customer request, please contact sales department.


G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy


SCREW PLUGGABLE SYSTEM







Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

VX



Pitch 3.5mm
Close Vertical
Poles 2*2p-2*24p
VXxx1100B0J0G* (THR Tape Reel)
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

VX



Pitch 3.5mm
Close Right-angle
Poles 2*2p-2*24p
VXxx1101B0J0G* (THR Tape Reel)
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

VX



Pitch 3.5mm
With Flange
Vertical
Poles 2*2p-2*24p
VXxx1200B0J0G* (THR Tape Reel)
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

VX



Pitch 3.5mm
With Flange
Right-angle
Poles 2*2p-2*24p
VXxx1201B0J0G* (THR Tape Reel)
Number of poles



Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

PART NUMBERS

VX | XX Number of contacts | X Pitch | X Body Type | X Color | X P.C.B Mounting | X X X X X

XX Number of contacts

Solid Block

For 3.5 Pitch
04 to 48 2*2 to 24 contacts

For 7.0 Pitch
04 to 24 2*2 to 12 contacts

X Pitch

1 3.5/.138"
2 7.0/.276"

X Body Type

0 Open
1 Close
2 With Flange

X Color

THR type
0 Black

DIP type
0 Black
3 Orange
5 Green
8 Grey

X P.C.B Mounting

0 Vertical
1 Right angle

X X X X

00J0 DIP Type
A0J0 THR Type
B0J0 THR Tape reel

Any special item by customer request, please contact sales department.

X


G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

SCREW PLUGGABLE SYSTEM

KU



Pitch 15.0mm
Vertical
Poles 2p~10p
KUxxC05000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	115A	125A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	2.2KV	8KV
Safety Approval:	cULus	

KU




Pitch 15.0mm
Right-angle
Poles 2P~10P
KUxxC05100J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	115A	125A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	2.2KV	8KV
Safety Approval:	cULus	

KU



Pitch 15.0mm
Vertical
With Flange
Poles 2p~10p
KUxxC15000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	115A	125A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	2.2KV	8KV
Safety Approval:	cULus	

KU




Pitch15.0mm
Right-angle
With Flange
Poles 2P~10P
KUxxC15100J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	115A	125A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	2.2KV	8KV
Safety Approval:	cULus	

KU




Pitch 15.0mm
Vertical With Flange and shield
feed-through on the inside of the device
Poles 4P
KU04C25000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	115A	125A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	2.2KV	8KV
Safety Approval:	cULus	

KU



Pitch 15.0mm
Right-angle With Flange and shield
feed-through on the inside of the device
Poles 4p
KU04C25100J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	115A	125A
Wire range:		
Solid wire(AWG):		
Stranded wire(AWG):		
Torque(Lb-In) :		
Screw:		
Wire strip length:		
Withstanding Voltage:	2.2KV	8KV
Safety Approval:	cULus	

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

PART NUMBERS




SCREW PLUGGABLE SYSTEM

KX



Pitch 15.0mm
Poles 2p-10p
KXxxC15000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	115A	125A
Wire range:		0.5-35mm^2
Solid wire(AWG):	2-20	
Stranded wire(AWG):	2-20	
Torque(Lb-In) :	36.5Lb-In	2.0N.m
Screw:	M5	
Wire strip length:	19-20mm	
Withstanding Voltage:	2.2KV	8KV
Safety Approval:	cULus	

KX



Pitch 15.0mm With Flange
Poles 2p-10p
KXxxC15100J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	115A	125A
Wire range:		0.5-35mm^2
Solid wire(AWG):	2-20	
Stranded wire(AWG):	2-20	
Torque(Lb-In) :	36.5Lb-In	2.0N.m
Screw:	M5	
Wire strip length:	19-20mm	
Withstanding Voltage:	2.2KV	8KV
Safety Approval:	cULus	

KX



Pitch 15.0mm
With Flange and handle
Poles 4p
KX04C15200J0G*
Number of poles



Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	115A	125A
Wire range:		0.5-35mm^2
Solid wire(AWG):	2-20	
Stranded wire(AWG):	2-20	
Torque(Lb-In) :	36.5Lb-In	2.0N.m
Screw:	M5	
Wire strip length:	19-20mm	
Withstanding Voltage:	2.2KV	8KV
Safety Approval:	cULus	

PART NUMBERS

KX — XX Number of contacts | X Pitch | X Screw & Clamp | X Color | X Body type | XXXX | X

XX Number of contacts

Solid Block

For 15.0 Pitch
02 to 10 2 to 10 contacts

X Pitch

C 15.0/.591"

X Screw & Clamp

1 "-"Slot type W/Steel Stamping Clamp

2 "*"Combination universal W/Steel Stamping Clamp

X Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

X Body type

0 W/O Flange
1 With Flange
2 With Flange (with handle) (only 4p)

XXXX

00J0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X

G RoHS compliant (lead<4%) In copper Alloy


H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

K4




Pitch 5.08mm (Monting fixed type)
Poles 3p-24p
K4xx53800J0G*




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	14-24
Torque(Lb-In) :	4.5
Screw:	M3.0
Wire strip length:	6-7
Safety Approval:	(cULus)pending

K4



Pitch 5.08mm (Dip solder type)
Poles 3p-24p
K4xx53820J0G*




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	14-24
Torque(Lb-In) :	4.5
Screw:	M3.0
Wire strip length:	6-7
Safety Approval:	(cULus)pending

EY



Pitch 5.08mm
Hook on entry side
Poles 2p~24p
EYxx510A00J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	20A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	4.0
Screw:	M3
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

K4

XX	X	X	X	X	X X X X	X
Number of contacts	Pitch	Screw & Clamp	Color	Body Type		

Number of contacts
Solid Block
03 to 24 3 to 24 contacts

Pitch
5 5.08/.20"

Screw & Clamp
2 "-/+"Combination type W/Zinc Alloy Clamp
3 "-"Slot type W/Zinc Alloy Clamp

Color
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)

Body Type
0 Mounting fixed type (W/O dip solder)
2 Dip solder type (Open stackable type)

XXXX
00J0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

EY

XX	X	X	X	X	X X X X	X
Number of contacts	Pitch	Screw & Clamp	Color	Body Type		

Number of contacts
Solid Block
For 5.08 Pitch
02 to 24 2 to 24 contacts
For 10.16 Pitch
02 to 12 2 to 12 contacts

Pitch
5 5.08/.20"
6 10.16/.40"

Screw & Clamp
0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Body Type
A Hook on Entry Side
B Hook on Back Side

XXXX
00J0 Standard (Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.


X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

SCREW PLUGGABLE SYSTEM

K5



Pitch 5.08mm
W/O Flange
Poles 2p-24p
K5xx515000J0G*




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	14-24
Torque(Lb-In) :	4.5
Screw:	M3.0
Wire strip length:	6-7
Safety Approval:	(cULus)pending

K5



Pitch 5.08mm
With Flange
Poles 2p-24p
K5xx515100J0G*




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	4.3
Screw:	
Wire strip length:	6-7
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

K5




Pitch 5.08mm
With Latch
Poles 2p-24p
K5xx515200J0G*



Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	12-24
Stranded wire(AWG):	12-24
Torque(Lb-In) :	4.3
Screw:	
Wire strip length:	6-7
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

PART NUMBERS



For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SCREW PLUGGABLE SYSTEM

KJ




Pitch 10.16mm
Poles 2P~12P
KJxx615000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	55A	76A
Wire range:		
Solid wire(AWG):	6-20	0.5-16mm²
Stranded wire(AWG):	6-20	0.5-16mm²
Torque(Lb-In) :	18Lb-In	1.2N.m
Screw:	M4.5	
Wire strip length:	13- 14mm	
Withstanding Voltage:	2.2KV	8KV
Safety Approval:	cULus	

FW



Pitch 5.0 mm
With Cover SMT type
Poles 2p~12p
FWxx000100J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	
Torque(Lb-In) :	
Screw:	
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

KJ

XX	X	X	X	0	X X X X	X
Number of contacts	Pitch	Screw & Clamp	Color			

Number of contacts

Solid Block

For 10.16 Pitch
02 to 12 2 to 12 contacts

For 20.32 Pitch
02 to 06 2 to 6 contacts

Pitch

6 10.16/.40"
7 20.32/.80"

Screw & Clamp

0 "-/+"Combination type W/Brass Machined Clamp
1 "-"Slot type W/Brass Machined Clamp

Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

X X X X

00J0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X

G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

FW

XX	X	X	X	X	X X X X	X
Number of contacts	Pitch	Pin length	Plated	Package		

Number of contacts

Solid Block

For 5.0 Pitch
02 to 12 2 to 12 contacts

For 10.0 Pitch
02 to 06 2 to 6 contacts

Pitch

0 5.0/.197"
1 10.0/.394"

Pin length

0 10.15mm & 16.3mm
1 10.4mm
2 15.5mm
3 14.2mm
4 16.0mm
5 13.0mm

Plated

0 Tin
1 No Plated
2 G/F

Package

1 T&R package
2 T/B package

X X X X

00J0 Standard

Any special item by customer request, please contact sales department.

X

G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

"*" means FCI Standard item, any other non-standard item, please consult FCI for up-to-date information.

TMBPLUGABSYS0214A4


Notes


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

SPRING CLAMP PLUGGABLE SYSTEM

OVERVIEW

For spring clamp pluggable system, the plug uses a spring clamp to contact.






Spring clamp pluggable systems have a quick assembly time. They function like clamps, where the wire is inserted into the terminal block and snapped into place. Spring clamp pluggable systems are used in common appliances because they are easy to set up.

SPRING CLAMP PLUGGABLE SYSTEM

HI



Pitch 5.0mm
With Hook and Pillar
Poles 2p~24p
HIxx005000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HI



Pitch 5.0mm
With Latch
Poles 2p~24p
HIxx005300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HI



Pitch 5.0mm
With Flange
Poles 2p~24p
HIxx005200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HI



Pitch 5.0mm
With Hook, 100% protected against mismating
Poles 2p~24p
HIxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

HI



Pitch 5.0mm
With Latch,100% protected against mismating
Poles 2p~24p
HIxx015300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

HI




Pitch 5.0mm
With Flange,100% protected against mismating
Poles 2p~24p
HIxx015200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

HI



Pitch 7.5mm
With Hook and Pillar
Poles 2p~16p
HIxx205000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HI



Pitch 7.5mm
With Latch
Poles 2p~16p
HIxx205300J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP PLUGGABLE SYSTEM

HI



Pitch 7.5mm
With Flange
Poles 2p~16p
HIxx205200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HI



Pitch 7.5mm
With Hook,100% protected against mismating
Poles 2~16p
HIxx215000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

HI



Pitch 7.5mm
With Flange,100% protected against mismating
Poles 2~16p
HIxx215200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

HI




Pitch 7.5mm
With Latch,100% protected against mismating
Poles 2~16p
HIxx215300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

HI



Pitch 7.62mm
With Hook and Pillar
Poles 2p~16p
HIxx305000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HI



Pitch 7.62mm
With Latch
Poles 2p~16p
HIxx305300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HI



Pitch 7.62mm
With Flange
Poles 2p~16p
HIxx305200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HN




Pitch 5.08mm
Poles 2p~24p
HNxx505000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	14-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

SPRING CLAMP PLUGGABLE SYSTEM

PART NUMBERS




For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP PLUGGABLE SYSTEM

HN



Pitch 5.08mm
With Flange
Poles 2p~24p
HNxx505200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	14-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HP



Pitch 3.81mm
Poles 2p~24p
HPxx305000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	5A
Wire range:	
Solid wire(AWG):	20-22
Stranded wire(AWG):	20-22
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HP



Pitch 3.81mm
With Flange
Poles 2p~24p
HPxx305200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	5A
Wire range:	
Solid wire(AWG):	20-22
Stranded wire(AWG):	20-22
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HP




Pitch 5.08mm
Poles 2p~24p
HPxx505000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	7A
Wire range:	
Solid wire(AWG):	18-22
Stranded wire(AWG):	18-22
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HP



Pitch 5.08mm
With Flange
Poles 2p~24p
HPxx505200J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	7A
Wire range:	
Solid wire(AWG):	18-22
Stranded wire(AWG):	18-22
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

SPRING CLAMP PLUGGABLE SYSTEM

PART NUMBERS

HN | X X Number of contacts | X Pitch | 0 | X Color | X Body type | X X X X | X


- Number of contacts: Solid Block; 02 to 24 — 2 to 24 contacts
- Pitch: 1 — 3.5/.138"; 5 — 5.08/.20"
- Color: 0 — Black; 5 — Green (RAL 6018/T); 6 — Blue; 8 — Grey (RAL 7035/D)
- Body type: 0 — W/O Flange; 2 — With Flange
- X X X X: 00J 0 — Standard. Any special item by customer request, please contact sales department.
- X: G — RoHS compliant (lead<4%) In copper Alloy; H — RoHS compliant (lead<1000ppm) In copper Alloy

HP | X X Number of contacts | X Pitch | 0 | X Color | X Body type | X X X X | X


- Number of contacts: Solid Block; 02 to 24 — 2 to 24 contacts
- Pitch: 3 — 3.81/.15"; 5 — 5.08/.20"
- Color: 0 — Black; 5 — Green (RAL 6018/T); 6 — Blue; 8 — Grey (RAL 7035/D)
- Body type: 0 — W/O Flange; 2 — With Flange
- X X X X: 00J 0 — Standard. Any special item by customer request, please contact sales department.
- X: G — RoHS compliant (lead<4%) In copper Alloy; H — RoHS compliant (lead<1000ppm) In copper Alloy

SPRING CLAMP PLUGGABLE SYSTEM

HW




Pitch 2.5mm
Poles 2p~24p
HWxxB05000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	4A
Wire range:	
Solid wire(AWG):	20-28
Stranded wire(AWG):	20-28
Wire strip length:	7~8mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

HW




Pitch 3.5mm
Poles 2p~24p
HWxx105000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW




Pitch 3.5mm
With Flange
Poles 2p~24p
HWxx105200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW




Pitch 3.81mm
Poles 2p~24p
HWxx305000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW




Pitch 3.81mm
With Flange
Poles 2p~24p
HWxx305200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW



Pitch 5.0mm
Contact on down side
Poles 2p~24p
HWxx705000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW



Pitch 5.0mm - With Flange
Contact on down side
Poles 2p~24p
HWxx705200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW



Pitch 5.0mm
Contact on up side
Poles 2p~24p
HWxx705100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

SPRING CLAMP PLUGGABLE SYSTEM

HW




Pitch 5.0mm - With Flange
Contact on up side
Poles 2p~24p
HWxx705300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW



Pitch 5.08mm
Contact on down side
Poles 2p~24p
HWxx505000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW



Pitch 5.08mm - With Flange
Contact on down side
Poles 2p~24p
HWxx505200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW



Pitch 5.08mm
Contact on up side
Poles 2p~24p
HWxx505100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW



Pitch 5.08mm - With Flange
Contact on up side
Poles 2p~24p
HWxx505300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW



Pitch 5.08mm
Contact in the middle
Poles 2p~24p
HWxx505400J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW



Pitch 5.08mm - With Flange
Contact in the middle
Poles 2p~24p
HWxx505500J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW



Pitch 7.5mm
Contact on down side
Poles 2p~16p
HWxxA05000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP PLUGGABLE SYSTEM

HW




Pitch 7.5mm - With Flange
Contact on down side
Poles 2p~16p
HWxxA05200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW



Pitch 7.62mm
Contact on down side
Poles 2p~16p
HWxx005000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HW



Pitch 7.62mm - With Flange
Contact on down side
Poles 2p~16p
HWxx005200J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

HW | XX Number of contacts | X Pitch | 0 | X Color | X Body type | XXXXX

XX Number of contacts

Solid Block

For 2.5 & 3.5 & 3.81 Pitch
02 to 24 2 to 24 contacts

For 7.5 & 7.62 Pitch
02 to 16 2 to 16 contacts

X Pitch

B 2.5/.098"
1 3.5/.138"
3 3.81/.15"
A 7.5/.295"
0 7.62/.30"

X Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)

X Body type

0 W/O Flange
2 With Flange
(Only pitch 3.5/3.81/7.5/7.62)

XXXXX

00J 0 Standard

Any special item by customer request, please contact sales department.

X

G RoHS compliant (lead<4%) In copper Alloy

H RoHS compliant (lead<1000ppm) In copper Alloy

HW | XX Number of contacts | X Pitch | 0 | X Color | X Body type | XXXXX

XX Number of contacts

Solid Block

02 to 24 2 to 24 contacts

X Pitch

5 5.08/.20"
7 5.0/.197"

X Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)

X Body type

0 W/O Flange
Contact on down side
1 W/O Flange
Contact on up side
2 With Flange
Contact on down side
3 With Flange
Contact on up side
4 W/O Flange
Contact in the middle
(Only pitch 5.08)
5 With Flange
Contact in the middle
(Only pitch 5.08)

XXXXX

00J 0 Standard

Any special item by customer request, please contact sales department.

X

G RoHS compliant (lead<4%) In copper Alloy


H RoHS compliant (lead<1000ppm) In copper Alloy

SPRING CLAMP PLUGGABLE SYSTEM

H4




Pitch 5.0mm
Hook on entry side
Poles 2p~24p
H4xx705A00J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H4



Pitch 5.0mm - With Flange
Hook on entry side
Poles 2p~24p
H4xx705C00J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H4



Pitch 5.0mm
Hook on back side
Poles 2p~24p
H4xx705B00J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H4



Pitch 5.0mm - With Flange
Hook on back side
Poles 2p~24p
H4xx705D00J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H4




Pitch 5.08mm
Hook on entry side
Poles 2p~24p
H4xx505A00J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H4



Pitch 5.08mm - With Flange
Hook on entry side
Poles 2p~24p
H4xx505C00J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H4



Pitch 5.08mm
Hook on back side
Poles 2p~24p
H4xx505B00J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H4



Pitch 5.08mm - With Flange
Hook on back side
Poles 2p~24p
H4xx505D00J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP PLUGGABLE SYSTEM

PART NUMBERS




SPRING CLAMP PLUGGABLE SYSTEM

H5



Pitch 3.5mm
Poles 2p~24p
H5xx105000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 3.5mm
Flange with Nut
Poles 2p~24p
H5xx105200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 3.5mm
Flange with Screw
Poles 2p~24p
H5xx105100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 3.81mm
Poles 2p~24p
H5xx305000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 3.81mm
Flange with Nut
Poles 2p~24p
H5xx305200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 3.81mm
Flange with Screw
Poles 2p~24p
H5xx305100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	4A
Wire range:	
Solid wire(AWG):	16-28
Stranded wire(AWG):	16-28
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 5.0mm
Poles 2p~24p
H5xx705000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 5.0mm
Flange with Nut
Poles 2p~24p
H5xx705200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP PLUGGABLE SYSTEM

H5



Pitch 5.0mm
Flange with Screw
Poles 2p~24p
H5xx705100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 5.08mm
Poles 2p~24p
H5xx505000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 5.08mm
Flange with Nut
Poles 2p~24p
H5xx505200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 5.08mm
Flange with Screw
Poles 2p~24p
H5xx505100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 7.5mm
Poles 2p~16p
H5xxA05000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 7.5mm
Flange with Nut
Poles 2p~16p
H5xxA05200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 7.5mm
Flange with Screw
Poles 2p~16p
H5xxA05100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

H5



Pitch 7.62mm
Poles 2p~16p
H5xx005000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

SPRING CLAMP PLUGGABLE SYSTEM

H5



Pitch 7.62mm
Flange with Nut
Poles 2p~16p
H5xx005200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	

H5



Pitch 7.62mm
Flange with Screw
Poles 2p~16p
H5xx005100J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	

PART NUMBERS

H5 | XX Number of contacts | X Pitch | 0 | X Color | X Body type | X X X X | X

Solid Block

For 3.5 & 3.81 & 5.0 & 5.08 Pitch
02 to 24 2 to 24 contacts

For 7.5 & 7.62 Pitch
02 to 16 2 to 16 contacts

1	3.5/.138"
3	3.81/.15"
7	5.0/.197"
5	5.08/.20"
0	7.62/.30"
A	7.5/.295"

0	Black
5	Green (RAL6018/T)
6	Blue
8	Grey (RAL 7035/D)

0	W/O Flange
1	Flange with Screw
2	Flange with Nut

00J 0 Standard

Any special item by customer request, please contact sales department.

G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP PLUGGABLE SYSTEM

NB



Pitch 5.0mm
W/O Flange
Poles 2p~24p
NBxx708000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NB



Pitch 5.0mm
With Flange
Poles 2p~24p
NBxx708100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NB



Pitch 5.0 mm
W/O Flange,100% protected against mismating
Poles 2p~24p
NBxx708200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NB



Pitch 5.0 mm
With Flange,100% protected against mismating
Poles 2p~24p
NBxx708300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NB



Pitch 5.0mm
Snap-in mounting feet,
Poles 2p~24p
NBxx708400J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NB



Pitch 5.0mm
Snap-in mounting feet,
100% protected against mismating
Poles 2p~24p
NBxx708500J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NB




Pitch 7.5mm
W/O Flange
Poles 2p~16p
NBxxA08000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

NB



Pitch 7.5mm
With Flange
Poles 2p~16p
NBxxA08100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

SPRING CLAMP PLUGGABLE SYSTEM

NB




Pitch 7.5mm
W/O Flange,100% protected against mismating
Poles 2p~16p
NBxxA08200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

NB



Pitch 7.5mm
With Flange,100% protected against mismating
Poles 2p~16p
NBxxA08300J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

NB



Pitch 7.5mm
Snap-in mounting feet,
Poles 2p~16p
NBxxA08400J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

NB



Pitch 7.5mm
Snap-in mounting feet,
100% protected against mismating
Poles 2p~16p
NBxxA08500J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8-9mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)Pending

PART NUMBERS

NB | XX Number of contacts | X Pitch | 0 | X Color | X Body type | X X X X | X

Number of contacts

Solid Block

For 5.0 Pitch
02 to 24 2 to 24 contacts

For 7.5 Pitch
02 to 16 2 to 16 contacts

Pitch

7 5.00/.197"
A 7.5/.295"

Color

0 Black
5 Green (RAL 6018/T)
6 Blue (RAL5015/A)
8 Grey (RAL 7035/D)

Body type

0 W/O Flange
1 With Flange
2 W/O Flange, 100% protected against mismating
3 With Flange, 100% protected against mismating
4 With snap-in mounting feet
5 With snap-in mounting feet, 100% protected against mismating

X X X X

00J 0 Standard

Any special item by customer request, please contact sales department.

X

G RoHS compliant (lead<4%) In copper Alloy

H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP PLUGGABLE SYSTEM

KD




Pitch 3.5mm
Poles 2p~24p
KDxx105000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Wire strip length:	9~10mm
Withstanding Voltage:	1.32KV
Safety Approval:	cULus

KD




Pitch 3.5mm
With Flange
Poles 2p~24p
KDxx105100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Wire strip length:	9~10mm
Withstanding Voltage:	1.32KV
Safety Approval:	cULus

KD




Pitch 3.5mm
With Latch
Poles 2p~24p
KDxx105200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Wire strip length:	9~10mm
Withstanding Voltage:	1.32KV
Safety Approval:	cULus

KD




Pitch 3.5mm
W/O Flange (Double level)
Poles 2*2p - 2*24p
KDxx1050A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Wire strip length:	9~10mm
Withstanding Voltage:	1.32KV
Safety Approval:	cULus

KD




Pitch 3.5mm
With Flange (Double level)
Poles 2*2p - 2*24p
KDxx1051A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Wire strip length:	9-10mm
Withstanding Voltage:	1.32KV
Safety Approval:	cULus

KD




Pitch 3.5mm
With Latch (Double level)
Poles 2*2p - 2*24p
KDxx1052A0J0G*
Number of poles




Electrical:	cULus
Voltage rating:	160V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Wire strip length:	9-10mm
Withstanding Voltage:	1.32KV
Safety Approval:	cULus

KD




Pitch 3.81mm
Poles 2p~24p
NDxx305000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Wire strip length:	9-10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

KD



Pitch 3.81mm
With Flange
Poles 2p~24p
KDxx305100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Wire strip length:	9-10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

SPRING CLAMP PLUGGABLE SYSTEM

KD



Pitch 3.81mm
With Latch
Poles 2p~24p
KDxx305200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	5.5A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Wire strip length:	9-10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

KD



Pitch 5.0mm
Poles 2p~24p
KDxx705000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	14-24
Wire strip length:	11-12mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

KD



Pitch 5.0mm
With Flange
Poles 2p~24p
KDxx705100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	14-24
Wire strip length:	11-12mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

KD




Pitch 5.0mm
With Latch
Poles 2p~24p
KDxx705200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	14-24
Wire strip length:	11-12mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

KD



Pitch 5.08mm
Poles 2p~24p
KDxx505000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	14-24
Wire strip length:	11-12mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

KD



Pitch 5.08mm
With Flange
Poles 2p~24p
KDxx505100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	14-24
Wire strip length:	11-12mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

KD



Pitch 5.08mm
With Latch
Poles 2p~24p
KDxx505200J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	12A
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	14-24
Wire strip length:	11-12mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP PLUGGABLE SYSTEM

PART NUMBERS




SPRING CLAMP PLUGGABLE SYSTEM

ND



Pitch 3.5mm
Poles 2p~24p
NDxx105000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending
With P.C.B thickness :	1.6±0.2mm

ND



Pitch 5.0mm
Poles 2p~24p
NDxx705000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-26
Stranded wire(AWG):	14-26
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus
With P.C.B thickness:	1.6±0.2mm

ND




Pitch 7.5mm
Poles 2p~16p
NDxxA05000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-26
Stranded wire(AWG):	14-26
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus
With P.C.B thickness:	1.6±0.2mm

PART NUMBERS




For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP PLUGGABLE SYSTEM

VW



Pitch 3.5mm
W/O Flange
Poles 2*2p ~ 2*24p
VWxx103000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	18-28
Stranded wire(AWG):	18-28
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

VW




Pitch 3.5mm
With Flange
Poles 2*2p ~ 2*24p
VWxx103100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	7A
Wire range:	
Solid wire(AWG):	18-28
Stranded wire(AWG):	18-28
Wire strip length:	
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

HN



Pitch 3.5mm
W/O Flange
Poles 2~24p
HNxx103000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-26
Stranded wire(AWG):	14-26
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HN



Pitch 3.5mm
With Flange
Poles 2~24p
HNxx1032000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	14-26
Stranded wire(AWG):	14-26
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

VW — XX (Number of contacts) X (Pitch) 0 X (Color) X (Body Type) — XXXX X

Number of contacts

Solid Block

For 3.5 Pitch
04 to 48 2*2 to 24 contacts

For 7.0 Pitch
04 to 24 2*2 to 12 contacts

Pitch

1 3.5/.138"
2 7.0/.276"

Color

0 Black
3 Orange (RAL2011/P)
5 Green (RAL 6018/T)
6 Blue (RAL5015/A)
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

Body Type

0 W/O Flange
1 With Flange

XXXX

00J0 Standard
(Steel screw plating Cr^{3+})
Any special item by customer request, please contact sales department.

X

G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

HN — XX (Number of contacts) X (Pitch) 0 X (Color) X (Body type) — XXXX X

Number of contacts

Solid Block

02 to 24 2 to 24 contacts

Pitch

1 3.5/.138"
5 5.08/.20"

Color

0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)

Body type

0 W/O Flange
2 With Flange

XXXX

00J0 Standard


Any special item by customer request, please contact sales department.

X


G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

SPRING CLAMP PLUGGABLE SYSTEM

NF




Pitch 5.08mm
W/O Flange
Poles 2~24p
NFxx505000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NF




Pitch 5.08mm
With Flange
Poles 2~24p
NFxx505100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NF



Pitch 5.08mm
With Latch
Poles 2~24p
NFxx505200J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	12-26
Wire strip length:	
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

NF | XX Number of contacts | X Pitch | 0 | X Color | X Body type | X X X X | X

Solid Block
02 to 24 2 to 24 contacts

5 5.08/.20"

Color
0 Black
5 Green (RAL 6018/T)
6 Blue
8 Grey (RAL 7035/D)

Body type
0 W/O Flange
1 With Flange
2 With Latch

00J 0 Standard
Any special item by customer request, please contact sales department.

G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

"*" means FCI Standard item, any other non-standard item, please consult FCI for up-to-date information.


TMBSRCLPPSYS0214A4

Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP SYSTEM


OVERVIEW

For spring clamp system, the terminal is fixed on the PCB. It uses spring clamp to contact. Easy for user to install wire.






SPRING CLAMP SYSTEM




HA

Pitch 2.54mm
Horizontal
(180D wire inlet)
Poles 2p~24p
HAxx515000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	2A
Wire range:	
Solid wire(AWG):	20-26
Stranded wire(AWG):	20-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus




HA

Pitch 2.54mm
Vertical
(90D wire inlet)
Poles 2p~24p
HAxx505000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	2A
Wire range:	
Solid wire(AWG):	20-26
Stranded wire(AWG):	20-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus




HA

Pitch 3.81mm
Horizontal
(180D wire inlet)
Poles 2p~24p
HAxx715000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	6A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus




HA

Pitch 3.81mm
Vertical
(90D wire inlet)
Poles 2p~24p
HAxx705000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	6A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus




HA

Pitch 5.0mm
Horizontal
(180D wire inlet)
Poles 2p~24p
HAxx315000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	10A	10A
Wire range:	0.75 - 1.5mm²	
Solid wire(AWG):	14-24	
Stranded wire(AWG):	14-24	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	VDE




HA

Pitch 5.0mm
Vertical
(90D wire inlet)
Poles 2p~24p
HAxx305000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	10A	10A
Wire range:	0.75 - 1.5mm²	
Solid wire(AWG):	14-24	
Stranded wire(AWG):	14-24	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	VDE




HA

Pitch 5.08mm
Horizontal
(180D wire inlet)
Poles 2p~24p
HAxx015000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	10A	10A
Wire range:	0.75 - 1.5mm²	
Solid wire(AWG):	14-24	
Stranded wire(AWG):	14-24	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	VDE



HA

Pitch 5.08mm
Vertical
(90D wire inlet)
Poles 2p~24p
HAxx005000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	10A	10A
Wire range:	0.75 - 1.5mm²	
Solid wire(AWG):	14-24	
Stranded wire(AWG):	14-24	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	VDE

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP SYSTEM

HA




Pitch 7.5mm
Horizontal
(180D wire inlet)
Poles 2p~16p
HAxx615000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	10A	10A
Wire range:	0.75 - 1.5mm²	
Solid wire(AWG):	14-24	
Stranded wire(AWG):	14-24	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

HA




Pitch 7.5mm
Vertical
(90D wire inlet)
Poles 2p~16p
HAxx605000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	10A	10A
Wire range:	0.75 - 1.5mm²	
Solid wire(AWG):	14-24	
Stranded wire(AWG):	14-24	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

HA




Pitch 7.62mm
Horizontal
(180D wire inlet)
Poles 2p~16p
HAxx215000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	10A	10A
Wire range:	0.75 - 1.5mm²	
Solid wire(AWG):	14-24	
Stranded wire(AWG):	14-24	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

HA




Pitch 7.62mm
Vertical
(90D wire inlet)
Poles 2p~16p
HAxx205000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	10A	10A
Wire range:	0.75 - 1.5mm²	
Solid wire(AWG):	14-24	
Stranded wire(AWG):	14-24	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

HA




Pitch 10.0mm
Horizontal
(180D wire inlet)
Poles 2p~12p
HAxx415000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	10A	10A
Wire range:	0.75 - 1.5mm²	
Solid wire(AWG):	14-24	
Stranded wire(AWG):	14-24	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

HA




Pitch 10.0mm
Vertical
(90D wire inlet)
Poles 2p~12p
HAxx405000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	10A	10A
Wire range:	0.75 - 1.5mm²	
Solid wire(AWG):	14-24	
Stranded wire(AWG):	14-24	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

NA




Pitch 2.5mm
Vertical (90D wire inlet)
Poles 2p~24p
NAxxB08000J0G* A Type
NAxxB08100J0G* B Type
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	3A
Wire range:	
Solid wire(AWG):	20-28
Stranded wire(AWG):	20-28
Wire strip length:	9~10mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

NA



Pitch 2.5mm
Right-angle (180D wire inlet)
Poles 2p~24p
NAxxB18000J0G* A Type
NAxxB18100J0G* B Type
Number of poles



Electrical:	cULus
Voltage rating:	150V
Current rating:	3A
Wire range:	
Solid wire(AWG):	20-28
Stranded wire(AWG):	20-28
Wire strip length:	9~10mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

SPRING CLAMP SYSTEM

PART NUMBERS

HA

XX Number of contacts	X Pitch	X Insulator	X Color	0	XXXX	X

End Stackable

For 2.54 & 3.81 & 5.0 & 5.08 Pitch
01 to 24 1 to 24 contacts

For 7.5 & 7.62 Pitch
01 to 16 1 to 16 contacts

For 10.0 & 10.16 Pitch
01 to 12 1 to 12 contacts

Pitch	
0	5.08/.20"
2	7.62/.30"
3	5.00/.197"
4	10.0/.394"
5	2.54/.10"
6	7.50/.295"
7	3.81/.15"

Insulator	
0	Vertical (90D wire inlet)
1	Horizontal (180D wire inlet)

Color	
0	Black
2	Red
5	Green (RAL 6018/T)
8	Grey (RAL 7004/P)
C	Multiple colors

00J 0 Standard

Any special item by customer request, please contact sales department.

G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy

NA

XX Number of contacts	X Pitch	X P.C.B Mounting	X Color	X Tail type	XXXX	X

End Stackable

01 to 24 1 to 24 contacts

Pitch	
B	2.5/.098"
5	2.54/.10"

P.C.B Mounting	
0	Vertical (90 wire inlet)
1	Horizontal (180 wire inlet)

Color	
0	Black
5	Green (RAL 6018/T)
6	Blue (RAL5015/A)
8	Grey (RAL 7004/P)

Tail type	
0	Double tail A type (standard)
1	Single tail B type
2	Single tail C type


00J 0 Standard


Any special item by customer request, please contact sales department.

G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy


Disclaimer
Please note that the above information is subject to change without notice.


SPRING CLAMP SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	
Stranded wire(AWG):	16-26
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

HX	XX	X	X	X	X	X X X X	X
	Number of contacts	Pitch	Insulator	Color	Body type		

Number of contacts

End Stackable

01 to 24 1 to 24 contacts

Pitch

0	5.00/.197"
2	3.5/.138"

Insulator

0	Vertical (90D wire inlet)
1	Horizontal (180D wire inlet)
0	Vertical (90D wire inlet) -Interlace(A type) (only pitch 3.5mm)
1	Vertical (Single contact) (90D wire inlet)(B type) (Only pitch 5.0mm)
2	Horizontal (180D wire inlet) -Interlace(A type) (Only pitch 3.5mm)
3	Horizontal (180D wire inlet) (B type)(Double contact) (Only pitch 3.5mm)
4	Horizontal (90D wire inlet) (B type)(Double contact) (Only pitch 3.5mm)

Color

0	Black
2	Red (RAL3001/D)
5	Green (RAL 6018/T)
8	Grey (RAL 7004/P)
9	White (RAL1002)
C	Multiple colors

Body type

0	Bevel Angle (only pitch 5.0)
1	Right Angle

X X X X


00J 0 Standard


Any special item by customer request, please contact sales department.

X


G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy


SPRING CLAMP SYSTEM







Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	10A	9A
Wire range:		0.5 - 0.75mm²
Solid wire(AWG):	16-20	
Stranded wire(AWG):	16-20	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	VDE







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-20
Stranded wire(AWG):	16-20
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-20
Stranded wire(AWG):	16-20
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	10A	6A
Wire range:		0.5mm²
Solid wire(AWG):	14-20	
Stranded wire(AWG):	14-20	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE







Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	10A	6A
Wire range:		0.5mm²
Solid wire(AWG):	14-20	
Stranded wire(AWG):	14-20	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	2*18-24
Stranded wire(AWG):	2*18-24
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus





Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	10A	6A
Wire range:		0.5mm²
Solid wire(AWG):	14-20	
Stranded wire(AWG):	14-20	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE






Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	10A	6A
Wire range:		0.5mm²
Solid wire(AWG):	14-20	
Stranded wire(AWG):	14-20	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP SYSTEM

HB




Pitch 7.5mm
Double With Lever
Poles 2p~16p
HBxx228000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	2*18-24
Stranded wire(AWG):	2* 18-24
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HB




Pitch 10.0mm
Single With Lever
Poles 2p~12p
HBxx118000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	10A	6A
Wire range:		0.5mm²
Solid wire(AWG):	14-20	
Stranded wire(AWG):	14-20	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

HB




Pitch 10.0mm
Single W/O Lever
Poles 2p~12p
HBxx118100J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	10A	6A
Wire range:		0.5mm²
Solid wire(AWG):	14-20	
Stranded wire(AWG):	14-20	
Wire strip length:	9~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:	cULus	VDE

HB



Pitch 10.0mm
Double With Lever
Poles 2p~12p
HBxx128000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	2*18-24
Stranded wire(AWG):	2* 18-24
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

HB | XX Number of contacts | X Pitch | X Body type | X Color | X Lever | XXXX | X

End Stackable

For 3.81 & 3.96 & 5.0 Pitch
01 to 24 1 to 24 contacts

For 7.5 Pitch
01 to 16 1 to 16 contacts

For 10.0 Pitch
01 to 12 1 to 12 contacts

Pitch	
0	5.0/.197"
1	10.0/.394"
2	7.5/.295"
3	3.81/.15"
4	3.96/.156"

Body type	
1	Single wire
2	Double wire

Color	
0	Black
2	Red (RAL3001/D)
5	Green (RAL 6018/T)
8	Grey (RAL 7004/P)

Lever	
0	With Lever
1	W/O Lever (Only single wire)


00J 0 Standard

Any special item by customer request, please contact sales department.


G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy

SPRING CLAMP SYSTEM

H6




Pitch 5.0mm
(Square hole)
Poles 2p~24p
H6xx008010J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	11A	12A
Wire range:		
Solid wire(AWG):	12-20	0.5mm²~4.0mm²
Stranded wire(AWG):	12-20	0.5mm²~2.5mm²
Wire strip length:	10~11mm	
Withstanding Voltage:	1.6KV	2.0KV
Safety Approval:		

H6




Pitch 7.5mm
(Square hole)
Poles 2p~16p
H6xx108010J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	11A	12A
Wire range:		
Solid wire(AWG):	12-20	0.5mm²~4.0mm²
Stranded wire(AWG):	12-20	0.5mm²~2.5mm²
Wire strip length:	10~11mm	
Withstanding Voltage:	1.6KV/2.5KV	
Safety Approval:		

H6



Pitch 10.0mm
(Square hole)
Poles 2p~12p
H6xx208010J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	11A
Wire range:	
Solid wire(AWG):	12-20
Stranded wire(AWG):	12-20
Wire strip length:	10~11mm
Withstanding Voltage:	1.6KV
Safety Approval:	

H6



Pitch 5.0mm
(Round hole)
Poles 2p-24p
H6xx008000J0G *
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	11A	12A
Wire range:	0.5~4.0mm²	
Solid wire(AWG):	12-20	
Stranded wire(AWG):	12-20	
Wire strip length:	10~11mm	
Withstanding Voltage:	1.6KV	2.0KV
Safety Approval:		

H6



Pitch 7.5/10.0mm
(Round hole)
Poles 2p-16p/2p-12p
H6xx108000J0G* / H6xx208000J0G*
Number of poles



Electrical:	cULus	VDE
Voltage rating:	300V	450V
Current rating:	11A	12A
Wire range:	0.5~4.0mm²	
Solid wire(AWG):	12-20	
Stranded wire(AWG):	12-20	
Wire strip length:	10~11mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		

PART NUMBERS

H6 | XX Number of contacts | X Pitch | 0 | X Color | 0 | XXXX | X

End Stackable

For 5.0 Pitch
01 to 24 1 to 24 contacts

For 7.5 Pitch
01 to 16 1 to 16 contacts

For 10.0 Pitch
01 to 12 1 to 12 contacts

0	5.00/.197"
1	7.5/.295"
2	10.0/.393"

0	Black
5	Green (RAL6018/T)
8	Grey (RAL7004/P)
C	Multiple colors

00J 0 Round hole

1 0J0 Square hole


Any special item by customer request, please contact sales department.


G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP SYSTEM









Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-20
Stranded wire(AWG):	16-20
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	

Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	16-20
Stranded wire(AWG):	16-20
Wire strip length:	7~8mm
Withstanding Voltage:	1.6KV
Safety Approval:	

PART NUMBERS

H7 | XX Number of contacts | X Pitch | 0 | X Color | X Foot Print | X X X X | X

XX Number of contacts

End Stackable

For 5.0 Pitch
01 to 24 1 to 24 contacts

For 7.5 Pitch
01 to 16 1 to 16 contacts

X Pitch

0 5.0/.197"
1 7.5/.295"

X Color

0 Black
5 Green (RAL6018/T)
8 Grey (RAL7004/P)
C Multiple colors

X Foot Print

0 Double row the 1st pole with center contact
1 Side Single Row
2 Center Single Row
3 Double row the 1st pole with side contact

X X X X

00J 0 Standard


Any special item by customer request, please contact sales department.


X

G RoHS compliant (lead<4%) In copper Alloy


H RoHS compliant (lead<1000ppm) In copper Alloy


SPRING CLAMP SYSTEM







Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	2A	2A
Wire range:	0.5 - 0.75mm²	
Solid wire(AWG):	18	
Stranded wire(AWG):	18	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:		







Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	2A	2A
Wire range:	0.5 - 0.75mm²	
Solid wire(AWG):	18	
Stranded wire(AWG):	18	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:		






Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	2A	2A
Wire range :	0.5 - 0.75mm²	
Solid wire(AWG):	18	
Stranded wire(AWG):	18	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	





Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	2A	2A
Wire range :	0.5 - 0.75mm²	
Solid wire(AWG):	18	
Stranded wire(AWG):	18	
Wire strip length:	6~7mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:	cULus	


PART NUMBERS




For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SPRING CLAMP SYSTEM







Electrical:	cULus	CQC	TÜV
Voltage rating:	300V	300V	150V
Current rating:	2A	2A	2A
Wire range:		0.2-0.5mm²	
Solid wire(AWG):	20-26	20	
Stranded wire(AWG):	20-26	20	
Wire strip length:		8.5~10mm	
Withstanding Voltage:	1.6KV	2.5KV	2.5KV
Safety Approval:			







Electrical:	cULus	CQC
Voltage rating:	300V	300V
Current rating:	2A	2A
Wire range:		
Solid wire(AWG):	20-26	20
Stranded wire(AWG):	20-26	20
Wire strip length:	8.5~10mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		





Electrical:	UL	VDE	CQC	TÜV
Voltage rating:	300V	130V	300V	500V
Current rating:	6A	6A	6A	8A
Wire range:	0.5 - 0.75mm²		0.5 - 1.5mm²	
Solid wire(AWG):	16-22		16-20	
Stranded wire(AWG):	16-22		16-20	
Wire strip length:	8.5~10mm			
Withstanding Voltage:	1.6KV	1.25KV	2.5KV	4KV
Safety Approval:				





Electrical:	UL	VDE
Voltage rating:	300V	250V
Current rating:	6A	6A
Wire range:	0.5 - 0.75mm²	
Solid wire(AWG):	16-22	
Stranded wire(AWG):	16-22	
Wire strip length:	8.5~10mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:		

PART NUMBERS

HC	XX Number of contacts	X Pitch	X Lever	X Color	X Foot Print	XXXX	X

End Stackable

For 2.5 & 3.5 Pitch
01 to 24 1 to 24 contacts

For 7.0 Pitch
01 to 12 1 to 12 contacts

Pitch
0 3.5/.138"
1 7.0/.276"
B 2.5/.098"

Lever
0 Standard
2 High profile (Only pitch2.5)


Color
2 Red (RAL3001/D)
3 Orange (RAL2011/P)
5 Green (RAL 6018/T)
8 Grey (RAL 7004/P)
C Multiple colors


Foot Print
0 Double row center contact link together with end cover
1 Side Single Row
2 Center Single Row
3 Double row side contact link together with end cover

XXXX
00J0 Standard
Any special item by customer request, please contact sales department.


X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy


SPRING CLAMP SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-20
Stranded wire(AWG):	
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-20
Stranded wire(AWG):	
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	150V
Current rating:	4A
Wire range:	
Solid wire(AWG):	22-28
Stranded wire(AWG):	22-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	150V
Current rating:	4A
Wire range:	
Solid wire(AWG):	22-28
Stranded wire(AWG):	22-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	150V
Current rating:	4A
Wire range:	
Solid wire(AWG):	22-28
Stranded wire(AWG):	22-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus







Electrical:	cULus
Voltage rating:	150V
Current rating:	4A
Wire range:	
Solid wire(AWG):	22-28
Stranded wire(AWG):	22-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus





Electrical:	cULus
Voltage rating:	150V
Current rating:	4A
Wire range:	
Solid wire(AWG):	22-28
Stranded wire(AWG):	22-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus






Electrical:	cULus
Voltage rating:	150V
Current rating:	4A
Wire range:	
Solid wire(AWG):	22-28
Stranded wire(AWG):	22-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP SYSTEM

PART NUMBERS






SPRING CLAMP SYSTEM

HD




Pitch 5.08mm
Poles 2p~24p
HDxx008000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	12A
Wire range:	
Solid wire(AWG):	16-22
Stranded wire(AWG):	16-22
Wire strip length:	6~7mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus

HG



Pitch 5.0mm
Poles 2p~24p
HGxx008000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HG




Pitch 5.08mm
Poles 2p~24p
HGxx308000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HG



Pitch 7.5mm
Poles 2p~16p
HGxx208000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HG




Pitch 7.62mm
Poles 2p~16p
HGxx508000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HG




Pitch 10.0mm
Poles 2p~12p
HGxx108000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HG



Pitch 10.16mm
Poles 2p~12p
HGxx408000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP SYSTEM


PART NUMBERS






SPRING CLAMP SYSTEM

HT




Pitch 5.0mm
Poles 2p~24p
HTxx008000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HT



Pitch 5.08mm
Poles 2p~24p
HTxx308000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HT



Pitch 7.5mm
Poles 2p~16p
HTxx208000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HT



Pitch 7.62mm
Poles 2p~16p
HTxx508000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HT



Pitch 10.0mm
Poles 2p~12p
HTxx108000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HT




Pitch 10.16mm
Poles 2p~12p
HTxx408000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HV



Pitch 3.81mm
Poles 2p~24p
HVxx308000J0G*
Number of poles




Electrical:	cULus	TUV
Voltage rating:	300V	500V
Current rating:	8A	10A
Wire range:	0.5~1.5mm²	
Solid wire(AWG):	16-20	
Stranded wire(AWG):	16-20	
Wire strip length:	8~9mm	
Withstanding Voltage:	1.6KV	1.89KV
Safety Approval:		

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.


SPRING CLAMP SYSTEM

PART NUMBERS




SPRING CLAMP SYSTEM

HF




Pitch 5.0mm
Low profile Type
Poles 2p~24p
HFxx708000J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	10A	10A
Wire range:	0.5~1.0mm²	
Solid wire(AWG):	16-20	
Stranded wire(AWG):	16-20	
Wire strip length:	8~9mm	
Withstanding Voltage:	1.6KV	2KV
Safety Approval:		

HF




Pitch 5.0mm
High profile Type
Poles 2p~24p
HFxx708100J0G*
Number of poles




Electrical:	cULus	VDE
Voltage rating:	300V	250V
Current rating:	10A	10A
Wire range:	0.5~1.0mm²	
Solid wire(AWG):	16-20	
Stranded wire(AWG):	16-20	
Wire strip length:	8~9mm	
Withstanding Voltage:	1.6KV	2.5KV
Safety Approval:		

HH



Pitch 5.0mm
Poles 2p~24p
HHxx008000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	14-28
Stranded wire(AWG):	14-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

PART NUMBERS

HF — XX Number of contacts | X Pitch | 0 | X Color | X Body type | XXXX | X

- **Number of contacts**: Solid Block; 02 to 24 — 2 to 24 contacts
- **Pitch**: 7 — 5.0/.197"; 8 — 10.0/.394"
- **Color**: 8 — Grey (RAL 7004/P); 9 — Orange (RAL2011/P)
- **Body type**: 0 — Low profile body; 1 — High profile body
- **XXXX**: 00J0 Standard. Any special item by customer request, please contact sales department.
- **X**: G — RoHS compliant (lead<4%) In copper Alloy; H — RoHS compliant (lead<1000ppm) In copper Alloy

HH — XX Number of contacts | X Pitch | 0 | X Color | 0 | XXXX | X


- **Number of contacts**: End Stackable; 01 to 24 — 1 to 24 contacts
- **Pitch**: 0 — 5.00/.197"
- **Color**: 0 — Black; 2 — Red (RAL3001/D); 5 — Green (RAL 6018/T); 8 — Grey (RAL 7004/P); C — Multiple colors
- **XXXX**: 00J0 Standard. Any special item by customer request, please contact sales department.
- **X**: G — RoHS compliant (lead<4%) In copper Alloy; H — RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP SYSTEM

HM




Pitch 3.81mm
Dip solder
Poles 2p~24p
HMxx308000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	8A
Wire range:	
Solid wire(AWG):	14-28
Stranded wire(AWG):	14-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

HM




Pitch 3.81mm
Press fit
Poles 2p~24p
HMxx308100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	14-28
Stranded wire(AWG):	14-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending
Diameter of metal-plated hole:	$1.0^{+0.09}_{-0.06}$

HM




Pitch 5.0mm
Dip solder
Poles 2p~24p
HMxx708000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus

HM




Pitch 5.0mm
Press fit
Poles 2p~24p
HMxx708100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus
Diameter of metal-plated hole:	$1.45^{+0.09}_{-0.06}$

HM




Pitch 5.08mm
Dip solder
Poles 2p~24p
HMxx508000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus

HM




Pitch 5.08mm
Press fit
Poles 2p~24p
HMxx508100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus
Diameter of metal-plated hole:	$1.45^{+0.09}_{-0.06}$

HM




Pitch 7.5mm
Dip solder
Poles 2p~16p
HMxx908000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus

HM




Pitch 7.5mm
Press fit
Poles 2p~16p
HMxx908100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus
Diameter of metal-plated hole:	$1.45^{+0.09}_{-0.06}$

SPRING CLAMP SYSTEM

HM




Pitch 7.62mm
Dip solder
Poles 2p~16p
HMxx408000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HM




Pitch 7.62mm
Press fit
Poles 2p~16p
HMxx408100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

Diameter of metal-plated hole: $1.45^{+0.09}_{-0.06}$

HM




Pitch 10.0mm
Dip solder
Poles 2p~12p
HMxx808000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus

HM




Pitch 10.0mm
Press fit
Poles 2p~12p
HMxx808100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus

Diameter of metal-plated hole: $1.45^{+0.09}_{-0.06}$

HM




Pitch 10.16mm
Dip solder
Poles 2p~12p
HMxx608000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus

HM



Pitch 10.16mm
Press fit
Poles 2p~12p
HMxx608100J0G*
Number of poles



Electrical:	cULus
Voltage rating:	250V
Current rating:	8A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	8~9mm
Withstanding Voltage:	1.5KV
Safety Approval:	cULus


Diameter of metal-plated hole: $1.45^{+0.09}_{-0.06}$

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.


SPRING CLAMP SYSTEM

PART NUMBERS





SPRING CLAMP SYSTEM







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	







Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	





Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	






Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

SPRING CLAMP SYSTEM

PART NUMBERS




SPRING CLAMP SYSTEM

HR



Pitch 5.08mm-Parallel
Poles 3*2p~3*24p
HRxx308000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HR



Pitch 5.08mm-Interlace
Poles 3*2p~3*24p
HRxx308100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HR




Pitch 7.62mm-Parallel
Poles 3*2p~3*16p
HRxx508000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HR



Pitch 7.62mm-Interlace
Poles 3*2p~3*16p
HRxx508100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HR




Pitch 10.16mm-Parallel
Poles 3*2p~3*12p
HRxx408000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HR



Pitch 10.16mm-Interlace
Poles 3*2p~3*12p
HRxx408100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.


SPRING CLAMP SYSTEM

PART NUMBERS




SPRING CLAMP SYSTEM

HS




Pitch 5.0mm-Parallel
Poles 4*2p-4*24p
HSxx008000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5-6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HS




Pitch 5.0mm-Interlace
Poles 4*2p-4*24p
HSxx008100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5-6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HS




Pitch 5.08mm-Parallel
Poles 4*2p-4*24p
HSxx308000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5-6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HS



Pitch 5.08mm-Interlace
Poles 4*2p-4*24p
HSxx308100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HS



Pitch 7.5mm-Parallel
Poles 4* 2p-4*16p
HSxx108000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5-6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HS



Pitch 7.5mm-Interlace
Poles 4*2p-4*16p
HSxx108100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HS



Pitch 7.62mm-Parallel
Poles 4*2p-4*16p
HSxx50X000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

HS



Pitch 7.62mm-Interlace
Poles 4*2p-4*16p
HSxx508100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP SYSTEM

HS




Pitch 10.0mm-Parallel
Poles 4*2p-4*12p
HSxx20X000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HS




Pitch 10.0mm-Interlace
Poles 4*2p-4*12p
HSxx208100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HS




Pitch 10.16mm-Parallel
Poles 4*2p-4*12p
HSxx408000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HS



Pitch 10.16mm-Interlace
Poles 4*2p-4*12p
HSxx408100J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	12-28
Stranded wire(AWG):	12-28
Wire strip length:	5~6mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

HS | XX Number of contacts | X Pitch | 0 | X Color | X Body type | X X X X | X

End Stackable

For 5.0 & 5.08 Pitch
04 to 96 4*1 to 24 contacts

For 7.5 & 7.62 Pitch
04 to 64 4*1 to 16 contacts

For 10.0 & 10.16 Pitch
04 to 48 4*1 to 12 contacts

Pitch

0 5.0/.197"
1 7.5/.295"
2 10.0/.394"
3 5.08/.20"
5 7.62/.30"
4 10.16/.40"

Color

0 Black
3 Orange (RAL 2011/P)
5 Green (RAL 6018/T)
8 Grey (RAL 7004/P)
C Multiple colors

Body type

0 Solder pin in line
1 Solder pins staggered by half pin spacing

X X X X

00J0 Standard

Any special item by customer request, please contact sales department.

X

G RoHS compliant (lead<4%) In copper Alloy


H RoHS compliant (lead<1000ppm) In copper Alloy

SPRING CLAMP SYSTEM

H3



Pitch 5.0mm
Poles 2p~24p
H3xx008000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	250V
Current rating:	10A	20A
Wire range:		0.08-4mm²
Solid wire(AWG):	12-28	
Stranded wire(AWG):	12-28	
Wire strip length:	8~9mm	
Withstanding Voltage:	1.6KV	4KV
Safety Approval:	cULus	

H3




Pitch 7.5mm
Poles 2p~16p
H3xx108000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	500V
Current rating:	10A	20A
Wire range:		0.08-4mm²
Solid wire(AWG):	12-28	
Stranded wire(AWG):	12-28	
Wire strip length:	8~9mm	
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	

H3



Pitch 10.0mm
Poles 2p~12p
H3xx208000J0G*
Number of poles



Electrical:	cULus	IEC
Voltage rating:	300V	630V
Current rating:	10A	20A
Wire range:		0.08-4mm²
Solid wire:(AWG)	12-28	
Stranded wire:(AWG)	12-28	
Wire strip length:	8~9mm	
Withstanding Voltage:	1.6KV	8KV
Safety Approval:	cULus	

PART NUMBERS

H3 | XX Number of contacts | X Pitch | 0 | X Color | 0 | X X X X | X

End Stackable

For 5.0 Pitch
01 to 24 1 to 24 contacts

For 7.5 Pitch
01 to 16 1 to 16 contacts

For 10.0 Pitch
01 to 12 1 to 12 contacts

0	5.00/.197"
1	7.5/.295"
2	10.0/.394"

0	Black
2	Red (RAL 3001/D)
5	Green (RAL 6018/T)
8	Grey (RAL 7004/P)
C	Multiple colors

00J 0 Standard

Any special item by customer request, please contact sales department.

G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP SYSTEM

H2



Pitch 7.5mm
Poles 2p~16p
H2xx008000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	500V
Current rating:	10A	32A
Wire range:		
Solid wire:	AWG 10-24/0.2-6mm²	
Stranded wire:	AWG 10-24/0.25-4mm²	
Wire strip length:	11~12mm	
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	

H2



Pitch 10.0mm
Poles 2p~12p
H2xx108000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	630V
Current rating:	10A	32A
Wire range:		
Solid wire:	AWG 10-24/0.2-6mm²	
Stranded wire:	AWG 10-24/0.25-4mm²	
Wire strip length:	11~12mm	
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	

H8



Pitch 10.0mm
Poles 2p~12p
H8xx008000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	250V
Current rating:	37A	76A
Wire range:		
Solid wire:	AWG 6-24/0.2-16mm²	
Stranded wire:	AWG 6-24/0.2-10mm²	
Wire strip length:	12~13mm	
Withstanding Voltage:	1.6KV/4KV	
Safety Approval:	cULus	

H8



Pitch 10.0mm
With Flange
Poles 2p~12p
H8xx008100J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	250V
Current rating:	37A	76A
Wire range:		
Solid wire:	AWG 6-24/0.2-16mm²	
Stranded wire:	AWG 6-24/0.2-10mm²	
Wire strip length:	12~13mm	
Withstanding Voltage:	1.6KV/4KV	
Safety Approval:	cULus	

H8



Pitch 15.0mm
Poles 2p~8p
H8xx108000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	37A	76A
Wire range:		
Solid wire:	AWG 6-24/0.2-16mm²	
Stranded wire:	AWG 6-24/0.2-10mm²	
Wire strip length:	12~13mm	
Withstanding Voltage:	1.6KV/8KV	
Safety Approval:	cULus	

H8



Pitch 15.0mm
Poles 2p~8p
H8xx108100J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	37A	76A
Wire range:		
Solid wire:	AWG 6-24/0.2-16mm²	
Stranded wire:	AWG 6-24/0.2-10mm²	
Wire strip length:	12~13mm	
Withstanding Voltage:	1.6KV/8KV	
Safety Approval:	cULus	

H8




Pitch 20.0mm
Poles 2p~8p
H8xx208000J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	37A	76A
Wire range:		
Solid wire:	AWG 6-24/0.2-16mm²	
Stranded wire:	AWG 6-24/0.2-10mm²	
Wire strip length:	12~13mm	
Withstanding Voltage:	2.2KV/8KV	
Safety Approval:	cULus	

H8




Pitch 20.0mm
With Flange
Poles 2p~8p
H8xx208100J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	600V	1000V
Current rating:	37A	76A
Wire range:		
Solid wire:	AWG 6-24/0.2-16mm²	
Stranded wire:	AWG 6-24/0.2-10mm²	
Wire strip length:	12~13mm	
Withstanding Voltage:	2.2KV/8KV	
Safety Approval:	cULus	

SPRING CLAMP SYSTEM


PART NUMBERS






SPRING CLAMP SYSTEM

HY




Pitch 5.0mm
Poles 2p~3p
HYxx008000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	7A
Wire range:	
Solid wire(AWG):	18-22
Stranded wire(AWG):	
Wire strip length:	7~7.5mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

HL



Pitch 3.5mm
Poles 2p~12p
HLxx009000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	2A
Wire range:	
Push-Wire Connection:	AWG 16-20 "sol" 1
Wire strip length:	7.5~8.5mm
IDC Connection:	AWG 22 "sol" 2
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

HY — XX (Number of contacts) X (Pitch) 0 X (Color) 0 XXXX X

- XX — End Stackable; 02 to 24 — 2 to 24 contacts
- X (Pitch): 0 — 5.00/.197"
- X (Color): 8 — Grey Body (RAL 7004/P) +White Lever
- XXXX: 00J0 — Standard. Any special item by customer request, please contact sales department.
- X: G — RoHS compliant (lead<4%) In copper Alloy; H — RoHS compliant (lead<1000ppm) In copper Alloy

HL — XX (Number of contacts) X (Pitch) 0 X (Color) 0 XXXX X


- XX — End Stackable; 01 to 12 — 1 to 12 contacts
- X (Pitch): 0 — 3.5/.138"
- X (Color): 9 — White (RAL1102)
- XXXX: 00J0 — Standard. Any special item by customer request, please contact sales department.
- X: G — RoHS compliant (lead<4%) In copper Alloy; H — RoHS compliant (lead<1000ppm) In copper Alloy

SPRING CLAMP SYSTEM

DS-240



Pitch 5.0mm
Poles 1p~24p
DS240xx080J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	400V
Current rating:	10A	18A
Wire range:		
Solid wire(AWG):	16-28/0.8-1.5mm^2	
Stranded wire(AWG):	16-28/0.8-1.5mm^2	
Wire strip length:	8-9mm	
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	

DS-240




Pitch 5.0mm
With Snap - In Mounting feet
Poles 1p~24p
DS240xx180J0G*
Number of poles




Electrical:	cULus	IEC
Voltage rating:	300V	400V
Current rating:	10A	18A
Wire range:		
Solid wire(AWG):	16-28/0.8-1.5mm^2	
Stranded wire(AWG):	16-28/0.8-1.5mm^2	
Wire strip length:	8-9mm	
Withstanding Voltage:	1.6KV	6KV
Safety Approval:	cULus	

NH




Pitch 3.5mm
Poles 2p~16p
NHxx105000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NH




Pitch 5.0mm
Poles 2p~24p
NHxx705000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NI




Pitch 3.81mm
Poles 2p~24p
NIxx305000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NI



Pitch 5.08mm
Poles 2p~24p
NIxx505000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-26
Stranded wire(AWG):	16-26
Wire strip length:	8~9mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP SYSTEM

PART NUMBERS









SPRING CLAMP SYSTEM

H9




Pitch 5.08mm
Poles 1p-24p
H9xx505000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	15A
Wire range:	
Solid wire(AWG):	12-26
Stranded wire(AWG):	14-26
Wire strip length:	11~12mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

NA




Pitch 2.54mm
Vertical (90D wire inlet)
Poles 2p~24p
NAxx508000J0G* A Type
NAxx508100J0G* B Type
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	3A
Wire range:	
Solid wire(AWG):	20-28
Stranded wire(AWG):	20-28
Wire strip length:	9~10mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

NA



Pitch 2.54mm
Horizontal (180D Wire inlet)
Poles 2p~24p
NAxx518000J0G* A Type
NAxx518100J0G* B Type
Number of poles



Electrical:	cULus
Voltage rating:	150V
Current rating:	3A
Wire range:	
Solid wire(AWG):	20-28
Stranded wire(AWG):	20-28
Wire strip length:	9~10mm
Withstanding Voltage:	1.3KV
Safety Approval:	cULus

PART NUMBERS

H9

XX	X	0	X	0	X X X X	X
Number of contacts	Pitch		Color			

Number of contacts
End Stackable
01 to 24 1 to 24 contacts

Pitch
5 5.08/.20"

Color
0 Black
3 Orange (RAL 2011/P)
5 Green (RAL 6018/T)
8 Grey (RAL 7004/P)
C Multiple colors

X X X X
00J 0 Standard
Any special item by customer request, please contact sales department.

X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

NA

XX	X	X	X	X	X X X X	X
Number of contacts	Pitch	P.C.B Mounting	Color	Tail type		

Number of contacts
End Stackable
01 to 24 1 to 24 contacts

Pitch
B 2.5/.098"
5 2.54/.10"

P.C.B Mounting
0 Vertical (90 wire inlet)
1 Horizontal (180 wire inlet)

Color
0 Black
5 Green (RAL 6018/T)
6 Blue (RAL 5015/A)
8 Grey (RAL 7004/P)

Tail type
0 Double tail A type (Standard)
1 Single tail B type
2 Single tail C type


X X X X
00J 0 Standard
Any special item by customer request, please contact sales department.

X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP SYSTEM




NJ

Pitch 3.5mm
Horizontal (180D Wire inlet)
Poles 2p-24p
NJxx215000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus




NJ

Pitch 3.5mm
Vertical (90D Wire inlet)
Poles 2p-24p
NJxx205000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	10A
Wire range:	
Solid wire(AWG):	16-24
Stranded wire(AWG):	16-24
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus




NJ

Pitch 5.0mm
Horizontal (180D Wire inlet)
Poles 2p-24p
NJxx015000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	16A(Str)/13A(Sol)
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	12-24
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus



NJ

Pitch 5.0mm
Vertical (90D Wire inlet)
Poles 2p-24p
NJxx005000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	16A(Str)/13A(Sol)
Wire range:	
Solid wire(AWG):	14-24
Stranded wire(AWG):	12-24
Wire strip length:	9~10mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

NJ	X X	X	X	X	0	X X X X	X
	Number of contacts	Pitch	P.C.B Mounting	Color			

End Stackable

01 to 24 1 to 24 contacts

0 5.0/.197"
2 3.5/.138"

0 Vertical (90 wire inlet)
1 Horizontal (180 wire inlet)

0 Black
2 Red (RAL 3001/D)
5 Green (RAL 6018/T)
8 Grey (RAL 7004/P)
C Multiple colors

00J 0 Standard

Any special item by customer request, please contact sales department.

G RoHS compliant (lead<4%) In copper Alloy


H RoHS compliant (lead<1000ppm) In copper Alloy

SPRING CLAMP SYSTEM

NK



Pitch 7.5mm
Horizontal (180D Wire inlet) Parallel A type
Poles 1p-16p
NKxxA15000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	35A(Str)/30A(Sol)
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	8-24
Wire strip length:	15~16mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NK



Pitch 7.5mm
Vertical (Parallel tail A type)
Poles 1p-16p
NKxxA05000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	35A(Str)/30A(Sol)
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	8-24
Wire strip length:	15~16mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NK



Pitch 7.5mm
Right-angle (Interlace tail B type)
Poles 1p-16p
NKxxA15100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	35A(Str)/30A(Sol)
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	8-24
Wire strip length:	15~16mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus

NK




Pitch 7.5mm
Vertical (Interlace tail B type)
Poles 1p-16p
NKxxA05100J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	35A(Str)/30A(Sol)
Wire range:	
Solid wire(AWG):	10-24
Stranded wire(AWG):	8-24
Wire strip length:	15~16mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus

PART NUMBERS




For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

SPRING CLAMP SYSTEM

NP



Pitch 10.0mm
Horizontal (180D Wire inlet)
Poles 2p-12p
NPxx115100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	600V
Current rating:	40A(Str)/30A(sol)
Wire range:	
Solid wire(AWG):	8-20
Stranded wire(AWG):	4-20
Wire strip length:	18~19mm
Withstanding Voltage:	2.2KV
Safety Approval:	cULus

NQ



Pitch 2.5mm
SMT type
Poles 2p-10p
NQxx000000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	150V
Current rating:	5A
Wire range:	
Solid wire(AWG):	20-24
Stranded wire(AWG):	
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

NQ



Pitch 4.0mm
SMT type
Poles 2p-10p
NQxx210000J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	7A
Wire range:	
Solid wire(AWG):	18-22
Stranded wire(AWG):	
Wire strip length:	6~7mm
Withstanding Voltage:	1.6KV
Safety Approval:	(cULus)pending

PART NUMBERS

NP

XX Number of contacts	X Pitch	X P.C.B Mounting	X Color	X Tail type	XXXX	X
End Stackable 01 to 16 1 to 16 contacts	1 10.0/.393"	1 Horizontal (180 wire inlet)	0 Black 5 Green (RAL 6018/T) 6 Blue (RAL 5015/A) 8 Grey (RAL 7004/P)	0 Parallel tail (A type) 1 Interlace tail (B type) (Front contact link together with end cover) 2 Interlace tail (C type) (After contact link together with end cover)	00J 0 Standard Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

NQ


XX Number of contacts	X Pitch	X Body Type	X Color	0	XXXX	X
End Stackable 01 to 10 1 to 10 contacts	0 2.5/0.10" 2 4.0/0.16"	0 With Flange (Only 2.5) 1 W/O Flange	0 Black 1 Natural Color		00J 0 Standard Any special item by customer request, please contact sales department.	G RoHS compliant (lead<4%) In copper Alloy H RoHS compliant (lead<1000ppm) In copper Alloy

SPRING CLAMP SYSTEM

NM



Pitch 3.5mm
Horizontal (180D wire inlet)
Poles 2p-24p
NMxx100100J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	7A Sol. / 10A Str.
Wire range:	
Solid wire(AWG):	18-24
Stranded wire(AWG):	16-22
Wire strip length:	12~13mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NM



Pitch 3.5mm
Vertical (90D wire inlet)
Poles 2p-24p
NMxx100000J0G*
Number of poles




Electrical:	cULus
Voltage rating:	300V
Current rating:	7A Sol. / 10A Str.
Wire range:	
Solid wire(AWG):	18-24
Stranded wire(AWG):	16-22
Wire strip length:	15~16mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

NM



Pitch 3.5mm
(45D wire inlet)
Poles 2p-24p
NMxx100200J0G*
Number of poles



Electrical:	cULus
Voltage rating:	300V
Current rating:	7A Sol. / 10A Str.
Wire range:	
Solid wire(AWG):	18-24
Stranded wire(AWG):	16-22
Wire strip length:	15~16mm
Withstanding Voltage:	1.6KV
Safety Approval:	cULus

PART NUMBERS

NM | XX Number of contacts | X Pitch | 0 | X Color | X Wire inlet | X X X X | X

Number of contacts
End Stackable
01 to 24 1 to 24 contacts

Pitch
1 3.5/.138"

Color
THT type
0 Black

DIP type
0 Black
3 Orange (RAL2011/P)
5 Green (RAL6018/T)
6 Blue (RAL5015/A)
8 Grey (RAL7004/P)

Wire inlet
0 Vertical (90D wire inlet)
1 Horizontal (180D wire inlet)
2 Slope (45D wire inlet)

X X X X
00J 0 THT Type
A0J 0 DIP Type
Any special item by customer request, please contact sales department.

X
G RoHS compliant (lead<4%) In copper Alloy
H RoHS compliant (lead<1000ppm) In copper Alloy


"*" means FCI Standard item, any other non-standard item, please consult FCI for up-to-date information.

TMBSRGCLPSYS0214A4

ACCESSORIES

OVERVIEW

There is a variety of accessories available. Ranging from assorted shells to installation tooling.




ACCESSORIES

AN-2P



AN02005000J0G*




Match with:
Male Header:EU 2P (Right)
EU 2P (Left)
Female Terminal Block:
TJ(5.0)2p (Contact on up side)

AN-4P



AN00005000J0G*




Match with:
Male Header:EU 4P (Right)
EU 4P (Left)
Female Terminal Block:
TJ(5.0)4p (Contact on up side)

AM-3P



Width: 15.2mm
AM00008000J0G*




Match with:
Male Header :EU 3P (Right)
EU 3P (Left)
Female Terminal Block:
TJ(5.0)3p (Contact on up side)

AM-4P



Width: 20.2mm
AM00008100J0G*



Match with:
Male Header:EU 4P (Right)
EU 4P (Left)
Female Terminal Block:
TJ(5.0)4p (Contact on up side)

PART NUMBERS

AN

00 0 0 X 0 — X X X X X

Color

- 00 4P
- 02 2P
- 5 Green (RAL 6018/T)
- 00J 0 Standard — Any special item by customer request, please contact sales department.
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

AM

00 0 0 X X — X X X X X

Color / Body Type

- 0 Black
- 5 Green (RAL 6018/T)
- 6 Blue
- 8 Grey (RAL 7035/D)
- C Green (RAL 6018/U)
- 0 15.2mm
- 1 20.2mm
- 00J 0 Standard — Any special item by customer request, please contact sales department.
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

ACCESSORIES

AP





Coding key
AP00002000J0G*

AE



Coding key (70°)
AE00002000J0G*





	VB	VC	ET	KK	KJ	KL
AP	●	●	●	●	●	●

	EV	EW	KT	KS		
AP	●	●	●	●		

Pitch 5.0/5.08/7.5/7.62

	TJ	TS	VM	VD	VH	EM
AE	●	●	●	●	●	●

	EZ	V7	V9	KI	EY	HI
AE	●	●	●	●	●	●

	HN	HP	HW	H4	KD	
AE	●	●	●	●	●	

PART NUMBERS

AP 00 0 0 X 0 — Color — XXXX X

- 2 Red (RAL3001/D)
- 00J 0 Standard
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

AE 00 0 0 X 0 — Color — XXXX X

- 2 Red (RAL3001/D)
- 00J 0 Standard
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

ACCESSORIES

AF





Coding key
AF00002000J0G*

AG



Coding key
AG00002000J0G*





Pitch 5.0/5.08/7.5/7.62

	OQ	VK	VE	VL	VF	VZ
AF	●	●	●	●	●	●

	V5	V8	H5	EU	KE	
AF	●	●	●	●	●	

Pitch 3.5/3.81

	OQ	VK	VL	VO	VZ	V5
AG	●	●	●	●	●	●

	V8	H5	VF	KE	EU	VS
AG	●	●	●	●	●	●

PART NUMBERS

AF 00 0 0 X 0 — Color — X X X X X

- 2 Red (RAL3001/D)
- 00J 0 Standard
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

AG 00 0 0 X 0 — Color — X X X X X

- 2 Red (RAL3001//D)
- 00J 0 Standard
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

ACCESSORIES

AU



Coding key (60°)
AU00002000J0G*




Pitch 5.0/5.08/7.5/7.62
(TJ 5.0&5.08 Contact on up side
HW 5.0/5.08 Contact on up side &
HW 5.08 Contact in the middle)

AI



AI00005000J0G*
AI with V7 5.0/5.08/7.5/7.62



Pitch 5.0/5.08/7.5/7.62

	V7					
AI	●					

PART NUMBERS

AU

00 0 0 X 0 — X X X X X

X (Color)
- 2 Red (RAL3001/D)

X X X X
- 00J 0 Standard

X
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

AI

00 0 0 X 0 — X X X X X

X (Color)
- 5 Green (RAL6018/T)

X X X X
- 00J 0 Standard


X
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

ACCESSORIES

AL




ALxxxx5000J0G* (72mm)



AL




ALxxxx5600J0G* (2-72mm)



AL




ALxxxx5100J0G* (107mm)



AL



ALxxxx5400J0G* (122mm)



PART NUMBERS

AL XXXX X X X X X X X X

PCB length

0450	45.0mm
0505	50.5mm
⋮	⋮
1000	100.0mm
450 to 1000	
45.0mm to100.0mm	

Color

5	Green (RAL6018/T)

Rail type

0	Width 72mm (assembled cover)
1	Width 107mm (assembled cover)
2	Width 72mm (but not assembled cover)
3	Width 107mm (but not assembled cover)
4	Width 122mm (assembled cover)
5	Width 122mm (but not assembled cover)
6	Width 2-72mm (assembled cover)
7	Width 2-72mm (but not assembled cover)

00J 0	Standard
W72 Rail (l=PCB L-1.8)	
W107 Rail (l=PCB L-3.8)	
01J0	Special type
02J0	Special type
03J0	Special type
.....	....
Serial number	

G	RoHS compliant (lead<4%) In copper Alloy
H	RoHS compliant (lead<1000ppm) In copper Alloy


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

ACCESSORIES

AJ

Handle
AJ00009000J0G*
AJ with HG5.0/5.08/7.5/7.62




Pitch 5.0/5.08/7.5/7.62

	HG					
AJ	●					

AK



Handle
AK00009000J0G*
AK with HI5.0/7.5/7.62



Pitch 5.0/7.5/7.62

	HI	NB				
Ak	●	●				

PART NUMBERS

AJ

00 0 0 X 0 — X X X X X

X — Color
- 9 White (RAL1102)

00J 0 Standard

G RoHS compliant (lead<4%) In copper Alloy

H RoHS compliant (lead<1000ppm) In copper Alloy

AK

00 0 0 X 0 — X X X X X

X — Color
- 9 White (RAL1102)

00J 0 Standard

G RoHS compliant (lead<4%) In copper Alloy


H RoHS compliant (lead<1000ppm) In copper Alloy

ACCESSORIES

AS




Poles 2P-24P
ASxx005000J0G*
Number of poles




Used for V8 W/F SERIES (V8+TJ 5.08mm)
Used for H5 W/F SERIES (H5+HW 5.08mm)

AT



Rail
With NB or Ds240
AT00008000J0G*



Used for NB with snap-in mounting feet type
Used for Th35 Dinrail

PART NUMBERS

AS

XX	X	0	X	0	X X X X	X
Number of contacts	Pitch		Color			

Solid Block
02 to 24 2 to 24 contacts

0 5.08/.20"

0 Black
5 Green (RAL 6018/T)
6 Blue (RAL5015/A)
8 Grey (RAL 7035/D)
C Green (RAL 6018/U)

00J 0 Standard

Any special item by customer request, please contact sales department.

G RoHS compliant (lead<4%) In copper Alloy

H RoHS compliant (lead<1000ppm) In copper Alloy

AT

00	0	0	X	0	X X X X	X
			Color			

0 Black
5 Green (RAL6018/T)
6 Blue (RAL5015/D)
8 Grey (RAL7035/D)
C Green (RAL6018/U)

00J 0 Standard

G RoHS compliant (lead<4%) In copper Alloy

H RoHS compliant (lead<1000ppm) In copper Alloy

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

ACCESSORIES

AD



Pitch 5.08mm
Poles 16P/18P
AD16505000J0G*
AD18505000J0G*
Number of poles




AD Cover 16p with TJ-5.08-16P used.
AD Cover 18p with TJ-5.08-18P used.

ANAA



ANAA006000J0G*
With AN
Number of poles



Used for AN series

PART NUMBERS

AD — XX (Number of contacts) X (Pitch) 0 X (Color) 0 | XXXX X

- Number of contacts: Solid Block; 16 — 16 contacts; 18 — 18 contacts
- Pitch: 5 — 5.08/.20"
- Color: 5 — Green (RAL 6018/T)
- XXXX: 00J 0 — Standard. Any special item by customer request, please contact sales department.
- X: G — RoHS compliant (lead<4%) In copper Alloy; H — RoHS compliant (lead<1000ppm) In copper Alloy

ANAA — 00 X (Color) 0 | XXXX X


- Color: 0 — Black; 5 — Green (RAL6018/T); 6 — Blue (RAL5015/D); 8 — Grey (RAL7035/D)
- XXXX: 00J 0 — Standard
- X: G — RoHS compliant (lead<4%) In copper Alloy; H — RoHS compliant (lead<1000ppm) In copper Alloy

ACCESSORIES

AH



Coding key
AH0000X000J0G*
AH with OQ 5.0/5.08



Pitch 5.0/5.08

	OQ	VK	VL	VF	V8	V5
AH	●	●	●	●	●	●

	VZ	H5	KE			
AH	●	●	●			

PART NUMBERS

AH 00 0 0 X 0 X X X X X

X = Color

- 5 Green (RAL6018/T)

X X X X = 00J 0 Standard

X =
- G RoHS compliant (lead<4%) In copper Alloy
- H RoHS compliant (lead<1000ppm) In copper Alloy

"*" means FCI Standard item, any other non-standard item, please consult FCI for up-to-date information.

TMBACCESSORI0214A4

Disclaimer
Please note that the above information is subject to change without notice.

BARRIER TERMINAL BLOCKS

OVERVIEW


There is a variety of barrier terminal blocks available. The pitch sizes range from 7.62mm to 16.00mm.



BARRIER TERMINAL BLOCKS

YK - 301 PITCH-7.62mm






Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22~14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus


YK - 302 PITCH-7.62mm






Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22~14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus


YK - 303 PITCH-7.62mm






Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22~14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus


YK - 304 PITCH-7.62mm






Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22~14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus


YK - 305 PITCH-7.62mm






Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22~14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus


YK - 306 PITCH-7.62mm






Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22~14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus


YK - 301 PITCH-7.62mm W/o cover






Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22~14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus

YK - 302 PITCH-7.62mm W/o cover






Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22~14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

BARRIER TERMINAL BLOCKS


YK - 303 PITCH-7.62mm W/o cover






Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22~14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus


YK - 304 PITCH-7.62mm W/o cover






Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22~14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus


YK - 305 PITCH-7.62mm W/o cover






Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22~14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus

YK - 306 PITCH-7.62mm W/o cover







Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22~14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus

YK - 30 Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20										
A		17.16	24.78	32.40	40.02	47.64	55.26	62.88	70.50	78.12	85.74	93.36	100.98	108.60	116.22	123.84	131.46	139.08	146.70	154.32										
B		7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58	76.20	83.82	91.44	99.06	106.68	114.30	121.92	129.54	137.16	144.78										


YK - 401 PITCH-8.25mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	7 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus


YK - 402 PITCH-8.25mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	7 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus

YK - 403 PITCH-8.25mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	7 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus

YK - 401 PITCH-8.25mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	7 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus

BARRIER TERMINAL BLOCKS

YK - 402 PITCH-8.25mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	7 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cRUus

YK - 403 PITCH-8.25mm W/o cover







Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	7 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cRUus

YK - 40 Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		18.50	26.75	35.00	43.25	51.50	59.75	68.00	76.25	84.50	92.75	101.00	109.25	117.50	125.75	134.00	142.25	150.50	158.75	167.00	175.25	183.50	189.75	200.00	208.25	216.50	224.75	233.00	241.25	249.50
B		8.25	16.50	24.75	33.00	41.25	49.50	57.75	66.00	74.25	82.50	90.75	99.00	107.25	115.50	123.75	132.00	140.25	148.50	156.75	165.00	173.25	181.50	189.75	198.00	206.25	214.50	222.75	231.00	239.25


YK-501 PITCH-9.50mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK-502 PITCH-9.50mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK-503 PITCH-9.50mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK-504 PITCH-9.50mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

BARRIER TERMINAL BLOCKS


YK - 505 PITCH-9.50mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 506 PITCH-9.50mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 501 PITCH-9.50mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 502 PITCH-9.50mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK - 503 PITCH-9.50mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK - 504 PITCH-9.50mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 505 PITCH-9.50mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 506 PITCH-9.50mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK - 50 Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		22.00	31.50	41.00	50.50	60.00	69.50	79.00	88.50	98.00	107.5	117.0	126.50	136.00	145.50	155.00	164.50	174.00	183.50	193.00	202.50	212.00	221.50	231.00	240.50	250.00	259.50	269.00	278.50	288.00
B		9.50	19.00	28.50	38.00	47.50	57.00	66.50	76.00	85.50	95.00	104.5	114.0	123.50	133.00	142.50	152.00	161.50	171.00	180.50	190.00	199.50	209.00	218.50	228.00	237.50	247.00	256.50	266.00	275.50

BARRIER TERMINAL BLOCKS

YK - 50A **PITCH-9.50mm**






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 50A **PITCH-9.50mm** W/o cover







Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 50A Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18											
A		21.5	31.0	40.5	50.0	59.5	69.0	78.5	88.0	97.5	107.0	117.0	126.0	136.0	145.0	155.0	164.0	174.0											
B		9.5	19.0	28.5	38.0	47.5	57.0	66.5	76.0	85.0	95.0	105.0	114.0	124.0	133.0	143.0	152.0	162.0											


YK - 601 **PITCH-10.0mm**






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK - 602 **PITCH-10.0mm**






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK - 603 **PITCH-10.0mm**






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 604 **PITCH-10.0mm**






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

BARRIER TERMINAL BLOCKS


YK - 605 PITCH-10.0mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 606 PITCH-10.0mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 601 PITCH-10.0mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 602 PITCH-10.0mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 603 PITCH-10.0mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 604 PITCH-10.0mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 605 PITCH-10.0mm W/o cover






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 606 PITCH-10.0mm W/o cover





Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK - 60 Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		23.5	33.5	43.5	53.5	63.5	73.5	83.5	93.5	103.5	113.5	123.5	133.5	143.5	153.5	163.5	173.5	183.5	193.5	203.5	213.5	223.5	233.5	243.5	253.5	263.5	273.5	283.5	293.5	303.5
B		10.0	20.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0	110.0	120.0	130.0	140.0	150.0	160.0	170.0	180.0	190.0	200.0	210.0	220.0	230.0	240.0	250.0	260.0	270.0	280.0	290.0

BARRIER TERMINAL BLOCKS

YK - 701 PITCH-11.0mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	13 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	cULus

YK - 701 PITCH-11.0mm W/o cover






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	13 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	cULus

YK - 70A PITCH-11.0mm






Materials Electrical	
Rated:	300V 40A/600V 5A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	16 Lb-In.
Suitable Electric Wire:	18 ~ 8AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.0t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	cULus

YK - 70A PITCH-11.0mm W/o cover





Materials Electrical	
Rated:	300V 40A/600V 5A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	16 Lb-In.
Suitable Electric Wire:	18 ~ 8AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.0t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	cULus

YK - 70 Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		24.0	35.0	46.0	57.0	68.0	79.0	90.0	101.0	112.0	123.0	134.0	145.0	156.0	167.0	178.0	189.0	200.0	211.0	222.0	233.0	244.0	255.0	266.0	277.0	288.0	299.0	310.0	321.0	332.0
B		11.0	22.0	33.0	44.0	55.0	66.0	77.0	88.0	99.0	110.0	121.0	132.0	143.0	154.0	165.0	176.0	187.0	198.0	209.0	220.0	231.0	242.0	253.0	264.0	275.0	286.0	297.0	308.0	319.0

YK - 70A Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
A		25.0	36.0	47.0	58.0	69.0	80.0	91.0	102.0	113.0	124.0	135.0	146.0	157.0	168.0	179.0
B		11.0	22.0	33.0	44.0	55.0	66.0	77.0	88.0	99.0	110.0	121.0	132.0	143.0	154.0	165.0

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

BARRIER TERMINAL BLOCKS

YK - 901 **PITCH-16.0mm**



Tail length:4.0mm




Materials Electrical	
Rated:	600V 65A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	26 Lb-In.
Suitable Electric Wire:	10 ~ 6AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.6t Tin Plated
3)Terminal Screw:	Steel M6.0 Ni Plated
Approval:	cRUus

YK - 901 **PITCH-16.0mm** W/o cover



Tail length:4.0mm




Materials Electrical	
Rated:	600V 65A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	26 Lb-In.
Suitable Electric Wire:	10 ~ 6AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.6t Tin Plated
3)Terminal Screw:	Steel M6.0 Ni Plated
Approval:	cRUus

YK - 902 **PITCH-16.0mm**



Tail length:6.0mm




Materials Electrical	
Rated:	600V 65A
Insulation Withstands Voltage:	AC3000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	26 Lb-In.
Suitable Electric Wire:	10 ~ 6AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.6t Tin Plated
3)Terminal Screw:	Steel M6.0 Ni Plated
Approval:	cRUus

YK - 902 **PITCH-16.0mm** W/o cover



Tail length:6.0mm



Materials Electrical	
Rated:	600V 65A
Insulation Withstands Voltage:	AC3000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	26 Lb-In.
Suitable Electric Wire:	10 ~ 6AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.6t Tin Plated
3)Terminal Screw:	Steel M6.0 Ni Plated
Approval:	cRUus

YK - 90 Series

POLE		2	3	4	5	6	7	8	9	10																			
A		36.0	52.0	68.0	84.0	100.0	116.0	132.0	148.0	164.0																			
B		16.0	32.0	48.0	64.0	80.0	96.0	112.0	128.0	144.0																			


PART NUMBERS


YK | XX Series No | X Changable code | XX Number of contacts | X Cover & Flange | X Screw & Contacts plating | X Body logo | X X X

- XX Series No: 30 Series, 40 Series, 50 Series, 60 Series, 70 Series, 90 Series, ...
- X Changable code: 1, 2, 3, 4, 5, ..., A, B, C, ...
- XX Number of contacts: 02, 03, 04, ..., 10, 11, 12, ..., 20, ..., 30, ...
- X Cover & Flange:
  - 0 W/O Flange & W/O Cover (only YK30/40/50/60/90)
  - 1 With Flange & With Cover
  - 2 W/O Flange & With Cover (only YK30/40/50/60/90)
  - 3 With Flange & W/O Cover
- X Screw & Contacts plating:
  - 0 Screw & Contacts plating G/F
  - 1 Screw plating Ni & contacts plating G/F
  - 2 Screw plating G/F & contacts plating Sn
  - 3 Screw plating Ni & contacts plating Sn (standard)
- X Body logo:
  - 0 "@" logo (standard)
- X X:
  - Customer's special requirements "J1~JZ"
  - J0 Standard
- X:
  - G RoHS compliant (lead<4%) In copper Alloy
  - H RoHS compliant (lead<1000ppm) In copper Alloy

BARRIER TERMINAL BLOCKS

YK - 211 **PITCH-6.35mm**





Materials Electrical	
Rated:	300V 10A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	6.5 Lb-In.
Suitable Electric Wire:	22 ~ 16AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 21 Series


POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		13.70	20.05	26.40	32.75	39.10	45.45	51.80	58.15	64.50	70.85	77.20	83.55	89.90	96.25	102.60	108.95	115.30	121.65	128.00	134.35	140.70	147.05	153.40	159.75	166.10	172.45	178.80	185.15	191.45
B		6.35	12.70	19.05	25.40	31.75	38.10	44.45	50.80	57.15	63.50	69.85	76.20	82.55	88.90	95.25	101.60	107.95	114.30	120.65	127.00	133.35	133.35	146.05	152.40	158.75	165.10	171.45	177.80	184.15


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

BARRIER TERMINAL BLOCKS

YK - 311 PITCH-7.62mm






Materials Electrical	
Rated:	250V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.3 Lb-In.
Suitable Electric Wire:	22 ~ 16AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	


YK - 312 PITCH-7.62mm






Materials Electrical	
Rated:	250V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.3 Lb-In.
Suitable Electric Wire:	22 ~ 16AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 313 PITCH-7.62mm






Materials Electrical	
Rated:	250V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.3 Lb-In.
Suitable Electric Wire:	22 ~ 16AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 314 PITCH-7.62mm





Materials Electrical	
Rated:	250V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.3 Lb-In.
Suitable Electric Wire:	22 ~ 16AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	


YK - 31 Series (311-314)

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		16.74	24.36	31.98	39.60	47.22	54.84	62.46	70.08	77.70	85.32	92.94	100.56	108.18	115.80	123.42	131.04	138.66	146.28	153.90	161.52	169.14	176.76	184.38	192.00	199.62	207.24	214.86	222.48	230.10
B		7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58	76.20	83.82	91.44	99.06	106.68	114.3	121.92	129.54	137.16	144.78	152.40	160.02	167.64	175.26	182.88	190.50	198.12	205.74	213.36	220.98

BARRIER TERMINAL BLOCKS


YK - 315 PITCH-7.62mm






Materials Electrical	
Rated:	250V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.3 Lb-In.
Suitable Electric Wire:	22 ~ 16AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 316 PITCH-7.62mm





Materials Electrical	
Rated:	250V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.3 Lb-In.
Suitable Electric Wire:	22 ~ 16AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 31 Series (315-316)

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		23.5	33.5	43.5	53.5	63.5	73.5	83.5	93.5	103.5	113.5	123.5	133.5	143.5	153.5	163.5	173.5	183.5	193.5	203.5	213.5	223.5	233.5	243.5	253.5	263.5	273.5	283.5	293.5	303.5
B		10.0	20.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0	110.0	120.0	130.0	140.0	150.0	160.0	170.0	180.0	190.0	200.0	210.0	220.0	230.0	240.0	250.0	260.0	270.0	280.0	290.0


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

BARRIER TERMINAL BLOCKS

YK - 321 PITCH-7.62mm







Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.2 Lb-In.
Suitable Electric Wire:	22 ~ 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel #5-40UNC Ni Plated
Approval:	

YK - 32 Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		16.10	23.72	31.34	38.96	46.58	54.20	61.82	69.44	77.06	84.68	92.30	99.92	107.54	115.16	122.78	130.40	138.02	145.64	153.26	160.88	168.85	176.12	183.74	191.36	198.98	206.60	214.22	221.84	229.46
B		7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58	76.20	83.82	91.44	99.06	106.68	114.3	121.92	129.54	137.16	144.78	152.40	160.02	167.64	175.26	182.88	190.50	198.12	205.74	213.36	220.98


YK - 411 PITCH-8.25mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 412 PITCH-8.25mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	


YK - 413 PITCH-8.25mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 414 PITCH-8.25mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

BARRIER TERMINAL BLOCKS


YK - 415 PITCH-8.25mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus

YK - 421 PITCH-8.25mm





Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	cULus

YK - 41 Series (411-415)

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20										
A		19.00	27.25	35.50	43.75	52.00	60.25	68.50	76.75	85.00	93.25	101.50	109.75	118.00	126.25	134.50	142.75	151.00	159.25	167.50										
B		8.25	16.50	24.75	33.00	41.25	49.50	57.75	66.00	74.25	82.50	90.75	99.00	107.25	115.50	123.75	132.00	140.25	148.50	156.75										

YK - 42 Series


POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20										
A		17.50	25.75	34.00	42.25	50.50	58.75	67.00	75.25	83.50	91.75	100.00	108.25	118.00	126.25	134.50	142.75	151.00	159.25	167.50										
B		8.25	16.50	24.75	33.00	41.25	49.50	57.75	66.00	74.25	82.50	90.75	99.00	107.25	115.50	123.75	132.00	140.25	148.50	156.75										


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

BARRIER TERMINAL BLOCKS


YK - 510 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	(cRUus)pending


YK - 511 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK - 512 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK - 513 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK - 514 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK - 515 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus

YK - 516 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	cRUus


YK - 51 Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		21.00	30.50	40.00	49.50	59.00	68.50	78.00	87.50	97.00	106.5	116.0	125.50	135.00	144.50	154.00	163.50	173.00	182.50	192.00	201.50	211.00	220.50	230.00	239.50	249.00	258.50	268.00	277.50	287.00
B		9.50	19.00	28.50	38.00	47.50	57.00	66.50	76.00	85.50	95.00	104.5	114.0	123.50	133.00	142.50	152.00	161.50	171.00	180.50	190.00	199.50	209.00	218.50	228.00	237.50	247.00	256.50	266.00	275.50

BARRIER TERMINAL BLOCKS


YK - 611 PITCH-10.0mm






Materials Electrical	
Rated:	300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	


YK - 612 PITCH-10.0mm






Materials Electrical	
Rated:	300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	


YK - 613 PITCH-10.0mm






Materials Electrical	
Rated:	300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	


YK - 614 PITCH-10.0mm






Materials Electrical	
Rated:	300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	


YK - 615 PITCH-10.0mm






Materials Electrical	
Rated:	300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	

YK - 616 PITCH-10.0mm





Materials Electrical	
Rated:	300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	

YK - 61 Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		22.0	32.0	42.0	52.0	62.0	72.0	82.0	92.0	102.0	112.0	122.0	132.0	142.0	152.0	162.0	172.0	182.0	192.0	202.0	212.0	222.0	232.0	242.0	252.0	262.0	272.0	282.0	292.0	302.0
B		10.0	20.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0	110.0	120.0	130.0	140.0	150.0	160.0	170.0	180.0	190.0	200.0	210.0	220.0	230.0	240.0	250.0	260.0	270.0	280.0	290.0

For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

BARRIER TERMINAL BLOCKS

YK - 61A

PITCH-10.0mm





Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12.0 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	

P = Number of poles (2p~30p)

Dim A	N*10.0+1.90
Dim B	(N-1)*10.0

PART NUMBERS


YK | XX Series No | X Changable code | XX Number of contacts | X Cover & Flange | X Screw & Contacts plating | X Body logo | X X X

- XX Series No: 21 Series; 31 Series; 32 Series; 41 Series; 42 Series; 51 Series; 61 Series; .....
- X Changable code: 1; 2; 3; 4; 5; ...; A; B; C; ...
- XX Number of contacts: 02; 03; 04; ...; 10; 11; 12; ...; 20; ...; 30; ...
- X Cover & Flange: 0 W/O Flange & W/O cover; 3 With Flange & W/O cover
- X Screw & Contacts plating: 0 Screw & Contacts plating G/F; 1 Screw plating Ni & contacts plating G/F; 2 Screw plating G/F & contacts plating Sn; 3 Screw plating Ni & contacts plating Sn (standard)
- X Body logo: 0 "@" logo (standard)
- X: Customer's special requirements "J1~JZ"; J0 Standard
- X: G RoHS compliant (lead<4%) In copper Alloy; H RoHS compliant (lead<1000ppm) In copper Alloy

BARRIER TERMINAL BLOCKS

YK - 111 PITCH-11.0mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	11.0 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.2t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	

N = Number of poles (2p~30p)

Dim A	(N+1)*11.0+8.0
Dim B	N*11.0+0.2
Dim C	(N+1)*11.0+1.0
Dim D	(N-1)*11.0

YK - 112 PITCH-11.0mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	11.0 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.2t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	

N = Number of poles (2p~30p)

Dim A	(N+1)*11.0+8.0
Dim B	N*11.0+0.2
Dim C	(N+1)*11.0+1.0
Dim D	(N-1)*11.0

YK - 113 PITCH-11.0mm







Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	11.0 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.2t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	

N = Number of poles (2p~30p)

Dim A	(N+1)*11.0+8.0
Dim B	N*11.0+0.2
Dim C	(N+1)*11.0+1.0
Dim D	(N-1)*11.0

YK - 114 PITCH-11.0mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	11.0 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.2t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	

N = Number of poles (2p~30p)

Dim A	(N+1)*11.0+8.0
Dim B	N*11.0+0.2
Dim C	(N+1)*11.0+1.0
Dim D	(N-1)*11.0

YK - 11E 3P PITCH-15.0mm






Materials Electrical	
Rated:	150V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.7 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.5t Tin Plated
3)Terminal Screw:	Steel M5.0 Ni Plated
Approval:	

YK - 11E 4P PITCH-11.0mm






Materials Electrical	
Rated:	150V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.7 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.3t Tin Plated
3)Terminal Screw:	Steel M5.0 Ni Plated
Approval:	


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

BARRIER TERMINAL BLOCKS


YK - 221 PITCH-6.35mm






Materials Electrical	
Rated:	250V 10A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.3 Lb-In.
Suitable Electric Wire:	22 ~ 18AWG/22 - 18AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 222 PITCH-6.35mm






Materials Electrical	
Rated:	250V 10A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.3 Lb-In.
Suitable Electric Wire:	22 ~ 18AWG/22 - 18AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 223 PITCH-6.35mm






Materials Electrical	
Rated:	250V 10A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.3 Lb-In.
Suitable Electric Wire:	22 ~ 18AWG/22 - 18AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 224 PITCH-6.35mm






Materials Electrical	
Rated:	250V 10A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	5.3 Lb-In.
Suitable Electric Wire:	22 ~ 18AWG/22 - 18AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	


YK - 22 Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		13.70	20.05	26.40	32.75	39.10	45.45	51.80	58.15	64.50	70.85	77.20	83.55	89.90	96.25	102.60	108.95	115.30	121.65	128.00	134.35	140.7	147.05	153.4	159.75	166.1	172.45	178.8	185.15	191.5
B		6.35	12.70	19.05	25.40	31.75	38.10	44.45	50.80	57.15	63.50	69.85	76.20	82.55	88.90	95.25	101.60	107.95	114.30	120.65	127.0	133.35	139.70	146.05	152.40	158.75	165.10	171.45	177.80	184.15

BARRIER TERMINAL BLOCKS

YK - 331 PITCH-8.25mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG/22 - 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 332 PITCH-8.25mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG/22 - 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	


YK - 333 PITCH-8.25mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG/22 - 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	


YK - 334 PITCH-8.25mm






Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG/22 - 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 335 PITCH-8.25mm





Materials Electrical	
Rated:	300V 20A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	8.8 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG/22 - 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

YK - 33 Series


POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		18.50	26.75	35.00	43.25	51.50	59.75	68.00	76.25	84.50	92.75	101.00	109.25	117.25	125.75	134.25	142.25	150.50	158.75	167.00	175.25	183.50	191.75	200.00	208.25	216.50	224.75	233.00	241.25	249.25
B		8.25	16.50	24.75	33.00	41.25	49.50	57.75	66.00	74.25	82.50	90.75	99.00	107.25	115.50	123.75	132.00	140.25	148.50	156.75	165.0	173.25	181.50	189.75	198.00	206.25	214.5	222.75	231.0	239.25


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks

Disclaimer
Please note that the above information is subject to change without notice.

BARRIER TERMINAL BLOCKS

YK - 441 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A/300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	10.54 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG/22 - 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	


YK - 442 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A/300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	10.54 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG/22 - 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	


YK - 443 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A/300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	10.54 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG/22 - 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	

YK - 444 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A/300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	10.54 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG/22 - 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	


YK - 445 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A/300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	10.54 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG/22 - 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	


YK - 446 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A/300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	10.54 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG/22 - 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	


YK - 447 PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A/300V 25A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	10.54 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG/22 - 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	

YK - 44A PITCH-9.50mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	10.54 Lb-In.
Suitable Electric Wire:	22 ~ 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	( )pending


YK - 44 Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		20.50	30.00	39.50	49.00	58.50	68.00	77.50	87.00	96.50	106.0	115.5	125.00	134.50	144.00	153.50	163.00	172.50	182.00	191.50	201.00	210.50	220.00	229.50	239.00	248.50	258.00	267.50	277.00	286.50
B		9.50	19.00	28.50	38.00	47.50	57.00	66.50	76.00	85.50	95.00	104.5	114.0	123.50	133.00	142.50	152.00	161.50	171.00	180.50	190.00	199.50	209.00	218.50	228.00	237.50	247.00	256.50	266.00	275.50

BARRIER TERMINAL BLOCKS


YK - 551 PITCH-11.0mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	9.5 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	

YK - 552 PITCH-11.0mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	9.5 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	

YK - 553 PITCH-11.0mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	9.5 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	


YK - 554 PITCH-11.0mm






Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	9.5 Lb-In.
Suitable Electric Wire:	22 ~ 10AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	

YK - 555 PITCH-11.0mm





Materials Electrical	
Rated:	300V 30A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	9.5 Lb-In.
Suitable Electric Wire:	12 ~ 22AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	

YK - 55 Series

POLE		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A		24.00	35.00	46.00	57.00	68.00	79.00	90.00	101.00	112.0	123.0	134.0	145.0	156.0	167.0	178.0	189.0	200.0	211.0	222.0										
B		11.00	22.00	33.00	44.00	55.00	66.00	77.00	88.00	99.00	110.0	121.0	132.0	143.0	154.0	165.0	176.0	187.0	198.0	209.0										


For more information,
please contact: Communications@fci.com
or visit us at www.fci.com/terminalblocks


Disclaimer
Please note that the above information is subject to change without notice.

BARRIER TERMINAL BLOCKS

YK - 881(2P - 20P)

PITCH-12.7mm






Materials Electrical	
Rated:	600V 45A
Insulation Withstands Voltage:	AC2500V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	16.0 Lb-In.
Suitable Electric Wire:	18 ~ 8AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 1.6t Tin Plated
3)Terminal Screw:	Steel M4.0 Ni Plated
Approval:	

P = Number of poles (2p~20p)


Dim A	(N-1)*12.7+15.24
Dim B	(N-1)*12.7


PART NUMBERS



BARRIER TERMINAL BLOCKS

YK - 66 (2*2P - 2*21P)
PITCH-7.62mm







Materials Electrical	
Rated:	300V 15A
Insulation Withstands Voltage:	AC2000V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	7.0 Lb-In.
Suitable Electric Wire:	22 ~ 12AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.0 Ni Plated
Approval:	

P = Number of poles (2*2p~2*21p)

Dim A	(P/2-1)*7.62+18.19
Dim B	(P/2-1)*7.62

YK - 77 (2*2P - 2*15P)
PITCH-9.52mm






Materials Electrical	
Rated:	300V 10A
Insulation Withstands Voltage:	AC2500V/min
Insulation Resistance:	1000MΩ or More at DC500V
Using Temperature Range:	-40℃ ~ +115℃
Screw Torque Value:	12.0 Lb-In.
Suitable Electric Wire:	20 ~ 14AWG
1)Molded Parts:	Thermoplastic UL94V-0 Black
2)Terminal:	Brass 0.8t Tin Plated
3)Terminal Screw:	Steel M3.5 Ni Plated
Approval:	

P = Number of poles (2*2p~2*15p)

Dim A	(P/2-1)*9.525+16.8
Dim B	(P/2-1)*9.525

PART NUMBERS



TMBBARRIERTB0214A4

FCI P/N	DINKLE P/N
Wire Protector System	
TC02236200J0G	ED508V
TDXX016100J0G	ED500R
T5XX015000J0G	ED350V
T3XX045100J0G	DT-126VP
T3XX045300J0G	DT-126RP
T4XX045000J0G	166
T4XX245000J0G	166-..P3
TR01055100J0G	DT-123RA
TR01255100J0G	DT-123RA-..P3
KH02055100J0G	DT-2300-02P
KH03055100J0G	DT-2300-03P
~	~
KH12055100J0G	DT-2300-12P
KH02055000J0G	DT-2301-02P
KH03055000J0G	DT-2301-03P
~	~
KH12055000J0G	DT-2301-12P
KH02155100J0G	DT-2320-02P
KH03155100J0G	DT-2320-03P
~	~
KH12155100J0G	DT-2320-12P
KH02155000J0G	DT-2321-02P
KH03155000J0G	DT-2321-03P
~	~
KH12155000J0G	DT-2321-12P

FCI P/N	DINKLE P/N
Rising Clamp System	
T202015100J0G	EK500A-02P
T203015100J0G	EK500A-03P
~	~
T224015100J0G	EK500A-24P
T202215100J0G	EK508A-02P
T203215100J0G	EK508A-03P
~	~
T224215100J0G	EK508A-24P
TO02015200J0G	ELK500V-02P
TO03015200J0G	ELK500V-03P
~	~
TO24015200J0G	ELK500V-24P
YC02215000J0G	ELK508V-02P
YC03215000J0G	ELK508V-03P
~	~
YC24215000J0G	ELK508V-24P
ED02315000J0G	ESK381V-02P
ED03315000J0G	ESK381V-03P
~	~
ED24315000J0G	ESK381V-24P
YD02015000J0G	EK500V-02p
YD03015000J0G	EK500V-03p
~	~
YD24015000J0G	EK500V-24p
YD02215000J0G	EK508V-02p
YD03215000J0G	EK508V-03p
~	~
YD24215000J0G	EK508V-24p
VJ02015200J0G	EHK500V-02P
VJ03015200J0G	EHK500V-03P
VJ02015000J0G	EHK500R-02P
VJ03015000J0G	EHK500R-03P
VJ02215200J0G	EHK508V-02P
VJ03215200J0G	EHK508V-03P
VJ02215000J0G	EHK508R-02P
VJ03215000J0G	EHK508R-03P
VJ02415200J0G	EHK750V-02P
VJ03415200J0G	EHK750V-03P
VJ02615200J0G	EHK762V-02P
VJ03615200J0G	EHK762V-03P
YE02015000J0G	EEK500V-02P
YE03015000J0G	EEK500V-03P
~	~
YE24015000J0G	EEK500V-24P
YE02215000J0G	EEK508V-02P
YE03215000J0G	EEK508V-03P
~	~
YE24215000J0G	EEK508V-24P
YL04015000J0G	EK500V4R-04P
YL04015000J0G	EK500V4R-06P
~	~
YL48015000J0G	EK500V4R-48P
YL04215000J0G	EK500V4L-04P
YL06215000J0G	EK500V4L-06P
~	~

FCI P/N	DINKLE P/N
Rising Clamp System	
YL48215000J0G	EK500V4L-48P
YL04415000J0G	EK508V4R-04P
YL06415000J0G	EK508V4R-06P
~	~
YL48415000J0G	EK508V4R-48P
YL04615000J0G	EK508V4L-04P
YL06615000J0G	EK508V4L-06P
~	~
YL48615000J0G	EK508V4L-48P
YO02015000J0G	EK350V-02P
YO03015000J0G	EK350V-03P
~	~
YO24015000J0G	EK350V-24P
YO02215000J0G	EK381V-02P
YO03215000J0G	EK381V-03P
~	~
YO24215000J0G	EK381V-24P
YP02215000J0G	EEK381V-02P
YP03215000J0G	EEK381V-03P
~	~
YP24215000J0G	EEK381V-24P
YP022150A0J0G	EESK381V-02P
YP032150A0J0G	EESK381V-03P
~	~
YP242150A0J0G	EESK381V-24P
YQ04015000J0G	EK350V4R-04P
YQ06015000J0G	EK350V4R-06P
~	~
YQ48015000J0G	EK350V4R-48P
YQ04215000J0G	EK350V4L-04P
YQ06215000J0G	EK350V4L-06P
~	~
YQ48215000J0G	EK350V4L-48P
YQ04415000J0G	EK381V4R-04P
YQ06415000J0G	EK381V4R-06P
~	~
YQ48415000J0G	EK381V4R-48P
YQ04615000J0G	EK381V4L-04P
YQ06615000J0G	EK381V4L-06P
~	~
YQ48615000J0G	EK381V4L-48P
YQ046150A0J0G	ESK381V4L-04P
YQ066150A0J0G	ESK381V4L-06P
~	~
YQ486150A0J0G	ESK381V4L-48P
YA06015100J0G	EK381V3L-06p
YA09015100J0G	EK381V3L-09p
~	
YA36015100J0G	EK381V3L-72p
YF02015000J0G	E3K500V-02P
YF03015000J0G	E3K500V-03P
~	~
YF24015000J0G	E3K500V-24P
YF02215000J0G	E3K508V-02P
YF03215000J0G	E3K508V-03P

FCI P/N	DINKLE P/N
Rising Clamp System	
~	~
YF24215000J0G	E3K508V-24P
YM04015000J0G	EK500V2R-04P
YM06015000J0G	EK500V2R-06P
	~
YM48015000J0G	EK500V2R-48P
YM04215000J0G	EK500V2L-04P
YM06215000J0G	EK500V2L-06P
~	~
YM48215000J0G	EK500V2L-48P
YM04415000J0G	EK508V2R-04P
YM06415000J0G	EK508V2R-06P
~	~
YM48415000J0G	EK508V2R-48P
YM04615000J0G	EK508V2L-04P
YM06615000J0G	EK508V2L-06P
~	~
YM48615000J0G	EK508V2L-48P
YN06015000J0G	EK500V3L-06P
YN09015000J0G	EK500V3L-09P
~	~
YN72015000J0G	EK500V3L-72P
YN06215000J0G	EK508V3L-06P
YN09215000J0G	EK508V3L-09P
~	~
YN72215000J0G	EK508V3L-72P
YH06215100J0G	EHK508V3L-06P
YH09215100J0G	EHK508V3L-09P
~	~
YH72215100J0G	EHK508V3L-72P
VV04015000J0G	EKB635V-04P
VV06015000J0G	EKB635V-06P
YS04215000J0G	EELK508V-04P
YS06215000J0G	EELK508V-06P
~	~
YS32215000J0G	EELK508V-32P
TV02115000J0G	EK350A-02P
TV03115000J0G	EK350A-03P
~	~
TV24115000J0G	EK350A-24P
TV02315000J0G	EK381A-02P
TV03315000J0G	EK381A-03P
~	~
TV24315000J0G	EK381A-24P
KP02015000J0G	EPK635VS-02P
KP03015000J0G	EPK635VS-02P
~	~
KP12015000J0G	EPK635VS-12P
KP02215000J0G	EPK116VS-02P
KP03215000J0G	EPK116VS-03P
~	~
KP12215000J0G	EPK116VS-12P
T702035000J0G	ESK635V-02P
T703035000J0G	ESK635V-03P
T702435000J0G	ESK762V-02P

FCI P/N	DINKLE P/N
Rising Clamp System	
YL48215000J0G	EK500V4L-48P
YL04415000J0G	EK508V4R-04P
YL06415000J0G	EK508V4R-06P
~	~
YL48415000J0G	EK508V4R-48P
YL04615000J0G	EK508V4L-04P
YL06615000J0G	EK508V4L-06P
~	~
YL48615000J0G	EK508V4L-48P
YO02015000J0G	EK350V-02P
YO03015000J0G	EK350V-03P
~	~
YO24015000J0G	EK350V-24P
YO02215000J0G	EK381V-02P
YO03215000J0G	EK381V-03P
~	~
YO24215000J0G	EK381V-24P
YP02215000J0G	EEK381V-02P
YP03215000J0G	EEK381V-03P
~	~
YP24215000J0G	EEK381V-24P
YP022150A0J0G	EESK381V-02P
YP032150A0J0G	EESK381V-03P
~	~
YP242150A0J0G	EESK381V-24P
YQ04015000J0G	EK350V4R-04P
YQ06015000J0G	EK350V4R-06P
~	~
YQ48015000J0G	EK350V4R-48P
YQ04215000J0G	EK350V4L-04P
YQ06215000J0G	EK350V4L-06P
~	~
YQ48215000J0G	EK350V4L-48P
YQ04415000J0G	EK381V4R-04P
YQ06415000J0G	EK381V4R-06P
~	~
YQ48415000J0G	EK381V4R-48P
YQ04615000J0G	EK381V4L-04P
YQ06615000J0G	EK381V4L-06P
~	~
YQ48615000J0G	EK381V4L-48P
YQ046150A0J0G	ESK381V4L-04P
YQ066150A0J0G	ESK381V4L-06P
~	~
YQ486150A0J0G	ESK381V4L-48P
YA06015100J0G	EK381V3L-06p
YA09015100J0G	EK381V3L-09p
~	~
YA36015100J0G	EK381V3L-72p
YF02015000J0G	E3K500V-02P
YF03015000J0G	E3K500V-03P
~	~
YF24015000J0G	E3K500V-24P
YF02215000J0G	E3K508V-02P
YF03215000J0G	E3K508V-03P

FCI P/N	DINKLE P/N
Rising Clamp System	
~	~
YF24215000J0G	E3K508V-24P
YM04015000J0G	EK500V2R-04P
YM06015000J0G	EK500V2R-06P
~	~
YM48015000J0G	EK500V2R-48P
YM04215000J0G	EK500V2L-04P
YM06215000J0G	EK500V2L-06P
~	~
YM48215000J0G	EK500V2L-48P
YM04415000J0G	EK508V2R-04P
YM06415000J0G	EK508V2R-06P
~	~
YM48415000J0G	EK508V2R-48P
YM04615000J0G	EK508V2L-04P
YM06615000J0G	EK508V2L-06P
~	~
YM48615000J0G	EK508V2L-48P
YN06015000J0G	EK500V3L-06P
YN09015000J0G	EK500V3L-09P
~	~
YN72015000J0G	EK500V3L-72P
YN06215000J0G	EK508V3L-06P
YN09215000J0G	EK508V3L-09P
~	~
YN72215000J0G	EK508V3L-72P
YH06215100J0G	EHK508V3L-06P
YH09215100J0G	EHK508V3L-09P
~	~
YH72215100J0G	EHK508V3L-72P
VV04015000J0G	EKB635V-04P
VV06015000J0G	EKB635V-06P
YS04215000J0G	EELK508V-04P
YS06215000J0G	EELK508V-06P
~	~
YS32215000J0G	EELK508V-32P
TV02115000J0G	EK350A-02P
TV03115000J0G	EK350A-03P
~	~
TV24115000J0G	EK350A-24P
TV02315000J0G	EK381A-02P
TV03315000J0G	EK381A-03P
~	~
TV24315000J0G	EK381A-24P
KP02015000J0G	EPK635VS-02P
KP03015000J0G	EPK635VS-02P
~	~
KP12015000J0G	EPK635VS-12P
KP02215000J0G	EPK116VS-02P
KP03215000J0G	EPK116VS-03P
~	~
KP12215000J0G	EPK116VS-12P
T702035000J0G	ESK635V-02P
T703035000J0G	ESK635V-03P
T702435000J0G	ESK762V-02P

FCI P/N	DINKLE P/N
Rising Clamp System	
T703435000J0G	ESK762V-03P
T702235000J0G	ESK950V-02P
T703235000J0G	ESK950V-03P
KQ02625000J0G	ESK116V-02P
KQ03625000J0G	ESK116V-03P
VP02655400J0G	ESKW116V-02P
VP03655400J0G	ESKW116V-03P
VP02855400J0G	ESK116V-02P2
VP03855400J0G	ESK116V-03P2
EI02C15300J0G	ESK150V-02P
EI03C15300J0G	ESK150V-03P
~	~
EI09C15300J0G	ESK150V-09P
EI02C15310J0G	ESK150VM-02P
EI03C15310J0G	ESK150VM03P
~	~
EI09C15310J0G	ESK150VM-09P
EK02215000J0G	EHK508V-02P
EK03215000J0G	EHK508V-03P
EK04215000J0G	EHK508V-04P
VN02A15000J0G	EK254V-02P
VN03A15000J0G	EK254V-03P
~	~
VN16A15000J0G	EK254V-16P
EB04215000J0G	EEHK508V-04P
EB06215000J0G	EEHK508V-06P
~	~
EB48215000J0G	EEHK508V-48P
TV02515000J0G	ELK500A-02P
TV03515000J0G	ELK500A-03P
~	~
TV16515000J0G	ELK500A-16P

FCI P/N	DINKLE P/N
Screw Pluggable System	
TH02016000J0G	ED130F-02P
TH03016000J0G	ED130F-03P
~	~
TH2401H000J0G	ED130F-24P
OP02000000J0G	EDH130F--02PTHT12.6
OP03000000J0G	EDH130F--03PTHT12.6
~	~
OP16000000J0G	EDH130F--24PTHT12.6
TY02010000J0G	ED130T-02P
TY03010000J0G	ED130T-03P
~	~
TY24010000J0G	ED130T-24P
TX02010000J0G	ED130W-02P
TX02010000J0G	ED130W-03P
~	~
TX24010000J0G	ED130W-24P
TJ02115300J0G	EC350V-02P
TJ03115300J0G	EC350V-03P
~	~
TJ24115300J0G	EC350V-24P
TJ02115200J0G	EC350VM-02P
TJ03115200J0G	EC350VM-03P
~	~
TJ24115200J0G	EC350VM-24P
TJ02315300J0G	EC381V-02P
TJ03315300J0G	EC381V-03P
~	~
TJ24315300J0G	EC381V-24P
TJ02315200J0G	EC381VM-02P
TJ03315200J0G	EC381VM-03P
~	~
TJ24315200J0G	EC381VM-24P
TJ02715000J0G	5ESDV-02P
TJ03715000J0G	5ESDV-03P
~	~
TJ24715000J0G	5ESDV-24P
TJ02715200J0G	5ESDVM-02P
TJ03715200J0G	5ESDVM-03P
~	~
TJ24715200J0G	5ESDVM-24P
TJ02515300J0G	2ESDV-02P
TJ03515300J0G	2ESDV-03P
~	~
TJ24515300J0G	2ESDV-24P
TJ02515200J0G	2ESDVM-02P
TJ03515200J0G	2ESDVM-03P
~	~
TJ24515200J0G	2ESDVM-24P
TJ02A15000J0G	7ESDV-02P
TJ03A15000J0G	7ESDV-03P
~	~
TJ12A15000J0G	7ESDV-12P
TJ02A15200J0G	7ESDVM-02P
TJ03A15200J0G	7ESDVM-03P
~	~

FCI P/N	DINKLE P/N
Screw Pluggable System	
TJ12A15200J0G	7ESDVM-12P
TJ02015000J0G	3ESDV-02P
TJ03015000J0G	3ESDV-03P
~	~
TJ12015000J0G	3ESDV-12P
TJ02015200J0G	3ESDVM-02P
TJ03015200J0G	3ESDVM-03P
~	~
TJ12015200J0G	3ESDVM-12P
TJ02715600J0G	5ESDT-02P
TJ03715600J0G	5ESDT-03P
~	~
TJ24715600J0G	5ESDT-24P
VR02515100J0G	EC508V-02P
VR03515100J0G	EC508V-03P
~	~
VR12515100J0G	EC508V-24P
VR02515300J0G	EC508VM-02P
VR03515300J0G	EC508VM-03P
~	~
VR12515300J0G	EC508VM-24P
VS02515000J0G	ECH508V-02P
VS03515000J0G	ECH508V-03P
~	~
VS24515000J0G	ECH508V-24P
VS02525000J0G	ECH508VM-02P
VS03525000J0G	ECH508VM-03P
~	~
VS24525000J0G	ECH508VM-24P
VS02515100J0G	ECH508R-02P
VS03515100J0G	ECH508R-03P
~	~
VS24515100J0G	ECH508R-24P
VS02525100J0G	ECH508RM-02P
VS03525100J0G	ECH508RM-03P
~	~
VS24525100J0G	ECH508RM-24P
VH02515000J0G	2ESDVB-02P
VH03515000J0G	2ESDVB-03P
~	~
VH12515000J0G	2ESDVB-12P
VH02515200J0G	2ESDVBM-02P
VH03515200J0G	2ESDVBM-03P
~	~
VH12515200J0G	2ESDVBM-12P
OQ02B15000J0G	ECH250V-02P
OQ03B15000J0G	ECH250V-03P
~	~
OQ24B15000J0G	ECH250V-24P
OQ02B15100J0G	ECH250R-02P
OQ03B15100J0G	ECH250R-03P
~	~
OQ24B15100J0G	ECH250R-24P
OQ02125000J0G	ECH350V-02P
OQ03125000J0G	ECH350V-03P

FCI P/N	DINKLE P/N
Screw Pluggable System	
~	~
OQ24125000J0G	ECH350V-24P
OQ02155000J0G	ECH350VM-02P
OQ03155000J0G	ECH350VM-03P
~	~
OQ24155000J0G	ECH350VM-24P
OQ02125100J0G	ECH350R-02P
OQ03125100J0G	ECH350R-03P
~	~
OQ24125100J0G	ECH350R-24P
OQ02155100J0G	ECH350RM-02P
OQ03155100J0G	ECH350RM-03P
~	~
OQ24155100J0G	ECH350RM-24P
OQ02325000J0G	ECH381V-02P
OQ03325000J0G	ECH381V-03P
~	~
OQ24325000J0G	ECH381V-24P
OQ02355000J0G	ECH381VM-02P
OQ03355000J0G	ECH381VM-03P
~	~
OQ24355000J0G	ECH381VM-24P
OQ02325100J0G	ECH381R-02P
OQ03325100J0G	ECH381R-03P
~	~
OQ24325100J0G	ECH381R-24P
OQ02355100J0G	ECH381RM-02P
OQ03355100J0G	ECH381RM-03P
~	~
OQ24355100J0G	ECH381RM-24P
OQ02705000J0G	5EHDV-02P
OQ03705000J0G	5EHDV-03P
~	~
OQ24705000J0G	5EHDV-24P
OQ02715000J0G	5EHDVC-02P
OQ03715000J0G	5EHDVC-03P
~	~
OQ24715000J0G	5EHDVC-24P
OQ02755000J0G	5EHDVM-02P
OQ03755000J0G	5EHDVM-03P
~	~
OQ24755000J0G	5EHDVM-24P
OQ02705100J0G	5EHDR-02P
OQ03705100J0G	5EHDR-03P
~	~
OQ24705100J0G	5EHDR-24P
OQ02715100J0G	5EHDRC-02P
OQ03715100J0G	5EHDRC-03P
~	~
OQ24715100J0G	5EHDRC-24P
OQ02755100J0G	5EHDRM-02P
OQ03755100J0G	5EHDRM-03P
~	~
OQ24755100J0G	5EHDRM-24P
OQ02535000J0G	2EHDV-02P

FCI P/N	DINKLE P/N
Screw Pluggable System	
OQ03535000J0G	2EHDV-03P
~	~
OQ24535000J0G	2EHDV-24P
OQ02545000J0G	2EHDVC-02P
OQ03545000J0G	2EHDVC-03P
~	~
OQ24545000J0G	2EHDVC-24P
OQ02555000J0G	2EHDVM-02P
OQ03555000J0G	2EHDVM-03P
~	~
OQ24555000J0G	2EHDVM-24P
OQ02545003J0G	2EHDVT-02P
OQ03545003J0G	2EHDVT-03P
~	~
OQ24545003J0G	2EHDVT-24P
OQ02535100J0G	2EHDR-02P
OQ03535100J0G	2EHDR-03P
~	~
OQ24535100J0G	2EHDR-24P
OQ02545100J0G	2EHDRC-02P
OQ03545100J0G	2EHDRC-03P
~	~
OQ24545100J0G	2EHDRC-24P
OQ02555100J0G	2EHDRM-02P
OQ03555100J0G	2EHDRM-03P
~	~
OQ24555100J0G	2EHDRM-24P
OQ02545103J0G	2EHDRT-02P
OQ03545103J0G	2EHDRT-03P
~	~
OQ24545103J0G	2EHDRT-24P
OQ02A05000J0G	7EHDV-02P
OQ03A05000J0G	7EHDV-03P
~	~
OQ12A05000J0G	7EHDV-12P
OQ02A15000J0G	7EHDVC-02P
OQ03A15000J0G	7EHDVC-03P
~	~
OQ12A15000J0G	7EHDVC-12P
OQ02A55000J0G	7EHDVM-02P
OQ03A55000J0G	7EHDVM-03P
~	~
OQ12A55000J0G	7EHDVM-12P
OQ02A05100J0G	7EHDR-02P
OQ03A05100J0G	7EHDR-03P
~	~
OQ12A05100J0G	7EHDR-12P
OQ02A15100J0G	7EHDRC-02P
OQ03A15100J0G	7EHDRC-03P
~	~
OQ12A15100J0G	7EHDRC-12P
OQ02A55100J0G	7EHDRM-02P
OQ03A55100J0G	7EHDRM-03P
~	~
OQ12A55100J0G	7EHDRM-12P

FCI P/N	DINKLE P/N
Screw Pluggable System	
OQ02005000J0G	3EHDV-02P
OQ03005000J0G	3EHDV-03P
~	~
OQ12005000J0G	3EHDV-12P
OQ02015000J0G	3EHDVC-02P
OQ03015000J0G	3EHDVC-03P
~	~
OQ12015000J0G	3EHDVC-12P
OQ02055000J0G	3EHDVM-02P
OQ03055000J0G	3EHDVM-03P
~	~
OQ12055000J0G	3EHDVM-12P
OQ02005100J0G	3EHDR-02P
OQ03005100J0G	3EHDR-03P
~	~
OQ12005100J0G	3EHDR-12P
OQ02015100J0G	3EHDRC-02P
OQ03015100J0G	3EHDRC-03P
~	~
OQ12015100J0G	3EHDRC-12P
OQ02055100J0G	3EHDRM-02P
OQ03055100J0G	3EHDRM-03P
~	~
OQ12055100J0G	3EHDRM-12P
VK02315000J0G	ECH381A-02P
VK03315000J0G	ECH381A-03P
~	~
VK24315000J0G	ECH381A-24P
VK02325000J0G	ECH381AM-02P
VK03325000J0G	ECH381AM-03P
~	~
VK24325000J0G	ECH381AM-24P
VK02505000J0G	2EHDA-02P
VK03505000J0G	2EHDA-03P
~	~
VK24505000J0G	2EHDA-24P
VK02515000J0G	2EHDAC-02P
VK03515000J0G	2EHDAC-03P
~	~
VK24515000J0G	2EHDAC-24P
VB02015000J0G	EC762V-02P
VB03015000J0G	EC762V-03P
~	~
VB12015000J0G	EC762V-12P
VB02015200J0G	EC762VM-02P
VB03015200J0G	EC762VM-03P
~	~
VB12015200J0G	EC762VM-12P
VC02005000J0G	ECH762R
VC02015000J0G	ECH762RM
VC02005100J0G	ECH762V
VC02015100J0G	ECH762VM
ET02025000J0G	EC762HV-02P
ET03025000J0G	EC762HV-03P
~	~

FCI P/N	DINKLE P/N
Screw Pluggable System	
ET12025000J0G	EC762HV-12P
ET02025200J0G	EC762HVM-02P
ET03025200J0G	EC762HVM-03P
~	~
ET12025200J0G	EC762HVM-12P
EV02615000J0G	EC116V -02P
EV03615000J0G	EC116V -03P
~	~
EV10615000J0G	EC116V -10P
EW02615200J0G	ECH116R
EW02615100J0G	ECH116L
TS02115A00J0G	EC350R-02P
TS03115A00J0G	EC350R-03P
~	~
TS24115A00J0G	EC350R-24P
TS02115C00J0G	EC350RM-02P
TS03115C00J0G	EC350RM-03P
~	~
TS24115C00J0G	EC350RM-24P
TS02115B00J0G	EC350RL-02P
TS03115B00J0G	EC350RL-03P
~	~
TS24115B00J0G	EC350RL-24P
TS02115D00J0G	EC350RLM-02P
TS03115D00J0G	EC350RLM-03P
~	~
TS24115D00J0G	EC350RLM-24P
TS02315A00J0G	EC381R-02P
TS03315A00J0G	EC381R-03P
~	~
TS24315A00J0G	EC381R-24P
TS02315C00J0G	EC381RM-02P
TS03315C00J0G	EC381RM-03P
~	~
TS24315C00J0G	EC381RM-24P
TS02315B00J0G	EC381RL-02P
TS03315B00J0G	EC381RL-03P
~	~
TS24315B00J0G	EC381RL-24P
TS02315D00J0G	EC381RLM-02P
TS03315D00J0G	EC381RLM-03P
~	~
TS24315D00J0G	EC381RLM-24P
TS02715A00J0G	5ESDP-02P
TS03715A00J0G	5ESDP-03P
~	~
TS24715A00J0G	5ESDP-24P
TS02715C00J0G	5ESDPM-02P
TS03715C00J0G	5ESDPM-03P
~	~
TS24715C00J0G	5ESDPM-24P
TS02715B00J0G	5ESDPL-02P
TS03715B00J0G	5ESDPL-03P
~	~
TS24715B00J0G	5ESDPL-24P

FCI P/N	DINKLE P/N
Screw Pluggable System	
TS02715D00J0G	5ESDPLM-02P
TS03715D00J0G	5ESDPLM-03P
~	~
TS24715D00J0G	5ESDPLM-24P
TS02515A00J0G	2ESDP-02P
TS03515A00J0G	2ESDP-03P
~	~
TS24515A00J0G	2ESDP-24P
TS02515C00J0G	2ESDPLM-02P
TS03515C00J0G	2ESDPLM-03P
~	~
TS24515C00J0G	2ESDPLM-24P
TS02515B00J0G	2ESDPL-02P
TS03515B00J0G	2ESDPL-03P
~	~
TS24515B00J0G	2ESDPL-24P
TS02515D00J0G	2ESDPLM-02P
TS03515D00J0G	2ESDPLM-03P
~	~
TS24515D00J0G	2ESDPLM-24P
TS02A15A00J0G	7ESDP-02P
TS03A15A00J0G	7ESDP-03P
~	~
TS16A15A00J0G	7ESDP-16P
TS02A15C00J0G	7ESDPM-02P
TS03A15C00J0G	7ESDPM-03P
~	~
TS16A15C00J0G	7ESDPM-16P
TS02A15B00J0G	7ESDPL-02P
TS03A15B00J0G	7ESDPL-03P
~	~
TS16A15B00J0G	7ESDPL-16P
TS02A15D00J0G	7ESDPLM-02P
TS03A15D00J0G	7ESDPLM-03P
~	~
TS16A15D00J0G	7ESDPLM-16P
TS02015A00J0G	3ESDP-02P
TS03015A00J0G	3ESDP-03P
~	~
TS16015A00J0G	3ESDP-16P
TS02015C00J0G	3ESDPM-02P
TS03015C00J0G	3ESDPM-03P
~	~
TS16015C00J0G	3ESDPM-16P
TS02015B00J0G	3ESDPL-02P
TS03015B00J0G	3ESDPL-03P
~	~
TS16015B00J0G	3ESDPL-16P
TS02015D00J0G	3ESDPLM-02P
TS03015D00J0G	3ESDPLM-03P
~	~
TS16015D00J0G	3ESDPLM-16P
VM02355000J0G	EC381F-02P
VM03355000J0G	EC381F-03P
~	~

FCI P/N	DINKLE P/N
Screw Pluggable System	
VM24355000J0G	EC381F-24P
VM02355200J0G	EC381FM-02P
VM03355200J0G	EC381FM-03P
~	~
VM24355200J0G	EC381MF-24P
VM02755000J0G	5ESDF-02P
VM03755000J0G	5ESDF-03P
~	~
VM24755000J0G	5ESDF-24P
VM02755200J0G	5ESDFM-02P
VM03755200J0G	5ESDFM-03P
~	~
VM24755200J0G	5ESDFM-24P
VM02555100J0G	2ESDF-02P
VM03555100J0G	2ESDF-03P
~	~
VM24555100J0G	2ESDF-24P
VM02555300J0G	2ESDFM-02P
VM03555300J0G	2ESDFM-03P
~	~
VM24555300J0G	2ESDFM-24P
EM02715000J0G	5ESDA-02P
EM03715000J0G	5ESDA-03P
~	~
EM24715000J0G	5ESDA-24P
EM02715200J0G	5ESDAM-02P
EM03715200J0G	5ESDAM-03P
~	~
EM24715200J0G	5ESDAM-24P
EM02515000J0G	2ESDA-02P
EM03515000J0G	2ESDA-03P
~	~
EM24515000J0G	2ESDA-24P
EM02515200J0G	2ESDAM-02P
EM03515200J0G	2ESDAM-03P
~	~
EM24515200J0G	2ESDAM-24P
VL04B15100J0G	ECHB250-04P
VL06B15100J0G	ECHB250-06P
~	~
VL48B15100J0G	ECHB250-48P
VL04135000J0G	ECHB350V-04P
VL06135000J0G	ECHB350V-06P
~	~
VL36135000J0G	ECHB350V-36P
VL04145000J0G	ECHB350VM-04P
VL06145000J0G	ECHB350VM-06P
~	~
VL36145000J0G	ECHB350VM-36P
VL04135100J0G	ECHB350R-04P
VL06135100J0G	ECHB350R-06P
~	~
VL36135100J0G	ECHB350R-36P
VL04145100J0G	ECHB350RM-04P
VL06145100J0G	ECHB350RM-06P

FCI P/N	DINKLE P/N
Screw Pluggable System	
~	~
VL36145100J0G	ECHB350RM-36P
VL04315000J0G	ECHB381V-04P
VL06315000J0G	ECHB381V-06P
~	~
VL36315000J0G	ECHB381V-36P
VL04325000J0G	ECHB381VM-04P
VL06325000J0G	ECHB381VM-06P
~	~
VL36325000J0G	ECHB381VM-36P
VL04315100J0G	ECHB381R-04P
VL06315100J0G	ECHB381R-06P
~	~
VL36315100J0G	ECHB381R-36P
VL04325100J0G	ECHB381RM-04P
VL06325100J0G	ECHB381RM-06P
~	~
VL36325100J0G	ECHB381RM-36P
VL04715000J0G	5EHDBV-04P
VL06715000J0G	5EHDBV-06P
~	~
VL48715000J0G	5EHDBV-48P
VL04725000J0G	5EHDBVM-04P
VL06725000J0G	5EHDBVM-06P
~	~
VL32725000J0G	5EHDBVM-48P
VL04715100J0G	5EHDBR-04P
VL06715100J0G	5EHDBR-06P
~	~
VL48715100J0G	5EHDBR-48P
VL04725100J0G	5EHDBRM-04P
VL06725100J0G	5EHDBRM-06P
~	~
VL32725100J0G	5EHDBRM-48P
VL04515000J0G	2EHDBV-04P
VL06515000J0G	2EHDBV-06P
~	~
VL32515000J0G	2EHDBV-48P
VL04525000J0G	2EHDBVM-04P
VL06525000J0G	2EHDBVM-06P
~	~
VL32525000J0G	2EHDBVM-48P
VL04515100J0G	2EHDBR-04P
VL06515100J0G	2EHDBR-06P
~	~
VL32515100J0G	2EHDBR-48P
VL04525100J0G	2EHDBRM-04P
VL06525100J0G	2EHDBRM-06P
~	~
VL32525100J0G	2EHDBRM-48P
VO04115000J0G	EECH350V-04P
VO06115000J0G	EECH350V-06P
~	~
VO32115000J0G	EECH350V-32P
VO04115100J0G	EECH350R-04P

FCI P/N	DINKLE P/N
Screw Pluggable System	
VO06115100J0G	EECH350R-06P
~	~
VO32115100J0G	EECH350R-32P
VO04125000J0G	EECH350VM-04P
VO06125000J0G	EECH350VM-06P
~	~
VO32125000J0G	EECH350VM-32P
VO04125100J0G	EECH350RM-04P
VO06125100J0G	EECH350RM-06P
~	~
VO32125100J0G	EECH350RM-32P
VO04315000J0G	EECH381V-04P
VO06315000J0G	EECH381V-06P
~	~
VO32315000J0G	EECH381V-32P
VO04315100J0G	EECH381R-04P
VO06315100J0G	EECH381R-06P
~	~
VO32315100J0G	EECH381R-32P
VO04325000J0G	EECH381VM-04P
VO06325000J0G	EECH381VM-06P
~	~
VO32325000J0G	EECH381VM-32P
VO04325100J0G	EECH381RM-04P
VO06325100J0G	EECH381RM-06P
~	~
VO32325100J0G	EECH381RM-32P
VF04705000J0G	5EEHDV-04P
VF06705000J0G	5EEHDV-06P
~	~
VF24705000J0G	5EEHDV-24P
VF04715000J0G	5EEHDVC-04P
VF06715000J0G	5EEHDVC-06P
~	~
VF24715000J0G	5EEHDVC-24P
VF04725000J0G	5EEHDVM-04P
VF06725000J0G	5EEHDVM-06P
~	~
VF24725000J0G	5EEHDVM-24P
VF04705100J0G	5EEHDR-04P
VF06705100J0G	5EEHDR-06P
~	~
VF24705100J0G	5EEHDR-24P
VF04715100J0G	5EEHDRC-04P
VF06715100J0G	5EEHDRC-06P
~	~
VF24715100J0G	5EEHDRC-24P
VF04725100J0G	5EEHDRM-04P
VF06725100J0G	5EEHDRM-06P
~	~
VF24725100J0G	5EEHDRM-24P
VF04505000J0G	2EEHDV-04P
VF06505000J0G	2EEHDV-06P
~	~
VF48505000J0G	2EEHDV-48P

FCI P/N	DINKLE P/N
Screw Pluggable System	
VF04515000J0G	2EEHDVC-04P
VF06515000J0G	2EEHDVC-06P
~	~
VF48515000J0G	2EEHDVC-48P
VF04525000J0G	2EEHDVM-04P
VF06525000J0G	2EEHDVM-06P
~	~
VF24525000J0G	2EEHDVM-48P
VF04505100J0G	2EEHDR-04P
VF06505100J0G	2EEHDR-06P
~	~
VF48505100J0G	2EEHDR-48P
VF04515100J0G	2EEHDRC-04P
VF06515100J0G	2EEHDRC-06P
~	~
VF48515100J0G	2EEHDRC-48P
VF04525100J0G	2EEHDRM-04P
VF06525100J0G	2EEHDRM-06P
~	~
VF24525100J0G	2EEHDRM-48P
VZ02305000J0G	ECHP381V-02P
VZ03305000J0G	ECHP381V-03P
~	~
VZ24305000J0G	ECHP381V-24P
VZ02505000J0G	2EHDP-02P
VZ03505000J0G	2EHDP-03P
~	~
VZ24505000J0G	2EHDP-24P
V702315000J0G	EC381CV-02P
V703315000J0G	EC381CV-03P
~	~
V724315000J0G	EC381CV-24P
V702315100J0G	EC381CR-02P
V703315100J0G	EC381CR-03P
~	~
V724315100J0G	EC381CR-24P
V702515000J0G	2ESDCV-02P
V703515000J0G	2ESDCV-03P
~	~
V724515000J0G	2ESDCV-24P
V702525000J0G	2ESDCVM-02P
V703525000J0G	2ESDCVM-03P
~	~
V724525000J0G	2ESDCVM-24P
V702515100J0G	2ESDCR-02P
V703515100J0G	2ESDCR-03P
~	~
V724515100J0G	2ESDCR-24P
V702525100J0G	2ESDCRM-02P
V703525100J0G	2ESDCRM-03P
~	~
V724525100J0G	2ESDCRM-24P
V502515000J0G	2EHDRS-02P
V503515000J0G	2EHDRS-03P
~	~

FCI P/N	DINKLE P/N
Screw Pluggable System	
V516515000J0G	2EHDRS-16P
V502515100J0G	2EHDRSM-02P
V503515100J0G	2EHDRSM-03P
~	~
V516515100J0G	2EHDRSM-16P
V502515400J0G	2EHDRD-02P
V503515400J0G	2EHDRD-03P
~	~
V516515400J0G	2EHDRD-16P
V502515500J0G	2EHDRDM-02P
V503515500J0G	2EHDRDM-03P
~	~
V516515500J0G	2EHDRDM-16P
KE04110000J0G	0221-2304THT
KE06110000J0G	0221-2306THT
~	~
KE48110000J0G	0221-2348THT
KE04110100J0G	0221-2204THT
KE06110100J0G	0221-2206THT
~	~
KE48110100J0G	0221-2248THT
KE04130100J0G	0221-2604THT
KE06130100J0G	0221-2606THT
~	~
KE48130100J0G	0221-2648THT
K306130100J0G	0221-2706THT
K309130100J0G	0221-2709THT
~	~
K372130100J0G	0221-2772THT
K306110100J0G	0221-2506THT
K309110100J0G	0221-2509THT
~	~
K372110100J0G	0221-2572THT
V802315000J0G	ECSH381V-02P
V803315000J0G	ECSH381V-03P
~	~
V824315000J0G	ECSH381V-24P
V802315100J0G	ECSH381VM-02P
V803315100J0G	ECSH381VM-03P
~	~
V824315100J0G	ECSH381VM-24P
V802515000J0G	2ESH-02P
V803515000J0G	2ESH-03P
~	~
V824515000J0G	2ESH-24P
V802515100J0G	2ESDHM-02P
V803515100J0G	2ESDHM-03P
~	~
V824515100J0G	2ESDHM-24P
V802515200J0G	2ESHM-02P
V803515200J0G	2ESHM-03P
~	~
V824515200J0G	2ESHM-24P
HW02B05000J0G	ESC250V-02P
HW03B05000J0G	ESC250V-03P

FCI P/N	DINKLE P/N
Screw Pluggable System	
~	~
HW24B05000J0G	ESC250V-24P
HW02305000J0G	ESC381V-02P
HW03305000J0G	ESC381V-03P
~	~
HW24305000J0G	ESC381V-24P
HW02305200J0G	ESC381VM-02P
HW03305200J0G	ESC381VM-03P
~	~
HW24305200J0G	ESC381VM-24P
HW02505000J0G	2ESDSR508-02P
HW03505000J0G	2ESDSR508-03P
~	~
HW24505000J0G	2ESDSR508-24P
HW02505200J0G	2ESDSRM508-02P
HW03505200J0G	2ESDSRM508-03P
~	~
HW24505200J0G	2ESDSRM508-24P
HW02505100J0G	2ESDS-02P
HW03505100J0G	2ESDS-03P
~	~
HW24505100J0G	2ESDS-24P
HW02505300J0G	2ESDSM-02P
HW03505300J0G	2ESDSM-03P
~	~
HW24505300J0G	2ESDSM-24P
HW02705000J0G	5ESDSR508-02P
HW03705000J0G	5ESDSR508-03P
~	~
HW24705000J0G	5ESDSR508-24P
HW02705200J0G	5ESDSRM508-02P
HW03705200J0G	5ESDSRM508-03P
~	~
HW24705200J0G	5ESDSRM508-24P
HW02005000J0G	3ESDSR-02P
HW03005000J0G	3ESDSR-02P
~	~
HW12005000J0G	3ESDSR-12P
HW02005200J0G	3ESDSRM-02P
HW03005200J0G	3ESDSRM-02P
~	~
HW12005200J0G	3ESDSRM-12P
KD02105000J0G	0221-2002
KD03105000J0G	0221-2003
~	~
KD20105000J0G	0221-2020
KD02105100J0G	0221-2802
KD03105100J0G	0221-2803
~	~
KD20105100J0G	0221-2820
KD02105200J0G	0221-2402
KD03105200J0G	0221-2403
~	~
KD20105200J0G	0221-2420
NF02505000J0G	2ESDBA-02P

FCI P/N	DINKLE P/N
Screw Pluggable System	
NF03505000J0G	2ESDBA-03P
~	~
NF16505000J0G	2ESDBA-24P
NF02505100J0G	2ESDBAM-02P
NF03505100J0G	2ESDBAM-03P
~	~
NF16505100J0G	2ESDBAT-24P
NF02505200J0G	2ESDBAT-02P
NF03505200J0G	2ESDBAT-03P
~	~
NF16505200J0G	2ESDBAT-24P

FCI P/N	DINKLE P/N
Spring Clamp System	
HA02515000J0G	141R-02P
HA03515000J0G	141R-03P
~	~
HA24515000J0G	141R-24P
HA02505000J0G	141V-02P
HA03505000J0G	141V-03P
~	~
HA24505000J0G	141V-24P
HA02015000J0G	142R-02P
HA03015000J0G	142R-03P
~	~
HA24015000J0G	142R-24P
HA02005000J0G	142V-02P
HA03005000J0G	142V-03P
~	~
HA24005000J0G	142V-24P
HA02215000J0G	142R-02P3
HA03215000J0G	142R-03P3
~	~
HA24215000J0G	142R-24P3
HA02205000J0G	142V-02P3
HA03205000J0G	142V-03P3
~	~
HA24205000J0G	142V-24P3
HB02318000J0G	144RA-02P1
HB03318000J0G	144RA-03P1
~	~
HB24318000J0G	144RA-24P1
HB02418000J0G	144RA-02P2
HB03418000J0G	144RA-03P2
~	~
HB24418000J0G	144RA-24P2
HB02418100J0G	144R-02P2
HB03418100J0G	144R-03P2
~	~
HB24418100J0G	144R-24P2
HB02018000J0G	144RA-02P
HB03018000J0G	144RA-03P
~	~
HB24018000J0G	144RA-24P
HB02018100J0G	144R-02P
HB03018100J0G	144R-03P
~	~
HB24018100J0G	144R-24P
HB02028000J0G	244RA-02P
HB03028000J0G	244RA-03P
~	~
HB24028000J0G	244RA-24P
HB02218000J0G	144RA-02P3
HB03218000J0G	144RA-03P3
~	~
HB24218000J0G	144RA-24P3
HB02218100J0G	144R-02P3
HB03218100J0G	144R-03P3
~	~

FCI P/N	DINKLE P/N
Spring Clamp System	
HB24218100J0G	144R-24P3
HB02228000J0G	244RA-02P3
HB03228000J0G	244RA-03P3
~	~
HB24228000J0G	244RA-24P3
HC02B08000J0G	0136-1002
HC03B08000J0G	0136-1003
~	~
HC24B08000J0G	0136-1024
HC02B08200J0G	0136-1102
HC03B08200J0G	0136-1103
~	~
HC24B08200J0G	0136-1124
HC02008000J0G	0136-2002
HC03008000J0G	0136-2003
~	~
HC24008000J0G	0136-2024
HC02008200J0G	0136-2102
HC03008200J0G	0136-2103
~	~
HC24008200J0G	0136-2124
VCxx005100J0G	ECH762V-xxp
VCxx015100J0G	ECH762VM-xxp
VCxx025100J0G	ECH762VTM-xxp
VCxx005000J0G	ECH762R-xxp
VCxx015000J0G	ECH762RM-xxp

FCI P/N	PHOENIX P/N
TR01055100J0G	FRONT 2,5-H/SA 5
TR01055000J0G	FRONT 2,5-V/SA 5
TR010551A0J0G	FRONT 2,5-H/SA 10
KH01055100J0G	FRONT4-H-6.35
KH01055000J0G	FRONT4-V-6.35
KH01155100J0G	FRONT4-H-7.62
KH01155000J0G	FRONT4-V-7.62
KY02015000J0G	PT 1.5/2-5.0-H
KY03015000J0G	PT 1.5/3-5.0-H
~	~
KY16015000J0G	PT 1.5/16-5.0-H
KY02015100J0G	PT 1.5/2-5.0-V
KY03015100J0G	PT 1.5/3-5.0-V
~	~
KY16015100J0G	PT 1.5/16-5.0-V
KZ02105000J0G	PTA 1.5/2-3.5
KZ03105000J0G	PTA 1.5/3-3.5
~	~
KZ16105000J0G	PTA 1.5/16-3.5
KZ02705000J0G	PTA 1.5/2-5.0
KZ03705000J0G	PTA 1.5/3-5.0
~	~
KZ16705000J0G	PTA 1.5/16-5.0
T202015100J0G	SMKDSP 1.5/2
T203015100J0G	SMKDSP 1.5/3
~	~
T212015100J0G	SMKDSP 1.5/12
T202215100J0G	SMKDSP 1.5/2-5.08
T203215100J0G	SMKDSP 1.5/3-5.08
~	~
T212215100J0G	SMKDSP 1.5/12-5.08
TI02015000J0G	MKDS 1,5/2
TI03015000J0G	MKDS 1,5/3
~	~
TI12015000J0G	MKDS 1,5/12
TI02215000J0G	GMKDS 1,5/2
TI03215000J0G	GMKDS 1,5/3
TI02415A00J0G	GMKDS 1,5/2-7.62
TI03415A00J0G	GMKDS 1,5/3-7.62
TO02015200J0G	MKDSN 1,5/2
TO03015200J0G	MKDSN 1,5/3
~	~
TO12015200J0G	MKDSN 1,5/12
YC02215000J0G	MKDSN 1,5/2-5,08
YC03215000J0G	MKDSN 1,5/3-5,08
~	~
YC12215000J0G	MKDSN 1,5/12-5,08
~	~
YD02015000J0G	MKDSP 1,5/2
YD03015000J0G	MKDSP 1,5/3
~	~
YD12015000J0G	MKDSP 1,5/12
YD02215000J0G	MKDSP 1,5/2-5.08
YD03215000J0G	MKDSP 1,5/3-5.08
~	~
YD12215000J0G	MKDSP 1,5/12-5.08

FCI P/N	PHOENIX P/N
VJ02015200J0G	MKDS 3/2
VJ03015200J0G	MKDS 3/3
VJ04015200J0G	MKDS 3/4
VJ02015000J0G	MKDSF 3/2
VJ03015000J0G	MKDSF 3/3
VJ04015000J0G	MKDSF 3/4
VJ06015000J0G	MKDSF 3/6
VJ08015000J0G	MKDSF 3/8
VJ02215200J0G	MKDS 3/2-5.08
VJ03215200J0G	MKDS 3/3-5.08
VJ04215200J0G	MKDS 3/4-5.08
VJ02215000J0G	MKDSF 3/2-5.08
VJ03215000J0G	MKDSF 3/3-5.08
VJ02415200J0G	GMKDS 3/2
VJ03415200J0G	GMKDS 3/3
VJ02615200J0G	GMKDS 3/2-7.62
VJ03615200J0G	GMKDS 3/3-7.62
YL04215000J0G	MKKDS 1,5/2
YL06215000J0G	MKKDS 1,5/3
YL04615100J0G	MKKDS 1,5/2-5.08
YL06615100J0G	MKKDS 1,5/3-5.08
YB06215000J0G	MK3DSN 1.5/2-5.08
YB09215000J0G	MK3DSN 1.5/3-5.08
YO02015000J0G	MKDS 1/2-3,5
YO03015000J0G	MKDS 1/3-3,5
~	~
YO16015000J0G	MKDS 1/16-3,5
YO02215000J0G	MKDS 1/2-3,81
YO03215000J0G	MKDS 1/3-3,81
~	~
YO16215000J0G	MKDS 1/16-3,81
YQ04215000J0G	MKKDS 1/2-3,5
YQ06215000J0G	MKKDS 1/3-3,5
~	~
YQ32215000J0G	MKKDS 1/16-3,5
YQ04615000J0G	MKKDS 1/2-3,81
YQ06615000J0G	MKKDS 1/3-3,81
~	~
YQ32615000J0G	MKKDS 1/16-3,81
YA06015100J0G	MK3DS 1/2-3.81
YA09015100J0G	MK3DS 1/3-3.81
~	~
YA36015100J0G	MK3DS 1/12-3.81
YM04415000J0G	MK3DS 1,5/2-5.08-BC
YM06415000J0G	MK3DS 1,5/3-5.08-BC
YN06215000J0G	MD3DS 1.5/2-5.08
YN09215000J0G	MD3DS 1.5/3-5.08
YH06215100J0G	MK3DS 3/2-5.08
YH09215100J0G	MK3DS 3/3-5.08
YT08215000J0G	MK4DS1.5/2-5.08
YT12215000J0G	MK4DS1.5/3-5.08
VV04015000J0G	MKKDS 5/2-6,35
VV06015000J0G	MKKDS 5/3-6,35
VV04215000J0G	MKKDS 5/2-9,5
VV06215000J0G	MKKDS 5/3-9,5
YS04015000J0G	MKKDSN 1.5/2

FCI P/N	PHOENIX P/N
YS05015000J0G	MKKDSN 1.5/3
~	~
YS16015000J0G	MKKDSN 1.5/8
YS04215000J0G	MKKDSN 1.5/2-5,08
YS05215000J0G	MKKDSN 1.5/3-5,08
~	~
YS16215000J0G	MKKDSN 1.5/8-5,08
TV02115000J0G	SMKDS 1/2-3,5
TV03115000J0G	SMKDS 1/3-3,5
~	~
TV16115000J0G	SMKDS 1/16-3,5
TV02315000J0G	SMKDS 1/2-3,81
TV03315000J0G	SMKDS 1/3-3,81
~	~
TV12315000J0G	SMKDS 1/12-3,81
KP02015000J0G	MKDS 5 HV/2-ZB-6.35
KP03015000J0G	MKDS 5 HV/3-ZB-6.35
~	~
KP12015000J0G	MKDS 5 HV/12-ZB-6.35
KP02215000J0G	MKDS 10 HV/2-ZB-10.16
KP03215000J0G	MKDS 10 HV/3-ZB-10.16
~	~
KP12215000J0G	MKDS 10 HV/12-ZB-10.16
KP01215100J0G	MKDS 10 HV/1-B-10.16
KP01215200J0G	MKDS 10 HV/1-F-10.16
T702035000J0G	MKDS 5/2-6,35
T703035000J0G	MKDS 5/3-6,35
T702035100J0G	SMKDS 5/2-6.35
T703035100J0G	SMKDS 5/3-6.35
T702435000J0G	MKDS 5/2-7,62
T703435000J0G	MKDS 5/3-7,62
KO02215000J0G	MKDS 5 HV/2-9.52
KO03215000J0G	MKDS 5 HV/3-9.52
KO02215100J0G	MKDS 5 HV/2-9.52-Z
KO03215100J0G	MKDS 5 HV/3-9.52-Z
T702235000J0G	MKDS 5/2-9,5
T703235000J0G	MKDS 5/3-9,5
T702235100J0G	SMKDS 5/2-9,5
T703235100J0G	SMKDS 5/3-9,5
KQ02625000J0G	MKDSP 10/2-10.16
KQ03625000J0G	MKDSP 10/3-10.16
VP02655400J0G	MKDSP 10HV/2-10.16
VP03655400J0G	MKDSP 10HV/3-10.16
VP02855400J0G	MKDSP 10HV/2-12.7
VP03855400J0G	MKDSP 10HV/3-12.7
EI02C15300J0G	MKDSP 25/2-15.00
EI03C15300J0G	MKDSP 25/3-15.00
~	~
EI09C15300J0G	MKDSP 25/9-15.00
EI02C15310J0G	MKDSP 25/2-15.00-F
EI03C15310J0G	MKDSP 25/3-15.00-F
~	~
EI09C15310J0G	MKDSP 25/9-15.00-F
EK02215000J0G	MKDS 3/2-5,08
EK03215000J0G	MKDS 3/3-5,08
EK04215000J0G	MKDS 3/4-5,08

FCI P/N	PHOENIX P/N
VN02A15000J0G	MPT 0,5/2-2,54
VN03A15000J0G	MPT 0,5/3-2,54
~	~
VN12A15000J0G	MPT 0,5/12-2,54
VT01215000J0G	KDS 3-MT
V402018000J0G	G 10/2
V403018000J0G	G 10/3
V404018000J0G	G 10/4
V405018000J0G	G 10/5
E402018000J0G	G 5/2
E403018000J0G	G 5/3
E404018000J0G	G 5/4
E406018000J0G	G 5/6
EB04015000J0G	MKKDS3/2
EB06015000J0G	MKKDS3/3
EB04215000J0G	MKKDS3/2-5.08
EB06215000J0G	MKKDS3/3-5.08
EB04015300J0G	MKKDSG 3/2
EB06015300J0G	MKKDSG 3/3
EB04215300J0G	MKKDSG 3/2-5.08
EB06215300J0G	MKKDSG 3/3-5.08
ES02015000J0G	MKDSFW1,5/2
ES03015000J0G	MKDSFW1,5/3
TV02515000J0G	SMKDSN 1.5/2
TV03515000J0G	SMKDSN 1.5/3
~	~
TV16515000J0G	SMKDSN 1.5/16
E602015000J0G	MKDSO 2.5/2-L
E603015000J0G	MKDSO 2.5/3-L
E604015000J0G	MKDSO 2.5/4-L
E602015100J0G	MKDSO 2.5/2-R
E603015100J0G	MKDSO 2.5/3-R
E604015100J0G	MKDSO 2.5/4-R
E602018000J0G	MKDSO 2.5/2-L KMGY
E603018000J0G	MKDSO 2.5/3-L KMGY
E604018000J0G	MKDSO 2.5/4-L KMGY
E602018100J0G	MKDSO 2.5/2-R KMGY
E603018100J0G	MKDSO 2.5/3-R KMGY
E604018100J0G	MKDSO 2.5/4-R KMGY
K703038000J0G	MKDSO 2,5 HV/3R-7,5 KMGY
K703038100J0G	MKDSO 2,5 HV/3L-7,5 KMGY
TT02015000J0G	PT 1,5/2-PVH-5.0
TT03015000J0G	PT 1,5/3-PVH-5.0
~	~
TT16015000J0G	PT 1,5/16-PVH-5.0
OP02000000J0G	PST 1,3/2-5.0
OP03000000J0G	PST 1,3/3-5.0
~	~
OP16000000J0G	PST 1,3/16-5.0
OP020F0000J0G	PST 1,3/2-H-5.0
OP030F0000J0G	PST 1,3/3-H-5.0
~	~
OP160F0000J0G	PST 1,3/16-H-5.0
EH02215000J0G	PT 1,5/2-PVH-3.5
EH03215000J0G	PT 1,5/3-PVH-3.5
~	~

FCI P/N	PHOENIX P/N
EH16215000J0G	PT 1,5/16-PVH-3.5
OP022B0100J0G	PST 1.0/2-3.5
OP032B0100J0G	PST 1.0/3-3.5
~	~
OP162B0100J0G	PST 1.0/16-3.5
TJ02115300J0G	MC 1,5/2-ST-3,5
TJ03115300J0G	MC 1,5/3-ST-3,5
~	~
TJ16115300J0G	MC 1,5/16-ST-3,5
TJ02115200J0G	MC 1,5/2-STF-3,5
TJ03115200J0G	MC 1,5/3-STF-3,5
~	~
TJ16115200J0G	MC 1,5/16-STF-3,5
TJ02315300J0G	MC 1,5/2-ST-3,81
TJ03315300J0G	MC 1,5/3-ST-3,81
~	~
TJ16315300J0G	MC 1,5/16-ST-3,81
TJ02315200J0G	MC 1,5/2-STF-3,81
TJ03315200J0G	MC 1,5/3-STF-3,81
~	~
TJ16315200J0G	MC 1,5/16-STF-3,81
TJ02715000J0G	MSTB 2,5/2-ST
TJ03715000J0G	MSTB 2,5/3-ST
~	~
TJ16715000J0G	MSTB 2,5/16-ST
TJ02715200J0G	MSTB 2,5/2-STF
TJ03715200J0G	MSTB 2,5/3-STF
~	~
TJ16715200J0G	MSTB 2,5/16-STF
TJ02515300J0G	MSTB 2,5/2-ST-5,08
TJ03515300J0G	MSTB 2,5/3-ST-5,08
~	~
TJ16515300J0G	MSTB 2,5/16-ST-5,08
TJ02515200J0G	MSTB 2,5/2-STF-5,08
TJ03515200J0G	MSTB 2,5/3-STF-5,08
~	~
TJ16515200J0G	MSTB 2,5/16-STF-5,08
TJ02A15000J0G	GMSTB 2,5/2-ST
TJ03A15000J0G	GMSTB 2,5/3-ST
~	~
TJ12A15000J0G	GMSTB 2,5/12-ST
TJ02A15200J0G	GMSTB 2,5/2-STF
TJ03A15200J0G	GMSTB 2,5/3-STF
~	~
TJ12A15200J0G	GMSTB 2,5/12-STF
TJ02015000J0G	GMSTB 2,5/2-ST-7,62
TJ03015000J0G	GMSTB 2,5/3-ST-7,62
~	~
TJ12015000J0G	GMSTB 2,5/12-ST-7,62
TJ02015200J0G	GMSTB 2,5/2-STF-7,62
TJ03015200J0G	GMSTB 2,5/3-STF-7,62
~	~
TJ12015200J0G	GMSTB 2,5/12-STF-7,62
TJ02715600J0G	MSTBT 2.5/2-ST
TJ03715600J0G	MSTBT 2.5/3-ST
~	~

FCI P/N	PHOENIX P/N
TJ16715600J0G	MSTBT 2.5/16-ST
TJ02715700J0G	MSTBT 2.5/2-STF
TJ03715700J0G	MSTBT 2.5/3-STF
~	~
TJ16715700J0G	MSTBT 2.5/16-STF
TJ02515600J0G	MSTBT 2.5/2-ST-5.08
TJ03515600J0G	MSTBT 2.5/3-ST-5.08
~	~
TJ16515600J0G	MSTBT 2.5/16-ST-5.08
TJ02515700J0G	MSTBT 2.5/2-STF-5.08
TJ03515700J0G	MSTBT 2.5/3-STF-5.08
~	~
TJ16515700J0G	MSTBT 2.5/16-STF-5.08
TJ08715400J0G	MSTB 2.5/8-STZ
TJ09715400J0G	MSTB 2.5/9-STZ
~	~
TJ16715400J0G	MSTB 2.5/16-STZ
TJ03515400J0G	MSTB 2.5/3-STZ-5.08
TJ04715400J0G	MSTB 2.5/4-STZ-5.08
~	~
TJ16715400J0G	MSTB 2.5/16-STZ-5.08
VR02515000J0G	MC 1,5/2-ST1-5.08
VR03515000J0G	MC 1,5/3-ST1-5.08
~	~
VR12515000J0G	MC 1,5/12-ST1-5.08
VR02515200J0G	MC 1,5/2-ST1F-5.08
VR03515200J0G	MC 1,5/3-ST1F-5.08
~	~
VR12515200J0G	MC 1,5/12-ST1F-5.08
VR02515100J0G	MC 1,5/2-ST-5.08
VR03515100J0G	MC 1,5/3-ST-5.08
~	~
VR12515100J0G	MC 1,5/12-ST-5.08
VR02515300J0G	MC1,5/2-STF-5.08
VR03515300J0G	MC1,5/3-STF-5.08
~	~
VR12515300J0G	MC1,5/12-STF-5.08
VS02515000J0G	MCV 1,5/2-G-5.08
VS03515000J0G	MCV 1,5/3-G-5.08
~	~
VS12515000J0G	MCV 1,5/12-G-5.08
VS02525000J0G	MCV 1,5/2-GF-5.08
VS03525000J0G	MCV 1,5/3-GF-5.08
~	~
VS12525000J0G	MCV 1,5/12-GF-5.08
VS02515100J0G	MC 1,5/2-G-5.08
VS03515100J0G	MC 1,5/3-G-5.08
~	~
VS12515100J0G	MC 1,5/12-G-5.08
VS02525100J0G	MC 1,5/2-GF-5.08
VS03525100J0G	MC 1,5/3-GF-5.08
~	~
VS12525100J0G	MC 1,5/12-GF-5.08
VH02515000J0G	TMSTBP 2,5/2-ST-5,08
VH03515000J0G	TMSTBP 2,5/3-ST-5,08
~	~

FCI P/N	PHOENIX P/N
VH10515000J0G	TMSTBP 2,5/10-ST-5,08
VH02515200J0G	TMSTBP 2,5/2-STF-5,08
VH03515200J0G	TMSTBP 2,5/3-STF-5,08
~	~
VH10515200J0G	TMSTBP 2,5/10-STF-5,08
OQ02B15000J0G	MCV 0,5/2-G-2.5
OQ03B15000J0G	MCV 0,5/3-G-2.5
~	~
OQ12B15000J0G	MCV 0,5/12-G-2.5
OQ02B15100J0G	MC 0,5/2-G-2.5
OQ03B15100J0G	MC 0,5/3-G-2.5
~	~
OQ12B15100J0G	MC 0,5/12-G-2.5
OQ02125000J0G	MCV 1,5/2-G-3.5
OQ03125000J0G	MCV 1,5/3-G-3.5
~	~
OQ16125000J0G	MCV 1,5/16-G-3.5
OQ02155000J0G	MCV 1,5/2-GF-3.5
OQ03155000J0G	MCV 1,5/3-GF-3.5
~	~
OQ16155000J0G	MCV 1,5/16-GF-3.5
OQ02125100J0G	MC 1,5/2-G-3.5
OQ03125100J0G	MC 1,5/3-G-3.5
~	~
OQ16125100J0G	MC 1,5/16-G-3.5
OQ02155100J0G	MC 1,5/2-GF-3.5
OQ03155100J0G	MC 1,5/3-GF-3.5
~	~
OQ16155100J0G	MC 1,5/16-GF-3.5
OQ02325000J0G	MCV 1,5/2-G-3.81
OQ03325000J0G	MCV 1,5/3-G-3.81
~	~
OQ16325000J0G	MCV 1,5/16-G-3.81
OQ02355000J0G	MCV 1,5/2-GF-3.81
OQ03355000J0G	MCV 1,5/3-GF-3.81
~	~
OQ16355000J0G	MCV 1,5/16-GF-3.81
OQ02325100J0G	MC 1,5/2-G-3.81
OQ03325100J0G	MC 1,5/3-G-3.81
~	~
OQ16325100J0G	MC 1,5/16-G-3.81
OQ02355100J0G	MC 1,5/2-GF-3.81
OQ03355100J0G	MC 1,5/3-GF-3.81
~	~
OQ16355100J0G	MC 1,5/16-GF-3.81
OQ02705000J0G	MSTBV 2,5/2-G
OQ03705000J0G	MSTBV 2,5/3-G
~	~
OQ16705000J0G	MSTBV 2,5/16-G
OQ02715000J0G	MSTBVA 2,5/2-G
OQ03715000J0G	MSTBVA 2,5/3-G
~	~
OQ16715000J0G	MSTBVA 2,5/16-G
OQ02755000J0G	MSTBV 2,5/2-GF
OQ03755000J0G	MSTBV 2,5/3-GF
~	~

FCI P/N	PHOENIX P/N
OQ16755000J0G	MSTBV 2,5/16-GF
OQ02715003J0G	MSTBVA 2,5/2-G-RN
OQ03715003J0G	MSTBVA 2,5/3-G-RN
~	~
OQ16715003J0G	MSTBVA 2,5/16-G-RN
OQ02705100J0G	MSTB 2,5/2-G
OQ03705100J0G	MSTB 2,5/3-G
~	~
OQ16705100J0G	MSTB 2,5/16-G
OQ02715100J0G	MSTBA 2,5/2-G
OQ03715100J0G	MSTBA 2,5/3-G
~	~
OQ16715100J0G	MSTBA 2,5/16-G
OQ02755100J0G	MSTB 2,5/2-GF
OQ03755100J0G	MSTB 2,5/3-GF
~	~
OQ16755100J0G	MSTB 2,5/16-GF
OQ02715103J0G	MSTBA 2,5/2-G-RN
OQ03715103J0G	MSTBA 2,5/3-G-RN
~	~
OQ16715103J0G	MSTBA 2,5/16-G-RN
OQ02535000J0G	MSTBV 2,5/2-G-5,08
OQ03535000J0G	MSTBV 2,5/3-G-5,08
~	~
OQ16535000J0G	MSTBV 2,5/16-G-5,08
OQ02545000J0G	MSTBVA 2,5/2-G-5,08
OQ03545000J0G	MSTBVA 2,5/3-G-5,08
~	~
OQ16545000J0G	MSTBVA 2,5/16-G-5,08
OQ02555000J0G	MSTBV 2,5/2-GF-5,08
OQ03555000J0G	MSTBV 2,5/3-GF-5,08
~	~
OQ16555000J0G	MSTBV 2,5/16-GF-5,08
OQ02545003J0G	MSTBVA 2,5/2-G-5.08-RN
OQ03545003J0G	MSTBVA 2,5/3-G-5.08-RN
~	~
OQ16545003J0G	MSTBVA 2,5/16-G-5.08-RN
OQ02535100J0G	MSTB 2,5/2-G-5,08
OQ03535100J0G	MSTB 2,5/3-G-5,08
~	~
OQ16535100J0G	MSTB 2,5/16-G-5,08
OQ02545100J0G	MSTBA 2,5/2-G-5,08
OQ03545100J0G	MSTBA 2,5/3-G-5,08
~	~
OQ16545100J0G	MSTBA 2,5/16-G-5,08
OQ02555100J0G	MSTB 2,5/2-GF-5,08
OQ03555100J0G	MSTB 2,5/3-GF-5,08
~	~
OQ16555100J0G	MSTB 2,5/16-GF-5,08
OQ02545103J0G	MSTBA 2,5/2-G-5,08-RN
OQ03545103J0G	MSTBA 2,5/3-G-5,08-RN
~	~
OQ16545103J0G	MSTBA 2,5/16-G-5,08-RN
OQ02A05000J0G	GMSTBV 2,5/2-G
OQ03A05000J0G	GMSTBV 2,5/3-G
~	~

FCI P/N	PHOENIX P/N
OQ12A05000J0G	GMSTBV 2,5/12-G
OQ02A15000J0G	GMSTBVA 2,5/2-G
OQ03A15000J0G	GMSTBVA 2,5/3-G
~	~
OQ12A15000J0G	GMSTBVA 2,5/12-G
OQ02A55000J0G	GMSTBV 2,5/2-GF
OQ03A55000J0G	GMSTBV 2,5/3-GF
~	~
OQ12A55000J0G	GMSTBV 2,5/12-GF
OQ02A05100J0G	GMSTB 2,5/2-G
OQ03A05100J0G	GMSTB 2,5/3-G
~	~
OQ12A05100J0G	GMSTB 2,5/12-G
OQ02A15100J0G	GMSTBA 2,5/2-G
OQ03A15100J0G	GMSTBA 2,5/3-G
~	~
OQ12A15100J0G	GMSTBA 2,5/12-G
OQ02A55100J0G	GMSTB 2,5/2-GF
OQ03A55100J0G	GMSTB 2,5/3-GF
~	~
OQ12A55100J0G	GMSTB 2,5/12-GF
OQ02005000J0G	GMSTBV 2,5/2-G-7,62
OQ03005000J0G	GMSTBV 2,5/3-G-7,62
~	~
OQ12005000J0G	GMSTBV 2,5/12-G-7,62
OQ02015000J0G	GMSTBVA 2,5/2-G-7,62
OQ03015000J0G	GMSTBVA 2,5/3-G-7,62
~	~
OQ12015000J0G	GMSTBVA 2,5/12-G-7,62
OQ02055000J0G	GMSTBV 2,5/2-GF-7,62
OQ03055000J0G	GMSTBV 2,5/3-GF-7,62
~	~
OQ12055000J0G	GMSTBV 2,5/12-GF-7,62
OQ02005100J0G	GMSTB 2,5/2-G-7,62
OQ03005100J0G	GMSTB 2,5/3-G-7,62
~	~
OQ12005100J0G	GMSTB 2,5/12-G-7,62
OQ02015100J0G	GMSTBA 2,5/2-G-7,62
OQ03015100J0G	GMSTBA 2,5/3-G-7,62
~	~
OQ12015100J0G	GMSTBA 2,5/12-G-7,62
OQ02055100J0G	GMSTB 2,5/2-GF-7,62
OQ03055100J0G	GMSTB 2,5/3-GF-7,62
~	~
OQ12055100J0G	GMSTB 2,5/12-GF-7,62
VK02115000J0G	SMC 1,5/2-G-3,5
VK03115000J0G	SMC 1,5/3-G-3,5
~	~
VK24115000J0G	SMC 1,5/24-G-3,5
VK02125000J0G	SMC 1,5/2-GF-3,5
VK03125000J0G	SMC 1,5/3-GF-3,5
~	~
VK24125000J0G	SMC 1,5/24-GF-3,5
VK02315000J0G	SMC 1,5/2-G-3,81
VK03315000J0G	SMC 1,5/3-G-3,81
~	~

FCI P/N	PHOENIX P/N
VK24315000J0G	SMC 1,5/24-G-3,81
VK02325000J0G	SMC 1,5/2-GF-3,81
VK03325000J0G	SMC 1,5/3-GF-3,81
~	~
VK24325000J0G	SMC 1,5/24-GF-3,81
VK02705000J0G	SMSTB 2,5/2-G
VK03705000J0G	SMSTB 2,5/3-G
~	~
VK24705000J0G	SMSTB 2,5/24-G
VK02715000J0G	SMSTBA 2,5/2-G
VK03715000J0G	SMSTBA 2,5/3-G
~	~
VK2415000J0G	SMSTBA 2,5/24-G
VK02725000J0G	SMSTB 2,5/2-GF
VK03725000J0G	SMSTB 2,5/3-GF
~	~
VK24725000J0G	SMSTB 2,5/24-GF
VK02505000J0G	SMSTB 2,5/2-G-5,08
VK03505000J0G	SMSTB 2,5/3-G-5,08
~	~
VK24505000J0G	SMSTB 2,5/24-G-5,08
VK02515000J0G	SMSTBA 2,5/2-G-5,08
VK03515000J0G	SMSTBA 2,5/3-G-5,08
~	~
VK24515000J0G	SMSTBA 2,5/24-G-5,08
VK02525000J0G	SMSTB 2,5/2-GF-5,08
VK03525000J0G	SMSTB 2,5/3-GF-5,08
~	~
VK24525000J0G	SMSTB 2,5/24-GF-5,08
VB02015000J0G	PC 4/2-ST-7,62
VB03015000J0G	PC 4/3-ST-7,62
~	~
VB12015000J0G	PC 4/12-ST-7,62
VB02015200J0G	PC 4/2-STF-7,62
VB03015200J0G	PC 4/3-STF-7,62
~	~
VB12015200J0G	PC 4/12-STF-7,62
VC02005000J0G	PC 4/2-G-7,62
VC03005000J0G	PC 4/3-G-7,62
~	~
VC12005000J0G	PC 4/12-G-7,62
VC02015000J0G	PC 4/2-GF-7,62
VC03015000J0G	PC 4/3-GF-7,62
~	~
VC12015000J0G	PC 4/12-GF-7,62
VC02005100J0G	PCV 4/2-G-7,62
VC03005100J0G	PCV 4/3-G-7,62
~	~
VC12005100J0G	PCV 4/12-G-7,62
VC02015100J0G	PCV 4/2-GF-7,62
VC03015100J0G	PCV 4/3-GF-7,62
~	~
VC12015100J0G	PCV 4/12-GF-7,62
VC02025100J0G	DFK-PC4/2-G-7.62-FS4,8
VC03025100J0G	DFK-PC4/3-G-7.62-FS4,8
~	~

FCI P/N	PHOENIX P/N
VC12025100J0G	DFK-PC4/12-G-7.62-FS4,8
ET02025000J0G	PC 5/2-ST-7,62
ET03025000J0G	PC 5/3-ST-7,62
~	~
ET12025000J0G	PC 5/12-ST-7,62
ET02025200J0G	PC 5/2-STF-7,62
ET03025200J0G	PC 5/3-STF-7,62
~	~
ET12025200J0G	PC 5/12-STF-7,62
ET03025300J0G	PC 5/3-STF-SH-7.62
ET04025300J0G	PC 5/4-STF-SH-7.62
EV02615000J0G	PC 16/2-ST-10.16
EV03615000J0G	PC 16/3-ST-10.16
~	~
EV10615000J0G	PC 16/10-ST-10.16
EV02615100J0G	PC 16/2-STF-10.16
EV03615100J0G	PC 16/3-STF-10.16
~	~
EV10615100J0G	PC 16/10-STF-10.16
EV03615200J0G	PC 16/3-STF-SH-10.16
EV04615200J0G	PC 16/4-STF-SH-10.16
EW02615000J0G	PCV 6-16/2-G1-10.16
EW03615000J0G	PCV 6-16/3-G1-10.16
~	~
EW10615000J0G	PCV 6-16/10-G1-10.16
EW02625000J0G	PCV 6-16/2-G1F-10.16
EW03625000J0G	PCV 6-16/3-G1F-10.16
~	~
EW10625000J0G	PCV 6-16/10-G1F-10.16
EW02615200J0G	PC 6-16/2-G1-10.16
EW03615200J0G	PC 6-16/3-G1-10.16
~	~
EW10615200J0G	PC 6-16/10-G1-10.16
EW02615100J0G	PC 6-16/2-G1U-10.16
EW03615100J0G	PC 6-16/3-G1U-10.16
~	~
EW10615100J0G	PC 6-16/10-G1U-10.16
EW02625200J0G	PC 6-16/2-G1F-10.16
EW03625200J0G	PC 6-16/3-G1F-10.16
~	~
EW10625200J0G	PC 6-16/10-G1F-10.16
EW02625100J0G	PC 6-16/2-G1FU-10.16
EW03625100J0G	PC 6-16/3-G1FU-10.16
~	~
EW10625100J0G	PC 6-16/10-G1FU-10.16
V902515000J0G	MSTBU 2.5/2-STD-5.08
V903515000J0G	MSTBU 2.5/3-STD-5.08
~	~
V924515000J0G	MSTBU 2.5/24-STD-5.08
V905515400J0G	UMSTBVK 2.5/5-ST-5.08
V906515400J0G	UMSTBVK 2.5/6-ST-5.08
~	~
V924515400J0G	UMSTBVK 2.5/24-ST-5.08
V905515500J0G	UMSTBVK2.5/5-STF-5.08
V906515500J0G	UMSTBVK2.5/6-STF-5.08
~	~

FCI P/N	PHOENIX P/N
V924515500J0G	UMSTBVK2.5/24-STF-5.08
TS02115A00J0G	MCVR 1,5/2-ST-3,5
TS03115A00J0G	MCVR 1,5/3-ST-3,5
~	~
TS24115A00J0G	MCVR 1,5/24-ST-3,5
TS02115C00J0G	MCVR 1,5/2-STF-3,5
TS03115C00J0G	MCVR 1,5/3-STF-3,5
~	~
TS24115C00J0G	MCVR 1,5/24-STF-3,5
TS02115B00J0G	MCVW 1,5/2-ST-3,5
TS03115B00J0G	MCVW 1,5/3-ST-3,5
~	~
TS24115B00J0G	MCVW 1,5/24-ST-3,5
TS02115D00J0G	MCVW 1,5/2-STF-3,5
TS03115D00J0G	MCVW 1,5/3-STF-3,5
~	~
TS24115D00J0G	MCVW 1,5/24-STF-3,5
TS02315A00J0G	MCVR 1,5/2-ST-3,81
TS03315A00J0G	MCVR 1,5/3-ST-3,81
~	~
TS24315A00J0G	MCVR 1,5/24-ST-3,81
TS02315C00J0G	MCVR 1,5/2-STF-3,81
TS03315C00J0G	MCVR 1,5/3-STF-3,81
~	~
TS24315C00J0G	MCVR 1,5/24-STF-3,81
TS02315B00J0G	MCVW 1,5/2-ST-3,81
TS03315B00J0G	MCVW 1,5/3-ST-3,81
~	~
TS24315B00J0G	MCVW 1,5/24-ST-3,81
TS02315D00J0G	MCVW 1,5/2-STF-3,81
TS03315D00J0G	MCVW 1,5/3-STF-3,81
~	~
TS24315D00J0G	MCVW 1,5/24-STF-3,81
TS02715A00J0G	MVSTBR 2,5/2-ST
TS03715A00J0G	MVSTBR 2,5/3-ST
~	~
TS24715A00J0G	MVSTBR 2,5/24-ST
TS02715C00J0G	MVSTBR 2,5/2-STF
TS03715C00J0G	MVSTBR 2,5/3-STF
~	~
TS24715C00J0G	MVSTBR 2,5/24-STF
TS02715B00J0G	MVSTBW 2,5/2-ST
TS03715B00J0G	MVSTBW 2,5/3-ST
~	~
TS24715B00J0G	MVSTBW 2,5/24-ST
TS02715D00J0G	MVSTBW 2,5/2-STF
TS03715D00J0G	MVSTBW 2,5/3-STF
~	~
TS24715D00J0G	MVSTBW 2,5/24-STF
TS02515A00J0G	MVSTBR 2,5/2-ST-5,08
TS03515A00J0G	MVSTBR 2,5/3-ST-5,08
~	~
TS24515A00J0G	MVSTBR 2,5/24-ST-5,08
TS02515C00J0G	MVSTBR 2,5/2-STF-5,08
TS03515C00J0G	MVSTBR 2,5/3-STF-5,08
~	~

FCI P/N	PHOENIX P/N
TS24515C00J0G	MVSTBR 2,5/24-STF-5,08
TS02515B00J0G	MVSTBW 2,5/2-ST-5,08
TS03515B00J0G	MVSTBW 2,5/3-ST-5,08
~	~
TS24515B00J0G	MVSTBW 2,5/24-ST-5,08
TS02515D00J0G	MVSTBW 2,5/2-STF-5,08
TS03515D00J0G	MVSTBW 2,5/3-STF-5,08
~	~
TS24515D00J0G	MVSTBW 2,5/24-STF-5,08
TS02A15A00J0G	GMVSTBR 2,5/2-ST
TS03A15A00J0G	GMVSTBR 2,5/3-ST
~	~
TS16A15A00J0G	GMVSTBR 2,5/16-ST
TS02A15C00J0G	GMVSTBR 2,5/2-STF
TS03A15C00J0G	GMVSTBR 2,5/3-STF
~	~
TS16A15C00J0G	GMVSTBR 2,5/16-STF
TS02A15B00J0G	GMVSTBW 2,5/2-ST
TS03A15B00J0G	GMVSTBW 2,5/3-ST
~	~
TS16A15B00J0G	GMVSTBW 2,5/24-ST
TS02A15D00J0G	GMVSTBW 2,5/2-STF
TS03A15D00J0G	GMVSTBW 2,5/3-STF
~	~
TS16A15D00J0G	GMVSTBW 2,5/24-STF
TS02015A00J0G	GMVSTBR 2,5/2-ST-7,62
TS03015A00J0G	GMVSTBR 2,5/3-ST-7,62
~	~
TS16015A00J0G	GMVSTBR 2,5/16-ST-7,62
TS02015C00J0G	GMVSTBR 2,5/2-STF-7,62
TS03015C00J0G	GMVSTBR 2,5/3-STF-7,62
~	~
TS16015C00J0G	GMVSTBR 2,5/16-STF-7,62
TS02015B00J0G	GMVSTBW 2,5/2-ST-7,62
TS03015B00J0G	GMVSTBW 2,5/3-ST-7,62
~	~
TS16015B00J0G	GMVSTBW 2,5/16-ST-7,62
TS02015D00J0G	GMVSTBW 2,5/2-STF-7,62
TS03015D00J0G	GMVSTBW 2,5/3-STF-7,62
~	~
TS16015D00J0G	GMVSTBW 2,5/16-STF-7,62
VM02155000J0G	FRONT-MC 1,5/2-ST-3,5
VM03155000J0G	FRONT-MC 1,5/3-ST-3,5
~	~
VM24155000J0G	FRONT-MC 1,5/24-ST-3,5
VM02155200J0G	FRONT-MC 1,5/2-STF-3,5
VM03155200J0G	FRONT-MC 1,5/3-STF-3,5
~	~
VM24155200J0G	FRONT-MC 1,5/24-STF-3,5
VM02355000J0G	FRONT-MC 1,5/2-ST-3,81
VM03355000J0G	FRONT-MC 1,5/3-ST-3,81
~	~
VM24355000J0G	FRONT-MC 1,5/24-ST-3,81
VM02355200J0G	FRONT-MC 1,5/2-STF-3,81
VM03355200J0G	FRONT-MC 1,5/3-STF-3,81
~	~

FCI P/N	PHOENIX P/N
VM24355200J0G	FRONT-MC 1,5/24-STF-3,81
VM02755000J0G	FRONT-MSTB 2,5/2-ST
VM03755000J0G	FRONT-MSTB 2,5/3-ST
~	~
VM24755000J0G	FRONT-MSTB 2,5/24-ST
VM02755200J0G	FRONT-MSTB 2,5/2-STF
VM03755200J0G	FRONT-MSTB 2,5/3-STF
~	~
VM24755200J0G	FRONT-MSTB 2,5/24-STF
VM02555100J0G	FRONT-MSTB 2,5/2-ST-5,08
VM03555100J0G	FRONT-MSTB 2,5/3-ST-5,08
~	~
VM24555100J0G	FRONT-MSTB 2,5/24-ST-5,08
VM02555300J0G	FRONT-MSTB 2,5/2-STF-5,08
VM03555300J0G	FRONT-MSTB 2,5/3-STF-5,08
~	~
VM24555300J0G	FRONT-MSTB 2,5/24-STF-5,08
VM02055100J0G	FRONT-GMSTB 2,5/2-ST-7.62
VM03055100J0G	FRONT-GMSTB 2,5/3-ST-7.62
~	~
VM16055100J0G	FRONT-GMSTB 2,5/16-ST-7.62
VM02055300J0G	FRONT-GMSTB 2,5/2-STF-7.62
VM03055300J0G	FRONT-GMSTB 2,5/3-STF-7.62
~	~
VM16055300J0G	FRONT-GMSTB 2,5/16-STF-7.62
EM02715000J0G	SMSTB 2,5/2-ST
EM03715000J0G	SMSTB 2,5/3-ST
~	~
EM24715000J0G	SMSTB 2,5/24-ST
EM02715200J0G	SMSTB 2,5/2-STF
EM03715200J0G	SMSTB 2,5/3-STF
~	~
EM24715200J0G	SMSTB 2,5/24-STF
EM02515000J0G	SMSTB 2,5/2-ST-5,08
EM03515000J0G	SMSTB 2,5/3-ST-5,08
~	~
EM24515000J0G	SMSTB 2,5/24-ST-5,08
EM02515200J0G	SMSTB 2,5/2-STF-5,08
EM03515200J0G	SMSTB 2,5/3-STF-5,08
~	~
EM24515200J0G	SMSTB 2,5/24-STF-5,08
VL04B15000J0G	MCDV 0,5/2-G1-2,5
VL06B15000J0G	MCDV 0,5/3-G1-2,5
~	~
VL48B15000J0G	MCDV 0,5/24-G1-2,5
VL04B15100J0G	MCD 0,5/2-G1-2,5
VL06B15100J0G	MCD 0,5/3-G1-2,5
~	~
VL48B15100J0G	MCD 0,5/24-G1-2,5
VL04135000J0G	MCDV 1,5/2-G1-3.5
VL06135000J0G	MCDV 1,5/3-G1-3.5
~	~
VL32135000J0G	MCDV 1,5/16-G1-3.5
VL04145000J0G	MCDV 1,5/2-G1F-3.5
VL06145000J0G	MCDV 1,5/3-G1F-3.5
~	~

FCI P/N	PHOENIX P/N
VL32145000J0G	MCDV 1,5/16-G1F-3.5
VL04135100J0G	MCD 1,5/2-G1-3.5
VL06135100J0G	MCD 1,5/3-G1-3.5
~	~
VL32135100J0G	MCD 1,5/16-G1-3.5
VL04145100J0G	MCD 1,5/2-G1F-3.5
VL06145100J0G	MCD 1,5/3-G1F-3.5
~	~
VL32145100J0G	MCD 1,5/16-G1F-3.5
VL04315000J0G	MCD 1,5/2-G1-3.81
VL06315000J0G	MCD 1,5/3-G1-3.81
~	~
VL32315000J0G	MCD 1,5/16-G1-3.81
VL04325000J0G	MCDV 1,5/2-G1F-3.81
VL06325000J0G	MCDV 1,5/3-G1F-3.81
~	~
VL32325000J0G	MCDV 1,5/16-G1F-3.81
VL04315100J0G	MCD 1,5/2-G1-3.81
VL06315100J0G	MCD 1,5/3-G1-3.81
~	~
VL32315100J0G	MCD 1,5/16-G1-3.81
VL04325100J0G	MCD 1,5/2-G1F-3.81
VL06325100J0G	MCD 1,5/3-G1F-3.81
~	~
VL32325100J0G	MCD 1,5/16-G1F-3.81
VL04715000J0G	MDSTBV 2,5/2-G1
VL06715000J0G	MDSTBV 2,5/3-G1
~	~
VL32715000J0G	MDSTBV 2,5/16-G1
VL04725000J0G	MDSTBV 2,5/2-G1F
VL06725000J0G	MDSTBV 2,5/3-G1F
~	~
VL32725000J0G	MDSTBV 2,5/16-G1F
VL04715100J0G	MDSTB 2,5/2-G1
VL06715100J0G	MDSTB 2,5/3-G1
~	~
VL32715100J0G	MDSTB 2,5/16-G1
VL04725100J0G	MDSTB 2,5/2-G1F
VL06725100J0G	MDSTB 2,5/3-G1F
~	~
VL32725100J0G	MDSTB 2,5/16-G1F
VL04515000J0G	MDSTBV 2,5/2-G1-5,08
VL06515000J0G	MDSTBV 2,5/3-G1-5,08
~	~
VL32515000J0G	MDSTBV 2,5/16-G1-5,08
VL04525000J0G	MDSTBV 2,5/2-G1F-5,08
VL06525000J0G	MDSTBV 2,5/3-G1F-5,08
~	~
VL32525000J0G	MDSTBV 2,5/16-G1F-5,08
VL04515100J0G	MDSTB 2,5/2-G1-5,08
VL06515100J0G	MDSTB 2,5/3-G1-5,08
~	~
VL32515100J0G	MDSTB 2,5/16-G1-5,08
VL04525100J0G	MDSTB 2,5/2-G1F-5,08
VL06525100J0G	MDSTB 2,5/3-G1F-5,08
~	~

FCI P/N	PHOENIX P/N
VL32525100J0G	MDSTB 2,5/16-G1F-5,08
VO04115000J0G	MCDV 1,5/2-G-3,5
VO06115000J0G	MCDV 1,5/3-G-3,5
~	~
VO32115000J0G	MCDV 1,5/16-G-3,5
VO04115100J0G	MCD 1,5/2-G-3,5
VO06115100J0G	MCD 1,5/3-G-3,5
~	~
VO32115100J0G	MCD 1,5/16-G-3,5
VO04125000J0G	MCDV 1,5/2-GF-3,5
VO06125000J0G	MCDV 1,5/3-GF-3,5
~	~
VO32125000J0G	MCDV 1,5/16-GF-3,5
VO04125100J0G	MCD 1,5/2-GF-3,5
VO06125100J0G	MCD 1,5/3-GF-3,5
~	~
VO32125100J0G	MCD 1,5/16-GF-3,5
VO04315000J0G	MCDV 1,5/2-G-3,81
VO06315000J0G	MCDV 1,5/3-G-3,81
~	~
VO32315000J0G	MCDV 1,5/16-G-3,81
VO04315100J0G	MCD 1,5/2-G-3,81
VO06315100J0G	MCD 1,5/3-G-3,81
~	~
VO32315100J0G	MCD 1,5/16-G-3,81
VO04325000J0G	MCDV 1,5/2-GF-3,81
VO06325000J0G	MCDV 1,5/3-GF-3,81
~	~
VO32325000J0G	MCDV 1,5/16-GF-3,81
VO04325100J0G	MCD 1,5/2-GF-3,81
VO06325100J0G	MCD 1,5/3-GF-3,81
~	~
VO32325100J0G	MCD 1,5/16-GF-3,81
VF04705000J0G	MDSTBV 2,5/2-G
VF06705000J0G	MDSTBV 2,5/3-G
~	~
VF24705000J0G	MDSTBV 2,5/12-G
VF04715000J0G	MDSTBVA 2,5/2-G
VF06715000J0G	MDSTBVA 2,5/3-G
~	~
VF24715000J0G	MDSTBVA 2,5/12-G
VF04725000J0G	MDSTBV 2,5/2-GF
VF06725000J0G	MDSTBV 2,5/3-GF
~	~
VF24725000J0G	MDSTBV 2,5/12-GF
VF04705100J0G	MDSTB 2,5/2-G
VF06705100J0G	MDSTB 2,5/3-G
~	~
VF24705100J0G	MDSTB 2,5/12-G
VF04715100J0G	MDSTBA 2,5/2-G
VF06715100J0G	MDSTBA 2,5/3-G
~	~
VF24715100J0G	MDSTBA 2,5/12-G
VF04725100J0G	MDSTB 2,5/2-GF
VF06725100J0G	MDSTB 2,5/3-GF
~	~

FCI P/N	PHOENIX P/N
VF24725100J0G	MDSTB 2,5/12-GF
VF04505000J0G	MDSTBV 2,5/2-G-5.08
VF06505000J0G	MDSTBV 2,5/3-G-5.08
~	~
VF24505000J0G	MDSTBV 2,5/12-G-5.08
VF04515000J0G	MDSTBVA 2,5/2-G-5.08
VF06515000J0G	MDSTBVA 2,5/3-G-5.08
~	~
VF24515000J0G	MDSTBVA 2,5/12-G-5.08
VF04525000J0G	MDSTBV 2,5/2-GF-5.08
VF06525000J0G	MDSTBV 2,5/3-GF-5.08
~	~
VF24525000J0G	MDSTBV 2,5/12-GF-5.08
VF04505100J0G	MDSTB 2,5/2-G-5.08
VF06505100J0G	MDSTB 2,5/3-G-5.08
~	~
VF24505100J0G	MDSTB 2,5/12-G-5.08
VF04515100J0G	MDSTBA 2,5/2-G-5.08
VF06515100J0G	MDSTBA 2,5/3-G-5.08
~	~
VF24515100J0G	MDSTBA 2,5/12-G-5.08
VF04525100J0G	MDSTB 2,5/2-GF-5.08
VF06525100J0G	MDSTB 2,5/3-GF-5.08
~	~
VF24525100J0G	MDSTB 2,5/12-GF-5.08
VZ02305000J0G	DFK-MC 1,5/2-GF-3,81
VZ03305000J0G	DFK-MC 1,5/3-GF-3,81
~	~
VZ24305000J0G	DFK-MC 1,5/24-GF-3,81
VZ02505000J0G	DFK-MSTB 2,5/2-GF-5.08
VZ03505000J0G	DFK-MSTB 2,5/3-GF-5.08
~	~
VZ24505000J0G	DFK-MSTB 2,5/24-GF-5.08
V702115000J0G	IMCV 1,5/2-G-3,5
V703115000J0G	IMCV 1,5/3-G-3,5
~	~
V724115000J0G	IMCV 1,5/24-G-3,5
V702125000J0G	IMCV 1,5/2-GF-3,5
V703125000J0G	IMCV 1,5/3-GF-3,5
~	~
V724125000J0G	IMCV 1,5/24-GF-3,5
V702115100J0G	IMC 1,5/2-G-3,5
V703115100J0G	IMC 1,5/3-G-3,5
~	~
V724115100J0G	IMC 1,5/24-G-3,5
V702125100J0G	IMC 1,5/2-GF-3,5
V703125100J0G	IMC 1,5/3-GF-3,5
~	~
V724125100J0G	IMC 1,5/24-GF-3,5
V702315000J0G	IMCV 1,5/2-G-3,81
V703315000J0G	IMCV 1,5/3-G-3,81
~	~
V724315000J0G	IMCV 1,5/24-G-3,81
V702325000J0G	IMCV 1,5/2-GF-3,81
V703325000J0G	IMCV 1,5/3-GF-3,81
~	~

FCI P/N	PHOENIX P/N
V724325000J0G	IMCV 1,5/24-GF-3,81
V702315100J0G	IMC 1,5/2-G-3,81
V703315100J0G	IMC 1,5/3-G-3,81
~	~
V724315100J0G	IMC 1,5/24-G-3,81
V702325100J0G	IMC 1,5/2-GF-3,81
V703325100J0G	IMC 1,5/3-GF-3,81
~	~
V724325100J0G	IMC 1,5/24-GF-3,81
V702715000J0G	ICV 2,5/2-G
V703715000J0G	ICV 2,5/3-G
~	~
V724715000J0G	ICV 2,5/24-G
V702725000J0G	ICV 2,5/2-GF
V703725000J0G	ICV 2,5/3-GF
~	~
V724725000J0G	ICV 2,5/24-GF
V702715100J0G	IC 2,5/2-G
V703715100J0G	IC 2,5/3-G
~	~
V724715100J0G	IC 2,5/24-G
V702725100J0G	IC 2,5/2-GF
V703725100J0G	IC 2,5/3-GF
~	~
V724725100J0G	IC 2,5/24-GF
V702515000J0G	ICV 2,5/2-G-5,08
V703515000J0G	ICV 2,5/3-G-5,08
~	~
V724515000J0G	ICV 2,5/24-G-5,08
V702525000J0G	ICV 2,5/2-GF-5,08
V703525000J0G	ICV 2,5/3-GF-5,08
~	~
V724525000J0G	ICV 2,5/24-GF-5,08
V702515100J0G	IC 2,5/2-G-5,08
V703515100J0G	IC 2,5/3-G-5,08
~	~
V724515100J0G	IC 2,5/24-G-5,08
V702525100J0G	IC 2,5/2-GF-5,08
V703525100J0G	IC 2,5/3-GF-5,08
~	~
V724525100J0G	IC 2,5/24-GF-5,08
V702A15000J0G	GICV 2,5/2-G
V703A15000J0G	GICV 2,5/3-G
~	~
V716A15000J0G	GICV 2,5/16-G
V702A25000J0G	GICV 2,5/2-GF
V703A25000J0G	GICV 2,5/3-GF
~	~
V716A25000J0G	GICV 2,5/16-GF
V702A15100J0G	GIC 2,5/2-G
V703A15100J0G	GIC 2,5/3-G
~	~
V716A15100J0G	GIC 2,5/16-G
V702A25100J0G	GIC 2,5/2-GF
V703A25100J0G	GIC 2,5/3-GF
~	~

FCI P/N	PHOENIX P/N
V716A25100J0G	GIC 2,5/16-GF
V702015000J0G	GICV 2,5/2-G-7,62
V703015000J0G	GICV 2,5/3-G-7,62
~	~
V716015000J0G	GICV 2,5/16-G-7,62
V702025000J0G	GICV 2,5/2-GF-7,62
V703025000J0G	GICV 2,5/3-GF-7,62
~	~
V716025000J0G	GICV 2,5/16-GF-7,62
V702015100J0G	GIC 2,5/2-G-7,62
V703015100J0G	GIC 2,5/3-G-7,62
~	~
V716015100J0G	GIC 2,5/16-G-7,62
V702025100J0G	GIC 2,5/2-GF-7,62
V703025100J0G	GIC 2,5/3-GF-7,62
~	~
V716025100J0G	GIC 2,5/16-GF-7,62
EU02705000J0G	MSTBO 2.5/2-G1L
EU02705100J0G	MSTBO 2.5/2-G1R
EU03705000J0G	MSTBO 2.5/3-G1L
EU03705100J0G	MSTBO 2.5/3-G1R
EU04705000J0G	MSTBO 2.5/4-G1L
EU04705100J0G	MSTBO 2.5/4-G1R
EU03108000J0G	MCO 1.5/3-G1L-3.5 KMGY
EU03108100J0G	MCO 1.5/3-G1R-3.5 KMGY(Right)
EU04108000J0G	MCO 1.5/4-G1L-3.5 KMGY
EU04108100J0G	MCO 1.5/4-G1R-3.5 KMGY(Right)
EU05108000J0G	MCO 1.5/5-G1L-3.5 KMGY
EU05108100J0G	MCO 1.5/5-G1R-3.5 KMGY(Right)
V502515000J0G	MVSTBU 2.5/2-GB-5.08
V503515000J0G	MVSTBU 2.5/3-GB-5.08
~	~
V516515000J0G	MVSTBU 2.5/16-GB-5.08
V502515100J0G	MVSTBU 2.5/2-GFB-5.08
V503515100J0G	MVSTBU 2.5/3-GFB-5.08
~	~
V516515100J0G	MVSTBU 2.5/16-GFB-5.08
V502515200J0G	MSTBVK 2,5/2-G-5.08
V503515200J0G	MSTBVK 2,5/3-G-5.08
~	~
V516515200J0G	MSTBVK 2,5/16-G-5.08
V502515300J0G	MSTBVK 2,5/2-GF-5.08
V503515300J0G	MSTBVK 2,5/3-GF-5.08
~	~
V516515300J0G	MSTBVK 2,5/16-GF-5.08
V502515400J0G	UMSTBVK2,5/2-G-5,08
V503515400J0G	UMSTBVK2,5/3-G-5,08
~	~
V516515400J0G	UMSTBVK2,5/16-G-5,08
V502515500J0G	UMSTBVK2,5/2-GF-5,08
V503515500J0G	UMSTBVK2,5/3-GF-5,08
~	~
V516515500J0G	UMSTBVK2,5/16-GF-5,08
KE04110000J0G	MCDNV 1,5/2-G1-3,5 P26THR
KE06110000J0G	MCDNV 1,5/3-G1-3,5 P26THR
~	~

FCI P/N	PHOENIX P/N
KE48110000J0G	MCDNV 1,5/24-G1-3,5 P26THR
KE04110100J0G	MCDN 1,5/2-G1-3,5 P26THR
KE06110100J0G	MCDN 1,5/3-G1-3,5 P26THR
~	~
KE48110100J0G	MCDN 1,5/24-G1-3,5 P26THR
KE04130000J0G	MCDNV 1,5/2-G1-3,5 RNP26THR
KE06130000J0G	MCDNV 1,5/3-G1-3,5 RNP26THR
~	~
KE48130000J0G	MCDNV 1,5/24-G1-3,5 RNP26THR
KE04130100J0G	MCDN 1,5/2-G1-3,5 RNP26THR
KE06130100J0G	MCDN 1,5/3-G1-3,5 RNP26THR
~	~
KE48130100J0G	MCDN 1,5/24-G1-3,5 RNP26THR
KE04710100J0G	CCDN 2.5/2-G1 P26 THR
KE06710100J0G	CCDN 2.5/3-G1 P26 THR
~	~
KE32710100J0G	CCDN 2.5/16-G1 P26 THR
KE04720100J0G	CCDN 2.5/2-G1F P26 THR
KE06720100J0G	CCDN 2.5/3-G1F P26 THR
~	~
KE32720100J0G	CCDN 2.5/16-G1F P26 THR
KK02615000J0G	IPC 16/2-ST-10,16
KK03615000J0G	IPC 16/3-ST-10,16
~	~
KK09615000J0G	IPC 16/9-ST-10,16
KK02615100J0G	IPC 16/2-STF-10,16
KK03615100J0G	IPC 16/3-STF-10,16
~	~
KK09615100J0G	IPC 16/9-STF-10,16
KK03615200J0G	IPC 16/3-STF-SH-10.16
KK04615200J0G	IPC 16/4-STF-SH-10.16
KK02615300J0G	IPC 16/2-STGF-10.16
KK03615300J0G	IPC 16/3-STGF-10.16
~	~
KK09615300J0G	IPC 16/9-STGF-10.16
KK03615400J0G	IPC 16/3-STGF-SH-10.16
KK04615400J0G	IPC 16/4-STGF-SH-10.16
KL02615000J0G	IPCV 16/2-G-10,16
KL03615000J0G	IPCV 16/3-G-10,16
~	~
KL09615000J0G	IPCV 16/9-G-10,16
KL02625000J0G	IPCV 16/2-GF-10,16
KL03625000J0G	IPCV 16/3-GF-10,16
~	~
KL09625000J0G	IPCV 16/9-GF-10,16
KL02615200J0G	IPC 16/2-G-10,16
KL02615200J0G	IPC 16/2-G-10,16
~	~
KL02615200J0G	IPC 16/2-G-10,16
KL02625200J0G	IPC 16/2-GF-10,16
KL03625200J0G	IPC 16/3-GF-10,16
~	~
KL09625200J0G	IPC 16/9-GF-10,16
KL02615100J0G	IPC 16/2-GU-10,16
KL03615100J0G	IPC 16/3-GU-10,16
~	~

FCI P/N	PHOENIX P/N
KL09615100J0G	IPC 16/9-GU-10,16
KL02625100J0G	IPC 16/2-GUF-10,16
KL03625100J0G	IPC 16/3-GUF-10,16
~	~
KL09625100J0G	IPC 16/9-GUF-10,16
KJ02615000J0G	PCU 6/2-STD-10,16
KJ03615000J0G	PCU 6/3-STD-10,16
~	~
KJ09615000J0G	PCU 6/9-STD-10,16
V502315100J0G	MCVU 1,5/2-GFD-3,81
V503315100J0G	MCVU 1,5/3-GFD-3,81
~	~
V516315100J0G	MCVU 1,5/16-GFD-3,81
V802315000J0G	IMC 1,5/2-ST-3,81
V803315000J0G	IMC 1,5/3-ST-3,81
~	~
V824315000J0G	IMC 1,5/24-ST-3,81
V802315100J0G	IMC 1,5/2-STGF-3,81
V803315100J0G	IMC 1,5/3-STGF-3,81
~	~
V824315100J0G	IMC 1,5/24-STGF-3,81
V802515000J0G	IC 2,5/2-ST-5,08
V803515000J0G	IC 2,5/3-ST-5,08
~	~
V824515000J0G	IC 2,5/24-ST-5,08
V802515100J0G	IC 2,5/2-STGF-5,08
V803515100J0G	IC 2,5/3-STGF-5,08
~	~
V824515100J0G	IC 2,5/24-STGF-5,08
V802515200J0G	IC 2,5/2-STF-5,08
V803515200J0G	IC 2,5/3-STF-5,08
~	~
V824515200J0G	IC 2,5/24-STF-5,08
V802015000J0G	GIC 2,5/2-ST-7,62
V803015000J0G	GIC 2,5/3-ST-7,62
~	~
V812015000J0G	GIC 2,5/12-ST-7,62
V802015100J0G	GIC 2,5/2-STGF-7,62
V803015100J0G	GIC 2,5/3-STGF-7,62
~	~
V812015100J0G	GIC 2,5/12-STGF-7,62
V802015200J0G	GIC 2,5/2-STF-7,62
V803015200J0G	GIC 2,5/3-STF-7,62
~	~
V812015200J0G	GIC 2,5/12-STF-7,62
KF02105000J0G	ZEC 1,0/2-LPV-3,5 C1
KF03105000J0G	ZEC 1,0/3-LPV-3,5 C1
~	~
KF12105000J0G	ZEC 1,0/12-LPV-3,5 C1
KF02705000J0G	ZEC 1,5/2-LPV-5.0 C2
KF03705000J0G	ZEC 1,5/3-LPV-5.0 C2
~	~
KF12705000J0G	ZEC 1,5/12-LPV-5.0 C2
KF02A05000J0G	ZEC 1,5/2-LPV-7,5 C2
KF03A05000J0G	ZEC 1,5/3-LPV-7,5 C2
~	~

FCI P/N	PHOENIX P/N
KF08A05000J0G	ZEC 1,5/8-LPV-7,5 C2
KI02305100J0G	MCC 1/2-STZ-3.81
KI03305100J0G	MCC 1/3-STZ-3.81
~	~
KI24305100J0G	MCC 1/24-STZ-3.81
KI02305300J0G	MCC 1/2-STZF-3.81
KI03305300J0G	MCC 1/3-STZF-3.81
~	~
KI24305300J0G	MCC 1/24-STZF-3.81
KI02505100J0G	MSTBC 2.5/2-ST-5.08
KI03505100J0G	MSTBC 2.5/3-ST-5.08
~	~
KI24505100J0G	MSTBC 2.5/24-ST-5.08
KI02505300J0G	MSTBC 2.5/2-STZF-5.08
KI03505300J0G	MSTBC 2.5/3-STZF-5.08
~	~
KI24505300J0G	MSTBC 2.5/24-STZF-5.08
KV02505300J0G	ICC 2.5/2-STZ-5.08
KV03505300J0G	ICC 2.5/3-STZ-5.08
~	~
KV24505300J0G	ICC 2.5/24-STZ-5.08
KV02505400J0G	ICC 2.5/2-STZF-5.08
KV03505400J0G	ICC 2.5/3-STZF-5.08
~	~
KV24505400J0G	ICC 2.5/24-STZF-5.08
KT02015000J0G	IPC 5/2-ST-7.62
KT03015000J0G	IPC 5/3-ST-7.62
~	~
KT12015000J0G	IPC 5/12-ST-7.62
KT02015400J0G	IPC 5/2-STF-7.62
KT03015400J0G	IPC 5/3-STF-7.62
~	~
KT12015400J0G	IPC 5/12-STF-7.62
KT03015500J0G	IPC 5/3-STF-SH-7.62
KT04015500J0G	IPC 5/4-STF-SH-7.62
KT02015200J0G	IPC 5/2-STGF-7.62
KT03015200J0G	IPC 5/3-STGF-7.62
~	~
KT12015200J0G	IPC 5/12-STGF-7.62
KT03015530J0G	IPC 5/3-STGF-SH-7.62
KT04015530J0G	IPC 5/4-STGF-SH-7.62
KS02015000J0G	IPCV 5/2-G-7.62
KS03015000J0G	IPCV 5/3-G-7.62
~	~
KS12015000J0G	IPCV 5/12-G-7.62
KS02025000J0G	IPCV 5/2-GF-7.62
KS03025000J0G	IPCV 5/3-GF-7.62
~	~
KS12025000J0G	IPCV 5/12-GF-7.62
KS02015200J0G	IPC 5/2-G-7.62
KS03015200J0G	IPC 5/3-G-7.62
~	~
KS12015200J0G	IPC 5/12-G-7.62
KS02025200J0G	IPC 5/2-GF-7.62
KS03025200J0G	IPC 5/3-GF-7.62
~	~

FCI P/N	PHOENIX P/N
KS12025200J0G	IPC 5/12-GF-7.62
KS02015100J0G	IPC 5/2-GU-7.62
KS03015100J0G	IPC 5/3-GU-7.62
~	~
KS12015100J0G	IPC 5/12-GU-7.62
KS02025100J0G	IPC 5/2-GFU-7.62
KS03025100J0G	IPC 5/3-GFU-7.62
~	~
KS12025100J0G	IPC 5/12-GFU-7.62
VC020051A0J0G	PCV 5/2-G-7.62
VC030051A0J0G	PCV 5/3-G-7.62
~	~
VC120051A0J0G	PCV 5/12-G-7.62
VC020151A0J0G	PCV 5/2-GF-7.62
VC030151A0J0G	PCV 5/3-GF-7.62
~	~
VC120151A0J0G	PCV 5/12-GF-7.62
VC020050B0J0G	PC 5/2-G-7.62
VC030050B0J0G	PC 5/3-G-7.62
~	~
VC120050B0J0G	PC 5/12-G-7.62
VC020050C0J0G	PC 5/2-GU-7.62
VC030050C0J0G	PC 5/3-GU-7.62
~	~
VC120050C0J0G	PC 5/12-GU-7.62
VC020150B0J0G	PC 5/2-GF-7.62
VC030150B0J0G	PC 5/3-GF-7.62
~	~
VC120150B0J0G	PC 5/12-GF-7.62
VC020150C0J0G	PC 5/2-GUF-7.62
VC030150C0J0G	PC 5/3-GUF-7.62
~	~
VC120150C0J0G	PC 5/12-GUF-7.62
KU02C15000J0G	PCV 35 HC/2-GF-15.00
KU03C15000J0G	PCV 35 HC/3-GF-15.00
~	~
KU06C15000J0G	PCV 35 HC/6-GF-15.00
KU02C15100J0G	PC 35 HC/2-GF-15.00
KU03C15100J0G	PC 35 HC/3-GF-15.00
~	~
KU06C15100J0G	PC 35 HC/6-GF-15.00
KU04C25000J0G	PCV 35 HC/4-GF-SH-15.00
KU04C25100J0G	PC 35 HC/4-GF-SH-15.00
KX02C15100J0G	PC 35 HC/2-STF-15.00
KX03C15100J0G	PC 35 HC/3-STF-15.00
~	~
KX06C15100J0G	PC 35 HC/6-STF-15.00
KX04C15200J0G	PC 35 HC/2-STF-SH-15.00
K402535200J0G	SKBD 2/MT-5.08
K403535200J0G	SKBD 3/MT-5.08
~	~
K424535200J0G	SKBD 24/MT-5.08
K502515000J0G	TVMSTB 2.5/2-ST-5.08
K503515000J0G	TVMSTB 2.5/3-ST-5.08
~	~
K524515000J0G	TVMSTB 2.5/24-ST-5.08

FCI P/N	PHOENIX P/N
K502515100J0G	TVMSTB 2.5/2-STF-5.08
K503515100J0G	TVMSTB 2.5/3-STF-5.08
~	~
K524515100J0G	TVMSTB 2.5/24-STF-5.08
HP02305000J0G	QC 0,5/2-ST-3,81
HP03305000J0G	QC 0,5/3-ST-3,81
~	~
HP24305000J0G	QC 0,5/24-ST-3,81
HP02305200J0G	QC 0,5/2-STF-3,81
HP03305200J0G	QC 0,5/3-STF-3,81
~	~
HP24305200J0G	QC 0,5/24-STF-3,81
HP02505000J0G	QC 1/2-ST-5,08
HP03505000J0G	QC 1/3-ST-5,08
~	~
HP16505000J0G	QC 1/16-ST-5,08
HP02505200J0G	QC 1/2-STF-5,08
HP03505200J0G	QC 1/3-STF-5,08
~	~
HP16505200J0G	QC 1/16-STF-5,08
HW02B05000J0G	FK-MC 0,5/2-ST-2,5
HW03B05000J0G	FK-MC 0,5/3-ST-2,5
~	~
HW24B05000J0G	FK-MC 0,5/24-ST-2,5
HW02105000J0G	FK-MCP 1,5/2-ST-3.5
HW03105000J0G	FK-MCP 1,5/3-ST-3.5
~	~
HW24105000J0G	FK-MCP 1,5/24-ST-3.5
HW02105200J0G	FK-MCP 1,5/2-STF-3.5
HW03105200J0G	FK-MCP 1,5/3-STF-3.5
~	~
HW24105200J0G	FK-MCP 1,5/24-STF-3.5
HW02305000J0G	FK-MCP 1,5/2-ST-3,81
HW03305000J0G	FK-MCP 1,5/3-ST-3,81
~	~
HW24305000J0G	FK-MCP 1,5/24-ST-3,81
HW02305200J0G	FK-MCP 1,5/2-STF-3,81
HW03305200J0G	FK-MCP 1,5/3-STF-3,81
~	~
HW24305200J0G	FK-MCP 1,5/24-STF-3,81
HW02505000J0G	FKC 2,5/2-ST-5,08
HW03505000J0G	FKC 2,5/3-ST-5,08
~	~
HW24505000J0G	FKC 2,5/24-ST-5,08
HW02505200J0G	FKC 2,5/2-STF-5,08
HW03505200J0G	FKC 2,5/3-STF-5,08
~	~
HW24505200J0G	FKC 2,5/24-STF-5,08
HW02505100J0G	FKCT 2,5/2-ST-5,08
HW03505100J0G	FKCT 2,5/3-ST-5,08
~	~
HW24505100J0G	FKCT 2,5/24-ST-5,08
HW02505300J0G	FKCT 2,5/2-STF-5,08
HW03505300J0G	FKCT 2,5/3-STF-5,08
~	~
HW24505300J0G	FKCT 2,5/24-STF-5,08

FCI P/N	PHOENIX P/N
HW02705000J0G	FKC 2,5/2-ST
HW03705000J0G	FKC 2,5/3-ST
~	~
HW24705000J0G	FKC 2,5/24-ST
HW02705200J0G	FKC 2,5/2-STF
HW03705200J0G	FKC 2,5/3-STF
~	~
HW24705200J0G	FKC 2,5/24-STF
HW02705100J0G	FKCT 2,5/2-ST
HW03705100J0G	FKCT 2,5/3-ST
~	~
HW24705100J0G	FKCT 2,5/24-ST
HW02705300J0G	FKCT 2,5/2-STF
HW03705300J0G	FKCT 2,5/3-STF
~	~
HW24705300J0G	FKCT 2,5/24-STF
HW02A05000J0G	GFKC 2,5/2-ST-7.5
HW03A05000J0G	GFKC 2,5/3-ST-7.5
~	~
HW12A05000J0G	GFKC 2,5/12-ST-7.5
HW02A05200J0G	GFKC 2,5/2-STF-7.5
HW03A05200J0G	GFKC 2,5/3-STF-7.5
~	~
HW12A05200J0G	GFKC 2,5/12-STF-7.5
HW02005000J0G	GFKC 2,5/2-ST-7.62
HW03005000J0G	GFKC 2,5/3-ST-7.62
~	~
HW12005000J0G	GFKC 2,5/12-ST-7.62
HW02005200J0G	GFKC 2,5/2-STF-7.62
HW03005200J0G	GFKC 2,5/3-STF-7.62
~	~
HW12005200J0G	GFKC 2,5/12-STF-7.62
H402705A00J0G	FKCVR 2,5/2-ST
H403705A00J0G	FKCVR 2,5/3-ST
~	~
H424705A00J0G	FKCVR 2,5/24-ST
H402705C00J0G	FKCVR 2,5/2-STF
H403705C00J0G	FKCVR 2,5/3-STF
~	~
H424705C00J0G	FKCVR 2,5/24-STF
H402705B00J0G	FKCVW 2,5/2-ST
H403705B00J0G	FKCVW 2,5/3-ST
~	~
H424705B00J0G	FKCVW 2,5/24-ST
H402705D00J0G	FKCVW 2,5/2-STF
H403705D00J0G	FKCVW 2,5/3-STF
~	~
H424705D00J0G	FKCVW 2,5/24-STF
H402505A00J0G	FKCVR 2,5/2-ST-5,08
H403505A00J0G	FKCVR 2,5/3-ST-5,08
~	~
H424505A00J0G	FKCVR 2,5/24-ST-5,08
H402505C00J0G	FKCVR 2,5/2-STF-5,05
H403505C00J0G	FKCVR 2,5/3-STF-5,05
~	~
H424505C00J0G	FKCVR 2,5/24-STF-5,05

FCI P/N	PHOENIX P/N
H402505B00J0G	FKCVW 2,5/2-ST-5,08
H403505B00J0G	FKCVW 2,5/3-ST-5,08
~	~
H424505B00J0G	FKCVW 2,5/24-ST-5,08
H402505D00J0G	FKCVW 2,5/2-STF-5,08
H403505D00J0G	FKCVW 2,5/3-STF-5,08
~	~
H424505D00J0G	FKCVW 2,5/24-STF-5,08
H502705000J0G	FKIC 2,5/2-ST
H503705000J0G	FKIC 2,5/3-ST
~	~
H524705000J0G	FKIC 2,5/24-ST
H502705200J0G	FKIC 2,5/2-STF
H503705200J0G	FKIC 2,5/3-STF
~	~
H524705200J0G	FKIC 2,5/24-STF
H502505000J0G	FKIC 2,5/2-ST-5.08
H503505000J0G	FKIC 2,5/3-ST-5.08
~	~
H524505000J0G	FKIC 2,5/24-ST-5.08
H502505200J0G	FKIC 2,5/2-STF-5.08
H503505200J0G	FKIC 2,5/3-STF-5.08
~	~
H524505200J0G	FKIC 2,5/24-STF-5.08
KD02105000J0G	FMC 1,5/2-ST-3,5
KD03105000J0G	FMC 1,5/3-ST-3,5
~	~
KD24105000J0G	FMC 1,5/24-ST-3,5
KD02105100J0G	FMC 1,5/2-STF-3,5
KD03105100J0G	FMC 1,5/3-STF-3,5
~	~
KD24105100J0G	FMC 1,5/24-STF-3,5
KD02105200J0G	FMC 1,5/2-ST-3,5-RF
KD03105200J0G	FMC 1,5/3-ST-3,5-RF
~	~
KD24105200J0G	FMC 1,5/24-ST-3,5-RF
KD02305000J0G	FMC 1,5/2-ST-3,81
KD03305000J0G	FMC 1,5/3-ST-3,81
~	~
KD24305000J0G	FMC 1,5/24-ST-3,81
KD02305100J0G	FMC 1,5/2-STF-3,81
KD03305100J0G	FMC 1,5/3-STF-3,81
~	~
KD24305100J0G	FMC 1,5/24-STF-3,81
KD02305200J0G	FMC 1,5/2-ST-3,81-RF
KD03305200J0G	FMC 1,5/3-ST-3,81-RF
~	~
KD24305200J0G	FMC 1,5/24-ST-3,81-RF
KD02705000J0G	FKCN 2.5/2-ST
KD03705000J0G	FKCN 2.5/3-ST
~	~
KD24705000J0G	FKCN 2.5/24-ST
KD02705100J0G	FKCN 2.5/2-STF
KD03705100J0G	FKCN 2.5/3-STF
~	~
KD24705100J0G	FKCN 2.5/24-STF

FCI P/N	PHOENIX P/N
KD02705200J0G	FKCN 2.5/2-STF-RF
KD03705200J0G	FKCN 2.5/3-STF-RF
~	~
KD24705200J0G	FKCN 2.5/24-STF-RF
KD02505000J0G	FKCN 2.5/2-ST-5.08
KD03505000J0G	FKCN 2.5/3-ST-5.08
~	~
KD24505000J0G	FKCN 2.5/24-ST-5.08
KD02505100J0G	FKCN 2.5/2-STF-5.08
KD03505100J0G	FKCN 2.5/3-STF-5.08
~	~
KD24505100J0G	FKCN 2.5/24-STF-5.08
KD02505200J0G	FKCN 2.5/2-STF-RF-5.08
KD03505200J0G	FKCN 2.5/3-STF-RF-5.08
~	~
KD24505200J0G	FKCN 2.5/24-STF-RF-5.08
ND02105000J0G	ZEC 1.5/2-ST-3.5 C1 R1
ND03105000J0G	ZEC 1.5/3-ST-3.5 C1 R1,3
ND04105000J0G	ZEC 1.5/4-ST-3.5 C1 R1,4
ND05105000J0G	ZEC 1.5/5-ST-3.5 C1 R1,5
ND06105000J0G	ZEC 1.5/6-ST-3.5 C1 R1,6
ND07105000J0G	ZEC 1.5/7-ST-3.5 C1 R1,7
ND08105000J0G	ZEC 1.5/8-ST-3.5 C1 R1,8
ND09105000J0G	ZEC 1.5/9-ST-3.5 C1 R1,9
ND10105000J0G	ZEC 1.5/10-ST-3.5 C1 R1,10
ND11105000J0G	ZEC 1.5/11-ST-3.5 C1 R1,11
ND12105000J0G	ZEC 1.5/12-ST-3.5 C1 R1,12
ND02705000J0G	ZEC 1.5/2-ST-5.0 C2 R1,2
ND03705000J0G	ZEC 1.5/3-ST-5.0 C2 R1,3
ND04705000J0G	ZEC 1.5/4-ST-5.0 C2 R1,4
ND05705000J0G	ZEC 1.5/5-ST-5.0 C2 R1,5
ND06705000J0G	ZEC 1.5/6-ST-5.0 C2 R1,6
ND07705000J0G	ZEC 1.5/7-ST-5.0 C2 R1,7
ND08705000J0G	ZEC 1.5/8-ST-5.0 C2 R1,8
ND09705000J0G	ZEC 1.5/9-ST-5.0 C2 R1,9
ND10705000J0G	ZEC 1.5/10-ST-5.0 C2 R1,10
ND11705000J0G	ZEC 1.5/11-ST-5.0 C2 R1,11
ND12705000J0G	ZEC 1.5/12-ST-5.0 C2 R1,12
ND02A05000J0G	ZEC 1.5/2-ST-7.5 C2 R1,2
ND03A05000J0G	ZEC 1.5/3-ST-7.5 C2 R1,3
ND04A05000J0G	ZEC 1.5/4-ST-7.5 C2 R1,4
ND05A05000J0G	ZEC 1.5/5-ST-7.5 C2 R1,5
ND06A05000J0G	ZEC 1.5/6-ST-7.5 C2 R1,6
ND07A05000J0G	ZEC 1.5/7-ST-7.5 C2 R1,7
ND08A05000J0G	ZEC 1.5/8-ST-7.5 C2 R1,8
ND09A05000J0G	ZEC 1.5/9-ST-7.5 C2 R1,9
ND10A05000J0G	ZEC 1.5/10-ST-7.5 C2 R1,10
ND11A05000J0G	ZEC 1.5/11-ST-7.5 C2 R1,11
ND12A05000J0G	ZEC 1.5/12-ST-7.5 C2 R1,12
KD041050A0J0G	FMCD 1,5/2-ST-3,5
KD061050A0J0G	FMCD 1,5/3-ST-3,5
~	~
KD481050A0J0G	FMCD 1,5/24-ST-3,5
KD041051A0J0G	FMCD 1,5/2-STF-3,5
KD061051A0J0G	FMCD 1,5/3-STF-3,5
~	~

FCI P/N	PHOENIX P/N
KD481051A0J0G	FMCD 1,5/24-STF-3,5
NF02505000J0G	TFKC 2.5/2-ST-5.08
NF03505000J0G	TFKC 2.5/3-ST-5.08
~	~
NF16505000J0G	TFKC 2.5/16-ST-5.08
NF02505100J0G	TFKC 2.5/2-STF-5.08
NF03505100J0G	TFKC 2.5/3-STF-5.08
~	~
NF16505100J0G	TFKC 2.5/16-STF-5.08
HA01515000J0G(without end cover)	FFKDS/H-2,54
HA01505000J0G(without end cover)	FFKDS/V-2,54
HA01715000J0G(without end cover)	FFKDS/H-3.81
HA01705000J0G(without end cover)	FFKDS/V-3.81
HA01515000J0G(without end cover)	FFKDS/H1-5.08
HA01505000J0G(without end cover)	FFKDS/V1-5.08
HA01215000J0G(without end cover)	FFKDSA/H1-7.62
HA01205000J0G(without end cover)	FFKDSA/V1-7.62
HC02B05300J0G	PTSA 0,5/2-2,5-Z
HC03B05000J0G	PTSA 0,5/3-2,5-Z
HC04B05300J0G	PTSA 0,5/4-2,5-Z
HC05B05000J0G	PTSA 0,5/5-2,5-Z
HC06B05300J0G	PTSA 0,5/6-2,5-Z
HC07B05000J0G	PTSA 0,5/7-2,5-Z
HC08B05300J0G	PTSA 0,5/8-2,5-Z
HC09B05000J0G	PTSA 0,5/9-2,5-Z
HC10B05300J0G	PTSA 0,5/10-2,5-Z
HC11B05000J0G	PTSA 0,5/11-2,5-Z
HC12B05300J0G	PTSA 0,5/12-2,5-Z
HC13B05000J0G	PTSA 0,5/13-2,5-Z
HC14B05300J0G	PTSA 0,5/14-2,5-Z
HC15B05000J0G	PTSA 0,5/15-2,5-Z
HC16B05300J0G	PTSA 0,5/16-2,5-Z
HC02B05200J0G	PTSA 0,5/2-2,5-F
HC03B05200J0G	PTSA 0,5/3-2,5-F
~	~
HC16B05200J0G	PTSA 0,5/16-2,5-F
HC02105300J0G	PTSA 1,5/2-2,5-Z
HC03105000J0G	PTSA 1,5/3-2,5-Z
HC04105300J0G	PTSA 1,5/4-2,5-Z
HC05105000J0G	PTSA 1,5/5-2,5-Z
HC06105300J0G	PTSA 1,5/6-2,5-Z
HC07105000J0G	PTSA 1,5/7-2,5-Z
HC08105300J0G	PTSA 1,5/8-2,5-Z
HC09105000J0G	PTSA 1,5/9-2,5-Z
HC10105300J0G	PTSA 1,5/10-2,5-Z
HC11105000J0G	PTSA 1,5/11-2,5-Z
HC12105300J0G	PTSA 1,5/12-2,5-Z
HC13105000J0G	PTSA 1,5/13-2,5-Z
HC14105300J0G	PTSA 1,5/14-2,5-Z
HC15105000J0G	PTSA 1,5/15-2,5-Z
HC16105300J0G	PTSA 1,5/16-2,5-Z
HC02105200J0G	PTSA 1,5/2-2,5-F
HC03105200J0G	PTSA 1,5/3-2,5-F
~	~
HC16105200J0G	PTSA 1,5/16-2,5-F
HD02005000J0G	MFKDSP/2-5,08

FCI P/N	PHOENIX P/N
HD03005000J0G	MFKDSP/3-5,08
~	~
HD12005000J0G	MFKDSP/12-5,08
HG01005000J0G(without end cover)	ZFKDS1,5C-5,0
HG01305000J0G(without end cover)	ZFKDS1,5-5,08
HQ02305000J0G(without end cover)	ZFKKDS 1,5-5,08
HR03305000J0G(without end cover)	ZFK3DS 1,5-5,08
HT01305000J0G(without end cover)	ZFKDS1,5-W-5,08
H2xx005000J0G	ZFKDS 4-7,5
H2xx105000J0G	ZFKDS 4-10
H8xx005000J0G	ZFKDS10-10.00
H8xx105000J0G	ZFKDS10-15.00
HS04305000J0G(without end cover)	ZFK4DS1.5-5.08
NH02105000J0G	SPTA 1/2-3.5
NH03105000J0G	SPTA 1/2-3.5
~	~
NH24105000J0G	SPTA 1/24-3.5
NH02705000J0G	SPTA 1/2-5.0
NH03705000J0G	SPTA 1/3-5.0
~	~
NH24705000J0G	SPTA 1/24-5.0
NI02305000J0G	SPTA 1.5/2-3.81
NI03305000J0G	SPTA 1.5/3-3.81
~	~
NI24305000J0G	SPTA 1.5/24-3.81
NI02505000J0G	SPTA 1.5/2-5.08
NI03505000J0G	SPTA 1.5/3-5.08
~	~
NI24505000J0G	SPTA 1.5/24-5.08
H901505000J0G	FKDS-5.08
NK01A05000J0G	SPT 5/1-V-7.5
NK01A15000J0G	SPT 5/1-H-7.5
NK02A05100J0G	SPT 5/2-V-7.5-ZB
NK03A05100J0G	SPT 5/3-V-7.5-ZB
~	~
NK12A05100J0G	SPT 5/12-V-7.5-ZB
NK02A15100J0G	SPT 5/2-H-7.5-ZB
NK03A15100J0G	SPT 5/3-H-7.5-ZB
~	~
NK12A15100J0G	SPT 5/12-H-7.5-ZB
NJ02205000J0G	SPT 1.5/2-V-7.5
NJ03205000J0G	SPT 1.5/3-V-7.5
~	~
NJ12205000J0G	SPT 1.5/12-V-7.5
NJ02215000J0G	SPT 1.5/2-H-7.5
NJ03215000J0G	SPT 1.5/3-H-7.5
~	~
NJ12215000J0G	SPT 1.5/12-H-7.5
NJ02005000J0G	SPT 2.5/2-V-7.5
NJ03005000J0G	SPT 2.5/3-V-7.5
~	~
NJ12005000J0G	SPT 2.5/12-V-7.5
NJ02015000J0G	SPT 2.5/2-H-7.5
NJ03015000J0G	SPT 2.5/3-H-7.5
~	~
NJ12015000J0G	SPT 2.5/12-H-7.5

FCI P/N	PHOENIX P/N
NP02115100J0G	SPT 16/2-H-10,0-ZB
NP03115100J0G	SPT 16/3-H-10,0-ZB
~	~
NP08115100J0G	SPT 16/8-H-10,0-ZB
NQ02000000J0G	PTSM 0,5/2-2,5-H SMD
NQ03000000J0G	PTSM 0,5/3-2,5-H SMD
~	~
NQ12000000J0G	PTSM 0,5/12-2,5-H SMD
AI	FLRP/ICV(rechts)/(links)
AN	ME17.5UTR/ME22.5UTR
AP	CP-HCC4
AM	MEMAX
AD	KGS-MSTB 2,5/..
AE	CP-MSTB
AF	CR-MSTB
AS	IC-DFR…

FCI P/N	WEIDMULLER P/N
Wire Protector System	
TC02236200J0G	PM 5.08/2/90
TC03236200J0G	PM 5.08/3/90
KH02055100J0G	TOP4GS 6.35/2/90
KH03055100J0G	TOP4GS 6.35/3/90
~	~
KH12055100J0G	TOP4GS 6.35/12/90
KH02055000J0G	TOP4GS 6.35/2/180
KH03055000J0G	TOP4GS 6.35/3/180
~	~
KH12055000J0G	TOP4GS 6.35/12/180
KH02155100J0G	TOP4GS 7.62/2/90
KH03155100J0G	TOP4GS 7.62/3/90
~	~
KH12155100J0G	TOP4GS 7.62/12/90
KH02155000J0G	TOP4GS 7.62/2/180
KH03155000J0G	TOP4GS 7.62/3/180
~	~
KH12155000J0G	TOP4GS 7.62/12/180

FCI P/N	WEIDMULLER P/N
Rising Clamp System	
T202015100J0G	LM 5.00/2/135
T203015100J0G	LM 5.00/3/135
~	~
T212015100J0G	LM 5.00/12/135
T202215100J0G	LM 5.08/2/135
T203215100J0G	LM 5.08/3/135
~	~
T212215100J0G	LM 5.08/12/135
VI02015000J0G	LM 5.00/2/180
VI03015000J0G	LM 5.00/3/180
~	~
VI12015000J0G	LM 5.00/12/180
~	~
VI02215000J0G	LM 5.08/2/180
VI03215000J0G	LM 5.08/3/180
~	~
VI12215000J0G	LM 5.08/12/180
YD02015000J0G	LM 5.00/2/90
YD03015000J0G	LM 5.00/3/90
~	~
YD12015000J0G	LM 5.00/12/90
YD02215000J0G	LM 5.08/2/90
YD03215000J0G	LM 5.08/3/90
~	~
YD12215000J0G	LM 5.08/12/90
VJ02015200J0G	LP 5.00/2/90
VJ03015200J0G	LP 5.00/3/90
VJ04015200J0G	LP 5.00/4/90
VJ02015000J0G	LP 5.00/2/180
VJ03015000J0G	LP 5.00/3/180
VJ04015000J0G	LP 5.00/4/180
VJ02215200J0G	LP 5.08/2/90
VJ03215200J0G	LP 5.08/3/90
VJ04215200J0G	LP 5.08/4/90
VJ02215000J0G	LP 5.08/2/180
VJ03215000J0G	LP 5.08/3/180
VJ02415200J0G	LP 7.50/2/90
VJ03415200J0G	LP 7.50/3/90
VJ02415000J0G	LP 7.50/2/180
VJ03415000J0G	LP 7.50/3/180
VJ02615200J0G	LP 7.62/2/90
VJ03615200J0G	LP 7.62/3/90
VJ02615000J0G	LP 7.62/2/180
VJ03615000J0G	LP 7.62/3/180
YE02215000J0G	LM1N 5.08/2/90
YE03215000J0G	LM1N 5.08/3/90
YL04615000J0G	LM2N 5.08/4/90
YL06615000J0G	LM2N 5.08/6/90
~	~
YL48615000J0G	LM2N 5.08/48/90
YF02215000J0G	LM1H 5.08/2/90
YF03215000J0G	LM1H 5.08/3/90
YM04415000J0G	LM2H 5.08/4/90
YM06415000J0G	LM2H 5.08/6/90

FCI P/N	WEIDMULLER P/N
Rising Clamp System	
YM48415000J0G	LM2H 5.08/48/90
YN06215000J0G	LM3R 5.08/6/90
YN09215000J0G	LM3R 5.08/9/90
~	~
YN72215000J0G	LM3R 5.08/72/90
YH06215100J0G	LP3R 5.08/6/90
YH09215100J0G	LP3R 5.08/9/90
~	~
YH30215100J0G	LP3R 5.08/30/90
KO02215000J0G	LL 9.5/2/90
KO03215000J0G	LL 9.5/3/90
VP02655400J0G	LU 10.16/2/90 2STI
VP03655400J0G	LU 10.16/3/90 2STI
VP02655500J0G	LU 10.16/2/90
VP03655500J0G	LU 10.16/3/90
VP02855400J0G	LU 12.7/2/90
VP03855400J0G	LU 12.7/3/90
EI02C15300J0G	LX 15.00/2/90
EI03C15300J0G	LX 15.00/3/90
~	~
EI09C15300J0G	LX 15.00/9/90
EI02C15310J0G	LXB 15.00/2/90
EI03C15310J0G	LXB 15.00/3/90
~	~
EI09C15310J0G	LXB 15.00/9/90
EB04015000J0G	LP2N 5.00/4/90
EB06015000J0G	LP2N 5.00/6/90
~	~
EB30015000J0G	LP2N 5.00/30/90
EB04215000J0G	LP2N 5.08/4/90
EB06215000J0G	LP2N 5.08/6/90
~	~
EB30215000J0G	LP2N 5.08/30/90

FCI P/N	WEIDMULLER P/N
Screw Pluggable System	
TJ02715000J0G	BLZ 5.00/2
TJ03715000J0G	BLZ 5.00/3
~	~
TJ24715000J0G	BLZ 5.00/24
TJ02515300J0G	BLZ 5.08/2
TJ03515300J0G	BLZ 5.08/3
~	~
TJ24515300J0G	BLZ 5.08/24
TJ02A15000J0G	BLZ 7.50/2
TJ03A15000J0G	BLZ 7.50/3
~	~
TJ12A15000J0G	BLZ 7.50/12
TJ02A15200J0G	BLZ 7.50/2B
TJ03A15200J0G	BLZ 7.50/3B
~	~
TJ12A15200J0G	BLZ 7.50/12B
TJ02015000J0G	BLZ 7.62/2
TJ03015000J0G	BLZ 7.62/3
~	~
TJ12015000J0G	BLZ 7.62/12
TJ02015200J0G	BLZ 7.62/2B
TJ03015200J0G	BLZ 7.62/3B
~	~
TJ12015200J0G	BLZ 7.62/12B
OQ02705000J0G	SL 5.00/2/180
OQ03705000J0G	SL 5.00/3/180
~	~
OQ24705000J0G	SL 5.00/24/180
OQ02715000J0G	SL 5.00/2/180B
OQ03715000J0G	SL 5.00/3/180B
~	~
OQ24715000J0G	SL 5.00/24/180B
OQ02705100J0G	SL 5.00/2/90
OQ03705100J0G	SL 5.00/3/90
~	~
OQ16705100J0G	SL 5.00/24/90
OQ02715100J0G	SL 5.00/2/90B
OQ03715100J0G	SL 5.00/3/90B
~	~
OQ16715100J0G	SL 5.00/24/90B
OQ02535000J0G	SL 5.08/2/90
OQ03535000J0G	SL 5.08/3/90
~	~
OQ16535000J0G	SL 5.08/24/90
OQ02545000J0G	SL 5.08/2/90B
OQ03545000J0G	SL 5.08/3/90B
~	~
OQ16545000J0G	SL 5.08/24/90B
OQ02A05000J0G	SL 7.50/2/180
OQ03A05000J0G	SL 7.50/3/180
~	~
OQ12A05000J0G	SL 7.50/12/180
OQ02A15000J0G	SL 7.50/2/180B
OQ03A15000J0G	SL 7.50/3/180B

FCI P/N	WEIDMULLER P/N
Screw Pluggable System	
OQ12A15000J0G	SL 7.50/12/180B
OQ02A05100J0G	SL 7.50/2/90
OQ03A05100J0G	SL 7.50/3/90
~	~
OQ12A05100J0G	SL 7.50/12/90
OQ02A15100J0G	SL 7.50/2/90B
OQ03A15100J0G	SL 7.50/3/90B
~	~
OQ12A15100J0G	SL 7.50/12/90B
OQ02005000J0G	SL 7.62/2/180
OQ03005000J0G	SL 7.62/3/180
~	~
OQ12005000J0G	SL 7.62/12/180
OQ02015000J0G	SL 7.62/2/180B
OQ03015000J0G	SL 7.62/3/180B
~	~
OQ12015000J0G	SL 7.62/12/180B
OQ02005100J0G	SL 7.62/2/90
OQ03005100J0G	SL 7.62/3/90
~	~
OQ12005100J0G	SL 7.62/12/90
OQ02015100J0G	SL 7.62/2/90B
OQ03015100J0G	SL 7.62/3/90B
~	~
OQ12015100J0G	SL 7.62/12/90B
VK02705000J0G	SL 5.00/2/135
VK03705000J0G	SL 5.00/3/135
~	~
VK24705000J0G	SL 5.00/24/135
VK02715000J0G	SL 5.00/2/135B
VK03715000J0G	SL 5.00/3/135B
~	~
VK2415000J0G	SL 5.00/24/135B
VK02505000J0G	SL 5.08/2/135
VK03505000J0G	SL 5.08/3/135
~	~
VK24505000J0G	SL 5.08/24/135
VK02515000J0G	SL 5.08/2/135B
VK03515000J0G	SL 5.08/3/135B
~	~
VK24515000J0G	SL 5.08/24/135B
TS02715A00J0G	BLZ 5.00/2/90
TS03715A00J0G	BLZ 5.00/3/90
~	~
TS24715A00J0G	BLZ 5.00/24/90
TS02715C00J0G	BLZ 5.00/2/90B
TS03715C00J0G	BLZ 5.00/3/90B
~	~
TS24715C00J0G	BLZ 5.00/24/90
TS02715B00J0G	BLZ 5.00/2/270
TS03715B00J0G	BLZ 5.00/3/270
~	~
TS24715B00J0G	BLZ 5.00/24/270
TS02715D00J0G	BLZ 5.00/2/270B

FCI P/N	WEIDMULLER P/N
Screw Pluggable System	
TS03715D00J0G	BLZ 5.00/3/270B
TS24715D00J0G	BLZ 5.00/24/270
TS02515A00J0G	BLT 5.08/2/90
TS03515A00J0G	BLT 5.08/3/90
~	~
TS24515A00J0G	BLT 5.08/24/90
TS02515C00J0G	BLT 5.08/2/90B
TS03515C00J0G	BLT 5.08/3/90B
~	~
TS24515C00J0G	BLT 5.08/24/90B
TS02515B00J0G	BLT 5.08/2/270
TS03515B00J0G	BLT 5.08/3/270
~	~
TS24515B00J0G	BLT 5.08/24/270
TS02515D00J0G	BLT 5.08/2/270B
TS03515D00J0G	BLT 5.08/3/270B
~	~
TS24515D00J0G	BLT 5.08/24/270B
TS02A15A00J0G	BLZ 7.50/2/90
TS03A15A00J0G	BLZ 7.50/3/90
~	~
TS16A15A00J0G	BLZ 7.50/16/90
TS02A15C00J0G	BLZ 7.50/2/90B
TS03A15C00J0G	BLZ 7.50/3/90B
~	~
TS16A15C00J0G	BLZ 7.50/16/90B
TS02A15B00J0G	BLZ 7.50/2/270
TS03A15B00J0G	BLZ 7.50/3/270
~	~
TS16A15B00J0G	BLZ 7.50/16/270
TS02A15D00J0G	BLZ 7.50/2/270B
TS03A15D00J0G	BLZ 7.50/3/270B
~	~
TS16A15D00J0G	BLZ 7.50/16/270B
TS02015A00J0G	BLZ 7.62/2/90
TS03015A00J0G	BLZ 7.62/3/90
~	~
TS16015A00J0G	BLZ 7.62/16/90
TS02015C00J0G	BLZ 7.62/2/90B
TS03015C00J0G	BLZ 7.62/3/90B
~	~
TS16015C00J0G	BLZ 7.62/16/90B
TS02015B00J0G	BLZ 7.62/2/270
TS03015B00J0G	BLZ 7.62/3/270
~	~
TS16015B00J0G	BLZ 7.62/16/270
TS02015D00J0G	BLZ 7.62/2/270B
TS03015D00J0G	BLZ 7.62/3/270B
~	~
TS16015D00J0G	BLZ 7.62/16/270B
VM02555100J0G	BLAT 2
VM03555100J0G	BLAT 3
~	~
VM24555100J0G	BLAT 24
VM02555300J0G	BLAT 2B

FCI P/N	WEIDMULLER P/N
Screw Pluggable System	
VM03555300J0G	BLAT 3B
~	~
VM24555300J0G	BLAT 24B
EM02515000J0G	BLZ 5.08/2/225
EM03515000J0G	BLZ 5.08/3/225
~	~
EM24515000J0G	BLZ 5.08/24/225
EM02515200J0G	BLZ 5.08/2/225B
EM03515200J0G	BLZ 5.08/3/225B
~	~
EM24515200J0G	BLZ 5.08/24/225B
VL04715000J0G	SLD 5.00R20/4/180
VL06715000J0G	SLD 5.00R20/6/180
~	~
VL48715000J0G	SLD 5.00R20/48/180
VL04715100J0G	SLD 5.00R20/4/90
VL06715100J0G	SLD 5.00R20/6/90
~	~
VL48715100J0G	SLD 5.00R20/48/90
VL04515000J0G	SLD 5.08R20/4/180
VL06515000J0G	SLD 5.08R20/6/180
~	~
VL32515000J0G	SLD 5.08R20/48/180
VL04515100J0G	SLD 5.08R20/4/90
VL06515100J0G	SLD 5.08R20/6/90
~	~
VL32515100J0G	SLD 5.08R20/48/90
VF04505000J0G	SLD 5.08V/4/180
VF06505000J0G	SLD 5.08V/6/180
~	~
VF48505000J0G	SLD 5.08V/48/180
VF04515000J0G	SLD 5.08V/4/180B
VF06515000J0G	SLD 5.08V/6/180B
~	~
VF48515000J0G	SLD 5.08V/48/180
VF04505100J0G	SLD 5.08V/4/90
VF06505100J0G	SLD 5.08V/6/90
~	~
VF48505100J0G	SLD 5.08V/48/90
VF04515100J0G	SLD 5.08V/4/90B
VF06515100J0G	SLD 5.08V/6/90B
~	~
VF48515100J0G	SLD 5.08V/48/90
V702515000J0G	BLL 5.08/2/180B
V703515000J0G	BLL 5.08/3/180B
~	~
V724515000J0G	BLL 5.08/24/180B
V702515100J0G	BLL 5.08/2/90B
V703515100J0G	BLL 5.08/3/90B
~	~
V724515100J0G	BLL 5.08/24/90B
V802515000J0G	SLS 5.08/2
V803515000J0G	SLS 5.08/3
~	~

FCI P/N	WEIDMULLER P/N
Screw Pluggable System	
V824515000J0G	SLS 5.08/24
KI02505100J0G	BLC 5.08/2 R
KI03505100J0G	BLC 5.08/3 R
~	~
KI24505100J0G	BLC 5.08/24 R
KI02505300J0G	BLC 5.08/2 BR
KI03505300J0G	BLC 5.08/3 BR
~	~
KI24505300J0G	BLC 5.08/24 BR
K502515000J0G	BLDT 5.08/2
K503515000J0G	BLDT 5.08/3
~	~
K524515000J0G	BLDT 5.08/24
K502515100J0G	BLDT 5.08/2B
K503515100J0G	BLDT 5.08/3B
~	~
K524515100J0G	BLDT 5.08/24B

FCI P/N	WEIDMULLER P/N
Spring Clamp Pluggable System	
HQ04308100J0G	LM2NZF 5.08/4/135
HQ06308100J0G	LM2NZF 5.08/6/135
~	~
HQ24308100J0G	LM2NZF 5.08/24/135
~	~
HR06308100J0G	LM3RZF 5.08/6/135
HR09308100J0G	LM3RZF 5.08/9/135
~	~
HR48308100J0G	LM3RZF 5.08/48/135
HP02503000J0G	BL1DC 5.08/2
HP03503000J0G	BL1DC 5.08/3
~	~
HP24503000J0G	BL1DC 5.08/24
HP02503200J0G	BL1DC 5.08/2B
HP03503200J0G	BL1DC 5.08/3B
~	~
HP24503200J0G	BL1DC 5.08/24B
HN02503000J0G	BLZF 5.08/2
HN05503000J0G	BLZF 5.08/3
~	~
HN24503000J0G	BLZF 5.08/24
HN02503200J0G	BLZF 5.08/2B
HN05503200J0G	BLZF 5.08/3B
~	~
HN24503200J0G	BLZF 5.08/24B
AH Series	SLAT
EL02120000J0G	SL-SMT 3.5/2/180G
EL03120000J0G	SL-SMT 3.5/3/180G
~	~
EL24120000J0G	SL-SMT 3.5/24/180G
EL02120100J0G	SL-SMT 3.5/2/90G
EL03120100J0G	SL-SMT 3.5/3/90G
~	~
EL24120100J0G	SL-SMT 3.5/24/90G
EL02150000J0G	SL-SMT 3.5/2/180LF
EL03150000J0G	SL-SMT 3.5/3/180LF
~	~
EL24150000J0G	SL-SMT 3.5/24/180LF
EL02150100J0G	SL-SMT 3.5/2/90LF
EL03150100J0G	SL-SMT 3.5/3/90LF
~	~
EL24150100J0G	SL-SMT 3.5/24/90LF
EL02123200J0G	SL 3.5/2/180G
EL03123200J0G	SL 3.5/3/180G
~	~
EL24123200J0G	SL 3.5/24/180G
EL02123300J0G	S 3.5/2/90G
EL03123300J0G	SL 3.5/3/90G
~	~
EL24123300J0G	SL 3.5/24/90G
EL02153200J0G	SL 3.5/2/180LF
EL03153200J0G	SL 3.5/3/180LF
~	~

FCI P/N	WEIDMULLER P/N
Spring Clamp Pluggable System	
EL24153200J0G	SL 3.5/24/180LF
EL02153300J0G	SL 3.5/2/90LF
EL03153300J0G	SL 3.5/3/90LF
~	~
EL24153300J0G	SL 3.5/24/90LF
EL02113200J0G	SL 3.5/2/180
EL03113200J0G	SL 3.5/3/180
~	~
EL24113200J0G	SL 3.5/24/180
EL02113300J0G	S 3.5/2/90
EL03113300J0G	SL 3.5/3/90
~	~
EL24113300J0G	SL 3.5/24/90
ET 7.62	BVZ 7.62
ET 7.62 W/F	BVZ 7.62F
VC 7.62 180D	SV 7.62/180
VC 7.62 180D W/F	SV7.62/180F
VC 7.62 90D	SV7.62/90
VC 7.62 90D W/F	SV7.62/90F
EV 10.16	BUZ10.16
EV 10.16 W/F	BUZ10.16F
EW 10.16 90D(down)	SU10.16/270
EW 10.16 90D(up)	SU10.16/90
EW 10.16 90D W/F(down)	SU10.16/270F
EW 10.16 90D W/F(up)	SU10.16/90F
EW 10.16 180D	SU10.16/180
EW 10.16 180D W/F	SU10.16/180F
VP 10.16 SERIES(Single tail)	LU 10.16/90 2ST1
VP 10.16(Double tail)	LU 10.16/../90
VP 12.7	LUP 12.7/90
E202113000J0G	BL3.5/2
E203113000J0G	BL3.5/3
~	~
E224113000J0G	BL3.5/24
VW04103000J0G	B2L 3.5/4
VW06103000J0G	B2L 3.5/6
~	~

FCI P/N	WEIDMULLER P/N
Spring Clamp Pluggable System	
VW36103000J0G	B2L 3.5/36
VW04103100J0G	B2L 3.5/4F
VW06103100J0G	B2L 3.5/6F
~	~
VW36103100J0G	B2L 3.5/36F
VX04103000J0G	S2L 3.5/4/180
VX06103000J0G	S2L 3.5/6/180
~	~
VX36103000J0G	S2L 3.5/36/180
VX04103100J0G	S2L 3.5/4/90
VX06103100J0G	S2L 3.5/6/90
~	~
VX36103100J0G	S2L 3.5/36/90
VX04113000J0G	S2L 3.5/4/180G
VX06113000J0G	S2L 3.5/6/180G
~	~
VX36113000J0G	S2L 3.5/36/180G
VX04113100J0G	S2L 3.5/4/90G
VX06113100J0G	S2L 3.5/6/90G
~	~
VX36113100J0G	S2L 3.5/36/90G
VX04123000J0G	S2L 3.5/4/180F
VX06123000J0G	S2L 3.5/6/180F
~	~
VX36123000J0G	S2L 3.5/36/180F
VX04123100J0G	S2L 3.5/4/90F
VX06123100J0G	S2L 3.5/6/90F
~	~
VX36123100J0G	S2L 3.5/36/90F
HN02103000J0G	BLZF 3.5/2
HN03103000J0G	BLZF 3.5/3
~	~
HN24103000J0G	BLZF 3.5/24
HN02103200J0G	BLZF 3.5/2F
HN03103200J0G	BLZF 3.5/3F
~	~
HN24103200J0G	BLZF 3.5/24F
NM02100000J0G	LSF-SMT 3.5/2/180
NM03100000J0G	LSF-SMT 3.5/3/180
~	~
NM24100000J0G	LSF-SMT 3.5/24/180
NM02100100J0G	LSF-SMT 3.5/2/90
NM03100100J0G	LSF-SMT 3.5/3/90
~	~
NM24100100J0G	LSF-SMT 3.5/24/90
NM02100200J0G	LSF-SMT 3.5/2/135
NM03100200J0G	LSF-SMT 3.5/3/135
~	~
NM24100200J0G	LSF-SMT 3.5/24/135



For more information about our products, FCI sales offices,
headquarters, agents and local distributors,
visit **www.fci.com**