

515-1016F

- Optopipe® Light Pipe Actuator Extensions
- Output dimensions (mm): \varnothing 1.63
- Mounting: Panel mountable
- Recommended LEDs
 - ◆ 597-2XX1-407F (single color)
 - ◆ 597-2X01-207F (bi color)

515-1049F

- Single round light pipe
- Output dimensions (mm): \varnothing 3.56
- Mounting: PCB mountable
- Recommended LEDs
 - ◆ PLCC-2 and PLCC-4 Series:
597-3XXX-207F (single color)
597-77XX-207F (bi color)

515-1038F

- Single round light pipe
- Output dimensions (mm): \varnothing 5.84
- Mounting: PCB mountable
- Recommended LEDs
 - ◆ PLCC-2 and PLCC-4 Series:
597-3XXX-207F (single color)
597-77XX-207F (bi color)

Panel Mount Light Pipe

- 3mm and 5mm mounting holes
- Vertical and Right Angle (5mm only)
- Flat, convex, and domed for optimal viewing angles
- Available in diffused textured lens only
- Recommended LEDs
 - ◆ PLCC-2 and PLCC-4 Series:
597-3XXX-207F (single color)
597-77XX-207F (bi color)

515-1027F

- Single element round light pipe
- Output dimensions (mm): \varnothing 1.68
- Mounting: Panel mountable
- Recommended LEDs
 - ◆ 597-2XX1-407F (single color)
 - ◆ 597-2X01-207F (bi color)

515-1011F

- Single round light pipe
- Output dimensions (mm): \varnothing 4.83
- Mounting: PCB mountable
- Recommended LEDs
 - ◆ PLCC-2 and PLCC-4 Series:
597-3XXX-207F (single color)
597-77XX-207F (bi color)

515-1118F

- 2 array round horizontal light pipe
- Output dimensions (mm): \varnothing 1.90
- Mounting: Over SFP cage assembly PCB mountable
- Recommended LEDs
 - ◆ PLCC-2 and PLCC-4 Series:
597-3XXX-207F (single color)
597-77XX-207F (bi color)



515-1094F

- 2 array bi level vertical light pipe
- Output dimensions (mm):
ø 3.05 round
- Mounting: PCB mountable
- Recommended LEDs
 - ◆ PLCC-2 and PLCC-4 Series:
597-3XXX-207F (single color)
597-77XX-207F (bi color)

515-1064F

- Tri level round light pipe
- Output dimensions (mm): ø 2.50
- Mounting: PCB mountable
- Also available with barrier,
P/N: 515-1064-811F
- Recommended LEDs
 - ◆ 597-3XX1-507F (single color)
 - ◆ 597-77X1-507F (bi color)

515-1020F

- 4 array horizontal light pipe
- Output dimensions (mm): ø 3.56
- Mounting: PCB mountable
- Also available with barrier,
P/N: 515-1020-806F
- Recommended LEDs
 - ◆ 1206 Series:
597-3111-407F 597-8210-107F
597-3311-407NF 597-3401-407NF

515-1230F

- Optopipe® High Density Light Pipe
- Available in 1, 2, 3, 4 high models
- Output dimensions (mm): ø 1.50
- Mounting: PCB mountable
- Recommended LEDs
 - ◆ Packages 0402, 0404, and 0603

515-1061F

- Bi level round vertical light pipe
- Output dimensions (mm): ø 3.05
- Mounting: PCB mountable
- Recommended LEDs
 - ◆ 597-3XX1-507F (single color)
 - ◆ 597-77X1-507F (bi color)

515-1069F

- 3 array round light pipe
- Output dimensions (mm): ø 3.65
- Mounting: PCB mountable
- Also available with barrier,
P/N: 515-1020-805F
- Recommended LEDs
 - ◆ 1206 Series:
597-3111-407F 597-8210-107F
597-3311-407NF 597-3401-407NF

515-1192, 515-1193 or 515-1194

- Flat, domed, and convex
- Available in clear and diffused lens
- Lengths varying from 0.250" to 1.250"
- Recommended LEDs
 - ◆ PLCC-2 and PLCC-4 Series:
597-XXXX-207F
 - ◆ Low profile surface mount
 - ◆ Reverse mount

