

FOR MORE INFORMATION

Technical Support

Internet:	www.te.com/ADM
USA:	+1 (800) 522-6752
Canada:	+1 (905) 470-4425
Mexico:	+52 (0) 55-1106-0814
C. America:	+52 (0) 55-1106-0814
South America:	+55 (0) 11-2103-6000
Germany:	+49 (0) 6251-133-1999
Great Britain:	+44 (0) 8706-080208
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

Follow us on Twitter for all the latest product news
@TEConnectivity, and on Facebook, TEConnectivity.



www.te.com/ADM

© 2012 Tyco Electronics Corporation. All Rights Reserved.

9-1773455-5 ADM/RRD 2.5M 1/2012

HarnWare, TE Connectivity, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies.

Other product or company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



Data Bus Components (MIL-STD-1553B) for Space Applications



Space-Grade MIL-STD-1553B Data Bus Components



Space-Grade MIL-STD-1553B Data Bus Components



KEY FEATURES

High packaging density and weight savings

Design flexibility

Complete line of space-qualified MIL-STD-1553B components

Low outgassing levels that meet NASA requirements

Rugged construction

Factory-built harnesses eliminate unnecessary splices and connectors, reducing the cost and increasing the reliability of the networks

Factory-built harnesses are pre-tested to customer requirements and are ready for installation

DESCRIPTION

A complete system of interconnection hardware for MIL-STD-1553B networks

Complete collection of components include:

- A wide selection of couplers such as micros, boxes, flat-packs, and ultra-lightweight versions
- Data bus cables
- Triax connectors and contacts with strain relief
- One-piece triaxial contacts for MIL-C-38999 connectors
- Bus and stub terminators
- Low outgassing components for use in space
- Cable identification sleeves
- Harness design software using HarnWare software
- Flexible cable splices

APPLICATIONS

Used in MIL-STD-1553B multiplexing space applications

Flight control for:

- Launch Vehicles
- Satellites
- Human Spacecraft
- Cargo Spacecraft
- Deep Space Probes

SPECIFICATION


Meets TE Specification D-6022 for space-grade data bus components.

Note:
TE is a major supplier of space data bus products to a number of space equipment OEMs.

COMPONENTS

In-Line Couplers and Terminators

- Tin/nickel-plated metallic parts
- Baked silicone rubber components
- Low outgassing tubing
- D-500-94XX-X-XXX series for couplers
- D-500-9463-XXX series for terminators



Threaded Triaxial Connectors

- Tin/nickel-plated metallic parts
- Baked silicone rubber components
- Low outgassing tubing
- DK-621-0911P
- DK-621-0911S
- DK-621-0912P
- DK-621-0912S



Bayonet Triaxial Connectors

- Tin/nickel-plated metallic parts
- Baked silicone rubber components
- Low outgassing tubing

- “A” Polarization
- DK-621-0933-1P or S
- DK-621-0934-1P or S

- “B” Polarization
- DK-621-0935-2P or S
- DK-621-0936-2P or S



- “C” Polarization
- DK-621-0937-3P or S
- DK-621-0938-3P or S

- “D” Polarization
- DK-621-0939-4P or S
- DK-621-0940-4P or S

Splice Kits

- Flux-coated, solder-impregnated copper shield braid encased in a transparent heat-shrinkable insulation sleeve provides a controlled soldering process, encapsulation, inspectability, strain relief and insulation

- D-150-9708-5



Standard Space Cables

- Single- or double-braid shield—with optional mumetal layer for EMP hardening—and radiation cross-linked ETFE insulation and jacket for low outgassing

- Optimized Single Shield
- S16 = 7724S1664-9
- S1L = 7724S1LL4 LF*

- EMP Hardened
- S86 = 7724S8664-9
- S8L = 7724S8LL4-9 LF
- Optimized Double Shield
- S36 = 7724S3664-9
- S3L = 7724S3LL4 LF

*LF = Low Fluoride



Demateable Terminators

- Available with and without lanyard
- DK-621-0937
- DK-621-0938
- DK-621-0939
- DK-621-0940
- DK-621-0933
- DK-621-0934
- DK-621-0935
- DK-621-0936



TE also manufactures complete harnesses to customer specifications and print.