

HDMI TYPE E CONNECTOR PORTFOLIO

for the Automotive Industry

The TE Connectivity HDMI Type E connector is designed for Automotive application and is compatible to HDMI Type E specification. It has a structure with vibration and shock resistance compared to consumer HDMI products.

With regard to EMI characteristics, it is fully shielded design with metal shell, and contributes to optimize EMI validation.

In order to avoid the half-mating issue, the design is optimized to make sufficient locking sound, therefore it supports to reduce the defect in car OEM's production line.



Applications

- Smart Phone Connection
- Blue-Ray Connection

Mechanical

- Mating Cycles: min. 10
- Connector Locking Strength:

min. 100 N

Mating / Unmating Force:

max. 70 N

Electrical

- Impedance: 100Ω
- Available Cable Length:

beyond 5m

• LLCR Change: $\max. 30 \Omega$

Product Offering

• HDMI Type A - Type E Harness

Standards and Specifications

108-78937

408-78075

• Product Specification:

• Instruction Sheet:

· RoHS compliant

HDMI Specification

- HDMI Type E Type E Harness
- HDMI Type E Header (H) (with or without Flange)



HDMI Type E Header (H)



HDMI Type E Header (H)

HDMI Type A Type E Harness

Material

Header

Contact: CuZn (Gold Plating)
 Housing: LCP
 Shell: CuSn / Steel (Tin Plating)

Plug

Housing: PBT Contact: CuSn (Gold Plating) Shield: CuSn (Tin Plating)

BENEFITS

- EMI optimized
- Designed for Automotive Application
- Cable Assembly
- Operating temperature -40°C ... 100°C

KEY FEATURES

Header - Compact (27mm depth)

- Reflow soldering capable

- Full shieled design

Plug - Type A Harness available

- Automotive shielded cable

CONTACT

ASIA/PACIFIC

UNITED STATES

Australia - Sydney Product Information Center: Phone: +61 2-9840-8200

United States - Harrisburgh

Product Information Center:

Phone: +1 800-522-6752

Japan - Kawasaki, Kanagawa Phone: +81-44-844-8111

Product Information Center:

Phone: +49 6251-133-1999

EUROPE

Germany - Bensheim

Korea - Seoul

Phone: +82 2-3415-4500

People's Republic of China

Hong Kong

Phone: +852 2738-8731

Shanghai

Phone: +86 21-3398-0000

For further information

please go to:

www.TE.com/support-center



TE Connectivity Germany GmbH AMPèrestrasse 12-14 64625 Bensheim | Germany

www.te.com www.te.com/automotive TE Connectivity Germany GmbH certified acc. ISO 14001 and ISO/TS 16949:2002 © 2015 TE Connectivity family of companies. All rights reserved.

South Africa - Port Elizabeth

Phone: +27 41-503-4500

TE, TE Connectivity, and TE connectivity (logo) are trademarks. 2654391-1 | Published 07-2015

AFRICA

TE Connectivity's only obligations are those stated in TE's General Terms and Conditions of Business (http://www.te.com/aboutus/tandc.asp). TE expressly disclaims any implied warranty regarding the information contained herein, including, but not limited to, the implied warranties of merchantability or fitness for a particular purpose.

