

TOSHIBA

MOSFETs

Selection Guide 2021

A decorative graphic on the left side of the page. It features a red triangle pointing downwards from the top left. Below it, a blue triangle points upwards from the bottom left. In the center, there is a yellow brushstroke that overlaps the blue triangle and extends towards the right.





Contents

I Small Signal MOSFETs	3 - 15
1. Over 500mA Series MOSFETs (Semi-Power Type)	3 - 7
2. Less than 500mA Series MOSFETs (Standard Type)	8 - 10
3. MOSFET with Diode	11
4. Part Naming Conventions	12
5. Device Packages	13 - 15
II Power MOSFETs	16 - 40
1. Low-Voltage MOSFET Series	16 - 22
2. Mid-High Voltage MOSFET Series	23 - 30
3. Automotive	31 - 32
4. Silicon Carbide (SiC) MOSFET Series	33
5. Part Naming Conventions	34
6. Device Packages	35 - 40

I Small Signal MOSFETs

1. Over 500mA Series MOSFETs (Semi-Power Type)





Package Dimensions (unit: mm)

CST3C	CST3 (SOT-883)	CST3B	VESM (SOT-723)	UFM (SOT-323F)	ES6 (SOT-563)	UF6 (SOT-363F)	WCSP6C
Bottom View  0.8x0.6	Bottom View  1.0x0.6	Bottom View  1.2x0.8	 1.2x1.2	 2.0x2.1	 1.6x1.6	 2.0x2.1	Bottom View  1.5x1.0

P-Channel Single MOSFET

Package	Part Number	V _{DS} (V)	V _{GS} (V)	I _D (A)	R _{DS(ON)} max (mΩ)						Q _g typ. (nC)	C _{iss} typ. (pF)	Note
					V _{GS} =-1.2V	V _{GS} =-1.5V	V _{GS} =-1.8V	V _{GS} =-2.5V	V _{GS} =-4V	V _{GS} =-4.5V			
CST3C	SSM3J64CTC	\$ -12	+/-10	-1.0	11300	1310	890	560	-	370	-	50	
	SSM3J65CTC	\$ -20	+/-10	-0.7	11300	1550	1070	700	-	500	-	48	
CST3	SSM3J56ACT	\$ -20	+/-8	-1.4	4000	900	660	480	-	390	-	1.6	100
CST3B	SSM3J46CTB ●	\$ -20	+/-8	-2.0	-	250	178	133	-	103	-	4.7	290 ⇒ SSM3J377R
VESM	SSM3J66MFV ☆ # \$	\$ -20	+6/-8	-0.8	4000	900	660	480	-	390	-	1.6	100
	SSM3J56MFV	\$ -20	+/-8	-0.8	4000	900	660	480	-	390	-	1.6	100
WCSP6C	SSM6J771G	\$ -20	+/-12	-5.0	-	-	-	47.5	-	35	34.7(@-8V) 31(@-8.5V)	9.8	870
ES6	SSM6J216FE	\$ -12	+/-8	-4.8	-	88.1	56	39.3	-	32	-	12.7	1040
	SSM6J213FE	\$ -20	+/-8	-2.6	-	250	178	133	-	103	-	4.7	290
	SSM6J215FE	\$ -20	+/-8	-3.4	-	154	104	79	-	59	-	10.4	630
	SSM6J212FE	\$ -20	+/-8	-4.0	-	94	65.4	49	-	40.7	-	14.1	970
	SSM6J207FE	\$ -30	+/-20	-1.4	-	-	-	-	491	-	251	-	137
	SSM6J214FE	\$ -30	+/-12	-3.6	-	-	149.6	77.6	-	57	50	7.9	560
UFM	SSM3J132TU	\$ -12	+/-6	-5.4	94	39	29	21	-	17	-	33	2700
	SSM3J135TU	\$ -20	+/-8	-3.0	-	260	180	132	-	103	-	4.6	270
	SSM3J145TU #	\$ -20	+6/-8	-3.0	-	260	180	132	-	103	-	4.6	270
	SSM3J134TU	\$ -20	+/-8	-3.2	-	240	168	123	-	93	-	4.7	290
	SSM3J144TU #	\$ -20	+6/-8	-3.2	-	240	168	123	-	93	-	4.7	290
	SSM3J120TU ●	\$ -20	+/-8	-4.0	-	140	78	49	38	-	-	22.3	1484 ⇒ SSM3J133TU
	SSM3J130TU	\$ -20	+/-8	-4.4	-	63.2	41.1	31	-	25.8	-	24.8	1800
	SSM3J140TU #	\$ -20	+6/-8	-4.4	-	63.2	41.1	31	-	25.8	-	24.8	1800
	SSM3J133TU	\$ -20	+/-8	-5.5	-	88.4	56	39.7	-	29.8	-	12.8	840
	SSM3J143TU #	\$ -20	+6/-8	-5.5	-	88.4	56	39.7	-	29.8	-	12.8	840
	SSM3J112TU #	\$ -30	+/-20	-1.1	-	-	-	-	790	-	390	-	86
	SSM3J118TU #	\$ -30	+/-20	-1.4	-	-	-	-	480	-	240	-	137
SSM3J117TU #	\$ -30	+/-20	-2.0	-	-	-	-	225	-	117	-	280	
UF6	SSM6J50TU	\$ -20	+/-10	-2.5	-	-	205(@-2V)	100	-	64	-	-	800
	SSM6J422TU ☆ # \$	\$ -20	+6/-8	-4.0	-	99.6	67.8	51.4	-	42.7	-	12.8	840
	SSM6J412TU	\$ -20	+/-8	-4.0	-	99.6	67.8	51.4	-	42.7	-	12.8	840
	SSM6J424TU ☆ # \$	\$ -20	+6/-8	-6.0	-	54	36	26	-	22.5	-	23.1	1650
	SSM6J414TU	\$ -20	+/-8	-6.0	-	54	36	26	-	22.5	-	23.1	1650
	SSM6J402TU #	\$ -30	+/-20	-2.0	-	-	-	-	225	-	117	5.3	280
	SSM6J410TU #	\$ -30	+/-20	-2.1	-	-	-	-	393	-	216	2.9	120
	SSM6J401TU #	\$ -30	+/-20	-2.5	-	-	-	-	145	-	73	16	730










☆ New Products, ● Recommend Another New Product
AEC-Q101 qualified, \$ With protection Zener diode between gate and source

UDFN6B (SOT-1220)	SOT-23F	S-Mini (SOT-346)	TSOP6F
Bottom View 			
2.0x2.0	2.9x2.4	2.9x2.5	2.9x2.8

P-Channel Single MOSFET

Package	Part Number	V _{DSS} (V)	V _{GSS} (V)	I _D (A)	R _{DS(ON)} max (mΩ)						Q _g typ. (nC)	C _{iss} typ. (pF)	Note		
					V _{GS} =-1.2V	V _{GS} =-1.5V	V _{GS} =-1.8V	V _{GS} =-2.5V	V _{GS} =-4V	V _{GS} =-4.5V				V _{GS} =-10V	
UDFN6B	SSM6J512NU	\$ -12	+/-10	-10.0	-	-	40.1	25.7	20.5(@-3.6V)	18.7	16.2(@-8V)	19.5	1400		
	SSM6J505NU	\$ -12	+/-6	-12.0	61	30	21	16	-	12	-	37.6	2700		
	SSM6J511NU	\$ -12	+/-10	-14.0	-	-	19.2	13.5	11.5(@-3.6V)	10	9.1(@-8V)	47	3350		
	SSM6J503NU	\$ -20	+/-8	-6.0	-	-	89.6	57.9	41.7	-	32.4	-	12.8	840	
	SSM6J502NU	\$ -20	+/-8	-6.0	-	-	60.5	38.4	28.3	-	23.1	-	24.8	1800	
	SSM6J501NU	\$ -20	+/-8	-10.0	-	-	43	26.5	19	-	15.3	-	29.9	2600	
	SSM6J507NU	\$ -30	+20/-25	-10.0	-	-	-	-	32	-	20	13.6	1150		
SOT-23F	SSM3J338R	\$ -12	+/-10	-6.0	-	-	45.3	27.9	21.9(@-3.6V)	20.2	17.6(@-8V)	19.5	1400		
	SSM3J327R	\$ -20	+/-8	-3.9	-	-	240	168	123	-	93	-	4.6	290	
	SSM3J377R	# \$ -20	+6/-8	-3.9	-	-	240	168	123	-	93	-	4.6	290	
	SSM3J331R	\$ -20	+/-8	-4.0	-	-	150	100	75	-	55	-	10.4	630	
	SSM3J371R	# \$ -20	+6/-8	-4.0	-	-	150	100	75	-	55	-	10.4	630	
	SSM3J328R	● \$ -20	+/-8	-6.0	-	-	88.4	56	39.7	-	29.8	-	12.8	840	⇒ SSM3J355R
	SSM3J378R	# \$ -20	+6/-8	-6.0	-	-	88.4	56	39.7	-	29.8	-	12.8	840	
	SSM3J355R	\$ -20	+/-10	-6.0	-	-	52.3	38.8	-	30.1	-	-	16.6	1030	
	SSM3J358R	\$ -20	+/-10	-6.0	-	-	49.3	32.8	27.7(@-3.6V)	25.3	22.1(@-8V)	38.5	1331		
	SSM3J334R	\$ -30	+/-20	-4.0	-	-	-	-	136	105	71	5.9	280		
	SSM3J374R	# \$ -30	+10/-20	-4.0	-	-	-	-	136	105	71	5.9	280		
	SSM3J340R	\$ -30	+20/-25	-4.0	-	-	-	-	86	73	45	6.2	492		
	SSM3J332R	\$ -30	+/-12	-6.0	-	-	144	72	-	50	42	8.2	560		
	SSM3J372R	# \$ -30	+6/-12	-6.0	-	-	144	72	-	50	42	8.2	560		
SSM3J356R	# \$ -60	+10/-20	-2.0	-	-	-	-	400	360	300	8.3	330			
SSM3J351R	# \$ -60	+10/-20	-3.5	-	-	-	-	184	164	134	15.1	660			
S-Mini	SSM3J325F	\$ -20	+/-8	-2.0	-	-	311	231	179	-	150	-	4.6	270	
	SSM3J375F	# \$ -20	+6/-8	-2.0	-	-	311	231	179	-	150	-	4.6	270	
	SSM3J352F	\$ -20	+/-12	-2.0	-	-	443	199	-	136	110	5.1	210		
	SSM3J353F	\$ -30	+20/-25	-2.0	-	-	-	-	274	232	150	3.4	159		
TSOP6F	SSM6J801R	\$ -20	+6/-8	-6.0	-	-	88.4	56	39.7	-	32.5	-	12.8	840	
	SSM6J808R	☆ # \$ -40	+10/-20	-7.0	-	-	-	-	52	48	35	24.2	1020		
	SSM6J811R	★ \$ -60	+10/-20	-4.0	-	-	-	-	184	164	134	15.1	660		



☆ New Products, ★ Under Development (The specification is subject to change without notice.), ● Recommend Another New Product
AEC-Q101 qualified, \$ With protection Zener diode between gate and source

CST3 (SOT-883)	CST3B	VESM (SOT-723)	SSM (SOT-416)	UFM (SOT-323F)	ES6 (SOT-563)	UF6 (SOT-363F)	UDFN6B (SOT-1220)	WCSP6C
Bottom View 	Bottom View 						Bottom View 	Bottom View 
1.0x0.6	1.2x0.8	1.2x1.2	1.6x1.6	2.0x2.1	1.6x1.6	2.0x2.1	2.0x2.0	1.5x1.0

N-Channel Single MOSFET

Package	Part Number	V _{oss} (V)	V _{ess} (V)	I _b (A)	R _{DS(ON)} max (mΩ)						Q _g typ. (nC)	C _{iss} typ. (pF)	Note	
					V _{GS} =1.2V	V _{GS} =1.5V	V _{GS} =1.8V	V _{GS} =2.5V	V _{GS} =4V	V _{GS} =4.5V				V _{GS} =10V
CST3	SSM3K56CT	\$ 20	+/-8	0.8	-	840	480	300	-	235	-	1.0	55	
	SSM3K56ACT	\$ 20	+/-8	1.4	-	840	480	300	-	235	-	1.0	55	
CST3B	SSM3K59CTB ●	\$ 40	+/-12	2.0	-	-	420	268	238(@3.6V) 231(@4.2V)	228	215(@8V)	1.1	130	⇒ SSM3K339R
VESM	SSM3K36MFV #	\$ 20	+/-10	0.5	-	1520	1140	850	-	660	630(@5V)	1.23	46	
	SSM3K56MFV	\$ 20	+/-8	0.8	-	840	480	300	-	235	-	1.0	55	
WCSP6C	SSM6K781G	12	+/-8	7.0	-	124	47.4	23.2	-	18	-	5.4	600	
SSM	SSM3K36FS #	\$ 20	+/-10	0.5	-	1520	1140	850	-	660	630(@5V)	1.23	46	
	SSM3K56FS	\$ 20	+/-8	0.8	-	840	480	300	-	235	-	1.0	55	
ES6	SSM6K204FE	\$ 20	+/-10	2.0	-	307	214	164	126	-	-	3.4	195	
	SSM6K211FE	\$ 20	+/-10	3.2	-	118	82	59	-	47	-	10.8	510	
	SSM6K24FE	\$ 30	+/-12	0.5	-	-	-	180	-	145	-	-	245	
	SSM6K208FE	\$ 30	+/-12	1.9	-	-	296	177	133	-	-	1.9	123	
	SSM6K202FE	\$ 30	+/-12	2.3	-	-	145	101	85	-	-	-	270	
	SSM6K217FE	\$ 40	+/-12	1.8	-	-	400	248	218(@3.6V) 211(@4.2V)	208	195(@8V)	1.1	130	
UFM	SSM3K36TU #	\$ 20	+/-10	0.5	-	1520	1140	850	-	660	630(@5V)	1.23	46	
	SSM3K62TU #	\$ 20	+/-8	0.8	432	139	89	68	-	57	-	2.0	177	
	SSM3K122TU #	\$ 20	+/-10	2.0	-	304	211	161	123	-	-	3.4	195	
	SSM3K121TU #	\$ 20	+/-10	3.2	-	140	93	63	48	-	-	5.9	400	
	SSM3K123TU #	\$ 20	+/-10	4.2	-	66	43	32	28	-	-	13.6	1010	
	SSM3K127TU #	\$ 30	+/-12	2.0	-	-	286	167	123	-	-	1.5	123	
	SSM3K116TU #	\$ 30	+/-12	2.2	-	-	-	135	-	100	-	-	245	
	SSM3K131TU #	\$ 30	+/-20	6.0	-	-	-	-	-	41.5	27.6	10.1	450	
	SSM3H137TU #	\$ 34	+/-20	2.0	-	-	-	-	295	280	240	3.0	119	Built-in Active Clamp Zener
	SSM3K2615TU #	\$ 60	+/-20	2.0	-	-	-	580(@3.3V)	440	-	300	6.0	150	
	SSM3K341TU #	\$ 60	+/-20	6.0	-	-	-	-	69	51	36	9.3	550	Tch=175°C
SSM3K361TU #	\$ 100	+/-20	3.5	-	-	-	-	-	92	69	3.2	430	Tch=175°C	
UF6	SSM6K405TU	\$ 20	+/-10	2.0	-	307	214	164	126	-	-	3.4	195	
	SSM6K404TU #	\$ 20	+/-10	3.0	-	147	100	70	55	-	-	5.9	400	
	SSM6K403TU #	\$ 20	+/-10	4.2	-	66	43	32	28	-	-	16.8	1050	
	SSM6K406TU #	\$ 30	+/-20	4.4	-	-	-	-	-	38.5	25	12.4	490	
	SSM6K407TU #	\$ 60	+/-20	2.0	-	-	-	-	440	-	300	6.0	150	
UDFN6B	SSM6K518NU ☆	20	+/-8	6.0	-	108	74	45	-	33	-	3.6	410	
	SSM6K517NU ☆	30	+12/-8	6.0	-	-	82	53	-	39.1	-	3.2	310	
	SSM6K504NU #	\$ 30	+/-20	9.0	-	-	-	-	-	26	19.5	4.8	620	
	SSM6K513NU	30	+/-20	15.0	-	-	-	-	-	12	8.9	7.5	1130	
	SSM6K516NU ☆	30	+20/-12	6.0	-	-	-	-	-	64	46	2.5	280	
	SSM6K514NU	40	+/-20	12.0	-	-	-	-	-	17.3	11.6	7.5	1110	
	SSM6K341NU	\$ 60	+/-20	6.0	-	-	-	-	69	51	36	9.3	550	
SSM6K361NU	\$ 100	+/-20	3.5	-	-	-	-	-	92	69	3.2	430		

☆ New Products, ● Recommend Another New Product
AEC-Q101 qualified, \$ With protection Zener diode between gate and source








SOT-23F	TSOP6F
	
2.9x2.4	2.9x2.8

N-Channel Single MOSFET

Package	Part Number	V _{DSS} (V)	V _{GSS} (V)	I _D (A)	R _{DS(ON)} max (mΩ)						Q _g typ. (nC)	C _{iss} typ. (pF)	Note	
					V _{GS} =1.2V	V _{GS} =1.5V	V _{GS} =1.8V	V _{GS} =2.5V	V _{GS} =4V	V _{GS} =4.5V				V _{GS} =10V
SOT-23F	SSM3K344R	§ 20	+/-8	3.0	-	232	139	91	-	71	-	2.0	153	
	SSM3K345R	§ 20	+/-8	4.0	-	108	74	45	-	33	-	3.6	410	
	SSM3K329R	§ 30	+/-12	3.5	-	-	289	170	126	-	-	1.5	123	
	SSM3K324R	§ 30	+/-12	4.0	-	-	109	72	-	56	-	2.2	200	
	SSM3K376R ☆ # §	30	+12/-8	4.0	-	-	109	72	-	56	-	2.2	200	
	SSM3K336R # §	30	+/-20	3.0	-	-	-	-	-	140	95	1.7	126	
	SSM3K333R #	30	+/-20	6.0	-	-	-	-	-	42	28	3.4	436	
	SSM3K335R # §	30	+/-20	6.0	-	-	-	-	-	56	38	2.7	340	
	SSM3K347R # §	38	+/-20	2.0	-	-	-	-	480	410	340	2.5	86	Built-in Active Clamp Zener
	SSM3K337R # §	38	+/-20	2.0	-	-	-	-	200	176	150	3.0	120	Built-in Active Clamp Zener
	SSM3K339R §	40	+/-12	2.0	-	-	390	238	208(@3.6V) 201(@4.2V)	198	185(@8V)	1.1	130	
	SSM3K357R ☆ # §	60	+/-12	0.65	-	-	-	2400(@3V)	-	1800(@5V)	-	1.5	43	Built-in Active Clamp Zener
	SSM3K2615R # §	60	+/-20	2.0	-	-	-	580(@3.3V)	440	-	300	6.0	150	
SSM3K318R # §	60	+/-20	2.5	-	-	-	-	-	145	107	7.0	235		
SSM3K341R # §	60	+/-20	6.0	-	-	-	-	69	51	36	9.3	550	Tch=175°C	
SSM3K361R # §	100	+/-20	3.5	-	-	-	-	-	92	69	3.2	430	Tch=175°C	
TSOP6F	SSM6K809R ☆ # §	60	+/-20	6.0	-	-	-	-	69	51	36	9.3	550	Tch=175°C
	SSM6K810R ☆ # §	100	+/-20	3.5	-	-	-	-	92	69	3.2	430	Tch=175°C	
	SSM6K818R ★	30	+/-20	15.0	-	-	-	-	-	12	8.9	7.5	1130	
	SSM6K819R ☆ # §	100	+/-20	10.0	-	-	-	-	-	36.4	25.8	8.5	1110	Tch=175°C

☆ New Products, ★ Under Development (The specification is subject to change without notice.)

AEC-Q101 qualified, § With protection Zener diode between gate and source

ES6 (SOT-563)	UF6 (SOT-363F)	US6 (SOT-363)	UDFN6 (SOT-1118)	TSOP6F	TCSP6A	TCSPAC-153001
			Bottom View 		Bottom View 	Bottom View 
1.6x1.6	2.0x2.1	2.0x2.1	2.0x2.0	2.9x2.8	2.14x1.67	2.98x1.49








Dual MOSFET

Package	Polarity	Part Number	V _{BSS} (V)	V _{GSS} (V)	I _D (A)	R _{DS(ON)} max (mΩ)							Q _g typ. (nC)	C _{iss} typ. (pF)	Note	
						V _{Gs} = 1.2V	V _{Gs} = 1.5V	V _{Gs} = 1.8V	V _{Gs} = 2.5V	V _{Gs} = 4V	V _{Gs} = 4.5V	V _{Gs} = 10V				
ES6	P-ch x2	SSM6P41FE	\$ -20	+/-8	-0.72	-	1040	670	440	-	300	-	1.76	110		
		SSM6P56FE ☆	\$ -20	+/-8	-0.8	4000	900	660	480	-	390	-	1.6	100		
	N-ch x2	SSM6N36FE #	\$ 20	+/-10	0.5	-	1520	1140	850	-	660	630(@5V)	1.23	46		
		SSM6N56FE	\$ 20	+/-8	0.8	-	840	480	300	-	235	-	1.0	55		
	N-ch + P-ch	SSM6L14FE	\$ 20	+/-10	0.8	-	600	450	330	-	240	-	2.0	90		
		SSM6L36FE #	\$ -20	+/-8	-0.72	-	1040	670	440	-	300	-	1.76	110		
			\$ 20	+/-10	0.5	-	1520	1140	850	-	660	630(@5V)	1.23	46		
UDFN6	P-ch x2	SSM6P47NU	\$ -20	+/-8	-4.0	-	242	170	125	-	95	-	4.6	290		
		SSM6P69NU ☆ #	\$ -20	+6/-12	-4.0	-	-	157	76	-	56	45	6.74	480		
		SSM6P49NU	\$ -20	+/-12	-4.0	-	-	157	76	-	56	45	6.74	480		
	N-ch x2	SSM6N61NU #	\$ 20	+/-8	4.0	-	108	74	45	-	33	-	3.6	410		
		SSM6N55NU	\$ 30	+/-20	4.0	-	-	-	-	-	64	46	2.5	280		
		SSM6N67NU #	\$ 30	+12/-8	4.0	-	-	82	53	-	39.1	-	3.2	310		
		SSM6N68NU #	\$ 30	+12/-8	4.0	-	-	180	117	-	84	-	1.8	129		
		SSM6N57NU	\$ 30	+/-12	4.0	-	-	82	53	-	39.1	-	3.2	310		
		SSM6N58NU	\$ 30	+/-12	4.0	-	-	180	117	-	84	-	1.8	129		
	N-ch + P-ch	SSM6L61NU	\$ 20	+/-8	4.0	-	108	74	45	-	33	-	3.6	410		
	UF6	P-ch x2	SSM6P54TU	\$ -20	+/-8	-1.2	-	555	350	228	-	-	-	7.7	331	
			SSM6P39TU #	\$ -20	+/-8	-1.5	-	-	430	294	213	-	-	6.4	250	
			SSM6P40TU #	\$ -30	+/-20	-1.4	-	-	-	-	403	-	226	2.9	120	
		N-ch x2	SSM6N36TU #	\$ 20	+/-10	0.5	-	1520	1140	850	-	660	630(@5V)	1.23	46	
			SSM6N62TU #	\$ 20	+/-8	0.8	456	173	120	98	-	85	-	2.0	177	
SSM6N39TU #			\$ 20	+/-10	1.6	-	247	190	139	119	-	-	7.5	260		
SSM6N24TU #			\$ 30	+/-12	0.5	-	-	-	180	-	145	-	-	245		
SSM6N40TU #			\$ 30	+/-20	1.6	-	-	-	-	182	-	122	5.1	180		
N-ch + P-ch			SSM6L36TU #	\$ 20	+/-10	0.5	-	1520	1140	850	-	660	630(@5V)	1.23	46	
		\$ -20		+/-8	-0.33	-	3600	2700	1600(@-2.8V)	-	1310	-	1.2	43		
		SSM6L39TU #	\$ 20	+/-10	1.6	-	247	190	139	119	-	-	7.5	260		
			\$ -20	+/-8	-1.5	-	-	430	294	213	-	-	6.4	250		
		SSM6L12TU #	\$ 30	+/-12	0.5	-	-	-	180	-	145	-	-	245		
			\$ -20	+/-12	-0.5	-	-	-	430	260	-	-	-	218		
SSM6L40TU #		\$ 30	+/-20	1.6	-	-	-	-	182	-	122	5.1	180			
	\$ -30	+/-20	-1.4	-	-	-	-	403	-	226	2.9	120				
US6	N-ch x2	SSM6N43FU #	\$ 20	+/-10	0.5	-	1520	1140	850	-	660	630(@5V)	1.23	46		
TSOP6F	N-ch x2	SSM6N357R ☆ #	\$ 60	+/-12	0.65	-	-	-	2400 (@3V)	-	1800 (@5V)	-	1.5	43	Built-in Active Clamp Zener	
		SSM6N815R	\$ 100	+/-20	2.0	-	-	-	-	180	142	103	3.1	290		
		SSM6N813R ☆ #	\$ 100	+/-20	3.5	-	-	-	-	-	154	112	3.6	242	T _J =175°C	
	P-ch x2	SSM6P816R ☆	\$ -20	+/-10	-6.0	-	-	52.3	38.8	-	30.1	-	16.6	1030		
		SSM6L807R ☆	\$ 30	+12/-12	4	-	-	82	53	-	39.1	-	3.2	310		
			\$ -20	+12/-12	-4	-	-	157	76	-	56	45	6.74	480		
N-ch + P-ch	SSM6L820R ☆ #	\$ 30	+12/-8	4	-	-	82	53	-	39.1	-	3.2	310			
		\$ -20	+6/-12	-4	-	-	157	76	-	56	45	6.74	480			
TCSP6A	N-ch x2	SSM6N951L ☆	\$ 12	+/-8	8	-	-	-	10	5.5(@3.8V)	5.1	-	26	-	Drain common	
TCSPAC-153001	N-ch x2	SSM10N954L ★	\$ 12	+/-8	13.5	-	-	-	-	2.85 (@3.8V)	2.75	-	25	-	Drain common	

☆ New Products, ★ Under Development (The specification is subject to change without notice.)
AEC-Q101 qualified, \$ With protection Zener diode between gate and source

2. Less than 500mA Series MOSFETs (Standard Type)






Package Dimensions (unit: mm)

CST3C	CST3 (SOT-883)	VESM (SOT-723)	SSM (SOT-416)	UFM (SOT-323F)	USM (SOT-323)	S-Mini (SOT-346)
Bottom View 	Bottom View 					
0.8x0.6	1.0x0.6	1.2x1.2	1.6x1.6	2.0x2.1	2.0x2.1	2.9x2.5

P-Channel Single MOSFET

Package	Part Number	V _{DSS} (V)	V _{ess} (V)	I _D (A)	R _{DS(ON)} max (Ω)							Note
					V _{GS} =-1.2V	V _{GS} =-1.5V	V _{GS} =-1.8V	V _{GS} =-2.5V	V _{GS} =-4V	V _{GS} =-4.5V	V _{GS} =-10V	
CST3C	SSM3J35CTC	\$ -20	+/-10	-0.25	20	4	2.9	2.1	-	1.4	-	
CST3	SSM3J35CT	\$ -20	+/-10	-0.1	44	22	-	11	8	-	-	
	SSM3J16CT ●	\$ -20	+/-10	-0.1	-	45	-	12	8	-	-	⇒ SSM3J35CT
	SSM3J15CT	\$ -30	+/-20	-0.1	-	-	-	32	12	-	-	
VESM	SSM3J35MFV ● #	\$ -20	+/-10	-0.1	44	22	-	11	8	-	-	⇒ SSM3J35AMFV
	SSM3J36MFV ●	\$ -20	+/-8	-0.33	-	3.6	2.7	1.6	-	1.36	-	⇒ SSM3J56MFV
	SSM3J16FV ●	\$ -20	+/-10	-0.1	-	45	-	12	8	-	-	⇒ SSM3J35AMFV
	SSM3J35AMFV	\$ -20	+/-10	-0.25	20	4	2.9	2.1	-	1.4	-	
	SSM3J15FV #	\$ -30	+/-20	-0.1	-	-	-	32	12	-	-	
SSM	SSM3J35FS #	\$ -20	+/-10	-0.1	44	22	-	11	8	-	-	
	SSM3J35AFS	\$ -20	+/-10	-0.25	20	4	2.9	2.1	-	1.4	-	
	SSM3J36FS #	\$ -20	+/-8	-0.33	-	3.6	2.7	1.6(@-2.8V)	-	1.31	-	
	SSM3J16FS ●	\$ -20	+/-10	-0.1	-	45	-	12	8	-	-	⇒ SSM3J35FS
	SSM3J15FS #	\$ -30	+/-20	-0.1	-	-	-	32	12	-	-	
UFM	SSM3J36TU #	\$ -20	+/-8	-0.33	-	3.6	2.7	1.6(@-2.8V)	-	1.31	-	
USM	SSM3J16FU #	\$ -20	+/-10	-0.1	-	45	-	12	8	-	-	
	SSM3J15FU #	\$ -30	+/-20	-0.1	-	-	-	32	12	-	-	
	SSM3J09FU	\$ -30	+/-20	-0.2	-	-	-	6(@-3.3V)	4.2	-	2.7	
S-Mini	SSM3J15F #	\$ -30	+/-20	-0.1	-	-	-	32	12	-	-	
	2SJ305	\$ -30	+/-20	-0.2	-	-	-	4	-	-	-	
	2SJ168 ●	\$ -60	+/-20	-0.2	-	-	-	-	-	-	2	⇒ SSM3J168F
	SSM3J168F ☆ #	\$ -60	+10/-20	-0.4	-	-	-	-	2	1.9	1.55	






☆ New Products, ● Recommend Another New Product, # AEC-Q101 qualified, \$ With protection Zener diode between gate and source

CST3C	CST3 (SOT-883)	VESM (SOT-723)	SSM (SOT-416)	USM (SOT-323)	SOT23 (SOT-23)	S-Mini (SOT-346)
Bottom View	Bottom View					
0.8x0.6	1.0x0.6	1.2x1.2	1.6x1.6	2.0x2.1	2.9x2.4	2.9x2.5

N-Channel Single MOSFET

Package	Part Number	V _{DSS} (V)	V _{GSS} (V)	I _D (A)	R _{DS(ON)} max (Ω)								Note
					V _{GS} =1.2V	V _{GS} =1.5V	V _{GS} =1.8V	V _{GS} =2.5V	V _{GS} =4V	V _{GS} =4.5V	V _{GS} =5V	V _{GS} =10V	
CST3C	SSM3K16CTC	\$ 20	+/-10	0.2	-	5.6	4	3	-	2.2	-	-	
	SSM3K35CTC	\$ 20	+/-10	0.25	9	3.1	2.4	1.6	-	1.1	-	-	
	SSM3K15ACTC	\$ 30	+/-20	0.1	-	-	-	6	3.6	-	-	-	
	SSM3K72CTC	\$ 60	+/-20	0.15	-	-	-	5.7(typ.)	-	4.7	4.4	3.9	
CST3	SSM3K16CT	● \$ 20	+/-10	0.1	-	15	-	4	3	-	-	-	⇒ SSM3K37CT
	SSM3K35CT	\$ 20	+/-10	0.18	20	8	-	4	3	-	-	-	
	SSM3K37CT	\$ 20	+/-10	0.2	-	5.6	4.05	3.02	-	2.2	-	-	
	SSM3K15CT	● \$ 30	+/-20	0.1	-	-	-	7	4	-	-	-	⇒ SSM3K15ACT
	SSM3K15ACT	\$ 30	+/-20	0.1	-	-	-	6	3.6	-	-	-	
	SSM3K72KCT	\$ 60	+/-20	0.4	-	-	-	-	-	1.75	1.65	1.5	
VESM	SSM3K16FV	\$ 20	+/-10	0.1	-	15	-	4	3	-	-	-	
	SSM3K35MFV	# \$ 20	+/-10	0.18	20	8	-	4	3	-	-	-	
	SSM3K37MFV	\$ 20	+/-10	0.25	-	5.6	4.05	3.02	-	2.2	-	-	
	SSM3K35AMFV	\$ 20	+/-10	0.25	9	3.1	2.4	1.6	-	1.1	-	-	
	SSM3K15AMFV	\$ 30	+/-20	0.1	-	-	-	6	3.6	-	-	-	
	SSM3K44MFV	# \$ 30	+/-20	0.1	-	-	-	7	4	-	-	-	
SSM	SSM3K16FS	● # \$ 20	+/-10	0.1	-	15	-	4	3	-	-	-	⇒ SSM3K37FS
	SSM3K35FS	● # \$ 20	+/-10	0.18	20	8	-	4	3	-	-	-	⇒ SSM3K35AFS
	SSM3K37FS	\$ 20	+/-10	0.2	-	5.6	4.05	3.02	-	2.2	-	-	
	SSM3K35AFS	\$ 20	+/-10	0.25	9	3.1	2.4	1.6	-	1.1	-	-	
	SSM3K15FS	● \$ 30	+/-20	0.1	-	-	-	7	4	-	-	-	⇒ SSM3K15AFS
	SSM3K44FS	# \$ 30	+/-20	0.1	-	-	-	7	4	-	-	-	
	SSM3K15AFS	\$ 30	+/-20	0.1	-	-	-	6	3.6	-	-	-	
	SSM3K72CFS	\$ 60	+/-20	0.17	-	-	-	-	-	4.7	4.4	3.9	
USM	SSM3K72KFS	# \$ 60	+/-20	0.3	-	-	-	-	-	1.75	1.65	1.5	
	SSM3K16FU	# \$ 20	+/-10	0.1	-	15	-	4	3	-	-	-	
	SSM3K15FU	# \$ 30	+/-20	0.1	-	-	-	7	4	-	-	-	
	SSM3K15AFU	\$ 30	+/-20	0.1	-	-	-	6	3.6	-	-	-	
	SSM3K48FU	\$ 30	+/-20	0.1	-	-	-	5.4	3.2	-	-	-	
	SSM3K09FU	\$ 30	+/-20	0.4	-	-	-	1.7(@3.3V)	1.2	-	-	0.7	
	SSM3K17FU	# \$ 50	+/-7	0.1	-	-	-	40	20	-	-	-	
	SSM3K7002CFU	\$ 60	+/-20	0.17	-	-	-	-	-	4.7	4.4	3.9	
SOT23	SSM3K7002KFU	# \$ 60	+/-20	0.4	-	-	-	-	-	1.75	1.65	1.5	
	T2N7002AK	\$ 60	+/-20	0.2	-	-	-	-	-	4.7	4.4	3.9	
S-Mini	T2N7002BK	\$ 60	+/-20	0.4	-	-	-	-	-	1.75	1.65	1.5	
	SSM3K15F	# \$ 30	+/-20	0.1	-	-	-	7	4	-	-	-	
	2SK2009	\$ 30	+/-20	0.2	-	-	-	2	-	-	-	-	
	SSM3K7002KF	# \$ 60	+/-20	0.4	-	-	-	-	-	1.75	1.65	1.5	

● Recommend Another New Product, # AEC-Q101 qualified, \$ With protection Zener diode between gate and source

ESV (SOT-553)	ES6 (SOT-563)	USV (SOT-353)	UF6 (SOT-363F)	US6 (SOT-363)
				
1.6x1.6	1.6x1.6	2.0x2.1	2.0x2.1	2.0x2.1




Dual MOSFET

Package	Polarity	Part Number	V _{DSS} (V)	V _{GSS} (V)	I _D (A)	R _{DS(ON)} max (Ω)								Note	
						V _{Gs} = 1.2V	V _{Gs} = 1.5V	V _{Gs} = 1.8V	V _{Gs} = 2.5V	V _{Gs} = 4V	V _{Gs} = 4.5V	V _{Gs} = 5V	V _{Gs} = 10V		
ESV	N-ch x2	SSM5N16FE	\$ 20	+/-10	0.1	-	15	-	4	3	-	-	-		
		SSM5N15FE	\$ 30	+/-20	0.1	-	-	-	7	4	-	-	-		
ES6	P-ch x2	SSM6P35FE	# \$ -20	+/-10	-0.1	44	22	-	11	8	-	-	-		
		SSM6P35AFE	\$ -20	+/-10	-0.25	20	4	2.9	2.1	-	1.4	-	-		
		SSM6P36FE	# \$ -20	+/-8	-0.33	-	3.6	2.7	1.6(@2.8V)	-	1.31	-	-		
		SSM6P16FE	● \$ -20	+/-10	-0.1	-	45	-	12	8	-	-	-	⇒ SSM6P35FE	
		SSM6P15FE	# \$ -30	+/-20	-0.1	-	-	-	32	12	-	-	-		
	N-ch x2	SSM6N16FE	\$ 20	+/-10	0.1	-	15	-	4	3	-	-	-		
		SSM6N35FE	● # \$ 20	+/-10	0.18	20	8	-	4	3	-	-	-	⇒ SSM6N35AFE	
		SSM6N37FE	\$ 20	+/-10	0.25	-	5.6	4.05	3.02	-	2.2	-	-		
		SSM6N35AFE	\$ 20	+/-10	0.25	9	3.1	2.4	1.6	-	1.1	-	-		
		SSM6N44FE	# \$ 30	+/-20	0.1	-	-	-	7	4	-	-	-		
		SSM6N15AFE	\$ 30	+/-20	0.1	-	-	-	6	3.6	-	-	-		
		SSM6N7002BFE	\$ 60	+/-20	0.2	-	-	-	-	-	3.3	2.6	2.1		
		SSM6L35FE	# \$ 20	+/-10	0.18	20	8	-	4	3	-	-	-		
	USV	P-ch x2	SSM5P15FU	\$ -30	+/-20	-0.1	-	-	-	32	12	-	-	-	
N-ch x2		SSM5N16FU	\$ 20	+/-10	0.1	-	15	-	4	3	-	-	-		
		SSM5N15FU	\$ 30	+/-20	0.1	-	-	-	7	4	-	-	-		
UF6	P-ch x2	SSM6P36TU	# \$ -20	+/-8	-0.33	-	3.6	2.7	1.6(@2.8V)	-	1.31	-	-		
US6	P-ch x2	SSM6P35FU	● # \$ -20	+/-10	-0.1	44	22	-	11	8	-	-	-	⇒ SSM6P35AFU	
		SSM6P35AFU	\$ -20	+/-10	-0.25	20	4	2.9	2.1	-	1.4	-	-		
		SSM6P16FU	● \$ -20	+/-10	-0.1	-	45	-	12	8	-	-	-	⇒ SSM6P35AFU	
		SSM6P15FU	# \$ -30	+/-20	-0.1	-	-	-	32	12	-	-	-		
		SSM6N16FU	● \$ 20	+/-10	0.1	-	15	-	4	3	-	-	-	⇒ SSM6N37FU	
	N-ch x2	SSM6N35FU	● # \$ 20	+/-10	0.18	20	8	-	4	3	-	-	-	⇒ SSM6N35AFU	
		SSM6N35AFU	\$ 20	+/-10	0.25	9	3.1	2.4	1.6	-	1.1	-	-		
		SSM6N37FU	\$ 20	+/-10	0.25	-	5.6	4.05	3.02	-	2.2	-	-		
		SSM6N48FU	\$ 30	+/-20	0.1	-	-	-	5.4	3.2	-	-	-		
		SSM6N44FU	# \$ 30	+/-20	0.1	-	-	-	7	4	-	-	-		
		SSM6N15FU	● \$ 30	+/-20	0.1	-	-	-	7	4	-	-	-	⇒ SSM6N15AFU	
		SSM6N15AFU	\$ 30	+/-20	0.1	-	-	-	6	3.6	-	-	-		
		SSM6N09FU	\$ 30	+/-20	0.4	-	-	-	1.7(@3.3V)	1.2	-	-	-	0.7	
		SSM6N17FU	# \$ 50	+/-7	0.1	-	-	-	40	20	-	-	-		
		SSM6N7002CFU	\$ 60	+/-20	0.17	-	-	-	-	-	4.7	4.4	3.9		
		SSM6N7002KFU	# \$ 60	+/-20	0.3	-	-	-	-	-	1.75	1.65	1.5		
		N-ch + P-ch	SSM6L35FU	# \$ 20	+/-10	0.18	20	8	-	4	3	-	-	-	
			SSM6L09FU	\$ -30	+/-20	-0.2	-	-	-	6(@-3.3V)	4.2	-	-	2.7	

● Recommend Another New Product, # AEC-Q101 qualified, \$ With protection Zener diode between gate and source

3. MOSFET with Diode

Package Dimensions (unit: mm)

ESV (SOT-553)	UFV (SOT-353F)	UDFN6 (SOT-1118)
		
1.6x1.6	2.0x2.1	2.0x2.0

Package	Polarity	Part Number	V _{DSS} (V)	V _{GSS} (V)	I _D (A)	MOSFET						Diode				Note		
						R _{DS(ON)} max (mΩ)						Ciss typ. (pF)	V _R (V)	I _O (A)	V _F max (V)			
						V _{Gs} = 1.5V	V _{Gs} = 1.8V	V _{Gs} = 2.5V	V _{Gs} = 4V	V _{Gs} = 4.5V	V _{Gs} = 5V				V _{Gs} = 10V		@I _F (A)	@I _F (A)
ESV	P-ch + SBD	SSM5G06FE	§ -20	+/-10	-0.1	45000	-	12000	8000	-	-	-	11	12	0.1	0.5	0.1	
	N-ch + SBD	SSM5H06FE	§ 20	+/-10	0.1	15000	-	4000	3000	-	-	-	9.3	12	0.1	0.5	0.1	
UFV	P-ch + SBD	SSM5G02TU	§ -12	+/-12	-1.0	-	-	240	160	-	-	-	310	12	0.5	0.43	0.5	
		SSM5G09TU	§ -12	+/-8	-1.5	-	-	200	130	-	-	-	550	12	0.5	0.43	0.5	
		SSM5G11TU	§ -30	+/-20	-1.4	-	-	-	403	-	-	226	120	30 (¥)	0.7 (¥¥)	0.44	0.7 (¥¥)	
	N-ch + SBD	SSM5H08TU	§ 20	+/-12	1.5	-	-	220	160	-	-	-	125	20	0.5	0.43 (typ.)	0.5	
		SSM5H01TU	§ 30	+/-20	1.4	-	-	-	450	-	-	200	106	20	0.5	0.43 (typ.)	0.5	
		SSM5H11TU	§ 30	+/-20	1.6	-	-	-	182	-	-	122	180	30 (¥)	0.7 (¥¥)	0.44	0.7	
		SSM5H16TU	§ 30	+/-12	1.9	-	296	177	133	-	-	-	123	30	0.8	0.55	0.8	
	N-ch + Switching Diode	SSM5H90ATU	§ 20	+/-10	2.4	-	-	89	65	-	-	-	200	80	0.1	1.2	0.1	
UDFN6	P-ch + SBD	SSM6G18NU	§ -20	+/-8	-2.0	261	185	143	-	112	-	-	270	30	1	0.58	1	
	N-ch + SBD	SSM6H19NU	§ 40	+/-12	2.0	-	390	238	208(@3.6V) 201(@4.2V)	198	-	185(@8V)	130	40	0.5	0.57	0.5	

§ With protection Zener diode between gate and source, ¥ V_{RRM}, ¥¥ I_{F(AV)}

4. Part Naming Conventions

Small Signal MOSFET SSM Series

Ex) SSM 3 K 329 R
① ② ③ ④ ⑤

① Small-Signal MOSFET

② Pin count

③ Polarity and internal configuration

K: N-channel, single

J: P-channel, single

N: N-channel, dual

P: P-channel, dual

L: N-channel and P-channel (dual)

E: N-channel and P-channel (pre-wired as a load switch)

H: N-channel and SBD

G: P-channel and SBD

Q: PNP and P-channel

④ Serial number of the products

⑤ Package

3-pin F: S-Mini

FU: USM

FS: SSM

FV: VESM

TU: UFM

CT: CST3

CTB: CST3B

CTC: CST3C

R: SOT-23F

5-pin F: SMV

FU: USV

FE: ESV

TU: UVF

6-pin G: WCSP6C

L: TCSP6A

R: TSOP6F

FU: US6

FE: ES6

TU: UF6

NU: UDFN6/UDFN6B

5. Device Packages

Dimensional Outline

VESM (SOT-723)		SSM (SOT-416)		UFM (SOT-323F)	
Package dimension	unit : mm	Package dimension	unit : mm	Package dimension	unit : mm
Land pattern example	unit : mm	Land pattern example	unit : mm	Land pattern example	unit : mm
USM (SOT-323)		SOT23 (SOT-23)		SOT-23F	
Package dimension	unit : mm	Package dimension	unit : mm	Package dimension	unit : mm
Land pattern example	unit : mm	Land pattern example	unit : mm	Land pattern example	unit : mm
S-Mini (SOT-346)		ESV (SOT-553)		UFV (SOT-353F)	
Package dimension	unit : mm	Package dimension	unit : mm	Package dimension	unit : mm
Land pattern example	unit : mm	Land pattern example	unit : mm	Land pattern example	unit : mm

USV (SOT-353)	SMV (SOT-25)	ES6 (SOT-563)
Package dimension unit : mm 	Package dimension unit : mm 	Package dimension unit : mm
Land pattern example unit : mm 	Land pattern example unit : mm 	Land pattern example unit : mm

UF6 (SOT-363F)	US6 (SOT-363)	TSOP6F
Package dimension unit : mm 	Package dimension unit : mm 	Package dimension unit : mm
Land pattern example unit : mm 	Land pattern example unit : mm 	Land pattern example unit : mm

Leadless packages

CST3 (SOT-883)	CST3B	CST3C
Package dimension unit : mm 	Package dimension unit : mm 	Package dimension unit : mm
Land pattern example unit : mm 	Land pattern example unit : mm 	Land pattern example unit : mm

UDFN6 (SOT-1118)	UDFN6B (SOT-1220)	WCSP6C
Package dimension unit : mm 	Package dimension unit : mm 	Package dimension unit : mm
Land pattern example unit : mm 	Land pattern example unit : mm 	Land pattern example unit : mm

TCSP6A	TCSPAC-153001
Package dimension unit : mm 	Package dimension unit : mm
Land pattern example unit : mm 	Land pattern example unit : mm

II Power MOSFETs

1. Low-Voltage MOSFET Series

TSON Advance (3.3x3.3)



Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)								Q _g typ.(nC)		C _{iss} typ. (pF)	Remark	
		V _{DS} (V)	V _{GS} (V)	I _O (A)	V _{GS} =10V	V _{GS} =6.5V	V _{GS} =6V	V _{GS} =4.5V	V _{GS} =4V	V _{GS} =2.5V	V _{GS} =2V	V _{GS} =1.8V	V _{GS} =10V	V _{GS} =4.5V			
N-ch Note(1)	TPN11003NL	30	+/-20	31 ^{SL}	11	-	-	16	-	-	-	7.5	3.3	510	U-MOSVIII-H		
	TPN8R903NL	30	+/-20	37 ^{SL}	8.9	-	-	12.7	-	-	-	9.8	4.4	630	U-MOSVIII-H		
	TPN6R003NL	30	+/-20	56 ^{SL}	6	-	-	8.3	-	-	-	17	8.2	1050	U-MOSVIII-H		
	TPN5R203PL	30	+/-20	76 ^{SL}	5.2	-	-	6.4	-	-	-	22	10	1520	U-MOSIX-H		
	TPN4R303NL	30	+/-20	63 ^{SL}	4.3	-	-	6.3	-	-	-	14.8	6.8	1110	U-MOSVIII-H		
	TPN2R903PL	30	+/-20	122 ^{SL}	2.9	-	-	4.1	-	-	-	26	12	1780	U-MOSIX-H		
	TPN2R703NL	30	+/-20	90 ^{SL}	2.7	-	-	4.1	-	-	-	21	9.5	1600	U-MOSVIII-H		
	TPN1R603PL	30	+/-20	188 ^{SL}	1.6	-	-	2.5	-	-	-	41	20	2970	U-MOSIX-H		
	TPN7R504PL	40	+/-20	68 ^{SL}	7.5	-	-	10	-	-	-	24	12	1570	U-MOSIX-H		
	TPN3R704PL	40	+/-20	92 ^{SL}	3.7	-	-	6	-	-	-	27	13.3	1910	U-MOSIX-H		
	TPN2R304PL	40	+/-20	100 ^{SL}	2.3	-	-	4	-	-	-	41	19.4	2750	U-MOSIX-H		
	TPN2R805PL	45	+/-20	139 ^{SL}	2.8	-	-	5	-	-	-	39	19	2450	U-MOSIX-H		
	TPN22006NH	60	+/-20	21 ^{SL}	22	64	-	-	-	-	-	12	-	710	U-MOSVIII-H		
	TPN14006NH	60	+/-20	33 ^{SL}	14	41	-	-	-	-	-	15	-	1000	U-MOSVIII-H		
	TPN11006NL	60	+/-20	37 ^{SL}	11.4	-	-	17	-	-	-	23	11.2	1500	U-MOSVIII-H		
	TPN11006PL	60	+/-20	54 ^{SL}	11.4	-	-	18.1	-	-	-	17	9	1250	U-MOSIX-H		
	TPN7R506NH	60	+/-20	53 ^{SL}	7.5	16	-	-	-	-	-	22	-	1410	U-MOSVIII-H		
	TPN7R006PL	60	+/-20	76 ^{SL}	7	-	-	13.5	-	-	-	20	9.8	1440	U-MOSIX-H		
	TPN4R806PL	60	+/-20	105 ^{SL}	4.8	-	-	9.1	-	-	-	29	14	2130	U-MOSIX-H		
	TPN30008NH	80	+/-20	22 ^{SL}	30	-	-	-	-	-	-	11	-	710	U-MOSVIII-H		
	TPN19008QM ☆	80	+/-20	38 ^{SL}	19	-	28	-	-	-	-	16	9.7(@6V)	1020	U-MOSX-H		
	TPN13008NH	80	+/-20	40 ^{SL}	13.3	-	-	-	-	-	-	18	-	1230	U-MOSVIII-H		
	TPN12008QM ☆	80	+/-20	60 ^{SL}	12.3	-	17.7	-	-	-	-	22	13.9(@6V)	1280	U-MOSX-H		
	TPN8R408QM ☆	80	+/-20	77 ^{SL}	8.4	-	12.4	-	-	-	-	28	17(@6V)	1750	U-MOSX-H		
	TPN3300ANH	100	+/-20	21 ^{SL}	33	-	-	-	-	-	-	11	-	680	U-MOSVIII-H		
	TPN1600ANH	100	+/-20	36 ^{SL}	16	-	-	-	-	-	-	19	-	1230	U-MOSVIII-H		
TPN1200APL \$	100	+/-20	66 ^{SL}	11.5	-	-	20	-	-	-	24	12	1425	U-MOSIX-H			
TPN5900CNH	150	+/-20	18 ^{SL}	59	-	-	-	-	-	-	7	-	460	U-MOSVIII-H			
TPN1110ENH	200	+/-20	13 ^{SL}	114	-	-	-	-	-	-	7	-	460	U-MOSVIII-H			
TPN2010FNH	250	+/-20	9.9 ^{SL}	198	-	-	-	-	-	-	7	-	460	U-MOSVIII-H			
N-ch	TPN6R303NC	30	+/-20	43 ^{SL}	6.3	-	-	8.4	-	-	-	24	-	1370	U-MOSVIII		
	TPN4R203NC	30	+/-20	53 ^{SL}	4.2	-	-	6.4	-	-	-	24	-	1370	U-MOSVIII		
	TPN2R203NC	30	+/-20	100 ^{SL}	2.2	-	-	3.6	-	-	-	34	-	2230	U-MOSVIII		
P-ch	TPCC8136	-20	+/-12	-9.4	-	-	-	16	-	22	37	60	-	36(@5V)	2350	U-MOSVI	
	TPCC8137	-20	+/-12	-13	-	-	-	10	-	16	30	52	-	43(@5V)	2990	U-MOSVI	
	TPCC8138	-20	+/-12	-18	-	-	-	7.5	-	11	21	42	-	63(@5V)	4165	U-MOSVI	
	TPN4R712MD	-20	+/-12	-36	-	-	-	4.7	-	8.1	-	-	-	65(@5V)	4300	U-MOSVI	
	TPCC8131	-30	+20/-25	-10	17.6	-	-	23	-	-	-	-	-	40	-	1700	U-MOSVI
	TPCC8104	-30	+20/-25	-20	8.8	-	-	12.4	-	-	-	-	-	58	-	2260	U-MOSVI
TPCC8105	-30	+20/-25	-23	7.8	-	-	10.4	-	-	-	-	-	76	-	3240	U-MOSVI	

☆ New Products, \$ With protection Zener diode between gate and source, ^{SL} I_{D(DC)} (Silicon Limit)
 Note(1) : High-speed switching type



SOP-8 (SO-8) (5x6)

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)		Q _g typ.(nC)		C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{VSS} (V)	I _D (A)	V _{GS} =10V	V _{GS} =4.5V	V _{GS} =10V	V _{GS} =4.5V		
N-ch Note(1)	TP89R103NL	30	+/-20	15 ^{SL}	9.1	12.9	9.8	4.4	630	U-MOSVIII-H
	TP86R203NL	30	+/-20	19 ^{SL}	6.2	8.5	17	8.2	1050	U-MOSVIII-H
P-ch	TPC8129	-30	+20/-25	-9	22	28	39	-	1650	U-MOSVI
	TPC8125	-30	+20/-25	-10	13	17	64	-	2580	U-MOSVI
	TPC8134	-40	+20/-25	-5	52	66	20	-	890	U-MOSVI
	TPC8132	-40	+20/-25	-7	25	33	34	-	1580	U-MOSVI
	TPC8133	-40	+20/-25	-9	15	18	64	-	2900	U-MOSVI
N-ch + P-ch	TPC8408	40	+/-20	6.1	32	36	14	-	850	U-MOSVI-H
		-40	+/-20	-5.3	43	53	24	-	1105	U-MOSVI



SOP Advance (5x6)

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)					Q _g typ.(nC)		C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{VSS} (V)	I _D (A)	V _{GS} =10V	V _{GS} =6.5V	V _{GS} =6V	V _{GS} =4.5V	V _{GS} =2.5V	V _{GS} =10V	V _{GS} =4.5V		
N-ch Note(1)	TPH11003NL	30	+/-20	32 ^{SL}	11	-	-	16	-	7.5	3.3	510	U-MOSVIII-H
	TPH8R903NL	30	+/-20	38 ^{SL}	8.9	-	-	12.7	-	9.8	4.4	630	U-MOSVIII-H
	TPH6R003NL	30	+/-20	57 ^{SL}	6	-	-	8.3	-	17	8.2	1050	U-MOSVIII-H
	TPH4R803PL	30	+/-20	90 ^{SL}	4.8	-	-	6.2	-	22	10	1520	U-MOSIX-H
	TPH4R003NL	30	+/-20	68 ^{SL}	4	-	-	6.2	-	14.8	6.8	1110	U-MOSVIII-H
	TPH3R203NL	30	+/-20	84 ^{SL}	3.2	-	-	4.7	-	21	9.5	1600	U-MOSVIII-H
	TPH3R003PL	30	+/-20	134 ^{SL}	3	-	-	4.2	-	50	24	2940	U-MOSIX-H
	TPH2R903PL	30	+/-20	124 ^{SL}	2.9	-	-	4.1	-	26	12	1780	U-MOSIX-H
	TPH2R003PL	30	+/-20	180 ^{SL}	2	-	-	2.6	-	86	41	4930	U-MOSIX-H
	TPH1R403NL	¥ 30	+/-20	150 ^{SL}	1.4	-	-	2.1	-	46	20	3400	U-MOSVIII-H
	TPHR9203PL	¥ 30	+/-20	280 ^{SL}	0.92	-	-	1.29	-	81	38	5800	U-MOSIX-H
	TPHR9003NL	¥ 30	+/-20	220 ^{SL}	0.9	-	-	1.4	-	74	32	5300	U-MOSVIII-H
	TPHR6503PL	¥ 30	+/-20	393 ^{SL}	0.65	-	-	0.89	-	110	52	7700	U-MOSIX-H
	TPH7R204PL	40	+/-20	72 ^{SL}	7.2	-	-	9.7	-	24	12	1570	U-MOSIX-H
	TPH6R004PL	40	+/-20	87 ^{SL}	6	-	-	8.4	-	30	15	2100	U-MOSIX-H
	TPH3R704PL	40	+/-20	92	3.7	-	-	6	-	27	13.3	1910	U-MOSIX-H
	TPH3R704PC	40	+/-20	118 ^{SL}	3.7	-	-	5.8	-	47	23	2780	U-MOSIX-H
	TPH2R104PL	40	+/-20	180 ^{SL}	2.1	-	-	3.1	-	78	37	4790	U-MOSIX-H
	TPH1R204PL	¥ 40	+/-20	246 ^{SL}	1.24	-	-	2.1	-	74	34	5500	U-MOSIX-H
	TPH1R204PB	40	+/-20	240 ^{SL}	1.2	-	1.96	-	-	62	-	4400	U-MOSIX-H (Low Spike)
	TPHR8504PL	¥ 40	+/-20	340 ^{SL}	0.85	-	-	1.4	-	103	49	7370	U-MOSIX-H
	TPH2R805PL	45	+/-20	150 ^{SL}	2.8	-	-	3.9	-	73	37	3980	U-MOSIX-H
	TPH1R405PL	45	+/-20	232 ^{SL}	1.4	-	-	2.3	-	74	36	4830	U-MOSIX-H
	TPH1R005PL	¥ 45	+/-20	280 ^{SL}	1.04	-	-	1.7	-	122	59	7700	U-MOSIX-H
	TPH14006NH	60	+/-20	34 ^{SL}	14	33	-	-	-	16	-	1000	U-MOSVIII-H
	TPH11006NL	60	+/-20	40 ^{SL}	11.4	-	-	17	-	23	11.2	1500	U-MOSVIII-H
	TPH9R506PL	60	+/-20	68 ^{SL}	9.5	-	-	15	-	21	11	1470	U-MOSIX-H

^{SL} I_D(DC) (Silicon Limit)

¥ The package can be selected according to your preference. For details, please contact your TOSHIBA sales representative.

Note(1) : High-speed switching type

SOP Advance (5x6)

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)						Q _g typ.(nC)		C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I ₀ (A)	V _{GS} =10V	V _{GS} =6.5V	V _{GS} =6V	V _{GS} =4.5V	V _{GS} =2.5V	V _{GS} =10V	V _{GS} =4.5V			
N-ch Note(1)	TPH7R506NH	60	+/-20	55 ^{SL}	7.5	19	-	-	-	31	-	1785	U-MOSVIII-H	
	TPH7R006PL	60	+/-20	79 ^{SL}	7	-	-	13.5	-	22	11	1440	U-MOSIX-H	
	TPH5R906NH	60	+/-20	71 ^{SL}	5.9	14	-	-	-	38	-	2340	U-MOSVIII-H	
	TPH4R606NH	60	+/-20	85 ^{SL}	4.6	11	-	-	-	49	-	3050	U-MOSVIII-H	
	TPH3R506PL	60	+/-20	135 ^{SL}	3.5	-	-	6.7	-	55	27	3400	U-MOSIX-H	
	TPH2R506PL ¥	60	+/-20	160 ^{SL}	2.5	-	-	4.4	-	60	32	4180	U-MOSIX-H	
	TPH2R306NH ¥	60	+/-20	130 ^{SL}	2.3	4.7	-	-	-	72	-	4700	U-MOSVIII-H	
	TPH1R306PL ¥	60	+/-20	260 ^{SL}	1.34	-	-	2.3	-	91	44	6250	U-MOSIX-H	
	TPH1R306P1 ☆	60	+/-20	260 ^{SL}	1.28	-	-	2.3	-	91	44	6250	U-MOSIX-H (Low Spike)	
	TPH2R608NH	75	+/-20	168 ^{SL}	2.6	-	-	-	-	72	-	4600	U-MOSVIII-H	
	TPH12008NH	80	+/-20	44 ^{SL}	12.3	-	-	-	-	22	-	1490	U-MOSVIII-H	
	TPH8R008NH	80	+/-20	63 ^{SL}	8	-	-	-	-	35	-	2300	U-MOSVIII-H	
	TPH4R008NH ¥	80	+/-20	100 ^{SL}	4	-	-	-	-	59	-	4100	U-MOSVIII-H	
	TPH2R408QM ☆ ¥	80	+/-20	200 ^{SL}	2.43	-	3.5	-	-	87	55(@6V)	5870	U-MOSX-H	
	TPH1400ANH	100	+/-20	42 ^{SL}	13.6	-	-	-	-	22	-	1440	U-MOSVIII-H	
	TPH8R80ANH	100	+/-20	59 ^{SL}	8.8	-	-	-	-	33	-	2180	U-MOSVIII-H	
	TPH6R30ANL §	100	+/-20	66 ^{SL}	6.3	-	-	10.3	-	55	27	3300	U-MOSVIII-H	
	TPH5R60APL	100	+/-20	110 ^{SL}	5.6	-	-	9.5	-	52	26	3300	U-MOSIX-H	
	TPH4R50ANH ¥	100	+/-20	93 ^{SL}	4.5	-	-	-	-	58	-	4000	U-MOSVIII-H	
	TPH4R10ANL	100	+/-20	92 ^{SL}	4.1	-	-	6.6	-	75	37	4850	U-MOSVIII-H	
	TPH3R70APL ¥	100	+/-20	150 ^{SL}	3.7	-	-	6.2	-	67	33	4850	U-MOSIX-H	
	TPH5900CNH	150	+/-20	18 ^{SL}	59	-	-	-	-	7	-	460	U-MOSVIII-H	
	TPH3300CNH	150	+/-20	29 ^{SL}	33	-	-	-	-	10.6	-	810	U-MOSVIII-H	
	TPH1500CNH ¥	150	+/-20	50 ^{SL}	15.4	-	-	-	-	22	-	1700	U-MOSVIII-H	
TPH1110ENH	200	+/-20	13 ^{SL}	114	-	-	-	-	7	-	460	U-MOSVIII-H		
TPH6400ENH	200	+/-20	21 ^{SL}	64	-	-	-	-	11.2	-	810	U-MOSVIII-H		
TPH2900ENH	200	+/-20	36 ^{SL}	29	-	-	-	-	22	-	1700	U-MOSVIII-H		
TPH2010FNH	250	+/-20	10 ^{SL}	198	-	-	-	-	7	-	460	U-MOSVIII-H		
TPH1110FNH	250	+/-20	15 ^{SL}	112	-	-	-	-	11	-	810	U-MOSVIII-H		
TPH5200FNH	250	+/-20	27 ^{SL}	52	-	-	-	-	22	-	1700	U-MOSVIII-H		
N-ch	TPHR9003NC	30	+/-20	220 ^{SL}	0.9	-	-	1.4	-	75	32	5300	U-MOSVIII	
P-ch	TPH1R712MD	-20	+/-12	-60	-	-	-	1.7	2.7	-	182(@-5V)	10900	U-MOSVI	
	TPCA8131	-30	+20/-25	-13	17	-	-	22	-	40	-	1700	U-MOSVI	
	TPCA8109	-30	+20/-25	-24	9	-	-	13	-	56	-	2400	U-MOSVI	
	TPCA8128	-30	+20/-25	-34	4.8	-	-	6.7	-	115	-	4800	U-MOSVI	
	TPCA8120	-30	+20/-25	-45	3	-	-	4	-	190	-	7420	U-MOSVI	

☆ New Products, ^{SL} I₀ (DC) (Silicon Limit)

§ With protection Zener diode between gate and source,

¥ The package can be selected according to your preference. For details, please contact your TOSHIBA sales representative.

Note(1) : High-speed switching type





SOP Advance (N) (4.9x6.1)

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(on)} max(mΩ)						Q _g typ.(nC)		C _{iss} typ. (pF)	R _{th} (ch-c) max (°C/W)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{Gs} =10V	V _{Gs} =6.5V	V _{Gs} =6V	V _{Gs} =4.5V	V _{Gs} =2.5V	V _{Gs} =10V	V _{Gs} =4.5V				
N-ch Note(1)	TPH1R403NL ¥	30	+/-20	150 ^{SL}	1.4	-	-	2.1	-	46	20	3400	1.95	U-MOSVIII-H	
	TPH1R403NL1 ☆	30	+/-20	230 ^{SL}	1.4	-	-	2.1	-	46	20	3400	0.88	U-MOSVIII-H	
	TPHR9203PL ¥	30	+/-20	280 ^{SL}	0.92	-	-	1.29	-	81	38	5800	1.13	U-MOSIX-H	
	TPHR9203PL1 ☆	30	+/-20	320 ^{SL}	0.92	-	-	1.29	-	81	38	5800	0.88	U-MOSIX-H	
	TPHR9003NL ¥	30	+/-20	220 ^{SL}	0.9	-	-	1.4	-	74	32	5300	1.6	U-MOSVIII-H	
	TPHR9003NL1 ☆	30	+/-20	320 ^{SL}	0.9	-	-	1.4	-	74	32	5300	0.71	U-MOSVIII-H	
	TPHR6503PL ¥	30	+/-20	393 ^{SL}	0.65	-	-	0.89	-	110	52	7700	0.88	U-MOSIX-H	
	TPHR6503PL1 ☆	30	+/-20	430 ^{SL}	0.65	-	-	0.89	-	110	52	7700	0.71	U-MOSIX-H	
	TPH1R204PL ¥	40	+/-20	246 ^{SL}	1.24	-	-	2.1	-	74	34	5500	1.13	U-MOSIX-H	
	TPH1R204PL1 ☆	40	+/-20	270 ^{SL}	1.24	-	-	2.1	-	74	34	5500	0.88	U-MOSIX-H	
	TPHR8504PL ¥	40	+/-20	340 ^{SL}	0.85	-	-	1.4	-	103	49	7370	0.88	U-MOSIX-H	
	TPHR8504PL1 ☆	40	+/-20	370 ^{SL}	0.85	-	-	1.4	-	103	49	7370	0.71	U-MOSIX-H	
	TPH1R005PL ☆ ¥	45	+/-20	280 ^{SL}	1.04	-	-	1.7	-	122	59	7700	0.88	U-MOSIX-H	
	TPH2R506PL ¥	60	+/-20	160 ^{SL}	2.5	-	-	4.4	-	60	32	4180	1.13	U-MOSIX-H	
	TPH2R306PL1 ☆	60	+/-20	180 ^{SL}	2.3	-	-	4.2	-	60	32	4180	0.88	U-MOSIX-H	
	TPH2R306NH ¥	60	+/-20	130 ^{SL}	2.3	4.7	-	-	-	72	-	4700	1.6	U-MOSVIII-H	
	TPH2R306NH1 ☆	60	+/-20	190 ^{SL}	2.3	4.7	-	-	-	72	-	4700	0.71	U-MOSVIII-H	
	TPH1R306PL ¥	60	+/-20	260 ^{SL}	1.34	-	-	2.3	-	91	44	6250	0.88	U-MOSIX-H	
	TPH1R306PL1 ☆	60	+/-20	280 ^{SL}	1.34	-	-	2.3	-	91	44	6250	0.71	U-MOSIX-H	
	TPH4R008NH ¥	80	+/-20	100 ^{SL}	4	-	-	-	-	59	-	4100	1.6	U-MOSVIII-H	
	TPH4R008NH1 ☆	80	+/-20	147 ^{SL}	4	-	-	-	-	59	-	4100	0.71	U-MOSVIII-H	
	TPH4R008QM ☆	80	+/-20	140 ^{SL}	4	-	5.6	-	-	57	35(@6V)	3750	0.88	U-MOSX-H	
	TPH2R408QM ☆ ¥	80	+/-20	200 ^{SL}	2.43	-	3.5	-	-	87	55(@6V)	5870	0.71	U-MOSX-H	
	TPH4R50ANH ¥	100	+/-20	93 ^{SL}	4.5	-	-	-	-	58	-	4000	1.6	U-MOSVIII-H	
	TPH4R50ANH1 ☆	100	+/-20	138 ^{SL}	4.5	-	-	-	-	58	-	4000	0.71	U-MOSVIII-H	
	TPH3R70APL ¥	100	+/-20	150 ^{SL}	3.7	-	-	6.2	-	67	33	4850	0.88	U-MOSIX-H	
TPH3R70APL1 ☆	100	+/-20	170 ^{SL}	3.7	-	-	6.2	-	67	33	4850	0.71	U-MOSIX-H		
TPH1500CNH ¥	150	+/-20	50 ^{SL}	15.4	-	-	-	-	22	-	1700	1.6	U-MOSVIII-H		
TPH1500CNH1 ☆	150	+/-20	74 ^{SL}	15.4	-	-	-	-	22	-	1700	0.71	U-MOSVIII-H		

☆ New Products, ^{SL} I_D(DC) (Silicon Limit)

¥ The package can be selected according to your preference. For details, please contact your TOSHIBA sales representative.

Note(1) : High-speed switching type

DSOP Advance (5x6)



Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)			Q _g typ.(nC)		C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V	V _{GS} =4.5V	V _{GS} =10V	V _{GS} =4.5V			
N-ch Note(1)	TPWR8503NL	30	+/-20	300 ^{SL}	0.85	1.3	74	32	5300	U-MOSVIII-H	
	TPWR6003PL	30	+/-20	412 ^{SL}	0.6	0.84	110	52	7700	U-MOSIX-H	
	TPWR8004PL	40	+/-20	340 ^{SL}	0.8	1.35	103	49	7370	U-MOSIX-H	
	TPW1R005PL	45	+/-20	300 ^{SL}	0.99	1.65	122	59	7700	U-MOSIX-H	
	TPW1R306PL	60	+/-20	260 ^{SL}	1.29	2.3	91	44	6250	U-MOSIX-H	
	TPW2R508NH	75	+/-20	170 ^{SL}	2.5	-	72	-	4600	U-MOSVIII-H	
	TPW4R008NH	80	+/-20	116	4	-	59	-	4100	U-MOSVIII-H	
	TPW4R50ANH	100	+/-20	92	4.5	-	58	-	4000	U-MOSVIII-H	
	TPW3R70APL ☆	100	+/-20	150 ^{SL}	3.7	6.2	67	33	4850	U-MOSIX-H	
	TPW1500CNH	150	+/-20	50 ^{SL}	15.4	-	22	-	1700	U-MOSVIII-H	
	TPW2900ENH	200	+/-20	36 ^{SL}	29	-	22	-	1700	U-MOSVIII-H	
TPW5200FNH	250	+/-20	27 ^{SL}	52	-	22	-	1700	U-MOSVIII-H		

DPAK+



Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)			Q _g typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V	V _{GS} =6.0V	V _{GS} =4.5V			
N-ch Note(1)	TK33S10N1H \$	100	+/-20	33	9.7	-	-	28	2050	U-MOSVIII-H

DPAK (TO-252) / New PW-Mold



Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)			Q _g typ.(nC)		C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V	V _{GS} =6V	V _{GS} =4.5V	V _{GS} =10V	V _{GS} =4.5V		
N-ch Note(1)	TK3R1P04PL	40	+/-20	130 ^{SL}	3.1	-	4.3	60	30	4670	U-MOSIX-H
	TK6R7P06PL	60	+/-20	74 ^{SL}	6.7	-	11.1	26	13	1990	U-MOSIX-H
	TK4R4P06PL	60	+/-20	106 ^{SL}	4.4	-	7.1	48.2	23.9	3280	U-MOSIX-H
	TK6R9P08QM ☆	80	+/-20	83 ^{SL}	6.9	9.6	-	39	24(@6V)	2700	U-MOSX-H
	TK5R1P08QM ☆	80	+/-20	105 ^{SL}	5.1	7	-	56	34(@6V)	3980	U-MOSX-H
	TK110P10PL ☆	100	+/-20	60 ^{SL}	10.6	-	16	33	17	2040	U-MOSIX-H
	TK7R7P10PL ☆	100	+/-20	79 ^{SL}	7.7	-	11.5	44	21	2800	U-MOSIX-H
P-ch	TJ15P04M3	-40	+/-20	-15	36	-	48	26	-	1100	U-MOSVI

☆ New Products, \$ With protection Zener diode between gate and source, ^{SL} I_{D(DC)} (Silicon Limit)
 Note(1) : High-speed switching type



TO-220

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)			Q _g typ.(nC)		C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{VES} (V)	I _D (A)	V _{GS} =10V	V _{GS} =6V	V _{GS} =4.5V	V _{GS} =10V	V _{GS} =4.5V		
N-ch Note(1)	TK3R1E04PL	40	+/-20	128 ^{SL}	3.1	-	3.8	63.4	29.7	4670	U-MOSIX-H
	TK30E06N1	60	+/-20	43 ^{SL}	15	-	-	16	-	1050	U-MOSVIII-H
	TK40E06N1	60	+/-20	60 ^{SL}	10.4	-	-	23	-	1700	U-MOSVIII-H
	TK8R2E06PL	60	+/-20	75 ^{SL}	8.2	-	11.4	28	15	1990	U-MOSIX-H
	TK58E06N1	60	+/-20	105 ^{SL}	5.4	-	-	46	-	3400	U-MOSVIII-H
	TK5R1E06PL	60	+/-20	98 ^{SL}	5.1	-	8.8	36	18	2380	U-MOSIX-H
	TK4R3E06PL	60	+/-20	106 ^{SL}	4.3	-	7.2	48.2	23.9	3280	U-MOSIX-H
	TK3R2E06PL	60	+/-20	160 ^{SL}	3.2	-	4.7	71	35	5000	U-MOSIX-H
	TK100E06N1	60	+/-20	263 ^{SL}	2.3	-	-	140	-	10500	U-MOSVIII-H
	TK35E08N1	80	+/-20	55	12.2	-	-	25	-	1700	U-MOSVIII-H
	TK46E08N1	80	+/-20	80	8.4	-	-	37	-	2500	U-MOSVIII-H
	TK7R0E08QM ☆	80	+/-20	82 ^{SL}	7	9.7	-	39	24(@6V)	2700	U-MOSX-H
	TK5R3E08QM ☆	80	+/-20	126 ^{SL}	5.3	7.3	-	55	33(@6V)	3980	U-MOSX-H
	TK72E08N1	80	+/-20	157 ^{SL}	4.3	-	-	81	-	5500	U-MOSVIII-H
	TK3R3E08QM ☆	80	+/-20	200 ^{SL}	3.3	4.2	-	110	67(@6V)	7670	U-MOSX-H
	TK100E08N1	80	+/-20	214 ^{SL}	3.2	-	-	130	-	9000	U-MOSVIII-H
	TK2R4E08QM ☆	80	+/-20	290 ^{SL}	2.44	3.2	-	178	109(@6V)	13000	U-MOSX-H
	TK22E10N1	100	+/-20	52	13.8	-	-	28	-	1800	U-MOSVIII-H
	TK110E10PL ☆	100	+/-20	64 ^{SL}	10.7	-	16	33	17	2040	U-MOSIX-H
	TK34E10N1	100	+/-20	75	9.5	-	-	38	-	2600	U-MOSVIII-H
	TK40E10N1	100	+/-20	90	8.2	-	-	49	-	3000	U-MOSVIII-H
	TK7R2E10PL ☆	100	+/-20	94 ^{SL}	7.2	-	11	44	21	2800	U-MOSIX-H
	TK6R4E10PL ☆	100	+/-20	112 ^{SL}	6.4	-	9.7	58	30	3455	U-MOSIX-H
	TK65E10N1	100	+/-20	148 ^{SL}	4.8	-	-	81	-	5400	U-MOSVIII-H
	TK3R9E10PL ☆	100	+/-20	180 ^{SL}	3.9	-	5.8	96	49	6320	U-MOSIX-H
	TK100E10N1	100	+/-20	207 ^{SL}	3.4	-	-	140	-	8800	U-MOSVIII-H
	TK2R9E10PL ☆	100	+/-20	240 ^{SL}	2.9	-	4.1	161	83	9500	U-MOSIX-H
	TK32E12N1	120	+/-20	60	13.8	-	-	34	-	2000	U-MOSVIII-H
TK42E12N1	120	+/-20	88	9.4	-	-	52	-	3100	U-MOSVIII-H	
TK56E12N1	120	+/-20	112 ^{SL}	7	-	-	69	-	4200	U-MOSVIII-H	
TK72E12N1	120	+/-20	179 ^{SL}	4.4	-	-	130	-	8100	U-MOSVIII-H	

☆ New Products, ^{SL} I_D(DC) (Silicon Limit)
 Note(1) : High-speed switching type

TO-220SIS



Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)			Q _g typ.(nC)		C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{CESS} (V)	I _B (A)	V _{GS} =10V	V _{GS} =6V	V _{GS} =4.5V	V _{GS} =10V	V _{GS} =4.5V		
N-ch Note(1)	TK3R1A04PL	40	+/-20	82	3.1	-	3.8	63.4	29.7	4670	U-MOSIX-H
	TK30A06N1	60	+/-20	43 ^{SL}	15	-	-	16	-	1050	U-MOSVIII-H
	TK40A06N1	60	+/-20	60 ^{SL}	10.4	-	-	23	-	1700	U-MOSVIII-H
	TK8R2A06PL	60	+/-20	50	8.2	-	11.4	28	15	1990	U-MOSIX-H
	TK58A06N1	60	+/-20	105 ^{SL}	5.4	-	-	46	-	3400	U-MOSVIII-H
	TK5R3A06PL	60	+/-20	62 ^{SL}	5.3	-	9.3	36	18	2380	U-MOSIX-H
	TK4R3A06PL	60	+/-20	68	4.3	-	7.2	48.2	23.9	3280	U-MOSIX-H
	TK3R3A06PL	60	+/-20	88 ^{SL}	3.3	-	4.9	71	35	5000	U-MOSIX-H
	TK100A06N1	60	+/-20	263 ^{SL}	2.7	-	-	140	-	10500	U-MOSVIII-H
	TK35A08N1	80	+/-20	55 ^{SL}	12.2	-	-	25	-	1700	U-MOSVIII-H
	TK46A08N1	80	+/-20	80 ^{SL}	8.4	-	-	37	-	2500	U-MOSVIII-H
	TK6R8A08QM ★	80	+/-20	58	6.8	9.5	-	39	23(@6V)	2700	U-MOSX-H
	TK5R1A08QM ★	80	+/-20	71 ^{SL}	5.1	7.1	-	54	32(@6V)	3980	U-MOSX-H
	TK72A08N1	80	+/-20	157 ^{SL}	4.5	-	-	81	-	5500	U-MOSVIII-H
	TK3R2A08QM ★	80	+/-20	92	3.2	4.1	-	102	58(@6V)	7670	U-MOSX-H
	TK100A08N1	80	+/-20	214 ^{SL}	3.2	-	-	130	-	9000	U-MOSVIII-H
	TK2R4A08QM ★	80	+/-20	116 ^{SL}	2.44	3.1	-	179	102(@6V)	13000	U-MOSX-H
	TK22A10N1	100	+/-20	52 ^{SL}	13.8	-	-	28	-	1800	U-MOSVIII-H
	TK110A10PL ☆	100	+/-20	41 ^{SL}	10.8	-	16	33	17	2040	U-MOSIX-H
	TK34A10N1	100	+/-20	75 ^{SL}	9.5	-	-	38	-	2600	U-MOSVIII-H
	TK40A10N1	100	+/-20	90 ^{SL}	8.2	-	-	49	-	3000	U-MOSVIII-H
	TK7R4A10PL ☆	100	+/-20	50	7.4	-	11.2	44	21	2800	U-MOSIX-H
	TK6R7A10PL ☆	100	+/-20	56	6.7	-	10.1	58	30	3455	U-MOSIX-H
	TK65A10N1	100	+/-20	148 ^{SL}	4.8	-	-	81	-	5400	U-MOSVIII-H
	TK4R1A10PL ☆	100	+/-20	85 ^{SL}	4.1	-	5.9	104	53	6320	U-MOSIX-H
	TK100A10N1	100	+/-20	207 ^{SL}	3.8	-	-	140	-	8800	U-MOSVIII-H
	TK3R2A10PL ☆	100	+/-20	106 ^{SL}	3.2	-	4.3	161	83	9500	U-MOSIX-H
	TK32A12N1	120	+/-20	60 ^{SL}	13.8	-	-	34	-	2000	U-MOSVIII-H
	TK42A12N1	120	+/-20	88 ^{SL}	9.4	-	-	52	-	3100	U-MOSVIII-H
	TK56A12N1	120	+/-20	112 ^{SL}	7.5	-	-	69	-	4200	U-MOSVIII-H
TK72A12N1	120	+/-20	179 ^{SL}	4.5	-	-	130	-	8100	U-MOSVIII-H	

☆ New Products, ★ Under Development (The specification is subject to change without notice.), ^{SL} I_{B(DC)} (Silicon Limit)
 Note(1) : High-speed switching type

2. Mid-High Voltage MOSFET Series



DPAK(TO-252)/New PW-Mold

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(Ω)	Q _g typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V			
N-ch	TK10P50W	500	+/-30	9.7	0.43	20	700	DTMOSIV
	TK12P50W	500	+/-30	11.5	0.34	25	890	DTMOSIV
	TK6P60W	600	+/-30	6.2	0.82	12	390	DTMOSIV
	TK560P60Y	600	+/-30	7	0.56	14.5	380	DTMOSV
	TK7P60W	600	+/-30	7	0.6	15	490	DTMOSIV
	TK7P60W5 &	600	+/-30	7	0.67	16	490	DTMOSIV(HSD)
	TK8P60W5 &	600	+/-30	8	0.56	22	590	DTMOSIV(HSD)
	TK8P60W	600	+/-30	8	0.5	18.5	570	DTMOSIV
	TK10P60W	600	+/-30	9.7	0.43	20	700	DTMOSIV
	TK380P60Y	600	+/-30	9.7	0.38	20	590	DTMOSV
	TK12P60W	600	+/-30	11.5	0.34	25	890	DTMOSIV
	TK290P60Y	600	+/-30	11.5	0.29	25	730	DTMOSV
	TK6P65W	650	+/-30	5.8	1.05	11	390	DTMOSIV
	TK7P65W	650	+/-30	6.8	0.8	15	490	DTMOSIV
	TK560P65Y	650	+/-30	7	0.56	14.5	380	DTMOSV
	TK8P65W	650	+/-30	7.8	0.67	16	570	DTMOSIV
	TK9P65W	650	+/-30	9.3	0.56	20	700	DTMOSIV
	TK380P65Y	650	+/-30	9.7	0.38	20	590	DTMOSV
	TK11P65W	650	+/-30	11.1	0.44	25	890	DTMOSIV
	TK290P65Y	650	+/-30	11.5	0.29	25	730	DTMOSV
N-ch	TK8P25DA	250	+/-20	7.5	0.5	16	550	π-MOSVII
	TK13P25D	250	+/-20	13	0.25	25	1100	π-MOSVII
	TK3P50D	500	+/-30	3	3	7	280	π-MOSVII
	TK4P50D	500	+/-30	4	2	9	380	π-MOSVII
	TK5P50D	500	+/-30	5	1.5	11	490	π-MOSVII
	TK7P50D	500	+/-30	7	1.22	12	600	π-MOSVII
	TK5P53D	525	+/-30	5	1.5	11	540	π-MOSVII
	TK6P53D	525	+/-30	6	1.3	12	600	π-MOSVII
	TK4P55DA	550	+/-30	3.5	2.45	9	380	π-MOSVII
	TK4P55D	550	+/-30	4	1.88	11	490	π-MOSVII
	TK2P60D	600	+/-30	2	4.3	7	280	π-MOSVII
	TK4P60DA	600	+/-30	3.5	2.2	11	490	π-MOSVII
	TK4P60DB	600	+/-30	3.7	2	11	540	π-MOSVII
	TK4P60D	600	+/-30	4	1.7	12	600	π-MOSVII
	TK3P80E	800	+/-30	3	4.9	12	500	π-MOSVIII
	TK2P90E	900	+/-30	2	5.9	12	500	π-MOSVIII

& High Speed Diode type

DFN 8x8

Circuit Configuration	Part Number	Absolute Maximum Ratings			$R_{DS(ON)}$ max(Ω)	Q_g typ. (nC)	C_{iss} typ. (pF)	Remark
		$V_{DSS}(V)$	$V_{GSS}(V)$	$I_D(A)$	$V_{GS}=10V$			
N-ch	TK10V60W	600	+/-30	9.7	0.38	20	700	DTMOSIV
	TK12V60W	600	+/-30	11.5	0.3	25	890	DTMOSIV
	TK16V60W5 &	600	+/-30	15.8	0.245	43	1350	DTMOSIV(HSD)
	TK16V60W	600	+/-30	15.8	0.19	38	1350	DTMOSIV
	TK20V60W5 &	600	+/-30	20	0.19	55	1800	DTMOSIV(HSD)
	TK20V60W	600	+/-30	20	0.17	48	1680	DTMOSIV
	TK25V60X5 &	600	+/-30	25	0.15	60	2400	DTMOSIV-H(HSD)
	TK25V60X	600	+/-30	25	0.135	40	2400	DTMOSIV-H
	TK31V60W5 &	600	+/-30	30.8	0.109	105	3000	DTMOSIV(HSD)
	TK31V60W	600	+/-30	30.8	0.098	86	3000	DTMOSIV
	TK31V60X	600	+/-30	30.8	0.098	65	3000	DTMOSIV-H
	TK14V65W	650	+/-30	13.7	0.28	35	1300	DTMOSIV
	TK210V65Z ☆	650	+/-30	15	0.21	25	1370	DTMOSVI
	TK17V65W	650	+/-30	17.3	0.21	45	1800	DTMOSIV
	TK170V65Z ☆	650	+/-30	18	0.17	29	1635	DTMOSVI
	TK22V65X5 &	650	+/-30	22	0.17	50	2400	DTMOSIV-H(HSD)
	TK28V65W5 &	650	+/-30	27.6	0.14	90	3000	DTMOSIV(HSD)
	TK125V65Z ☆	650	+/-30	24	0.125	40	2250	DTMOSVI
TK28V65W	650	+/-30	27.6	0.12	75	3000	DTMOSIV	
TK099V65Z ☆	650	+/-30	30	0.099	47	2780	DTMOSVI	

D2PAK

Circuit Configuration	Part Number	Absolute Maximum Ratings			$R_{DS(ON)}$ max(Ω)	Q_g typ. (nC)	C_{iss} typ. (pF)	Remark
		$V_{DSS}(V)$	$V_{GSS}(V)$	$I_D(A)$	$V_{GS}=10V$			
N-ch	TK16G60W5 &	600	+/-30	15.8	0.23	43	1350	DTMOSIV(HSD)
	TK16G60W	600	+/-30	15.8	0.19	38	1350	DTMOSIV
	TK20G60W	600	+/-30	20	0.155	48	1680	DTMOSIV
	TK14G65W5 &	650	+/-30	13.7	0.3	40	1300	DTMOSIV(HSD)
	TK14G65W	650	+/-30	13.7	0.25	35	1300	DTMOSIV

TOLL

Circuit Configuration	Part Number	Absolute Maximum Ratings			$R_{DS(ON)}$ max(Ω)	Q_g typ. (nC)	C_{iss} typ. (pF)	Remark
		$V_{DSS}(V)$	$V_{GSS}(V)$	$I_D(A)$	$V_{GS}=10V$			
N-ch	TK190U65Z ☆	650	+/-28	15	0.19	25	1370	DTMOSVI
	TK155U65Z ☆	650	+/-29	18	0.155	29	1635	DTMOSVI
	TK110U65Z ☆	650	+/-30	24	0.11	40	2250	DTMOSVI
	TK090U65Z ☆	650	+/-30	30	0.09	47	2780	DTMOSVI
	TK065U65Z ☆	650	+/-30	38	0.065	62	3650	DTMOSVI

☆ New Products
& High Speed Diode type



IPAK/New PW-Mold2

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(Ω)	Q _s typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GSS} =10V			
N-ch	TK6Q60W	600	+/-30	6.2	0.82	12	390	DTMOSIV
	TK7Q60W	600	+/-30	7	0.6	15	490	DTMOSIV
	TK8Q60W	600	+/-30	8	0.5	18.5	570	DTMOSIV
	TK10Q60W	600	+/-30	9.7	0.43	20	700	DTMOSIV
	TK12Q60W	600	+/-30	11.5	0.34	25	890	DTMOSIV
	TK6Q65W	650	+/-30	5.8	1.05	11	390	DTMOSIV
	TK7Q65W	650	+/-30	6.8	0.8	15	490	DTMOSIV
	TK8Q65W	650	+/-30	7.8	0.67	16	570	DTMOSIV
	TK9Q65W	650	+/-30	9.3	0.56	20	700	DTMOSIV
TK11Q65W	650	+/-30	11.1	0.44	25	890	DTMOSIV	
N-ch	TK2Q60D	600	+/-30	2	4.3	7	280	π-MOSVII
	TK4Q60DA	600	+/-30	3.5	2.2	11	490	π-MOSVII
	TK1Q90A	900	+/-30	1	9	13	320	π-MOSIV



TO-220

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(Ω)	Q _s typ. (nC)	C _{iss} typ. (pF)	Remark	
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GSS} =10V				
N-ch	TK10E60W	600	+/-30	9.7	0.38	20	700	DTMOSIV	
	TK12E60W	600	+/-30	11.5	0.3	25	890	DTMOSIV	
	TK16E60W5	&	600	+/-30	15.8	0.23	43	1350	DTMOSIV(HSD)
	TK16E60W		600	+/-30	15.8	0.19	38	1350	DTMOSIV
	TK20E60W5	&	600	+/-30	20	0.175	55	1800	DTMOSIV(HSD)
	TK20E60W		600	+/-30	20	0.155	48	1680	DTMOSIV
	TK25E60X5	&	600	+/-30	25	0.14	60	2400	DTMOSIV-H(HSD)
	TK25E60X		600	+/-30	25	0.125	40	2400	DTMOSIV-H
	TK31E60W		600	+/-30	30.8	0.088	86	3000	DTMOSIV
	TK31E60X		600	+/-30	30.8	0.088	65	3000	DTMOSIV-H
	TK14E65W5	&	650	+/-30	13.7	0.3	40	1300	DTMOSIV(HSD)
	TK14E65W		650	+/-30	13.7	0.25	35	1300	DTMOSIV
	TK17E65W		650	+/-30	17.3	0.2	45	1800	DTMOSIV
	TK28E65W		650	+/-30	27.6	0.11	75	3000	DTMOSIV
	TK7E80W		800	+/-20	6.5	0.95	13	700	DTMOSIV
	TK10E80W		800	+/-20	9.5	0.55	19	1150	DTMOSIV
	TK12E80W		800	+/-20	11.5	0.45	23	1400	DTMOSIV
	TK17E80W		800	+/-20	17	0.29	32	2050	DTMOSIV
N-ch	TK13E25D	250	+/-20	13	0.25	25	1100	π-MOSVII	

& High Speed Diode type

\$ With protection Zener diode between gate and source

TO-220SIS



Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(Ω)	Q _g typ. (nC)	C _{iss} typ. (pF)	Remark	
		V _{DSS} (V)	V _{GSS} (V)	I _O (A)	V _{GS} =10V				
N-ch	TK10A50W	500	+/-30	9.7	0.38	20	700	DTMOSIV	
	TK12A50W	500	+/-30	11.5	0.3	25	890	DTMOSIV	
	TK19A50W	500	+/-30	18.5	0.19	38	1350	DTMOSIV	
	TK6A60W	600	+/-30	6.2	0.75	12	390	DTMOSIV	
	TK7A60W5	&	600	+/-30	7	0.65	16	490	DTMOSIV(HSD)
	TK7A60W		600	+/-30	7	0.6	15	490	DTMOSIV
	TK560A60Y		600	+/-30	7	0.56	14.5	380	DTMOSV
	TK8A60W5	&	600	+/-30	8	0.54	22	590	DTMOSIV(HSD)
	TK8A60W		600	+/-30	8	0.5	18.5	570	DTMOSIV
	TK10A60W5	&	600	+/-30	9.7	0.45	25	720	DTMOSIV(HSD)
	TK10A60W		600	+/-30	9.7	0.38	20	700	DTMOSIV
	TK380A60Y		600	+/-30	9.7	0.38	20	590	DTMOSV
	TK12A60W		600	+/-30	11.5	0.3	25	890	DTMOSIV
	TK290A60Y		600	+/-30	11.5	0.29	25	730	DTMOSV
	TK16A60W5	&	600	+/-30	15.8	0.23	43	1350	DTMOSIV(HSD)
	TK16A60W		600	+/-30	15.8	0.19	38	1350	DTMOSIV
	TK20A60W5	&	600	+/-30	20	0.175	55	1800	DTMOSIV(HSD)
	TK20A60W		600	+/-30	20	0.155	48	1680	DTMOSIV
	TK25A60X5	&	600	+/-30	25	0.14	60	2400	DTMOSIV-H(HSD)
	TK25A60X		600	+/-30	25	0.125	40	2400	DTMOSIV-H
	TK31A60W		600	+/-30	30.8	0.088	86	3000	DTMOSIV
	TK39A60W		600	+/-30	38.8	0.065	110	4100	DTMOSV
	TK6A65W		650	+/-30	5.8	1	11	390	DTMOSIV
	TK7A65W		650	+/-30	6.8	0.78	15	490	DTMOSIV
	TK560A65Y		650	+/-30	7	0.56	14.5	380	DTMOSV
	TK8A65W		650	+/-30	7.8	0.65	16	570	DTMOSIV
	TK9A65W		650	+/-30	9.3	0.5	20	700	DTMOSIV
	TK380A65Y		650	+/-30	9.7	0.38	20	590	DTMOSV
	TK11A65W		650	+/-30	11.1	0.39	25	890	DTMOSIV
	TK290A65Y		650	+/-30	11.5	0.29	25	730	DTMOSV
	TK14A65W5	&	650	+/-30	13.7	0.3	40	1300	DTMOSIV(HSD)
	TK14A65W		650	+/-30	13.7	0.25	35	1300	DTMOSIV
	TK17A65W5	&	650	+/-30	17.3	0.23	50	1800	DTMOSIV(HSD)
	TK17A65W		650	+/-30	17.3	0.2	45	1800	DTMOSIV
	TK190A65Z	☆	650	+/-30	15	0.19	25	1370	DTMOSVI
	TK22A65X5	&	650	+/-30	22	0.16	50	2400	DTMOSIV-H(HSD)
	TK155A65Z	☆	650	+/-30	18	0.155	29	1635	DTMOSVI
	TK22A65X		650	+/-30	22	0.15	50	2400	DTMOSIV-H
	TK110A65Z	☆	650	+/-30	24	0.11	40	2250	DTMOSVI
	TK28A65W		650	+/-30	27.6	0.11	75	3000	DTMOSIV
TK35A65W5	&	650	+/-30	35	0.095	115	4100	DTMOSIV(HSD)	
TK090A65Z	☆	650	+/-30	30	0.09	47	2780	DTMOSVI	
TK35A65W		650	+/-30	35	0.08	100	4100	DTMOSIV	
TK7A80W		800	+/-20	6.5	0.95	13	700	DTMOSIV	
TK10A80W		800	+/-20	9.5	0.55	19	1150	DTMOSIV	
TK12A80W		800	+/-20	11.5	0.45	23	1400	DTMOSIV	
TK17A80W		800	+/-20	17	0.29	32	2050	DTMOSIV	

☆ New products, & High Speed Diode type



TO-220SIS

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(on)} max(Ω)	Q _g typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V			
N-ch	TK9A20DA	200	+/-20	8.5	0.4	14	550	π-MOSVII
	TK15A20D	200	+/-20	15	0.18	26	1050	π-MOSVII
	TK20A20D	200	+/-20	20	0.109	43	1650	π-MOSVII
	TK25A20D	200	+/-20	25	0.07	60	2550	π-MOSVII
	TK8A25DA	250	+/-20	7.5	0.5	16	550	π-MOSVII
	TK13A25D	250	+/-20	13	0.25	25	1100	π-MOSVII
	TK17A25D	250	+/-20	17	0.15	43	1650	π-MOSVII
	TK20A25D	250	+/-20	20	0.1	55	2550	π-MOSVII
	TK18A30D	300	+/-20	18	0.139	60	2600	π-MOSVII
	TK5A45DA	450	+/-30	4.5	1.75	9	380	π-MOSVII
	TK6A45DA	450	+/-30	5.5	1.35	11	490	π-MOSVII
	TK7A45DA	450	+/-30	6.5	1.2	11	540	π-MOSVII
	TK8A45D	450	+/-30	8	0.9	16	700	π-MOSVII
	TK9A45D	450	+/-30	9	0.77	16	800	π-MOSVII
	TK11A45D	450	+/-30	11	0.62	20	1050	π-MOSVII
	TK12A45D	450	+/-30	12	0.52	24	1200	π-MOSVII
	TK13A45D	450	+/-30	13	0.46	25	1350	π-MOSVII
	TK19A45D	450	+/-30	19	0.25	45	2600	π-MOSVII
	TK4A50D	500	+/-30	4	2	9	380	π-MOSVII
	TK5A50D	500	+/-30	5	1.5	11	490	π-MOSVII
	TK6A50D	500	+/-30	6	1.4	11	540	π-MOSVII
	TK7A50D	500	+/-30	7	1.22	12	600	π-MOSVII
	TK8A50DA	500	+/-30	7.5	1.04	16	700	π-MOSVII
	TK8A50D	500	+/-30	8	0.85	16	800	π-MOSVII
	TK10A50D	500	+/-30	10	0.72	20	1050	π-MOSVII
	TK11A50D	500	+/-30	11	0.6	24	1200	π-MOSVII
	TK12A50D	500	+/-30	12	0.52	25	1350	π-MOSVII
	TK13A50DA	500	+/-30	12.5	0.47	28	1550	π-MOSVII
	TK13A50D	500	+/-30	13	0.4	38	1800	π-MOSVII
	TK15A50D	500	+/-30	15	0.3	40	2300	π-MOSVII
	TK18A50D	500	+/-30	18	0.27	45	2600	π-MOSVII
	TK4A53D	525	+/-30	4	1.7	11	490	π-MOSVII
	TK5A53D	525	+/-30	5	1.5	11	540	π-MOSVII
	TK6A53D	525	+/-30	6	1.3	12	600	π-MOSVII
	TK12A53D	525	+/-30	12	0.58	25	1350	π-MOSVII
	TK4A55DA	550	+/-30	3.5	2.45	9	380	π-MOSVII
	TK4A55D	550	+/-30	4	1.88	11	490	π-MOSVII
	TK5A55D	550	+/-30	5	1.7	11	540	π-MOSVII
	TK6A55DA	550	+/-30	5.5	1.48	12	600	π-MOSVII
	TK7A55D	550	+/-30	7	1.25	16	700	π-MOSVII
	TK8A55DA	550	+/-30	7.5	1.07	16	800	π-MOSVII
	TK9A55DA	550	+/-30	8.5	0.86	20	1050	π-MOSVII
TK10A55D	550	+/-30	10	0.72	24	1200	π-MOSVII	
TK11A55D	550	+/-30	11	0.63	25	1350	π-MOSVII	
TK12A55D	550	+/-30	12	0.57	28	1550	π-MOSVII	

TO-220SIS



Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(Ω)	Q _g typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _O (A)	V _{GS} =10V			
N-ch	TK13A55DA	550	+/-30	12.5	0.48	38	1800	π-MOSVII
	TK14A55D	550	+/-30	14	0.37	40	2300	π-MOSVII
	TK16A55D	550	+/-30	16	0.33	45	2600	π-MOSVII
	TK4K1A60F ☆	600	+/-30	2	4.1	8	270	π-MOSIX
	TK3A60DA	600	+/-30	2.5	2.8	9	380	π-MOSVII
	TK2K2A60F ☆	600	+/-30	3.5	2.2	13	450	π-MOSIX
	TK1K9A60F ☆	600	+/-30	3.7	1.9	14	490	π-MOSIX
	TK1K7A60F ☆	600	+/-30	4	1.7	16	560	π-MOSIX
	TK5A60D	600	+/-30	5	1.43	16	700	π-MOSVII
	TK1K2A60F ☆	600	+/-30	6	1.2	21	740	π-MOSIX
	TK1K0A60F ☆	600	+/-30	7.5	1	24	890	π-MOSIX
	TK9A60D	600	+/-30	9	0.83	24	1200	π-MOSVII
	TK750A60F ☆	600	+/-30	10	0.75	30	1130	π-MOSIX
	TK650A60F ☆	600	+/-30	11	0.65	34	1320	π-MOSIX
	TK12A60D	600	+/-30	12	0.55	38	1800	π-MOSVII
	TK430A60F ☆	600	+/-30	13	0.43	49	1900	π-MOSIX
	TK370A60F ☆	600	+/-30	15	0.37	56	2200	π-MOSIX
	TK2A65D	650	+/-30	2	3.26	9	380	π-MOSVII
	TK3A65DA	650	+/-30	2.5	2.51	11	490	π-MOSVII
	TK3A65D	650	+/-30	3	2.25	11	540	π-MOSVII
	TK4A65DA	650	+/-30	3.5	1.9	12	600	π-MOSVII
	TK5A65DA	650	+/-30	4.5	1.67	16	700	π-MOSVII
	TK5A65D	650	+/-30	5	1.43	16	800	π-MOSVII
	TK6A65D	650	+/-30	6	1.11	20	1050	π-MOSVII
	TK7A65D	650	+/-30	7	0.98	24	1200	π-MOSVII
	TK8A65D	650	+/-30	8	0.84	25	1350	π-MOSVII
	TK11A65D	650	+/-30	11	0.7	30	1700	π-MOSVII
	TK12A65D	650	+/-30	12	0.54	40	2300	π-MOSVII
	TK13A65D	650	+/-30	13	0.47	45	2600	π-MOSVII
	TK4A80E	800	+/-30	4	3.5	15	650	π-MOSVIII
	TK5A80E	800	+/-30	5	2.4	20	950	π-MOSVIII
	TK6A80E	800	+/-30	6	1.7	32	1350	π-MOSVIII
	2SK4013	800	+/-30	6	1.7	45	1400	π-MOSIV
	TK10A80E	800	+/-30	10	1	46	2000	π-MOSVIII
	2SK3566	900	+/-30	2.5	6.4	12	470	π-MOSIV
	TK3A90E	900	+/-30	2.5	4.6	15	650	π-MOSVIII
	2SK3564	900	+/-30	3	4.3	17	700	π-MOSIV
	2SK3798	900	+/-30	4	3.5	26	800	π-MOSIV
	TK5A90E	900	+/-30	4.5	3.1	20	950	π-MOSVIII
	2SK3565	900	+/-30	5	2.5	28	1150	π-MOSIV
2SK3742	900	+/-30	5	2.5	25	1150	π-MOSIV	
2SK4014	900	+/-30	6	2	45	1400	π-MOSIV	
TK7A90E	900	+/-30	7	2	32	1350	π-MOSVIII	
2SK3799	900	+/-30	8	1.3	60	2200	π-MOSIV	
TK9A90E	900	+/-30	9	1.3	46	2000	π-MOSVIII	

☆ New products



TO-3P(N)

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(Ω)	Q _s typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V			
N-ch	TK12J60W	600	+/-30	11.5	0.3	25	890	DTMOSIV
	TK16J60W5 &	600	+/-30	15.8	0.23	43	1350	DTMOSIV(HSD)
	TK16J60W	600	+/-30	15.8	0.19	38	1350	DTMOSIV
	TK20J60W5 &	600	+/-30	20	0.175	55	1800	DTMOSIV(HSD)
	TK20J60W	600	+/-30	20	0.155	48	1680	DTMOSIV
	TK31J60W5 &	600	+/-30	30.8	0.099	105	3000	DTMOSIV(HSD)
	TK31J60W	600	+/-30	30.8	0.088	86	3000	DTMOSIV
	TK39J60W5 &	600	+/-30	38.8	0.074	135	4100	DTMOSIV(HSD)
	TK39J60W	600	+/-30	38.8	0.065	110	4100	DTMOSIV
	TK62J60W5 &	600	+/-30	61.8	0.045	205	6500	DTMOSIV(HSD)
TK62J60W	600	+/-30	61.8	0.04	180	6500	DTMOSIV	
N-ch	TK40J20D	200	+/-20	40	0.044	100	4300	π-MOSVII
	TK70J20D	200	+/-20	70	0.027	160	6950	π-MOSVII
	TK30J25D	250	+/-20	30	0.06	100	4300	π-MOSVII
	TK60J25D	250	+/-20	60	0.038	160	7000	π-MOSVII
	TK50J30D	300	+/-20	50	0.052	160	7000	π-MOSVII
	TK15J50D	500	+/-30	15	0.4	38	1800	π-MOSVII
	TK20J50D	500	+/-30	20	0.27	45	2600	π-MOSVII
	TK12J55D	550	+/-30	12	0.57	28	1550	π-MOSVII
	TK16J55D	550	+/-30	16	0.37	40	2300	π-MOSVII
	TK19J55D	550	+/-30	19	0.33	45	2600	π-MOSVII
	2SK3633	800	+/-30	7	1.7	35	1500	π-MOSIV
	TK10J80E	800	+/-30	10	1	46	2000	π-MOSVIII
	2SK3700	900	+/-30	5	2.5	28	1150	π-MOSIV
	2SK4115	900	+/-30	7	2	45	1650	π-MOSIV
	TK7J90E	900	+/-30	7	2	32	1350	π-MOSVIII
	TK9J90E	900	+/-30	9	1.3	46	2000	π-MOSVIII
2SK4207	900	+/-30	13	0.95	45	2790	π-MOSIV	

& High Speed Diode type

TO-247



Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(Ω)	Q _g typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V			
N-ch	TK16N60W5 &	600	+/-30	15.8	0.23	43	1350	DTMOSIV(HSD)
	TK16N60W	600	+/-30	15.8	0.19	38	1350	DTMOSIV
	TK20N60W5 &	600	+/-30	20	0.175	55	1800	DTMOSIV(HSD)
	TK20N60W	600	+/-30	20	0.155	48	1680	DTMOSIV
	TK25N60X5 &	600	+/-30	25	0.14	60	2400	DTMOSIV-H(HSD)
	TK25N60X	600	+/-30	25	0.125	40	2400	DTMOSIV-H
	TK31N60W5 &	600	+/-30	30.8	0.099	105	3000	DTMOSIV(HSD)
	TK31N60W	600	+/-30	30.8	0.088	86	3000	DTMOSIV
	TK31N60X	600	+/-30	30.8	0.088	65	3000	DTMOSIV-H
	TK39N60W5 &	600	+/-30	38.8	0.074	135	4100	DTMOSIV(HSD)
	TK39N60W	600	+/-30	38.8	0.065	110	4100	DTMOSIV
	TK39N60X	600	+/-30	38.8	0.065	85	4100	DTMOSIV-H
	TK62N60W5 &	600	+/-30	61.8	0.045	205	6500	DTMOSIV(HSD)
	TK62N60W	600	+/-30	61.8	0.04	180	6500	DTMOSIV
	TK62N60X	600	+/-30	61.8	0.04	135	6500	DTMOSIV-H
	TK14N65W5 &	650	+/-30	13.7	0.3	40	1300	DTMOSIV(HSD)
	TK14N65W	650	+/-30	13.7	0.25	35	1300	DTMOSIV
	TK17N65W	650	+/-30	17.3	0.2	45	1800	DTMOSIV
	TK28N65W5 &	650	+/-30	27.6	0.13	90	3000	DTMOSIV(HSD)
	TK110N65Z ☆	650	+/-30	24	0.11	40	2250	DTMOSVI
TK28N65W	650	+/-30	27.6	0.11	75	3000	DTMOSIV	
TK35N65W5 &	650	+/-30	35	0.095	115	4100	DTMOSIV(HSD)	
TK090N65Z ☆	650	+/-30	30	0.09	47	2780	DTMOSVI	
TK35N65W	650	+/-30	35	0.08	100	4100	DTMOSIV	
TK065N65Z ☆	650	+/-30	38	0.065	62	3650	DTMOSVI	
TK49N65W5 &	650	+/-30	49.2	0.057	185	6500	DTMOSIV(HSD)	
TK49N65W	650	+/-30	49.2	0.055	160	6500	DTMOSIV	
TK040N65Z ☆	650	+/-30	57	0.04	105	6250	DTMOSVI	

TO-247-4L



Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(Ω)	Q _g typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V			
N-ch	TK25Z60X	600	+/-30	25	0.125	40	2400	DTMOSIV-H
	TK31Z60X	600	+/-30	30.8	0.088	65	3000	DTMOSIV-H
	TK39Z60X	600	+/-30	38.8	0.065	85	4100	DTMOSIV-H
	TK62Z60X	600	+/-30	61.8	0.04	135	6500	DTMOSIV-H
	TK110Z65Z ☆	650	+/-30	24	0.11	40	2250	DTMOSVI
	TK090Z65Z ☆	650	+/-30	30	0.09	47	2780	DTMOSVI
	TK065Z65Z ☆	650	+/-30	38	0.065	62	3650	DTMOSVI
	TK040Z65Z ☆	650	+/-30	57	0.04	105	6250	DTMOSVI

TO-3P(L)



Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(Ω)	Q _g typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V			
N-ch	TK100L60W	600	+/-30	100	0.018	360	15000	DTMOSIV

☆ New products, & High Speed Diode type

3. Automotive

PS-8 (2.9x2.8)

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)			Q _s typ. (nC)	C _{ISS} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V	V _{GS} =6V				
N-ch	TPCP8011 # \$	40	+/-20	5	31.8	51.2	11.8	505	U-MOSIV	
	TPCP8010 # \$	40	+/-20	6	23.8	38.4	13.1	600	U-MOSIV	
	TPCP8009 # \$	40	+/-20	10	11.8	19.5	25.1	1250	U-MOSIV	
	TPCP8013 # \$	60	+/-20	4	51.8	77.9	12	515	U-MOSIV	
	TPCP8012 # \$	60	+/-20	8	20.2	29.1	26.6	1160	U-MOSIV	
P-ch	TPCP8109 # \$	-40	+10/-20	-4.5	52.3	76.8	18	810	U-MOSVI	
	TPCP8107 # \$	-40	+10/-20	-8	18	26.8	44.6	2160	U-MOSVI	
	TPCP8111 # \$	-60	+10/-20	-3	117	158.4	17	760	U-MOSVI	
	TPCP8110 # \$	-60	+10/-20	-5	39.5	53.2	45	2075	U-MOSVI	
N-ch x 2	TPCP8207 # \$	40	+/-20	5	36.3	62.8	11.8	505	U-MOSIV	
N-ch + P-ch	TPCP8407 # \$	40	+/-20	5	36.3	62.8	11.8	505	U-MOSIV	
		-40	+10/-20	-4	56.8	82.2	18	810	U-MOSVI	

DKPAK+

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)			Q _s typ. (nC)	C _{ISS} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V	V _{GS} =6.0V	V _{GS} =4.5V			
N-ch	TK15S04N1L # \$	40	+/-20	15	17.8	-	37	10	610	U-MOSVIII-H
	TK35S04K3L # \$	40	+/-20	35	10.3	15	-	28	1370	U-MOSIV
	TK65S04N1L # \$	40	+/-20	65	4.3	-	7.8	39	2550	U-MOSVIII-H
	TK100S04N1L # \$	40	+/-20	100	2.3	-	4.5	76	5490	U-MOSVIII-H
	TK1R4S04PB # \$	40	+/-20	120	1.35	1.9	-	103	5500	U-MOSIX-H
	TK8S06K3L # \$	60	+/-20	8	54	80	-	10	400	U-MOSIV
	TK25S06N1L # \$	60	+/-20	25	18.5	-	36.8	15	855	U-MOSVIII-H
	TK40S06N1L # \$	60	+/-20	40	10.5	-	18	26	1650	U-MOSVIII-H
	TK60S06K3L # \$	60	+/-20	60	8	12.3	-	60	2900	U-MOSIV
	TK90S06N1L # \$	60	+/-20	90	3.3	-	5.2	81	5400	U-MOSVIII-H
	TK7S10N1Z # \$	100	+/-20	7	48	-	-	7.1	470	U-MOSVIII-H
	TK11S10N1L # \$	100	+/-20	11	28	-	50	15	850	U-MOSVIII-H
	TK33S10N1L # \$	100	+/-20	33	9.7	-	16.2	33	2250	U-MOSVIII-H
	TK33S10N1Z # \$	100	+/-20	33	9.7	-	-	28	2050	U-MOSVIII-H
TK55S10N1 # \$	100	+/-20	55	6.5	-	-	49	3280	U-MOSVIII-H	
TK60S10N1L ☆ # \$	100	+/-20	60	6.11	9.25	-	60	4320	U-MOSVIII-H	
P-ch	TJ10S04M3L # \$	-40	+10/-20	-10	44	62	-	19	930	U-MOSVI
	TJ20S04M3L # \$	-40	+10/-20	-20	22.2	32	-	37	1850	U-MOSVI
	TJ40S04M3L # \$	-40	+10/-20	-40	9.1	13	-	83	4140	U-MOSVI
	TJ60S04M3L # \$	-40	+10/-20	-60	6.3	9.4	-	125	6510	U-MOSVI
	TJ80S04M3L # \$	-40	+10/-20	-80	5.2	7.9	-	158	7770	U-MOSVI
	TJ90S04M3L # \$	-40	+10/-20	-90	4.3	-	6	172	7700	U-MOSVI
	TJ8S06M3L # \$	-60	+10/-20	-8	104	130	-	19	890	U-MOSVI
	TJ15S06M3L # \$	-60	+10/-20	-15	50	63	-	36	1770	U-MOSVI
	TJ30S06M3L # \$	-60	+10/-20	-30	21.8	28	-	80	3950	U-MOSVI
	TJ50S06M3L # \$	-60	+10/-20	-50	13.8	17.4	-	124	6290	U-MOSVI
	TJ60S06M3L # \$	-60	+10/-20	-60	11.2	14.5	-	156	7760	U-MOSVI
TJ15S10M3 # \$	-100	+10/-20	-15	130	-	-	69	3200	U-MOSVI	

☆ New Products, # AEC-Q101 qualified, \$ With protection Zener diode between gate and source

TSON Advance(WF) (3.1x3.6)

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)			Q _g typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V	V _{GS} =6V	V _{GS} =4.5V			
N-ch	XPN7R104NC ☆◆# \$	40	+/-20	20	7.1	-	14.2	21	1290	U-MOSVIII-H
	XPN3R804NC ☆◆# \$	40	+/-20	40	3.8	-	7.8	35	2230	U-MOSVIII-H
	XPN12006NC ☆◆# \$	60	+/-20	20	12	-	23.7	23	1100	U-MOSVIII-H
	XPN6R706NC ☆◆# \$	60	+/-20	40	6.7	-	13.3	35	2000	U-MOSVIII-H
	XPN2400ANC ☆◆# \$	100	+/-20	20	23.5	-	42.7	20	920	U-MOSVIII-H
P-ch	XPN1300ANC ☆◆# \$	100	+/-20	30	13.3	-	24.2	28	1470	U-MOSVIII-H
	XPN9R614MC ◆#	-40	+10/-20	-40	9.6	-	13.4	64	3000	U-MOSVI

SOP Advance(WF) (5x6)

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)			Q _g typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V	V _{GS} =6V	V _{GS} =4.5V			
N-ch	XPH3R304PB ☆◆#	40	+/-20	60	3.3	6.3	-	30	1660	U-MOSIX-H
	XPH2R404PB ☆◆#	40	+/-20	90	2.4	4.1	-	40	2500	U-MOSIX-H
	TPH1R104PB ☆◆#	40	+/-20	120	1.14	1.96	-	55	4560	U-MOSIX-H
	TPHR7904PB ☆◆#	40	+/-20	150	0.79	1.3	-	85	6650	U-MOSIX-H
	XPH3R206NC ☆◆# \$	60	+/-20	70	3.2	-	6.2	65	4180	U-MOSVIII-H
	XPH2R106NC ☆◆#	60	+/-20	110	2.1	-	4.1	104	6900	U-MOSVIII-H
	XPH6R30ANB ☆◆# \$	100	+/-20	45	6.3	9.5	-	52	3240	U-MOSVIII-H
	XPH4R10ANB ☆◆#	100	+/-20	70	4.1	6.2	-	75	4970	U-MOSVIII-H
P-ch	XPH4R714MC ☆◆#	-40	+10/-20	-60	4.7	-	6.9	160	5640	U-MOSVI
	XPH3R114MC ☆◆#	-40	+10/-20	-100	3.1	-	4.7	230	9500	U-MOSVI

DSOP Advance(WF) (5x6)

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)			Q _g typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V	V _{GS} =6V	V _{GS} =4.5V			
N-ch	TPW1R104PB * ☆◆#	40	+/-20	120	1.14	1.96	-	55	4560	U-MOSIX-H
	TPWR7904PB ** ☆◆#	40	+/-20	150	0.79	1.3	-	85	6650	U-MOSIX-H
	XPW4R10ANB ** ☆◆#	100	+/-20	70	4.1	6.2	-	75	4970	U-MOSVIII-H
	XPW6R30ANB * ☆◆# \$	100	+/-20	45	6.3	9.5	-	52	3240	U-MOSVIII-H


D2PAK+

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)		Q _g typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V	V _{GS} =6V			
N-ch	TK1R5R04PB #	40	+/-20	160	1.5	2.05	103	5500	U-MOSIX-H

TO-220SM(W)

Circuit Configuration	Part Number	Absolute Maximum Ratings			R _{DS(ON)} max(mΩ)		Q _g typ. (nC)	C _{iss} typ. (pF)	Remark
		V _{DSS} (V)	V _{GSS} (V)	I _D (A)	V _{GS} =10V	V _{GS} =6V			
N-ch	TK1R4F04PB ☆#	40	+/-20	160	1.35	1.9	103	5500	U-MOSIX-H
	TK200F04N1L ☆#	40	+/-20	200	0.9	1.37	214	14920	U-MOSVIII-H
	TKR74F04PB ☆#	40	+/-20	250	0.74	0.98	227	14200	U-MOSIX-H
	TK60F10N1L ☆#	100	+/-20	60	6.11	9.25	60	4320	U-MOSVIII-H
	TK160F10N1L #	100	+/-20	160	2.4	3.7	122	10100	U-MOSVIII-H
	XXK1R9F10QB ☆#	100	+/-20	160	1.92	3.31	184	11500	U-MOSX-H
P-ch	TJ200F04M3L #	-40	+10/-20	-200	1.8	2.6	460	12800	U-MOSVI

☆ New Products, # AEC-Q101 qualified, \$ With protection Zener diode between gate and source, ◆ Wettable Flank Lead Terminal
* DSOP Advance(WF)M, ** DSOP Advance(WF)L



4. Silicon Carbide (SiC) MOSFET Series



TO-3P(N)

Circuit Configuration	Part Number	Absolute Maximum Ratings			$R_{DS(ON)}$ max(m Ω)	Q_s typ. (nC)	C_{iss} typ. (pF)	Remark
		V_{DSS} (V)	V_{GS} (V)	I_D (A)	$V_{GS}=20V$			
N-ch	TW070J120B ☆	1200	+25/-10	36	0.09	70	1680	

☆ New Products

5. Part Naming Conventions

Conventional Multi-Pin Series

Ex) TPC8 0 67 -H
 ① ② ③ ④

- Package
 TPCP8: PS-8 Series TPC8: SOP-8 Series
 TPCP8: TSON Advance Series TPCA8: SOP Advance Series
- Polarity / Configuration
 0: N-channel, single 3: P-channel, dual
 1: P-channel, single 4: N-channel and P-channel, dual
 2: N-channel, dual J: P-channel and NPN
- Serial number of the products
- Additional information
 H: High-speed type None: Low-on-resistance type

New Multi-Pin Series

Ex) TPH 4R3 0 4 N C
 ① ② ③ ④ ⑤ ⑥

- Package
 TPP: PS-8 Series TPH / XPH: SOP Advance Series
 TPN / XPN: TSON Advance Series TP8: SOP-8 Series
 TPW / XPW: DSOP Advance Series
- Max. on-resistance (at max drive conditions)
 R79 = 0.79 mΩ 100 = $10 \times 10^0 = 10$ mΩ
 4R3 = 4.3 mΩ 101 = $10 \times 10^1 = 100$ mΩ
- Polarity / Configuration
 0: Single N-ch 1: Single P-ch
- Drain-source voltage (V_{DS})
 2: 15 to 24V 7: 65 to 74V D: 180 to 199V
 3: 25 to 34V 8: 75 to 84V E: 200 to 249V
 4: 35 to 44V A: 95 to 124V F: 250 to 299V
 5: 45 to 54V B: 125 to 149V
 6: 55 to 64V C: 150 to 179V
- Series
 M: U-MOSVI N: U-MOSVII/U-MOSVIII-H P: U-MOSIX-H
 Q: U-MOSX-H
- Additional information
 1 to 5: Serial number of the products
 A: $V_{GS} = 10$ V (Drive)
 B: $V_{GS} = 6$ V (Drive)
 C: $V_{GS} = 4.5$ V (Drive)
 D: $V_{GS} = 2.5$ V (Drive)
 E: $V_{GS} = 2.0$ V (Drive)
 F: $V_{GS} = 1.8$ V (Drive)
 H: Low-rg, $V_{GS} = 10$ V (Drive)
 M: Low-rg, $V_{GS} = 6$ V (Drive)
 L: Low-rg, $V_{GS} = 4.5$ V (Drive)
 Q: $T_{ch(max)}$ = Guaranteed up to 175°C + ZD
 R: $T_{ch(max)}$ = Guaranteed up to 150°C + ZD
 S: $T_{ch(max)}$ = Guaranteed up to 175°C
 T: $T_{ch(max)}$ = Guaranteed up to 150°C

Silicon carbide (SiC) Series

Ex) TW 070 J 120 B
 ① ② ③ ④ ⑤

- Polarity
 TW: N-channel
- Typ. on-resistance (at max drive conditions)
 070 = 70 mΩ
- Package
 A: TO-220SIS N: TO-247
 E: TO-220 V: DFN8x8
 J: TO-3P(N) Z: TO-247-4L
- Drain-source voltage V_{DS} : Display value $\times 10$ times = V_{DS}
 120: $V_{DS} = 1200$ V
- Generation
 B: 2nd Generation

3-Pin Series

Ex) TK 40 S 10 K 3 Z
 ① ② ③ ④ ⑤ ⑥ ⑦

- Polarity
 TK: N-channel TJ: P-channel
- Drain current (I_b)
- Package
 A: TO-220SIS N: TO-247
 E: TO-220 P: DPAK/New PW-Mold
 F: TO-220SM(W) Q: IPAK/New PW-Mold2
 G: D2PAK S: DPAK +
 J: TO-3P(N) V: DFN8 x 8
 L: TO-3P(L) Z: TO-247-4L
- Drain-source voltage (V_{DS}): Display value $\times 10 = V_{DS}$
 06: $V_{DS} = 60$ V 10: $V_{DS} = 100$ V
- Series
 A: π -MOSIV J: U-MOSIII U: DTMOS II
 C: π -MOSVI K: U-MOSIV V: DTMOS III
 D: π -MOSVII M: U-MOSVI W: DTMOSIV
 E: π -MOSVIII N: U-MOSVIII X: DTMOSIV-H
- Additional information (1)
 1: Low-capacitance type 5: Fast body diode type
 3: Low-on-resistance type
- Additional information (2)
 L: $V_{GS} = 4.5$ V (Drive) S: $V_{GS} = 4.5$ V (Drive)
 H: $V_{GS} = 10$ V (Drive) Z: With protection Zener diode
 M: $V_{GS} = 6$ V (Drive) between gate and source

New 3-Pin Series

Ex) TK R74 F 04 P B
 ① ② ③ ④ ⑤ ⑥

- Polarity
 TK / XK: N-channel TJ / XJ: P-channel
- Max. on-resistance $V_{DS} = 400$ V less than the product (at max drive conditions)
 R74 = 0.74 mΩ 100 = $10 \times 10^0 = 10$ mΩ
 8R2 = 8.2 mΩ 101 = $10 \times 10^1 = 100$ mΩ
 Max. on-resistance $V_{DS} = 400$ V or more products (at max drive conditions)
 047 = 0.047 Ω 410 = 0.41 Ω 4K7 = 4.7 Ω
- Package
 A: TO-220SIS N: TO-247 V: DFN8 x 8
 E: TO-220 P: DPAK/New PW-Mold Z: TO-247-4L
 F: TO-220SM(W) Q: IPAK/New PW-Mold 2
 G: D2PAK R: D2PAK +
 J: TO-3P(N) S: DPAK +
 L: TO-3P(L) U: TOLL
- Drain-source voltage V_{DS} : Display value $\times 10$ times = V_{DS}
 04: $V_{DS} = 40$ V 10: $V_{DS} = 100$ V
- Series
 F: π -MOSIX N: U-MOSVIII-H Y: DTMOS V
 M: U-MOSVI P: U-MOSIX-H Z: DTMOSVI
- Additional information
 A: $V_{GS} = 10$ V (Drive) H: Low-rg, $V_{GS} = 10$ V (Drive)
 B: $V_{GS} = 6$ V (Drive) M: Low-rg, $V_{GS} = 6$ V (Drive)
 C: $V_{GS} = 4.5$ V (Drive) L: Low-rg, $V_{GS} = 4.5$ V (Drive)

JEITA registration Item Series

Ex) N-channel MOS P-channel MOS
 2SK*** * 2SJ*** *

6. Device Packages

Dimensional Out Line

DPAK+ (6.5x9.5)	New PW-Mold (6.5x9.5)	DPAK 2-7K1S (TO-252)
<p>Package dimension unit : mm</p>	<p>Package dimension unit : mm</p>	<p>Package dimension unit : mm</p>
<p>Land pattern example unit : mm</p>	<p>Land pattern example unit : mm</p>	<p>Land pattern example unit : mm</p>

DPAK 2-7N1S (TO-252)	TO-220SM(W) (10.0x13.0)	D2PAK+ (10.0x15.0)
<p>Package dimension unit : mm</p>	<p>Package dimension unit : mm</p>	<p>Package dimension unit : mm</p>
<p>Land pattern example unit : mm</p>	<p>Land pattern example unit : mm</p>	<p>Land pattern example unit : mm</p>

Dimensional Out Line

D2PAK (10.35x15.3)		DFN8X8 (8.0x8.0)		PS-8 (2.9x2.8)	
Package dimension	unit : mm	Package dimension	unit : mm	Package dimension	unit : mm
Land pattern example	unit : mm	Land pattern example	unit : mm	Land pattern example	unit : mm

TSON Advance (3.1x3.3)		TSON Advance (WF) (3.1x3.6) ★		SOP-8 2-5R1S (4.9x6.0)	
Package dimension	unit : mm	Package dimension	unit : mm	Package dimension	unit : mm
Land pattern example	unit : mm	Land pattern example	unit : mm	Land pattern example	unit : mm

★ Wettable Flank Lead Terminal

Dimensional Out Line

SOP-8 2-6J1S		DSOP Advance (5.0x6.0)		DSOP Advance (WF)L (5.0x6.0) ★	
Package dimension	unit : mm	Package dimension	unit : mm	Package dimension	unit : mm
Land pattern example	unit : mm	Land pattern example	unit : mm	Land pattern example	unit : mm

★ Wettable Flank Lead Terminal

DSOP Advance (WF)M (5.0x6.0) ★		SOP Advance (5.0x6.0)		SOP Advance(N) (4.9x6.1)	
Package dimension	unit : mm	Package dimension	unit : mm	Package dimension	unit : mm
Land pattern example	unit : mm	Land pattern example	unit : mm	Land pattern example	unit : mm


★ Wettable Flank Lead Terminal

Dimensional Out Line

SOP Advance(WF) (5.0x6.0) ★		TOLL (9.9x11.68)	
<p>Package dimension unit : mm</p>	<p>Package dimension unit : mm</p>		
<p>Land pattern example unit : mm</p>	<p>Land pattern example unit : mm</p>		

★ Wettable Flank Lead Terminal

Dimensional Out Line



RESTRICTIONS ON PRODUCT USE

Toshiba Corporation and its subsidiaries and affiliates are collectively referred to as "TOSHIBA". Hardware, software and systems described in this document are collectively referred to as "Product".

- TOSHIBA reserves the right to make changes to the information in this document and related Product without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, lifesaving and/or life supporting medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, and devices related to power plant. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT.** For details, please contact your TOSHIBA sales representative or contact us via our website.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**

TOSHIBA

Toshiba Electronic Devices & Storage Corporation
Toshiba Electronic Device Solutions Corporation

<https://toshiba.semicon-storage.com/>