


## High Current Density Surface Mount Schottky Barrier Rectifiers

### eSMP™ Series



TO-277A (SMPC)



### PRIMARY CHARACTERISTICS

|                        |             |
|------------------------|-------------|
| $I_{F(AV)}$            | 5.0 A       |
| $V_{RRM}$              | 90 V, 100 V |
| $I_{FSM}$              | 150 A       |
| $V_F$ at $I_F = 5.0$ A | 0.649 V     |
| $I_R$                  | 4.5 $\mu$ A |
| $T_J$ max.             | 150 °C      |

### TYPICAL APPLICATIONS

For use in high frequency rectifier of switching mode power supplies, freewheeling diodes, dc-to-dc converters and polarity protection application.

### FEATURES

- Very low profile - typical height of 1.1 mm
- Ideal for automated placement
- Guardring for overvoltage protection
- Low forward voltage drop, low power losses
- High efficiency
- Low thermal resistance
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Solder dip 265 °C max. 10 s, per JESD 22-A111
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC
- **Halogen-free according to IEC 61249-2-21 definition**



**RoHS**  
COMPLIANT  
HALOGEN  
FREE

### MECHANICAL DATA

**Case:** TO-277A (SMPC)

Molding compound meets UL 94 V-0 flammability rating

Base P/N-M3 - halogen-free and RoHS compliant, commercial grade

Base P/NHM3 - halogen-free and RoHS compliant, AEC-Q101 qualified

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

M3 suffix meets JESD 201 class 1A whisker test, HM3 suffix meets JESD 201 class 2 whisker test

### MAXIMUM RATINGS ( $T_A = 25$ °C unless otherwise noted)

| PARAMETER                                                                         | SYMBOL         | SS5P9         | SS5P10 | UNIT |
|-----------------------------------------------------------------------------------|----------------|---------------|--------|------|
| Device marking code                                                               |                | S59           | S510   |      |
| Maximum repetitive peak reverse voltage                                           | $V_{RRM}$      | 90            | 100    | V    |
| Maximum average forward rectified current (Fig. 1)                                | $I_{F(AV)}$    | 5.0           |        | A    |
| Peak forward surge current 10 ms single half sine-wave superimposed on rated load | $I_{FSM}$      | 150           |        | A    |
| Non-repetitive avalanche energy at $I_{AS} = 2$ A, $T_J = 25$ °C                  | $E_{AS}$       | 20            |        | mJ   |
| Operating junction and storage temperature range                                  | $T_J, T_{STG}$ | - 55 to + 150 |        | °C   |

## SS5P9, SS5P10

Vishay General Semiconductor



| ELECTRICAL CHARACTERISTICS ( $T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise noted) |                                              |                                                                           |        |                |           |                     |
|-----------------------------------------------------------------------------------------|----------------------------------------------|---------------------------------------------------------------------------|--------|----------------|-----------|---------------------|
| PARAMETER                                                                               | TEST CONDITIONS                              |                                                                           | SYMBOL | TYP.           | MAX.      | UNIT                |
| Instantaneous forward voltage <sup>(1)</sup>                                            | $I_F = 2.5\text{ A}$<br>$I_F = 5.0\text{ A}$ | $T_A = 25\text{ }^{\circ}\text{C}$                                        | $V_F$  | 0.708<br>0.832 | -<br>0.88 | V                   |
|                                                                                         | $I_F = 2.5\text{ A}$<br>$I_F = 5.0\text{ A}$ | $T_A = 125\text{ }^{\circ}\text{C}$                                       |        | 0.571<br>0.649 | -<br>0.68 |                     |
| Reverse current <sup>(2)</sup>                                                          | Rated $V_R$                                  | $T_A = 25\text{ }^{\circ}\text{C}$<br>$T_A = 125\text{ }^{\circ}\text{C}$ | $I_R$  | 4.5<br>2.7     | 15<br>5   | $\mu\text{A}$<br>mA |
| Typical junction capacitance                                                            | 4.0 V, 1 MHz                                 |                                                                           | $C_J$  | 130            | -         | pF                  |

**Notes:**(1) Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle(2) Pulse test: Pulse width  $\leq 40\text{ ms}$ 

| THERMAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |                                 |       |        |      |
|-------------------------------------------------------------------------|---------------------------------|-------|--------|------|
| PARAMETER                                                               | SYMBOL                          | SS5P9 | SS5P10 | UNIT |
| Typical thermal resistance                                              | R <sub>θJA</sub> <sup>(1)</sup> | 65    |        | °C/W |
|                                                                         | R <sub>θJL</sub>                | 3     |        |      |

**Note:**

(1) Units mounted on recommended P.C.B. 1 oz. pad layout

| ORDERING INFORMATION (Example) |                 |                        |               |                                    |
|--------------------------------|-----------------|------------------------|---------------|------------------------------------|
| PREFERRED P/N                  | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE                      |
| SS5P10-M3/86A                  | 0.10            | 86A                    | 1500          | 7" diameter plastic tape and reel  |
| SS5P10-M3/87A                  | 0.10            | 87A                    | 6500          | 13" diameter plastic tape and reel |
| SS5P10HM3/86A <sup>(1)</sup>   | 0.10            | 86A                    | 1500          | 7" diameter plastic tape and reel  |
| SS5P10HM3/87A <sup>(1)</sup>   | 0.10            | 87A                    | 6500          | 13" diameter plastic tape and reel |

**Note:**

(1) AEC-Q101 qualified



## RATINGS AND CHARACTERISTICS CURVES

( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)




Figure 1. Maximum Forward Current Derating Curve




Figure 4. Typical Reverse Characteristics




Figure 2. Forward Power Loss Characteristics




Figure 5. Typical Junction Capacitance




Figure 3. Typical Instantaneous Forward Characteristics





Figure 6. Typical Transient Thermal Impedance

## SS5P9, SS5P10

Vishay General Semiconductor

**PACKAGE OUTLINE DIMENSIONS** in inches (millimeters)

Conform to JEDEC TO-277A



### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.