


## Metallized Polyester Film Capacitors MKT Radial Type



### FEATURES

- 10.0 mm to 27.5 mm lead pitch
- Self-healing properties
- Flame retardant case
- Material categorization:  
for definitions of compliance please see  
[www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)

### APPLICATIONS

Blocking, bypassing, filtering, timing, coupling and decoupling circuits, interference suppression in low voltage applications.


### QUICK REFERENCE DATA

|                                                        |                                                                                                                                   |
|--------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Capacitance range (E12 series)                         | 1000 pF to 15 $\mu$ F (preferred values according to E6)                                                                          |
| Capacitance tolerance                                  | $\pm 20\%$ (M), $\pm 10\%$ (K), $\pm 5\%$ (J) (on request)                                                                        |
| Climatic testing class according to IEC 60068          | 55/100/56                                                                                                                         |
| Reference standards                                    | IEC 60384-2                                                                                                                       |
| Dielectric                                             | Polyester film                                                                                                                    |
| Electrodes                                             | Vacuum deposited aluminum                                                                                                         |
| Construction                                           | Extended metallized film                                                                                                          |
| Encapsulation                                          | Flame retardant plastic case UL-class 94 V-0                                                                                      |
| Leads                                                  | Tinned wire                                                                                                                       |
| Marking                                                | Manufacturer's logo; type; C-value; rated voltage; tolerance; date of manufacture                                                 |
| Temperature range                                      | -55 °C to +100 °C                                                                                                                 |
| Rated DC voltage                                       | 63 V <sub>DC</sub> , 100 V <sub>DC</sub> , 250 V <sub>DC</sub> , 400 V <sub>DC</sub> , 630 V <sub>DC</sub> , 1000 V <sub>DC</sub> |
| Permissible AC voltages (RMS) up to 60 Hz              | 40 V <sub>AC</sub> , 63 V <sub>AC</sub> , 160 V <sub>AC</sub> , 200 V <sub>AC</sub> , 220 V <sub>AC</sub>                         |
| Capacitance drift                                      | Up to +40 °C, $\pm 1.5\%$ for a period of two years                                                                               |
| Derating for DC and AC category voltage U <sub>C</sub> | At +85 °C: U <sub>C</sub> = 1.0 U <sub>R</sub><br>At +100 °C: U <sub>C</sub> = 0.8 U <sub>R</sub>                                 |
| Self inductance                                        | ~ 6 nH measured with 2 mm long leads                                                                                              |
| Pull test on leads                                     | $\geq 30$ N in direction of leads according to IEC 60068-2-21                                                                     |


#### Note

- For more detailed data and test requirements, contact [dc-film@vishay.com](mailto:dc-film@vishay.com)

### DIMENSIONS in millimeters



## COMPOSITION OF CATALOG NUMBER



### Note

- For detailed tape specifications refer to packaging information [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139) or “Recommended Packaging” table

### SPECIFIC REFERENCE DATA

| DESCRIPTION                                                                                                               |                                        |                     |                     | MAX. VALUE          |                                |                      |
|---------------------------------------------------------------------------------------------------------------------------|----------------------------------------|---------------------|---------------------|---------------------|--------------------------------|----------------------|
| Tangent of loss angle:<br>$C \leq 0.1 \mu\text{F}$<br>$0.1 \mu\text{F} < C \leq 1.0 \mu\text{F}$<br>$C > 1.0 \mu\text{F}$ |                                        |                     |                     | at 1 kHz            | at 10 kHz                      | at 100 kHz           |
|                                                                                                                           |                                        |                     |                     | $8 \times 10^{-3}$  | $15 \times 10^{-3}$            | $25 \times 10^{-3}$  |
|                                                                                                                           |                                        |                     |                     | $8 \times 10^{-3}$  | $15 \times 10^{-3}$            | -                    |
|                                                                                                                           |                                        |                     |                     | $10 \times 10^{-3}$ | -                              | -                    |
| PCM<br>(mm)                                                                                                               | MAXIMUM PULSE RISE TIME (dV/dt) [V/μs] |                     |                     |                     |                                |                      |
|                                                                                                                           | 63 V <sub>DC</sub>                     | 100 V <sub>DC</sub> | 250 V <sub>DC</sub> | 400 V <sub>DC</sub> | 630 V <sub>DC</sub>            | 1000 V <sub>DC</sub> |
| 10                                                                                                                        | 11                                     | 13                  | 22                  | 37                  | 60                             | 130                  |
| 15                                                                                                                        | 7                                      | 8                   | 13                  | 21                  | 33                             | 65                   |
| 22.5                                                                                                                      | 4                                      | 5                   | 8                   | 13                  | 19                             | 34                   |
| 27.5                                                                                                                      | 3                                      | 4                   | 6                   | 10                  | 14                             | 25                   |
| If the maximum pulse voltage is less than the rated voltage higher dV/dt values can be permitted.                         |                                        |                     |                     |                     |                                |                      |
| R between leads, for $C \leq 0.33 \mu\text{F}$ and $U_R \leq 100 \text{ V}$                                               |                                        |                     |                     |                     | > 15 000 MΩ                    |                      |
| R between leads, for $C \leq 0.33 \mu\text{F}$ and $U_R > 100 \text{ V}$                                                  |                                        |                     |                     |                     | > 30 000 MΩ                    |                      |
| RC between leads, for $C > 0.33 \mu\text{F}$ and $U_R \leq 100 \text{ V}$                                                 |                                        |                     |                     |                     | > 5000 s                       |                      |
| RC between leads, for $C > 0.33 \mu\text{F}$ and $U_R > 100 \text{ V}$                                                    |                                        |                     |                     |                     | > 10 000 s                     |                      |
| R between leads and case, 100 V; (foil method)                                                                            |                                        |                     |                     |                     | > 30 000 MΩ                    |                      |
| Withstanding (DC) voltage (cut off current 10 mA); rise time < 1000 V/s                                                   |                                        |                     |                     |                     | 1.6 x U <sub>RDC</sub> , 1 min |                      |
| Withstanding (DC) voltage between leads and case                                                                          |                                        |                     |                     |                     | 2 x U <sub>RDC</sub> , 1 min   |                      |
| Maximum application temperature                                                                                           |                                        |                     |                     |                     | 100 °C                         |                      |



| ELECTRICAL DATA         |              |                     |                 |                 |                         |      |
|-------------------------|--------------|---------------------|-----------------|-----------------|-------------------------|------|
| U <sub>RDC</sub><br>(V) | CAP.<br>(μF) | CAPACITANCE<br>CODE | VOLTAGE<br>CODE | V <sub>AC</sub> | DIMENSIONS<br>W x H x L | PCM  |
| 63                      | 0.22         | -422                | 06              | 40              | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.33         | -433                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.47         | -447                |                 |                 | 5.5 x 10.5 x 13.0       | 10   |
|                         | 0.68         | -468                |                 |                 | 5.5 x 10.5 x 18.0       | 15   |
|                         | 1.0          | -510                |                 |                 | 5.5 x 10.5 x 18.0       | 15   |
|                         | 1.5          | -515                |                 |                 | 6.5 x 12.5 x 18.0       | 15   |
|                         | 2.2          | -522                |                 |                 | 7.5 x 13.5 x 18.0       | 15   |
|                         | 3.3          | -533                |                 |                 | 7.5 x 15.5 x 26.5       | 22.5 |
|                         | 4.7          | -547                |                 |                 | 8.5 x 16.5 x 26.5       | 22.5 |
|                         | 6.8          | -568                |                 |                 | 10.5 x 18.5 x 26.5      | 22.5 |
|                         | 10.0         | -610                |                 |                 | 11.5 x 20.5 x 31.5      | 27.5 |
|                         | 15.0         | -615                |                 |                 | 13.5 x 23.5 x 31.5      | 27.5 |
| 100                     | 0.068        | -368                | 01              | 63              | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.10         | -410                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.15         | -415                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.22         | -422                |                 |                 | 4.5 x 9.5 x 13.0        | 10   |
|                         | 0.33         | -433                |                 |                 | 5.5 x 10.5 x 18.0       | 15   |
|                         | 0.47         | -447                |                 |                 | 5.5 x 10.5 x 18.0       | 15   |
|                         | 0.68         | -468                |                 |                 | 6.5 x 12.5 x 18.0       | 15   |
|                         | 1.0          | -510                |                 |                 | 7.5 x 13.5 x 18.0       | 15   |
|                         | 1.5          | -515                |                 |                 | 7.5 x 15.5 x 26.5       | 22.5 |
|                         | 2.2          | -522                |                 |                 | 8.5 x 16.5 x 26.5       | 22.5 |
|                         | 3.3          | -533                |                 |                 | 10.5 x 18.5 x 26.5      | 22.5 |
|                         | 4.7          | -547                |                 |                 | 11.5 x 20.5 x 31.5      | 27.5 |
|                         | 6.8          | -568                |                 |                 | 13.5 x 23.5 x 31.5      | 27.5 |
|                         | 10.0         | -610                |                 |                 | 15.0 x 24.5 x 31.5      | 27.5 |
|                         | 15.0         | -615                |                 |                 | 16.5 x 29.5 x 31.5      | 27.5 |
| 250                     | 0.033        | -333                | 25              | 160             | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.047        | -347                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.068        | -368                |                 |                 | 4.5 x 9.5 x 13.0        | 10   |
|                         | 0.10         | -410                |                 |                 | 5.5 x 10.5 x 18.0       | 15   |
|                         | 0.15         | -415                |                 |                 | 5.5 x 10.5 x 18.0       | 15   |
|                         | 0.22         | -422                |                 |                 | 5.5 x 10.5 x 18.0       | 15   |
|                         | 0.33         | -433                |                 |                 | 6.5 x 12.5 x 18.0       | 15   |
|                         | 0.47         | -447                |                 |                 | 6.5 x 14.5 x 26.5       | 22.5 |
|                         | 0.68         | -468                |                 |                 | 7.5 x 15.5 x 26.5       | 22.5 |
|                         | 1.0          | -510                |                 |                 | 8.5 x 16.5 x 26.5       | 22.5 |
|                         | 1.5          | -515                |                 |                 | 9.0 x 18.5 x 31.5       | 27.5 |
|                         | 2.2          | -522                |                 |                 | 11.5 x 20.5 x 31.5      | 27.5 |
|                         | 3.3          | -533                |                 |                 | 13.5 x 23.5 x 31.5      | 27.5 |
|                         |              |                     |                 |                 |                         |      |
|                         |              |                     |                 |                 |                         |      |
| 400                     | 0.0010       | -210                | 40              | 200             | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0015       | -215                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0022       | -222                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0033       | -233                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0047       | -247                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0068       | -268                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.010        | -310                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.015        | -315                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.022        | -322                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.033        | -333                |                 |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.047        | -347                |                 |                 | 5.5 x 10.5 x 18.0       | 15   |
|                         | 0.068        | -368                |                 |                 | 5.5 x 10.5 x 18.0       | 15   |
|                         | 0.10         | -410                |                 |                 | 5.5 x 10.5 x 18.0       | 15   |
|                         | 0.15         | -415                |                 |                 | 6.5 x 12.5 x 18.0       | 15   |
|                         | 0.22         | -422                |                 |                 | 7.5 x 15.5 x 26.5       | 22.5 |
|                         | 0.33         | -433                |                 |                 | 8.5 x 16.5 x 26.5       | 22.5 |
|                         | 0.47         | -447                |                 |                 | 10.5 x 18.5 x 26.5      | 22.5 |
|                         | 0.68         | -468                |                 |                 | 11.5 x 20.5 x 31.5      | 27.5 |
|                         | 1.0          | -510                |                 |                 | 11.5 x 20.5 x 31.5      | 27.5 |
|                         | 1.5          | -515                |                 |                 | 13.5 x 23.5 x 31.5      | 27.5 |
|                         |              |                     |                 |                 |                         |      |



| ELECTRICAL DATA         |              |                     |                   |                 |                         |      |
|-------------------------|--------------|---------------------|-------------------|-----------------|-------------------------|------|
| U <sub>RDC</sub><br>(V) | CAP.<br>(μF) | CAPACITANCE<br>CODE | VOLTAGE<br>CODE   | V <sub>AC</sub> | DIMENSIONS<br>W x H x L | PCM  |
| 630                     | 0.0010       | -210                | 63 <sup>(1)</sup> | 220             | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0015       | -215                |                   |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0022       | -222                |                   |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0033       | -233                |                   |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0047       | -247                |                   |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0068       | -268                |                   |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.010        | -310                |                   |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.015        | -315                |                   |                 | 5.5 x 10.5 x 13.0       | 10   |
|                         | 0.022        | -322                |                   |                 | 6.5 x 11.5 x 13.0       | 10   |
|                         | 0.033        | -333                |                   |                 | 5.5 x 10.5 x 18.0       | 15   |
|                         | 0.047        | -347                |                   |                 | 6.5 x 12.5 x 18.0       | 15   |
|                         | 0.068        | -368                |                   |                 | 7.5 x 13.5 x 18.0       | 15   |
|                         | 0.10         | -410                |                   |                 | 6.5 x 14.5 x 26.5       | 22.5 |
|                         | 0.15         | -415                |                   |                 | 7.5 x 15.5 x 26.5       | 22.5 |
|                         | 0.22         | -422                |                   |                 | 8.5 x 16.5 x 26.5       | 22.5 |
|                         | 0.33         | -433                |                   |                 | 11.5 x 20.5 x 31.5      | 27.5 |
|                         | 0.47         | -447                |                   |                 | 11.5 x 20.5 x 31.5      | 27.5 |
|                         | 0.68         | -468                |                   |                 | 13.5 x 23.5 x 31.5      | 27.5 |
|                         | 1.0          | -510                |                   |                 | 15.0 x 24.5 x 31.5      | 27.5 |
| 1000                    | 0.0010       | -210                | 10 <sup>(1)</sup> | 220             | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0015       | -215                |                   |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0022       | -222                |                   |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0033       | -233                |                   |                 | 4.0 x 9.0 x 13.0        | 10   |
|                         | 0.0047       | -247                |                   |                 | 5.5 x 10.5 x 13.0       | 10   |
|                         | 0.0068       | -268                |                   |                 | 6.5 x 11.5 x 13.0       | 10   |
|                         | 0.010        | -310                |                   |                 | 5.5 x 10.5 x 18.0       | 15   |
|                         | 0.015        | -315                |                   |                 | 6.5 x 12.5 x 18.0       | 15   |
|                         | 0.022        | -322                |                   |                 | 7.5 x 13.5 x 18.0       | 15   |
|                         | 0.033        | -333                |                   |                 | 6.5 x 14.5 x 26.5       | 22.5 |
|                         | 0.047        | -347                |                   |                 | 7.5 x 15.5 x 26.5       | 22.5 |
|                         | 0.068        | -368                |                   |                 | 8.5 x 16.5 x 26.5       | 22.5 |
|                         | 0.10         | -410                |                   |                 | 10.5 x 18.5 x 26.5      | 22.5 |
|                         | 0.15         | -415                |                   |                 | 11.5 x 20.5 x 31.5      | 27.5 |
|                         | 0.22         | -422                |                   |                 | 13.5 x 23.5 x 31.5      | 27.5 |
|                         | 0.33         | -433                |                   |                 | 16.5 x 29.5 x 31.5      | 27.5 |
|                         | 0.47         | -447                |                   |                 | 20.0 x 35.0 x 31.5      | 27.5 |







**Note**<sup>(1)</sup> Not suitable for mains applications

| RECOMMENDED PACKAGING |                      |                       |                          |                           |           |           |                     |
|-----------------------|----------------------|-----------------------|--------------------------|---------------------------|-----------|-----------|---------------------|
| LETTER<br>CODE        | TYPE OF<br>PACKAGING | HEIGHT<br>(H)<br>(mm) | REEL<br>DIAMETER<br>(mm) | ORDERING CODE<br>EXAMPLES | PCM<br>10 | PCM<br>15 | PCM<br>22.5 TO 27.5 |
| G                     | Ammo                 | 18.5                  | S <sup>(1)</sup>         | MKT1822-422-065-G         | X         | X         | -                   |
| W                     | Reel                 | 18.5                  | 350                      | MKT1822-422-065-W         | X         | X         | -                   |
| V                     | Reel                 | 18.5                  | 500                      | MKT1822-510-255-V         | -         | X         | X                   |
| G                     | Ammo                 | 18.5                  | L <sup>(2)</sup>         | MKT1822-510-255-G         | -         | -         | X                   |
| -                     | Bulk                 | -                     | -                        | MKT1822-510-255           | X         | X         | X                   |
| -                     | Bulk                 | -                     | -                        | MKT1822-522-255           | X         | -         | X                   |

**Notes**<sup>(1)</sup> S = Box size 55 mm x 210 mm x 340 mm (W x H x L)<sup>(2)</sup> L = Box size 60 mm x 360 mm x 510 mm (W x H x L)



PERMISSIBLE AC VOLTAGE VS. FREQUENCY





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.